



Product Data Sheet

Epolene® C-13 Polymer

Application/Uses

- Automotive refinish
- Building and Construction
- Hot Melt Adhesives
- Inks
- Packaging
- Solvent borne Adhesives
- Wax Modification

Key Attributes

- Enhances paraffin wax coating properties like gloss, grease resistance, and MVTR
- Excellent thermal stability
- Low color
- Medium molecular weight
- Useful in color concentrates

Product Description

Epolene C-13 is a branched low density polyethylene homopolymer with low color and medium molecular weight. It is useful as a base polymer for adhesives and coatings, color concentrate dispersions, and to provide lubricity in rubber compounding. Coatings produced with *Epolene* C-13 exhibit high gloss, low moisture vapor transmission rates, grease resistance, and good heat seal ability.

Typical Properties

| Property | Test Method | Typical Value, Units |
|--|-------------|----------------------|
| Polymer Type | | PE |
| Ring and Ball Softening Point | ASTM E 28 | 110°C |
| Penetration Hardness ^a | ASTM D 5 | 3 dmm |
| Viscosity, Brookfield ^b @ 190°C (374°F) | | MI = 190 |

| | |
|-------------------------------|--------|
| Molecular Weight ^c | 76,000 |
|-------------------------------|--------|

^a Needle under 100-g load for 5s @ 25 deg C, tenths of mm

^b MI = Melt Index @ 190 deg C, 2.16 kg weight

^c Molecular weight measured via Gel Permeation Chromatography (GPC) using polystyrene standards

Comments

Properties reported here are typical of average lots. Westlake makes no representation that the material in any particular shipment will conform exactly to the values given.

Compatibility and Solubility

Epolene polymers are compatible with many polymers, resins, and natural and synthetic waxes.

Packaging

Epolene C-13 polymer is supplied as free-flowing pellets, packaged in multiwall paper bags with a polyethylene coated inner liner [22.67 kg (50 lb) net weight]. The bags are palletized and stretch wrapped to prevent contamination during storage and shipment. Many *Epolene* polymers are also shipped in a variety of bulk containers.

Epolene C-13 polymer is also available in powder form as *Epolene* C-13P polymer.

Storage

The useful life of this product can be affected by storage and handling conditions. When stored in the original unopened container in an enclosed area and protected from moisture, extreme temperatures and contamination, this product is estimated to continue to meet applicable sales specifications for more than 2 years from the date of manufacture. First in first out (FIFO) inventory control is recommended.