

# SAFETY DATA SHEET



## DryFilm 2000/IPA

Version 6.6      Revision Date: 08/27/2021      SDS Number: 1331647-00040      Date of last issue: 11/06/2020  
Date of first issue: 02/27/2017

---

### SECTION 1. IDENTIFICATION

Product name : DryFilm 2000/IPA

SDS-Identcode : 130000028496

#### Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street  
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

#### Recommended use of the chemical and restrictions on use

Recommended use : Dry lubricant

Restrictions on use : For professional users only., For industrial use only.  
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

---

### SECTION 2. HAZARDS IDENTIFICATION



#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 2

Eye irritation : Category 2A

Specific target organ toxicity : Category 3  
- single exposure

#### GHS label elements

Hazard pictograms :  

Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.

# SAFETY DATA SHEET



## DryFilm 2000/IPA

Version 6.6      Revision Date: 08/27/2021      SDS Number: 1331647-00040      Date of last issue: 11/06/2020  
Date of first issue: 02/27/2017

---

H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

Precautionary Statements :

**Prevention:**

P210 Keep away from heat, sparks, open flame and hot surfaces. - No smoking.  
P233 Keep container tightly closed.  
P241 Use explosion-proof electrical, ventilating and lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing mist or vapors.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves, eye protection and face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical attention.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents and container to an approved waste disposal plant.

**Other hazards**

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.  
Vapors may form explosive mixture with air.

---

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Propan-2-ol	67-63-0	>= 70 - < 90

Actual concentration is withheld as a trade secret

---

### SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical ad-

# SAFETY DATA SHEET



## DryFilm 2000/IPA

Version 6.6      Revision Date: 08/27/2021      SDS Number: 1331647-00040      Date of last issue: 11/06/2020  
Date of first issue: 02/27/2017

---

- vice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention if symptoms occur.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water  
for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Inhalation may provoke the following symptoms:  
Dizziness  
Drowsiness  
Eye contact may provoke the following symptoms  
Irritation  
Causes serious eye irritation.  
May cause drowsiness or dizziness.
- Protection of first-aiders : First Aid responders should pay attention to self-protection,  
and use the recommended personal protective equipment  
when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread  
fire.  
Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides  
Hydrogen fluoride  
carbonyl fluoride  
potentially toxic fluorinated compounds

# SAFETY DATA SHEET



## DryFilm 2000/IPA

Version 6.6      Revision Date: 08/27/2021      SDS Number: 1331647-00040      Date of last issue: 11/06/2020  
Date of first issue: 02/27/2017

---

- aerosolized particulates
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Ventilate the area.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
- 

### SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.

# SAFETY DATA SHEET



## DryFilm 2000/IPA

Version 6.6      Revision Date: 08/27/2021      SDS Number: 1331647-00040      Date of last issue: 11/06/2020  
Date of first issue: 02/27/2017

---

- Advice on safe handling : Avoid breathing mist or vapors.  
Do not swallow.  
Do not get in eyes.  
Avoid prolonged or repeated contact with skin.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Non-sparking tools should be used.  
Keep container tightly closed.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.  
Store locked up.  
Keep tightly closed.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Keep away from heat and sources of ignition.
- Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents  
Organic peroxides  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives  
Gases
- Further information on storage stability : Do not freeze.

---

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		ST	500 ppm 1,225 mg/m <sup>3</sup>	NIOSH REL
		TWA	400 ppm 980 mg/m <sup>3</sup>	NIOSH REL
		TWA	400 ppm 980 mg/m <sup>3</sup>	OSHA Z-1

# SAFETY DATA SHEET



## DryFilm 2000/IPA

Version 6.6      Revision Date: 08/27/2021      SDS Number: 1331647-00040      Date of last issue: 11/06/2020  
 Date of first issue: 02/27/2017

### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrofluoric acid	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
		C	6 ppm 5 mg/m <sup>3</sup>	NIOSH REL
Carbonyl difluoride	353-50-4	TWA	3 ppm 2.5 mg/m <sup>3</sup>	NIOSH REL
		TWA	3 ppm	OSHA Z-2
		TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m <sup>3</sup>	NIOSH REL
Carbon dioxide	124-38-9	ST	5 ppm 15 mg/m <sup>3</sup>	NIOSH REL
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	NIOSH REL
		ST	30,000 ppm 54,000 mg/m <sup>3</sup>	NIOSH REL
Carbon monoxide	630-08-0	TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	OSHA Z-1
		TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m <sup>3</sup>	NIOSH REL
		C	200 ppm 229 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm 55 mg/m <sup>3</sup>	OSHA Z-1

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
 Minimize workplace exposure concentrations.  
 If sufficient ventilation is unavailable, use with local exhaust ventilation.

# SAFETY DATA SHEET



## DryFilm 2000/IPA

Version 6.6      Revision Date: 08/27/2021      SDS Number: 1331647-00040      Date of last issue: 11/06/2020  
Date of first issue: 02/27/2017

---

Use explosion-proof electrical, ventilating and lighting equipment.

### Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

### Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

# SAFETY DATA SHEET



## DryFilm 2000/IPA

Version 6.6      Revision Date: 08/27/2021      SDS Number: 1331647-00040      Date of last issue: 11/06/2020  
Date of first issue: 02/27/2017

---

Color : white, translucent

Odor : alcohol-like, characteristic

Odor Threshold : No data available

pH : 4 - 7

Melting point/freezing point : -128 °F / -89 °C

Initial boiling point and boiling range : 180 °F / 82 °C

Flash point : 54 °F / 12 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper flammability limit : 12.0 %(V)

Lower explosion limit / Lower flammability limit : 2.0 %(V)

Vapor pressure : 44 hPa (68 °F / 20 °C)

Relative vapor density : 2.07  
(Air = 1.0)

Relative density : 0.89 (72 °F / 22 °C)

Solubility(ies)  
Water solubility : partly soluble

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : 750 °F / 399 °C

Decomposition temperature : 572 °F / 300 °C

Viscosity  
Viscosity, kinematic : No data available

Explosive properties : Not explosive



# SAFETY DATA SHEET



## DryFilm 2000/IPA

Version 6.6      Revision Date: 08/27/2021      SDS Number: 1331647-00040      Date of last issue: 11/06/2020  
Date of first issue: 02/27/2017

---

Oxidizing properties : The substance or mixture is not classified as oxidizing.  
Particle size : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.  
Chemical stability : Stable under normal conditions.  
Possibility of hazardous reactions : Highly flammable liquid and vapor.  
Vapors may form explosive mixture with air.  
Can react with strong oxidizing agents.  
Hazardous decomposition products will be formed at elevated temperatures.  
Conditions to avoid : Heat, flames and sparks.  
Incompatible materials : Oxidizing agents

#### Hazardous decomposition products

Thermal decomposition : Hydrofluoric acid  
Carbonyl difluoride  
Carbon dioxide  
Carbon monoxide

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

##### Propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): > 25 mg/l  
Exposure time: 6 h  
Test atmosphere: vapor  
Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

#### Skin corrosion/irritation

Not classified based on available information.

# SAFETY DATA SHEET



## DryFilm 2000/IPA

Version 6.6      Revision Date: 08/27/2021      SDS Number: 1331647-00040      Date of last issue: 11/06/2020  
Date of first issue: 02/27/2017

---

### Components:

#### **Propan-2-ol:**

Species : Rabbit  
Result : No skin irritation

#### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### Components:

#### **Propan-2-ol:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

#### **Respiratory or skin sensitization**

##### **Skin sensitization**

Not classified based on available information.

##### **Respiratory sensitization**

Not classified based on available information.

### Components:

#### **Propan-2-ol:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

#### **Germ cell mutagenicity**

Not classified based on available information.

### Components:

#### **Propan-2-ol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
  
Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

#### **Carcinogenicity**

Not classified based on available information.

# SAFETY DATA SHEET



## DryFilm 2000/IPA

Version 6.6      Revision Date: 08/27/2021      SDS Number: 1331647-00040      Date of last issue: 11/06/2020  
Date of first issue: 02/27/2017

---

### Components:

#### **Propan-2-ol:**

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 104 weeks  
Method : OECD Test Guideline 451  
Result : negative

**IARC** No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### **Reproductive toxicity**

Not classified based on available information.

### Components:

#### **Propan-2-ol:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

### **STOT-single exposure**

May cause drowsiness or dizziness.

### Components:

#### **Propan-2-ol:**

Assessment : May cause drowsiness or dizziness.

### **STOT-repeated exposure**

Not classified based on available information.

### **Repeated dose toxicity**

### Components:

#### **Propan-2-ol:**

Species : Rat  
NOAEL : 12.5 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 104 Weeks

# SAFETY DATA SHEET



## DryFilm 2000/IPA

Version 6.6      Revision Date: 08/27/2021      SDS Number: 1331647-00040      Date of last issue: 11/06/2020  
Date of first issue: 02/27/2017

---

### Aspiration toxicity

Not classified based on available information.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### Propan-2-ol:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 24 h
- Toxicity to microorganisms : EC50 (Pseudomonas putida): > 1,050 mg/l  
Exposure time: 16 h

### Persistence and degradability

#### Components:

##### Propan-2-ol:

- Biodegradability : Result: rapidly degradable
- BOD/COD : BOD: 1.19 (BOD5)COD: 2.23BOD/COD: 53 %

### Bioaccumulative potential

#### Components:

##### Propan-2-ol:

- Partition coefficient: n-octanol/water : log Pow: 0.05

### Mobility in soil

No data available

### Other adverse effects

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

- Waste from residues : Dispose of in accordance with local regulations.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or ex-

# SAFETY DATA SHEET



## DryFilm 2000/IPA

Version            Revision Date:            SDS Number:            Date of last issue: 11/06/2020  
6.6                08/27/2021                1331647-00040            Date of first issue: 02/27/2017

---

pose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

UN number                : UN 1219  
Proper shipping name    : ISOPROPANOL SOLUTION  
Class                     : 3  
Packing group            : II  
Labels                    : 3

##### IATA-DGR

UN/ID No.                : UN 1219  
Proper shipping name    : Isopropanol solution  
Class                     : 3  
Packing group            : II  
Labels                    : Flammable Liquids  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

##### IMDG-Code

UN number                : UN 1219  
Proper shipping name    : ISOPROPANOL SOLUTION  
  
Class                     : 3  
Packing group            : II  
Labels                    : 3  
EmS Code                 : F-E, S-D  
Marine pollutant         : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

##### 49 CFR

UN/ID/NA number        : UN 1219  
Proper shipping name    : Isopropanol SOLUTION  
  
Class                     : 3  
Packing group            : II  
Labels                    : FLAMMABLE LIQUID  
ERG Code                 : 129  
Marine pollutant         : no

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

# SAFETY DATA SHEET



## DryFilm 2000/IPA

Version 6.6      Revision Date: 08/27/2021      SDS Number: 1331647-00040      Date of last issue: 11/06/2020  
Date of first issue: 02/27/2017

---

### SECTION 15. REGULATORY INFORMATION

#### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Serious eye damage or eye irritation  
Specific target organ toxicity (single or repeated exposure)

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Propan-2-ol      67-63-0      >= 70 - < 90 %

#### Volatile organic compounds (VOC) content

VOC content: 719.2 g/l  
Remarks: less exempt

VOC content: 719.2 g/l  
Remarks: as packaged

#### US State Regulations

##### Pennsylvania Right To Know

Propan-2-ol      67-63-0  
Fluoropolymer      Trade secret

##### California Prop. 65

WARNING: This product can expose you to chemicals including Pentadecafluorooctanoic acid, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov). Note to User: This product is not made with PFOA nor is PFOA intentionally present in the product; however, it is possible that PFOA may be present as an impurity at background (environmental) levels.

##### California List of Hazardous Substances

Propan-2-ol      67-63-0

##### California Permissible Exposure Limits for Chemical Contaminants

Propan-2-ol      67-63-0

---

### SECTION 16. OTHER INFORMATION

#### Further information


# SAFETY DATA SHEET



## DryFilm 2000/IPA

Version 6.6      Revision Date: 08/27/2021      SDS Number: 1331647-00040      Date of last issue: 11/06/2020  
Date of first issue: 02/27/2017

### NFPA 704:



### HMIS® IV:

HEALTH	/	2
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information. For further information contact the local Chemours office or nominated distributors.

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	:	USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organiza-

# SAFETY DATA SHEET



## DryFilm 2000/IPA

Version	Revision Date:	SDS Number:	Date of last issue: 11/06/2020
6.6	08/27/2021	1331647-00040	Date of first issue: 02/27/2017

---

tion; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 08/27/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8