

**Eastman(TM) Cellulose Acetate Propionate  
(CAP-482-20)**

Version	Revision Date:	SDS Number:	Date of last issue: -
2.1	08/28/2019	150000001224	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

---

**SECTION 1. IDENTIFICATION**

Product name : Eastman(TM) Cellulose Acetate Propionate (CAP-482-20)

Product code : 01861-00, P0186152, P0186100, P0186101, P0186132, P01861AB, P0186138, P01861SB, P0186139, E0186101, P0186108, P0186134, P01861A8, P018611S, P018611E, P01861AL, P01861TR, P0186140, P0186109, P01861EH, P0186179

**Manufacturer or supplier's details**

Company name of supplier : Eastman Chemical Company

Address : 200 South Wilcox Drive  
Kingsport TN 37660-5280

Telephone : (423) 229-2000

Emergency telephone : CHEMTREC: +1-800-424-9300, +1-703-527-3887 CCN7321

**Recommended use of the chemical and restrictions on use**

Recommended use : Polymer

Restrictions on use : None known.

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200**

Combustible dust

**GHS label elements**

Signal Word : Warning

Hazard Statements : May form combustible dust concentrations in air.

Precautionary Statements : **Prevention:**  
P210 Keep away from heat/sparks/open flames/hot surfaces.  
No smoking.  
P243 Take action to prevent static discharges.

**Disposal:**  
P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

**Other hazards**

None known.

**Eastman(TM) Cellulose Acetate Propionate  
(CAP-482-20)**

Version	Revision Date:	SDS Number:	Date of last issue: -
2.1	08/28/2019	150000001224	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Components**

Chemical name	CAS-No.	Concentration (% w/w)
cellulose acetate propionate	9004-39-1	100

**SECTION 4. FIRST AID MEASURES**

- If inhaled : Move to fresh air.  
Treat symptomatically.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off with soap and water.  
If symptoms persist, call a physician.  
Cool skin rapidly with cold water after contact with molten material.  
Do not peel solidified product off the skin.  
Burns must be treated by a physician.
- In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Remove contact lenses, if present and easy to do. Continue rinsing.
- If swallowed : Seek medical advice.
- Most important symptoms and effects, both acute and delayed : The molten product can cause serious burns.
- Notes to physician : Treat symptomatically.

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Water spray  
Dry chemical  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.
- Specific hazards during fire fighting : Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
- Hazardous combustion products : No hazardous combustion products are known
- Further information : Minimize dust generation and accumulation.

**Eastman(TM) Cellulose Acetate Propionate  
(CAP-482-20)**

Version	Revision Date:	SDS Number:	Date of last issue: -
2.1	08/28/2019	150000001224	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

Special protective equipment : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Wear appropriate personal protective equipment. Local authorities should be advised if significant spillages cannot be contained.

Environmental precautions : Avoid release to the environment.

Methods and materials for containment and cleaning up : Sweep up and shovel into suitable containers for disposal.

**SECTION 7. HANDLING AND STORAGE**

Advice on protection against fire and explosion : Minimize dust generation and accumulation.

Advice on safe handling : Mixing cellulose esters in a nonpolar hydrocarbon, such as toluene or xylene, may result in the buildup of static electricity, which can cause a flash fire or an explosion. When adding cellulose ester to any flammable liquid, an inert gas atmosphere should be maintained within the vessel.

Conditions for safe storage : Keep container tightly closed.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Ingredients with workplace control parameters**

Contains no substances with occupational exposure limit values.

**Engineering measures** : Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Personal protective equipment**

Respiratory protection : If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Hand protection

**Eastman(TM) Cellulose Acetate Propionate  
(CAP-482-20)**

Version	Revision Date:	SDS Number:	Date of last issue: -
2.1	08/28/2019	150000001224	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

Remarks	: Wear suitable gloves. When handling hot material, use heat resistant gloves.
Eye protection	: Safety glasses Wear a face shield when working with molten material.
Skin and body protection	: Wear suitable protective clothing.
Protective measures	: Ensure that eye flushing systems and safety showers are located close to the working place.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: powder
Color	: white
Odor	: slight
Odor Threshold	: not determined
pH	: not determined
Melting point/range	: 370 - 410 °F / 188 - 210 °C
Boiling point/boiling range	: not determined
Flash point	: not applicable, combustible solid
Evaporation rate	: not determined
Upper explosion limit / Upper flammability limit	: not determined
Lower explosion limit / Lower flammability limit	: not determined
Vapor pressure	: not determined
Relative vapor density	: not determined
Relative density	: 1.22 - 1.26
Solubility(ies) Water solubility	: negligible

**Eastman(TM) Cellulose Acetate Propionate  
(CAP-482-20)**

Version	Revision Date:	SDS Number:	Date of last issue: -
2.1	08/28/2019	150000001224	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	810 °F / 432 °C Method: ASTM D2155
Decomposition temperature	:	Thermal stability not tested. Low stability hazard expected at normal operating temperatures.
Viscosity		
Viscosity, dynamic	:	not determined
Viscosity, kinematic	:	not determined
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Dust explosion class	:	St 2 - strong explosion

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	None reasonably foreseeable.
Chemical stability	:	Stable under normal conditions.
Conditions to avoid	:	Minimize dust generation and accumulation.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	Carbon monoxide Carbon dioxide (CO <sub>2</sub> )

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Product:**

Acute oral toxicity	:	Remarks: No data available
Acute inhalation toxicity	:	Remarks: No data available
Acute dermal toxicity	:	Remarks: No data available

**Components:****cellulose acetate propionate:**

Acute oral toxicity	:	LD50 Oral (Rat): > 6,400 mg/kg
---------------------	---	--------------------------------

**Eastman(TM) Cellulose Acetate Propionate  
(CAP-482-20)**

Version	Revision Date:	SDS Number:	Date of last issue: -
2.1	08/28/2019	150000001224	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

---

Remarks: (highest dose tested)

LD50 Oral (Mouse): &gt; 6,400 mg/kg

Remarks: (highest dose tested)

Acute dermal toxicity : LD50 Dermal (Guinea pig): > 5,000 mg/kg  
Remarks: (highest dose tested)

**Skin corrosion/irritation**

Not classified based on available information.

**Product:**

Remarks : No data available

**Components:****cellulose acetate propionate:**

Species : Guinea pig  
Exposure time : 24 h  
Result : slight

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks : No data available

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Product:**

Remarks : No data available

**Components:****cellulose acetate propionate:**

Test Type : Skin Sensitization  
Species : Guinea pig  
Result : Does not cause skin sensitization.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Eastman(TM) Cellulose Acetate Propionate  
(CAP-482-20)**

Version	Revision Date:	SDS Number:	Date of last issue: -
2.1	08/28/2019	150000001224	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

---

**Product:**

Remarks : This information is not available.

**IARC** No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified based on available information.

**Product:**

Effects on fertility : Remarks: No data available

**STOT-single exposure**

Not classified based on available information.

**Product:**

Remarks : No data available

**STOT-repeated exposure**

Not classified based on available information.

**Product:**

Remarks : No data available

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No data available

**Information on likely routes of exposure****Product:**

Inhalation : Remarks: None known.

Skin contact : Remarks: Molten material will produce thermal burns.

Eye contact : Remarks: Molten material will produce thermal burns.

Ingestion : Remarks: None known.

**Eastman(TM) Cellulose Acetate Propionate  
(CAP-482-20)**

Version	Revision Date:	SDS Number:	Date of last issue: -
2.1	08/28/2019	150000001224	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****cellulose acetate propionate:**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 mg/l  
Exposure time: 48 h  
Remarks: (highest concentration tested)

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

Not regulated as a dangerous good

**Eastman(TM) Cellulose Acetate Propionate  
(CAP-482-20)**

Version	Revision Date:	SDS Number:	Date of last issue: -
2.1	08/28/2019	150000001224	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

---

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Combustible dust

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**California Prop. 65**

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

**The ingredients of this product are reported in the following inventories:**

DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
ISHL	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TCSI	: On the inventory, or in compliance with the inventory
TSCA	: On the inventory, or in compliance with the inventory

**TSCA list**

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.


## Eastman(TM) Cellulose Acetate Propionate (CAP-482-20)

Version	Revision Date:	SDS Number:	Date of last issue: -
2.1	08/28/2019	150000001224	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

### SECTION 16. OTHER INFORMATION

#### Further information

##### NFPA 704:



##### HMIS® IV:

HEALTH	/	1
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amend-

**Eastman(TM) Cellulose Acetate Propionate  
(CAP-482-20)**

Version	Revision Date:	SDS Number:	Date of last issue: -
2.1	08/28/2019	150000001224	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

---

ments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 08/28/2019

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8