

Version 1.1 Revision Date 2020-04-09

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

**Product information** 

Product Name : PRF Octane Blend No. 80

Material : 1024376, 1024372, 1024375, 1024374, 1093788, 1024377

Use : Reference Fuel

Company : Chevron Phillips Chemical Company LP

Specialty Chemicals 10001 Six Pines Drive The Woodlands, TX 77380

#### **Emergency telephone:**

Health:

866.442.9628 (North America) 1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090 EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

Responsible Department : Product Safety and Toxicology Group

E-mail address : SDS@CPChem.com Website : www.CPChem.com

#### **SECTION 2: Hazards identification**

#### Classification of the substance or mixture

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

Classification

: Flammable liquids, Category 2 Skin irritation, Category 2

Specific target organ toxicity - single exposure, Category 3,

Central nervous system
Aspiration hazard, Category 1

SDS Number:100000100076 1/16

## PRF Octane Blend No. 80

Version 1.1 Revision Date 2020-04-09

#### Labeling

Symbol(s)







Signal Word Danger

**Hazard Statements** : H225: Highly flammable liquid and vapor.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

**Precautionary Statements Prevention:** 

> Keep away from heat/ sparks/ open flames/ hot P210

surfaces. No smoking.

Keep container tightly closed. P233

Ground/bond container and receiving equipment. P240

P241 Use explosion-proof electrical/ ventilating/ lighting/

equipment.

P242 Use only non-sparking tools.

Take precautionary measures against static discharge. P243

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

IF ON SKIN (or hair): Take off P303 + P361 + P353 immediately all contaminated clothing. Rinse skin with water/

shower

P304 + P340 + P312 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Call a POISON

CENTER/ doctor if you feel unwell. Do NOT induce vomiting. P331

Take off contaminated clothing and wash before reuse. P362

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Carcinogenicity:

**IARC** No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

**NTP** No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SDS Number:100000100076

2/16

## PRF Octane Blend No. 80

Version 1.1 Revision Date 2020-04-09

#### **SECTION 3: Composition/information on ingredients**

Synonyms : Primary Reference Fuel

PRF (ASTM) Octane Blend No. 80

Octane Reference Fuel

Molecular formula : Mixture

Component	CAS-No.	Weight %
2,2,4-Trimethylpentane (Isooctane)	540-84-1	79.9 - 80.1
n-Heptane	142-82-5	19.7 - 20.3

#### **SECTION 4: First aid measures**

General advice : Move out of dangerous area. Show this material safety data

sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

If inhaled : Consult a physician after significant exposure. If unconscious,

place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well

with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution. Remove contact

lenses. Protect unharmed eye. Keep eye wide open while

rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Never give anything by mouth to

an unconscious person. If symptoms persist, call a physician.

Take victim immediately to hospital.

#### **SECTION 5: Firefighting measures**

Flash point : -8°C (18°F)

Method: Tag closed cup

Autoignition temperature : No data available

Suitable extinguishing

media

: Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable extinguishing

media

: High volume water jet.

Specific hazards during fire

fighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Special protective

equipment for fire-fighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in

SDS Number:100000100076 3/16

## PRF Octane Blend No. 80

Version 1.1 Revision Date 2020-04-09

accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

Fire and explosion protection

 Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames,

hot surfaces and sources of ignition.

Hazardous decomposition

products

: Carbon oxides.

#### **SECTION 6: Accidental release measures**

Personal precautions : Use personal protective equipment. Ensure adequate

ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low

areas.

Environmental precautions : Prevent product from entering drains. Prevent further leakage

or spillage if safe to do so. If the product contaminates rivers

and lakes or drains inform respective authorities.

Methods for cleaning up : Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

## **SECTION 7: Handling and storage**

#### Handling

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid

exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with

local and national regulations.

Advice on protection against fire and explosion

Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames,

hot surfaces and sources of ignition.

## Storage

Requirements for storage areas and containers

: No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

SDS Number:100000100076 4/16

## PRF Octane Blend No. 80

Version 1.1 Revision Date 2020-04-09

Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Use : Reference Fuel

### SECTION 8: Exposure controls/personal protection

#### Ingredients with workplace control parameters

#### US

Components	Basis	Value	Control parameters	Note
2,2,4-Trimethylpentane (Isooctane)	ACGIH	TWA	300 ppm,	
n-Heptane	OSHA Z-1	TWA	500 ppm, 2,000 mg/m3	
	OSHA Z-1-A	TWA	400 ppm, 1,600 mg/m3	
	OSHA Z-1-A	STEL	500 ppm, 2,000 mg/m3	
	ACGIH	TWA	400 ppm,	
	ACGIH	STEL	500 ppm.	

#### Immediately Dangerous to Life or Health Concentrations (IDLH)

Substance name	CAS-No.	Control parameters	Update
n-Heptane	142-82-5	Immediately Dangerous to Life or Health Concentration Value 750 parts per million	1995-03-01
		Immediately Dangerous to Life or Health Concentration Value 750 parts per million	1995-03-01

#### **Engineering measures**

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

#### Personal protective equipment

Respiratory protection

: Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as:. Air-Purifying Respirator for Organic Vapors. Full-Face Air-Purifying Respirator for Organic Vapors, Dusts and Mists. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection

: The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

SDS Number:100000100076 5/16

## PRF Octane Blend No. 80

Version 1.1 Revision Date 2020-04-09

Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Flame retardant antistatic protective clothing. Workers should wear antistatic

footwear.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

## **SECTION 9: Physical and chemical properties**

## Information on basic physical and chemical properties

**Appearance** 

Physical state : Liquid
Color : Colorless
Odor : gasoline-like

Safety data

Flash point : -8°C (18°F)

Method: Tag closed cup

Lower explosion limit : 1 %(V)

Upper explosion limit : 7 %(V)

Oxidizing properties : No

Autoignition temperature : No data available

Molecular formula : Mixture

Molecular weight : Not applicable

pH : Not applicable

Freezing point : No data available

Pour point No data available

Boiling point/boiling range : 96-103°C (205-217°F)

Vapor pressure : 1.70 PSI

at 37.8°C (100.0°F)

Relative density : 0.693

at 15.6 °C (60.1 °F)

Water solubility : Negligible

Partition coefficient: n-

octanol/water

: No data available

Viscosity, kinematic : No data available

SDS Number:100000100076 6/16

## PRF Octane Blend No. 80

Version 1.1 Revision Date 2020-04-09

Relative vapor density : 3

(Air = 1.0)

Evaporation rate : 1

Percent volatile : > 99 %

## **SECTION 10: Stability and reactivity**

## Possibility of hazardous reactions

Hazardous reactions : Hazardous polymerization does not

occur.

Hazardous reactions: Vapors may form explosive mixture with

air.

Further information: No decomposition if stored and applied as

directed.

Conditions to avoid : Heat, flames and sparks.

Materials to avoid : May react with oxygen and strong oxidizing agents, such as

chlorates, nitrates, peroxides, etc.

Hazardous decomposition

products

: Carbon oxides

Other data : No decomposition if stored and applied as directed.

## **SECTION 11: Toxicological information**

PRF Octane Blend No. 80

Acute oral toxicity : LD50: > 5,000 mg/kg

Species: Rat

Method: Acute toxicity estimate

PRF Octane Blend No. 80

Acute inhalation toxicity : LC50: > 20 mg/l

Species: Rat

Test atmosphere: dust/mist Method: Acute toxicity estimate

PRF Octane Blend No. 80

Acute dermal toxicity : LD50: > 2,000 mg/kg

Species: Rabbit

Method: Acute toxicity estimate

PRF Octane Blend No. 80

**Skin irritation** : Skin irritation

largely based on animal evidence.

PRF Octane Blend No. 80

**Eye irritation** : No eye irritation

SDS Number:100000100076 7/16

## PRF Octane Blend No. 80

Version 1.1 Revision Date 2020-04-09

largely based on animal evidence.

PRF Octane Blend No. 80

Sensitization

: Did not cause sensitization on laboratory animals.

Repeated dose toxicity

2,2,4-Trimethylpentane

(Isooctane)

: Species: Rat, Male and female

Sex: Male and female

Application Route: Inhalation Dose: 0, 668, 2220, 6646 ppm Exposure time: 13 weeks

Number of exposures: 6 hr/day 5 d/wk

NOEL: 8.117 mg/l 2220 ppm Method: OECD Guideline 413

Information given is based on data obtained from similar

substances.

n-Heptane Species: Rat, male

Sex: male

Application Route: Inhalation

Dose: 12.47 mg/l Exposure time: 16 wk

Number of exposures: 12 h/d, 7 d/wk

NOEL: 12.47 mg/l

No adverse effect has been observed in chronic toxicity tests.

Species: Rat, Male and female

Sex: Male and female Application Route: Inhalation

Dose: 12.35 mg/l Exposure time: 26 wk

Number of exposures: 6 h/d, 5 d/wk Method: OECD Test Guideline 413

No adverse effect has been observed in chronic toxicity tests.

Genotoxicity in vitro

2,2,4-Trimethylpentane

(Isooctane)

: Test Type: Ames test

Method: Mutagenicity (Escherichia coli - reverse mutation

assay)

Result: negative

Test Type: Mouse lymphoma assay Method: OECD Guideline 476

Result: negative

Test Type: Sister Chromatid Exchange Assay

Result: negative

Test Type: Unscheduled DNA synthesis assay

Result: negative

n-Heptane Test Type: Ames test

Method: Mutagenicity (Escherichia coli - reverse mutation

assay)

Result: negative

SDS Number:100000100076

8/16

Version 1.1 Revision Date 2020-04-09

Test Type: Mammalian cell gene mutation assay

Method: OECD Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Guideline 473

Result: negative

Test Type: Mitotic recombination

Result: negative

#### Genotoxicity in vivo

2,2,4-Trimethylpentane

(Isooctane)

: Test Type: Unscheduled DNA synthesis assay

Species: Mouse Dose: 500 mg/kg Result: negative

Test Type: Unscheduled DNA synthesis assay

Species: Rat Dose: 500 mg/kg Result: negative

#### Reproductive toxicity

2,2,4-Trimethylpentane

(Isooctane)

Species: Rat

Sex: male and female Application Route: Inhalation Dose: 0, 900, 3000, 9000 ppm Number of exposures: 6 h/d 5 d/wk Method: OECD Test Guideline 416

NOAEL Parent: 3000 ppm NOAEL F1: 3000 ppm NOAEL F2: 3000 ppm

Information given is based on data obtained from similar

substances.

n-Heptane Species: Rat

Sex: male and female Application Route: Inhalation Dose: 0, 900, 3000, 9000 ppm Number of exposures: 6 hr/d, 5 d/wk

Test period: 13 wk

Method: OECD Test Guideline 416

NOAEL Parent: 9000 ppm NOAEL F1: 3000 ppm NOAEL F2: 3000 ppm

Information given is based on data obtained from similar

substances.

#### **Developmental Toxicity**

2,2,4-Trimethylpentane

(Isooctane)

: Species: Rat

Application Route: Inhalation Dose: 0, 400, 1200 ppm Number of exposures: 6h/d Test period: GD6-15

NOAEL Teratogenicity: 1200 ppm

SDS Number:100000100076 9/16

Version 1.1 Revision Date 2020-04-09

NOAEL Maternal: 1200 ppm

Information given is based on data obtained from similar

substances.

Species: Rat

Application Route: Inhalation Dose: 0, 900, 3000, 9000 ppm Number of exposures: 6h/d Test period: GD6-15

Method: OECD Guideline 414 NOAEL Teratogenicity: 9000 ppm NOAEL Maternal: 3000 ppm

Information given is based on data obtained from similar

substances.

n-Heptane Species: Rat

Application Route: Inhalation Dose: 0, 900, 3000, 9000 ppm Exposure time: GD6-15 Number of exposures: 6 hrs/d NOAEL Teratogenicity: 9000 ppm NOAEL Maternal: 3000 ppm

PRF Octane Blend No. 80

Aspiration toxicity

: May be fatal if swallowed and enters airways.

**CMR** effects

2,2,4-Trimethylpentane

(Isooctane)

: Mutagenicity: Tests on bacterial or mammalian cell cultures

did not show mutagenic effects.

Teratogenicity: Animal testing did not show any effects on

fetal development.

Reproductive toxicity: Animal testing did not show any effects

on fertility.

n-Heptane Mutagenicity: Tests on bacterial or mammalian cell cultures

did not show mutagenic effects.

Teratogenicity: Animal testing did not show any effects on

fetal development.

Reproductive toxicity: No toxicity to reproduction

PRF Octane Blend No. 80

**Further information** 

: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially

above the TLV value may cause narcotic effects. Solvents

may degrease the skin.

## **SECTION 12: Ecological information**

#### Toxicity to fish

2,2,4-Trimethylpentane

(Isooctane)

: LC50: 0.11 mg/l

Exposure time: 96 h

Species: Oncorhynchus mykiss (rainbow trout) semi-static test Method: OECD Test Guideline 203 Information given is based on data obtained from similar

SDS Number:100000100076 10/16

Version 1.1 Revision Date 2020-04-09

substances.

n-Heptane LL50: 5.738 mg/l

Exposure time: 96 h

Species: Oncorhynchus mykiss (rainbow trout)

Method: QSAR modeled data

#### Toxicity to daphnia and other aquatic invertebrates

2,2,4-Trimethylpentane : EC50: 0.4 mg/l

(Isooctane) Exposure time: 48 h

Species: Daphnia magna (Water flea)

static test Information given is based on data obtained from

similar substances.

n-Heptane EC50: 1.5 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea) static test Toxic to aquatic organisms.

LC50: 0.1 mg/l Exposure time: 96 h

Species: Mysidopsis bahia (mysid shrimp) semi-static test Very toxic to aquatic organisms.

#### Toxicity to algae

2,2,4-Trimethylpentane

(Isooctane)

: EL50: 2.943 mg/l Exposure time: 72 h

Method: QSAR modeled data

n-Heptane EL50: 4.338 mg/l

Exposure time: 72 h

Species: Pseudokirchneriella subcapitata (microalgae)

Method: QSAR

#### **Toxicity to fish (Chronic toxicity)**

n-Heptane : NOELR: 1.284 mg/l

Exposure time: 28 d

Species: Oncorhynchus mykiss (rainbow trout)

Method: QSAR modeled data

## Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

2,2,4-Trimethylpentane

: NOEL: 0.17 mg/l Exposure time: 21 d (Isooctane)

Species: Daphnia magna (Water flea)

Method: OECD Test Guideline 211

Information given is based on data obtained from similar

substances.

Biodegradability

SDS Number:100000100076 11/16

## PRF Octane Blend No. 80

Version 1.1 Revision Date 2020-04-09

2,2,4-Trimethylpentane

(Isooctane)

: Result: Not readily biodegradable. Method: OECD Test Guideline 301

Expected to be inherently biodegradable.

Information given is based on data obtained from similar

substances.

n-Heptane : Result: Readily biodegradable.

70 %

Testing period: 10 d

Results of PBT assessment

2,2,4-Trimethylpentane

: Non-classified PBT substance, Non-classified vPvB substance

(Isooctane)

n-Heptane : Non-classified PBT substance, Non-classified vPvB substance

Additional ecological

information

: Very toxic to aquatic life with long lasting effects.

**Ecotoxicology Assessment** 

Short-term (acute) aquatic

hazard

uatic : Very toxic to aquatic life.

Long-term (chronic) aquatic

hazard

: Very toxic to aquatic life with long lasting effects.

## **SECTION 13: Disposal considerations**

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water

courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed

waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product.

Do not re-use empty containers. Do not burn, or use a cutting

torch on, the empty drum.

## **SECTION 14: Transport information**

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

#### **US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)**

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, MARINE POLLUTANT, (2,2,4-

SDS Number:100000100076 12/16

Version 1.1 Revision Date 2020-04-09

TRIMETHYLPENTANE (ISOOCTANE), HEPTANE)

### **IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)**

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, (-8°C), MARINE POLLUTANT, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), HEPTANE)

#### IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II

## ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), HEPTANE)

## RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), HEPTANE)

# ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), HEPTANE)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

#### **SECTION 15: Regulatory information**

#### **National legislation**

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Skin corrosion or irritation

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

CERCLA Reportable

Quantity

: 1020 lbs

2,2,4-Trimethylpentane (Isooctane)

SARA 302 Reportable

Quantity

: This material does not contain any components with a SARA

302 RQ.

SARA 302 Threshold

Planning Quantity

: This material does not contain any components with a section

302 EHS TPQ.

SARA 304 Reportable : This material does not contain any components with a section

SDS Number:100000100076 13/16

## PRF Octane Blend No. 80

Version 1.1 Revision Date 2020-04-09

Quantity 304 EHS RQ.

SARA 313 Components : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### Clean Air Act

Ozone-Depletion Potential

: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR

82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

: 2,2,4-Trimethylpentane (Isooctane) - 540-84-1

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

### **US State Regulations**

Pennsylvania Right To Know

: 2,2,4-Trimethylpentane (Isooctane) - 540-84-1

n-Heptane - 142-82-5

California Prop. 65

Components

: This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive

defects.

**Notification status** 

Europe REACH : This mixture contains only ingredients which have been

registered according to Regulation (EU) No. 1907/2006

(REACH).

SDS Number:100000100076 14/16

Version 1.1 Revision Date 2020-04-09

Switzerland CH INV : On the inventory, or in compliance with the inventory

United States of America (USA) : On or in compliance with the active portion of the

TSCA TSCA inventory

Canada DSL : All components of this product are on the Canadian

DSL

Australia AICS : On the inventory, or in compliance with the inventory
New Zealand NZIoC : On the inventory, or in compliance with the inventory
Japan ENCS : On the inventory, or in compliance with the inventory
Con the inventory, or in compliance with the inventory
Korea KECI : All substances in this product were registered, notified

All substances in this product were registered, notified to be registered, or exempted from registration by CPChem through an Only Representative according to K-REACH regulations. Importation of this product is permitted if the Korean Importer of Record was included on CPChem's notifications or if the Importer of


Record themselves notified the substances.

Philippines PICCS : On the inventory, or in compliance with the inventory China IECSC : On the inventory, or in compliance with the inventory Taiwan TCSI : On the inventory, or in compliance with the inventory

#### **SECTION 16: Other information**

NFPA Classification : Health Hazard: 2

Fire Hazard: 3 Reactivity Hazard: 0



#### **Further information**

Legacy SDS Number : 28440

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of

SDS Number:100000100076 15/16

## PRF Octane Blend No. 80

Version 1.1 Revision Date 2020-04-09

			Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		

SDS Number:100000100076 16/16