

# SAFETY DATA SHEET

### THE DOW CHEMICAL COMPANY\*

Product name: PARALOID™ K-175 PROCCESING AID Issue Date: 03/25/2015

**Print Date:** 03/26/2015

THE DOW CHEMICAL COMPANY\* encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

### 1. IDENTIFICATION

Product name: PARALOID™ K-175 PROCCESING AID

Recommended use of the chemical and restrictions on use

Identified uses: Plastics Additive

### **COMPANY IDENTIFICATION**

THE DOW CHEMICAL COMPANY\*
Agent for Rohm and Haas Chemicals LLC
100 INDEPENDENCE MALL WEST
PHILADELPHIA PA 19106-2399
UNITED STATES

Customer Information Number: 215-592-3000

SDSQuestion@dow.com

#### **EMERGENCY TELEPHONE NUMBER**

**24-Hour Emergency Contact:** 1 800 424 9300 **Local Emergency Contact:** 989-636-4400

### 2. HAZARDS IDENTIFICATION

#### Hazard classification

This material is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Combustible dust

#### Label elements

Signal word: WARNING!

## **Hazards**

May form combustible dust concentrations in air

### **Precautionary statements**

#### Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting/ equipment.
Take precautionary measures against static discharge.

#### Other hazards

no data available

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Synonyms:** 2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate and ethenylbenzene

This product is a substance.

ComponentCASRNConcentrationP(BA/MMA/STY)27136-15-899.0 - 100.0 %Individual residual monomersNot Required< 0.1 %</td>

### 4. FIRST AID MEASURES

# Description of first aid measures

Inhalation: Move to fresh air.

**Skin contact:** Wash with water and soap as a precaution. Remove and wash contaminated clothing before re-use. If skin irritation persists, call a physician.

**Eye contact:** Rinse with water. If eye irritation persists, consult a specialist.

**Ingestion:** Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person. Consult a physician if necessary.

**Most important symptoms and effects, both acute and delayed:** Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

### 5. FIREFIGHTING MEASURES

Suitable extinguishing media: Carbon dioxide (CO2) Dry chemical Water spray

Unsuitable extinguishing media: no data available

Special hazards arising from the substance or mixture

Page 2 of 9

Product name: PARALOID™ K-175 PROCCESING AID Issue Date: 03/25/2015

Hazardous combustion products: Carbon oxides

**Unusual Fire and Explosion Hazards:** Material as sold is combustible; burns vigorously with intense heat. Dusts at sufficient concentrations can form explosive mixtures with air. DO NOT use a solid stream of water. A solid stream of water directed at this material may create a potentially explosive airborne dust mixture.

Advice for firefighters

Fire Fighting Procedures: no data available

**Special protective equipment for firefighters:** Wear self-contained breathing apparatus and protective suit.

### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures:** Wear compatible, chemically resistant gloves. Use personal protective equipment. Avoid breathing dust. Material can create slippery conditions. Remove all sources of ignition. Ensure adequate ventilation.

**Environmental precautions:** CAUTION: Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

**Methods and materials for containment and cleaning up:** Sweep up and shovel into suitable containers for disposal. Use water spray to keep dusting to a minimum.

#### 7. HANDLING AND STORAGE

**Precautions for safe handling:** Do not breathe dust. Do not breathe vapors, mist or gas. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep away from heat and sources of ignition. Ground all metal containers during storage and handling. Ensure adequate ventilation. Keep container tightly closed.

**Conditions for safe storage:** Store at room temperature in the original container. Keep away from heat and sources of ignition. Material can burn; limit indoor storage to approved areas equipped with automatic sprinklers. Avoid all ignition sources. This material is not hazardous under normal storage conditions. However, all materials of this type release some monomer vapors or gases when stored for prolonged periods at elevated temperatures.

**Other data:** Avoid high concentrations of dust in air and accumulation of dust on equipment. An airborne dust of this material can create a dust explosion. When handling and processing this material local exhaust ventilation may be required to control dust and reduce exposure to vapors. To prevent dust explosions employ bonding and grounding for operations capable of generating static electricity. Protect all equipment from explosions by following the guidelines in NFPA-68 and NFPA-69. For electrical equipment follow local codes and electrical classification NFPA-70 (the National Electrical Code), class II, division 2, group G.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control parameters**

Exposure limits are listed below, if they exist.

Exposure limits are listed bein	w, ii they exist.		
	Regulation	Type of listing	Value/Notation

Page 3 of 9

Product Rohm and Haas TWA Respirable 1 mg/m3 fraction.

#### **Exposure controls**

**Engineering controls:** Use explosion-proof local exhaust ventilation with a minimum capture velocity of 150 ft/min (0.75 m/sec) at the point of dust or mist evolution. Refer to the current edition of Industrial Ventilation: A Manual of Recommended Practice published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

**Protective measures:** Facilities storing or utilizing this material should be equipped with an eyewash facility.

#### Individual protection measures

**Eye/face protection:** Safety glasses with side-shields Eye protection worn must be compatible with respiratory protection system employed.

Skin protection

Hand protection: For prolonged or repeated contact use protective gloves. Respiratory protection: A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements or equivalent must be followed whenever workplace conditions warrant a respirator's use. None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. When dusty conditions are encountered, wear a properly fitted NIOSH approved (or equivalent) half-mask, air-purifying respirator. Air-purifying respirators should be equipped with NIOSH approved (or equivalent) N95 filters. If oil mist is present, use R95 or P95 filters.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** 

Physical state powder

Color Free-flowing white
Odor Pungent, sweet odor
Odor Threshold no data available
pH no data available

Melting point/range 132.00 - 149.00 °C (269.60 - 300.20 °F)

Freezing point no data available

Boiling point (760 mmHg) Not applicable

Flash point no data available

Evaporation Rate (Butyl Acetate Not applicable

= 1)

Flammability (solid, gas) May form combustible dust concentrations in air

Lower explosion limitno data availableUpper explosion limitNot applicableVapor PressureNot applicableRelative Vapor Density (air = 1)Not applicable

Relative Density (water = 1) 1.1100

Product name: PARALOID™ K-175 PROCCESING AID

Water solubility insoluble

Partition coefficient: n- no data available

octanol/water

Auto-ignition temperature 400.00 °C (752.00 °F)

Decomposition temperatureno data availableDynamic ViscosityNot applicableKinematic Viscosityno data availableExplosive propertiesno data availableOxidizing propertiesno data availableMolecular weightno data availablePercent volatilityno data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

### 10. STABILITY AND REACTIVITY

Reactivity: no data available

Chemical stability: no data available

Possibility of hazardous reactions: None known.

Product will not undergo polymerization.

Stable

Conditions to avoid: no data available

**Incompatible materials:** Prolonged contact with acids, alkalies and strong oxidizing agents may attack or dissolve the polymer.

**Hazardous decomposition products:** Heating above the decomposition temperature will release acrylic monomers.

# 11. TOXICOLOGICAL INFORMATION

Toxicological information on this product or its components appear in this section when such data is available.

### **Acute toxicity**

**Acute oral toxicity** 

For similar material(s): LD50, Rat, > 5,000 mg/kg

**Acute dermal toxicity** 

For similar material(s):

LD50, Rabbit, > 5,000 mg/kg

## Acute inhalation toxicity

For similar material(s):

LC50, Rat, 4 Hour, dust/mist, > 3.4 mg/l The LC50 value is greater than the Maximum Attainable Concentration.

#### Skin corrosion/irritation

For similar material(s):

Brief contact may cause slight skin irritation with local redness.

#### Serious eye damage/eye irritation

For similar material(s):

May cause slight eye irritation.

#### Sensitization

Product test data not available.

# **Specific Target Organ Systemic Toxicity (Single Exposure)**

Product test data not available.

### Specific Target Organ Systemic Toxicity (Repeated Exposure)

A 13-week inhalation study in rats of a compositionally similar acrylic powder showed inflammatory effects in the lung at concentrations of 6 mg/m3 for 6 hours per day, 5 days per week. These findings were consistent with high concentration exposure effects reported for other non-soluble dusts. Maintaining airborne dust concentrations within the recommended exposure limit is not expected to produce adverse effects within the lung.

#### Carcinogenicity

Product test data not available.

#### **Teratogenicity**

Product test data not available.

#### Reproductive toxicity

Product test data not available.

### Mutagenicity

Product test data not available.

# **Aspiration Hazard**

Product test data not available.

### **Additional information**

Information given is based on data obtained from similar substances.

# 12. ECOLOGICAL INFORMATION

Ecotoxicological information on this product or its components appear in this section when such data is available.

Product name: PARALOID™ K-175 PROCCESING AID

#### **General Information**

There is no data available for this product.

**Toxicity** 

### P(BA/MMA/STY)

Acute toxicity to fish

No relevant data found.

Persistence and degradability

### P(BA/MMA/STY)

Biodegradability: No relevant data found.

Bioaccumulative potential

#### P(BA/MMA/STY)

Bioaccumulation: No relevant data found.

Mobility in soil

### P(BA/MMA/STY)

No relevant data found.

# 13. DISPOSAL CONSIDERATIONS

**Disposal methods:** Place powder in air-tight bags. For disposal, incinerate or landfill at a permitted facility in accordance with local, state, and federal regulations.

# 14. TRANSPORT INFORMATION

DOT

Not regulated for transport

#### Classification for SEA transport (IMO-IMDG):

Not regulated for transport

Consult IMO regulations before transporting ocean bulk

Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code

# Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional

Page 7 of 9

transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

Issue Date: 03/25/2015

### 15. REGULATORY INFORMATION

#### **OSHA Hazard Communication Standard**

This product is considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Chronic Health Hazard

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This product does not contain a chemical which is listed in Section 313 at or above de minimis concentrations.

### **Pennsylvania**

Any material listed as "Not Hazardous" in the CAS REG NO. column of SECTION 2, Composition/Information On Ingredients, of this MSDS is a trade secret under the provisions of the Pennsylvania Worker and Community Right-to-Know Act.

### **United States TSCA Inventory (TSCA)**

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

.

### 16. OTHER INFORMATION

# **Hazard Rating System**

Н	MIS		
	Health	Flammability	Physical
	Health	i iaiiiiiabiiity	Hazard
	1	1	0

#### Revision

Identification Number: 101080356 / 1001 / Issue Date: 03/25/2015 / Version: 2.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

#### Legend

	O .		
Rohm and Haas	Rohm and Haas OEL's		

Page 8 of 9

TWA Time Weighted Average (TWA):

#### **Information Source and References**

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY\* urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

Page 9 of 9