

Version 1.7 Revision Date 2020-04-08

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product information

Product Name : Jet RF (AMS 2629B Type 1)

Material : 1102078, 1024360, 1024363, 1024362, 1024361, 1105002

Use : Reference Fluid

Company : Chevron Phillips Chemical Company LP

Specialty Chemicals 10001 Six Pines Drive The Woodlands, TX 77380

Emergency telephone:

Health:

866.442.9628 (North America) 1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090 EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

Responsible Department : Product Safety and Toxicology Group

E-mail address : SDS@CPChem.com Website : www.CPChem.com

SECTION 2: Hazards identification

Classification of the substance or mixture

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

Classification

: Flammable liquids, Category 2 Skin irritation, Category 2 Reproductive toxicity, Category 2

Specific target organ toxicity - single exposure, Category 3,

Central nervous system

Specific target organ toxicity - repeated exposure, Category 2,

SDS Number:100000014265 1/19

Version 1.7 Revision Date 2020-04-08

Inhalation, Auditory organs, color vision Aspiration hazard, Category 1

Labeling

Symbol(s)







Signal Word : Danger

Hazard Statements : H225: Highly flammable liquid and vapor.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness. H361d: Suspected of damaging the unborn child.

H373: May cause damage to organs (Auditory organs, color vision) through prolonged or repeated exposure if inhaled.

Precautionary Statements

: Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapor/spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON

CENTER/ doctor if you feel unwell.
P308 + P313 IF exposed or concerned: Get medical advice/

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

attention.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Version 1.7 Revision Date 2020-04-08

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Carcinogenicity:

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 3: Composition/information on ingredients

Synonyms Jet RF (AMS 2629B Type 1)

Molecular formula Mixture

Component	CAS-No.	Weight %
Cyclohexane	110-82-7	30 - 60
2,2,4-Trimethylpentane (Isooctane)	540-84-1	30 - 60
Toluene	108-88-3	25 - 60
tert-Butyl Disulfide	110-06-5	1 - 5

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data

sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

If inhaled : Consult a physician after significant exposure. If unconscious,

place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well

with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution. Remove contact

lenses. Protect unharmed eye. Keep eye wide open while

rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Never give anything by mouth to

an unconscious person. If symptoms persist, call a physician.

Take victim immediately to hospital.

SECTION 5: Firefighting measures

: -17°C (1°F) Flash point

Autoignition temperature : No data available

SDS Number:100000014265 3/19

SAFETY DATA SHEET

Jet RF (AMS 2629B Type 1)

Version 1.7 Revision Date 2020-04-08

Suitable extinguishing

media

: Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable extinguishing

media

High volume water jet.

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Special protective

equipment for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed

of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed

containers.

Fire and explosion

protection

Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames,

hot surfaces and sources of ignition.

Hazardous decomposition

products

: Hydrocarbons. Carbon oxides.

SECTION 6: Accidental release measures

Personal precautions : Use personal protective equipment. Ensure adequate

ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low

areas.

Environmental precautions : Prevent product from entering drains. Prevent further leakage

or spillage if safe to do so. If the product contaminates rivers

and lakes or drains inform respective authorities.

Methods for cleaning up : Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

SECTION 7: Handling and storage

Handling

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid

exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with

SDS Number:100000014265 4/19

Version 1.7 Revision Date 2020-04-08

local and national regulations.

Advice on protection against fire and explosion

: Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers

: No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Use : Reference Fluid

SECTION 8: Exposure controls/personal protection

Ingredients with workplace control parameters

US

Components	Basis	Value	Control parameters	Note
Cyclohexane	ACGIH	TWA	100 ppm,	
	OSHA Z-1	TWA	300 ppm, 1,050 mg/m3	
	OSHA Z-1-A	TWA	300 ppm, 1,050 mg/m3	
2,2,4-Trimethylpentane (Isooctane)	ACGIH	TWA	300 ppm,	
Toluene	ACGIH	TWA	20 ppm,	A4,
	OSHA Z-2	TWA	200 ppm,	
	OSHA Z-2	CEIL	300 ppm,	
_	OSHA Z-2	Peak	500 ppm,	
	OSHA Z-1-A	TWA	100 ppm, 375 mg/m3	
	OSHA Z-1-A	STEL	150 ppm, 560 mg/m3	

A4 Not classifiable as a human carcinogen

Immediately Dangerous to Life or Health Concentrations (IDLH)

Substance name	CAS-No.	Control parameters	Update
Cyclohexane	110-82-7	Immediately Dangerous to Life or Health Concentration Value 1300 parts per million	
Toluene	108-88-3	Immediately Dangerous to Life or Health Concentration Value 500 parts per million	

Biological exposure indices

US

03				
Substance name	CAS-No.	Control parameters	Sampling time	Update
Toluene	108-88-3	Toluene: 0.02 mg/l (In blood)	Prior to last shift of workweek	2010-03-01
		Toluene: 0.03 mg/l (Urine)	End of shift (As soon as possible after exposure ceases)	2010-03-01
		o-Cresol: 0.3 mg/g Creatinine Background (Urine) With hydrolyses ()	End of shift (As soon as possible after exposure ceases)	2010-03-01

Engineering measures

SDS Number:100000014265 5/19

Version 1.7 Revision Date 2020-04-08

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection : Wear a supplied-air NIOSH approved respirator unless

ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as:. Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators

may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed

with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Flame retardant antistatic protective clothing. Workers should wear antistatic

footwear.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance

Form : Liquid
Physical state : Liquid
Color : Colorless
Odor : gasoline-like

Safety data

Flash point : -17°C (1°F)

Lower explosion limit : No data available

Upper explosion limit : No data available

SDS Number:100000014265 6/19

Version 1.7 Revision Date 2020-04-08

Oxidizing properties : No

Autoignition temperature : No data available

Molecular formula : Mixture

Molecular weight : Not applicable

pH : No data available

Freezing point : No data available

Pour point No data available

Boiling point/boiling range : 82-138°C (180-280°F)

Vapor pressure : 2.00 PSI

at 38°C (100°F)

Relative density : 0.77

at 15.6 °C (60.1 °F)

Water solubility : Negligible

Partition coefficient: n-

octanol/water

: No data available

Viscosity, kinematic : No data available

Relative vapor density : 1

(Air = 1.0)

Evaporation rate : No data available

Percent volatile : > 99 %

SECTION 10: Stability and reactivity

Reactivity: Stable under recommended storage conditions.

Chemical stability : This material is considered stable under normal ambient and

anticipated storage and handling conditions of temperature

and pressure.

Possibility of hazardous reactions

Hazardous reactions : Hazardous reactions: Hazardous polymerization does not

occur.

Further information: No decomposition if stored and applied as

SDS Number:100000014265 7/19

Version 1.7 Revision Date 2020-04-08

directed.

Hazardous reactions: Vapors may form explosive mixture with

air.

Conditions to avoid : Heat, flames and sparks.

Materials to avoid : May react with oxygen and strong oxidizing agents, such as

chlorates, nitrates, peroxides, etc.

Hazardous decomposition

products

: Hydrocarbons Carbon oxides

Other data : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

Jet RF (AMS 2629B Type 1)

Acute oral toxicity

: LD50 Oral: > 5,000 mg/kg

Species: Rat

Method: Acute toxicity estimate

Jet RF (AMS 2629B Type 1)

Acute inhalation toxicity

: LC50: > 20 mg/l Exposure time: 4 h

Species: Rat

Test atmosphere: vapor

Method: Acute toxicity estimate

Acute toxicity estimate: 80.13 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Jet RF (AMS 2629B Type 1)

Acute dermal toxicity

: LD50 Dermal: > 5,000 mg/kg

Species: Rabbit

Method: Acute toxicity estimate

Jet RF (AMS 2629B Type 1)

Skin irritation

: May cause skin irritation in susceptible persons.

Jet RF (AMS 2629B Type 1)

Eye irritation

Vapors may cause irritation to the eyes, respiratory system

and the skin.

Jet RF (AMS 2629B Type 1)

Sensitization

Did not cause sensitization on laboratory animals. Information

refers to the main ingredient.

Repeated dose toxicity

Cyclohexane : Species: Rat

Application Route: Inhalation Dose: 0, 500, 2000, 7000 ppm

SDS Number:100000014265 8/19

Version 1.7 Revision Date 2020-04-08

Exposure time: 90 day

Number of exposures: 6 h/d, 5 d/wk

NOEL: 2000 ppm

Species: Rat, Male and female

Sex: Male and female Application Route: Inhalation Dose: 0, 500, 2,000, 7000 ppm Exposure time: 13-14 wk

Number of exposures: 6 hr/d, 5 d/wk

NOEL: 7000 ppm

Species: Mouse, Male and female

Sex: Male and female Application Route: Inhalation Dose: 0, 500, 2000, 7000 ppm Exposure time: 13-14 wk

Number of exposures: 6 hr/d, 5 d/wk

NOEL: 2000 ppm Target Organs: Blood

2,2,4-Trimethylpentane

(Isooctane)

Species: Rat, Male and female

Sex: Male and female Application Route: Inhalation Dose: 0, 668, 2220, 6646 ppm Exposure time: 13 weeks

Number of exposures: 6 hr/day 5 d/wk

NOEL: 8.117 mg/l 2220 ppm Method: OECD Guideline 413

Information given is based on data obtained from similar

substances.

Toluene Species: Rat

Application Route: Inhalation Dose: 0, 100, 625, 1250, 3000 ppm

Exposure time: 15 wk

Number of exposures: 6.5 h/d, 5 d/wk

NOEL: 625 ppm

Species: Mouse

Application Route: Inhalation Dose: 0, 100, 625, 1250, 3000 ppm

Exposure time: 14 wk

Number of exposures: 6.5 h/d, 5 d/wk

NOEL: 100 ppm

Genotoxicity in vitro

Cyclohexane : Test Type: Ames test

Metabolic activation: with and without metabolic activation Method: Mutagenicity (Escherichia coli - reverse mutation

assay)

Result: negative

SDS Number:100000014265

9/19

Version 1.7 Revision Date 2020-04-08

Test Type: Mouse lymphoma assay

Metabolic activation: with and without metabolic activation

Result: negative

Test Type: Mouse lymphoma assay

Metabolic activation: with and without metabolic activation

Method: OECD Guideline 476

Result: negative

2,2,4-Trimethylpentane

(Isooctane)

Test Type: Ames test

Method: Mutagenicity (Escherichia coli - reverse mutation

assay)

Result: negative

Test Type: Mouse lymphoma assay Method: OECD Guideline 476

Result: negative

Test Type: Sister Chromatid Exchange Assay

Result: negative

Test Type: Unscheduled DNA synthesis assay

Result: negative

Toluene Test Type: Ames test

Result: negative

Test Type: Sister Chromatid Exchange Assay

Result: negative

Test Type: Mouse lymphoma assay

Result: negative

Test Type: Cytogenetic assay

Result: negative

tert-Butyl Disulfide Test Type: Ames test

Result: negative

Test Type: Mouse lymphoma assay

Result: negative

Test Type: Sister Chromatid Exchange Assay

Result: negative

Genotoxicity in vivo

Cyclohexane : Test Type: Cytogenetic assay

Species: Rat

Cell type: Bone marrow

Dose: 96.6, 307.2, 10141.6 ppm

Result: negative

2,2,4-Trimethylpentane

(Isooctane)

Test Type: Unscheduled DNA synthesis assay

Species: Mouse Dose: 500 mg/kg Result: negative

SDS Number:100000014265

10/19

Version 1.7 Revision Date 2020-04-08

Test Type: Unscheduled DNA synthesis assay

Species: Rat Dose: 500 mg/kg Result: negative

Toluene Test Type: Cytogenetic assay

Result: negative

Test Type: Mouse micronucleus assay

Result: negative

Carcinogenicity

Toluene : Species: Rat

Dose: 0, 600, 1200 ppm Exposure time: 2 yrs

Number of exposures: 6.5 h/d, 5 d/wk Remarks: No evidence of carcinogenicity

Species: Mouse Dose: 0, 600, 1200 ppm Exposure time: 2 yrs

Number of exposures: 6.5 h/d, 5 d/wk Remarks: No evidence of carcinogenicity

Reproductive toxicity

Cyclohexane : Species: Rat

Application Route: Inhalation Dose: 0, 500, 2000, 7000 ppm Number of exposures: 6 hr/d, 5 d/wk Method: OECD Test Guideline 416

NOAEL Parent: 500 ppm NOAEL F1: 7000 ppm NOAEL F2: 7000 ppm

2,2,4-Trimethylpentane

(Isooctane)

Species: Rat

Sex: male and female Application Route: Inhalation Dose: 0, 900, 3000, 9000 ppm Number of exposures: 6 h/d 5 d/wk Method: OECD Test Guideline 416

NOAEL Parent: 3000 ppm NOAEL F1: 3000 ppm NOAEL F2: 3000 ppm

Information given is based on data obtained from similar

substances.

Toluene Species: Rat

Application Route: Inhalation Dose: 0, 100, 500, 2000 ppm

Test period: 95 d

NOAEL Parent: 2000 ppm

Developmental Toxicity

Cyclohexane : Species: Rat

Application Route: Inhalation

SDS Number:100000014265 11/19

Version 1.7 Revision Date 2020-04-08

Dose: 0, 500, 2,000, 7,000 PPM Number of exposures: 6 hr/d

Test period: GD 6-15

Method: OECD Guideline 414 NOAEL Teratogenicity: 7,000 ppm NOAEL Maternal: 500 ppm

Species: Rabbit

Application Route: Inhalation Dose: 0, 500, 2,000, 7,000 PPM Number of exposures: 6 hr/d

Test period: GD 6-18

Method: OECD Guideline 414 NOAEL Teratogenicity: 7,000 ppm NOAEL Maternal: 500 ppm

2,2,4-Trimethylpentane

(Isooctane)

Species: Rat

Application Route: Inhalation Dose: 0, 400, 1200 ppm Number of exposures: 6h/d Test period: GD6-15

NOAEL Teratogenicity: 1200 ppm NOAEL Maternal: 1200 ppm

Information given is based on data obtained from similar

substances.

Species: Rat

Application Route: Inhalation Dose: 0, 900, 3000, 9000 ppm Number of exposures: 6h/d Test period: GD6-15

Method: OECD Guideline 414 NOAEL Teratogenicity: 9000 ppm NOAEL Maternal: 3000 ppm

Information given is based on data obtained from similar

substances.

Toluene Species: Rat

Application Route: Inhalation Dose: 0, 100, 500, 2000 ppm

Test period: 95 d

NOAEL Teratogenicity: 400-750 ppm

Jet RF (AMS 2629B Type 1)

Aspiration toxicity

May be fatal if swallowed and enters airways.

Substances known to cause human aspiration toxicity hazards or to be regarded as if they cause human aspiration toxicity

hazard.

CMR effects

Cyclohexane : Carcinogenicity: Not classifiable as a human carcinogen.

Mutagenicity: Did not show mutagenic effects in animal

experiments.

Teratogenicity: Did not show teratogenic effects in animal

experiments.

Reproductive toxicity: No toxicity to reproduction

2,2,4-Trimethylpentane Mutagenicity: Tests on bacterial or mammalian cell cultures

SDS Number:100000014265 12/19

Version 1.7 Revision Date 2020-04-08

(Isooctane) did not show mutagenic effects.

Teratogenicity: Animal testing did not show any effects on

fetal development.

Reproductive toxicity: Animal testing did not show any effects

on fertility.

Toluene Carcinogenicity: Not classifiable as a human carcinogen.

Mutagenicity: Animal testing did not show any mutagenic

effects.

Teratogenicity: Some evidence of adverse effects on

development, based on animal experiments.

Reproductive toxicity: Some evidence of adverse effects on sexual function and fertility, and/or on development, based on

animal experiments.

Jet RF (AMS 2629B Type 1)

Further information

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents

may degrease the skin.

SECTION 12: Ecological information

Toxicity to fish

Cyclohexane : LC50: 4.53 mg/l

Exposure time: 96 h

Species: Pimephales promelas (fathead minnow)

Method: OECD Test Guideline 203

2,2,4-Trimethylpentane

(Isooctane)

LC50: 0.11 mg/l Exposure time: 96 h

Species: Oncorhynchus mykiss (rainbow trout) semi-static test Method: OECD Test Guideline 203 Information given is based on data obtained from similar

substances.

Toluene LC50: 18 - 36 mg/l

Exposure time: 96 h

Species: Pimephales promelas (fathead minnow)

Toxicity to daphnia and other aquatic invertebrates

Cyclohexane : EC50: 0.9 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 202

2,2,4-Trimethylpentane

(Isooctane)

EC50: 0.4 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea)

static test Information given is based on data obtained from

similar substances.

Toluene EC50: 3.78 mg/l

Exposure time: 48 h

SDS Number:100000014265 13/19

Version 1.7 Revision Date 2020-04-08

Species: Daphnia magna (Water flea)

Toxicity to algae

Cyclohexane : EbC50: 3.4 mg/l

Exposure time: 72 h

Species: Selenastrum capricornutum (algae)

NOEC: 0.925 mg/l Exposure time: 72 h

Species: Pseudokirchneriella subcapitata (microalgae)

Method: OECD Test Guideline 201

2,2,4-Trimethylpentane

(Isooctane)

EL50: 2.943 mg/l Exposure time: 72 h

Method: QSAR modeled data

Toluene EC50: 134 mg/l

Exposure time: 72 h

Species: Chlamydomonas angulosa (Green algae)

M-Factor

cyclohexane : M-Factor (Acute Aquat. Tox.)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

2,2,4-Trimethylpentane

(Isooctane)

: NOEL: 0.17 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Method: OECD Test Guideline 211 Information given is based on data obtained from similar

substances.

Biodegradability : This material is not expected to be readily biodegradable.

Elimination information (persistence and degradability)

Bioaccumulation

Cyclohexane : Bioconcentration factor (BCF): 167

This material is not expected to bioaccumulate.

Results of PBT assessment

Cyclohexane : Non-classified PBT substance, Non-classified vPvB substance

2,2,4-Trimethylpentane

(Isooctane)

: Non-classified PBT substance, Non-classified vPvB substance

Toluene : Non-classified vPvB substance, Non-classified PBT substance

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life

with long lasting effects.

Ecotoxicology Assessment

SDS Number:100000014265 14/19

Version 1.7 Revision Date 2020-04-08

Short-term (acute) aquatic hazard

Cyclohexane : Very toxic to aquatic life.

2,2,4-Trimethylpentane

(Isooctane)

: Very toxic to aquatic life.

Toluene : Toxic to aquatic life.

tert-Butyl Disulfide : Toxic to aquatic life.

Long-term (chronic) aquatic hazard

Cyclohexane : Very toxic to aquatic life with long lasting effects.

2,2,4-Trimethylpentane

(Isooctane) Toluene : Very toxic to aquatic life with long lasting effects.

: Harmful to aquatic life with long lasting effects.

tert-Butyl Disulfide : Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water

courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed

waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product.

Do not re-use empty containers. Do not burn, or use a cutting

torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, MARINE POLLUTANT, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

SDS Number:100000014265 15/19

Version 1.7 Revision Date 2020-04-08

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, (-17°C), MARINE POLLUTANT, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), CYCLOHEXANE)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), CYCLOHEXANE)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), CYCLOHEXANE)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), CYCLOHEXANE)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

National legislation

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

> Skin corrosion or irritation Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

CERCLA Reportable

Quantity

: 2949 lbs

Cyclohexane

SARA 302 Reportable

Quantity

: This material does not contain any components with a SARA

302 RQ.

SARA 302 Threshold

Planning Quantity

: This material does not contain any components with a section

302 EHS TPQ.

SARA 304 Reportable

Quantity

: This material does not contain any components with a section

304 EHS RQ.

SDS Number:100000014265 16/19

Version 1.7 Revision Date 2020-04-08

SARA 313 Components : The following components are subject to reporting levels

established by SARA Title III, Section 313:

: Cyclohexane - 110-82-7 Toluene - 108-88-3

Clean Air Act

Ozone-Depletion : This product neither contains, nor was manufactured with a Class I or Potential : Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR

82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

: 2,2,4-Trimethylpentane (Isooctane) - 540-84-1

Toluene - 108-88-3

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

: Cyclohexane - 110-82-7 Toluene - 108-88-3

US State Regulations

Pennsylvania Right To Know

: Cyclohexane - 110-82-7

2,2,4-Trimethylpentane (Isooctane) - 540-84-1

Toluene - 108-88-3

California Prop. 65

Components

: WARNING: This product contains a chemical known in the State of California to cause birth defects or other reproductive

harm.

Toluene 108-88-3

Notification status

SDS Number:100000014265 17/19

Version 1.7 Revision Date 2020-04-08

Europe REACH : A substance or substances in this product is not

registered or notified to be registered. Importation or manufacture of this product is still permitted provided that it does not exceed the REACH minimum threshold

quantity of the non-regulated substances.

Switzerland CH INV : On the inventory, or in compliance with the inventory

United States of America (USA) : On or in compliance with the active portion of the

TSCA TSCA inventory

Canada NDSL : This product contains one or several components listed

in the Canadian NDSL.

Australia AICS : On the inventory, or in compliance with the inventory New Zealand NZIoC : On the inventory, or in compliance with the inventory Japan ENCS : On the inventory, or in compliance with the inventory Korea KECI : A substance(s) in this product was not registered,

notified to be registered, or exempted from registration by CPChem according to K-REACH regulations. Importation or manufacture of this product is still permitted provided the Korean Importer of Record has

themselves notified the substance.

Philippines PICCS : On the inventory, or in compliance with the inventory

China IECSC : Not in compliance with the inventory

Taiwan TCSI : On the inventory, or in compliance with the inventory

SECTION 16: Other information

NFPA Classification : Health Hazard: 2

Fire Hazard: 3 Reactivity Hazard: 0



Further information

Legacy SDS Number : 432570

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet				
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%	
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level	
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency	

SDS Number:100000014265 18/19

SAFETY DATA SHEET

Jet RF (AMS 2629B Type 1)

Version 1.7 Revision Date 2020-04-08

NDSL	Canada, Non-Domestic	NIOSH	National Institute for Occupational
	Substances List		Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of
			Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect
			Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure	OSHA	Occupational Safety & Health
	Scenario Tool		Administration
EOSCA	European Oilfield Specialty	PEL	Permissible Exposure Limit
	Chemicals Association		
EINECS	European Inventory of Existing	PICCS	Philippines Inventory of
	Chemical Substances		Commercial Chemical Substances
MAK	Germany Maximum Concentration	PRNT	Presumed Not Toxic
	Values		
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery
			Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and
			Reauthorization Act.
IARC	International Agency for Research	TLV	Threshold Limit Value
	on Cancer		
IECSC	Inventory of Existing Chemical	TWA	Time Weighted Average
	Substances in China		
ENCS	Japan, Inventory of Existing and	TSCA	Toxic Substance Control Act
	New Chemical Substances		
KECI	Korea, Existing Chemical	UVCB	Unknown or Variable Composition,
	Inventory		Complex Reaction Products, and
			Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials
			Information System
LC50	Lethal Concentration 50%		

SDS Number:100000014265 19/19