

**Toluene Reference, Fuel Grade**

Version 1.7

Revision Date 2020-08-10

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****Product information**

Product Name : Toluene Reference, Fuel Grade  
Material : 1016965, 1016964, 1016968, 1016967, 1016963, 1016966

Use : Reference Fuel

**Company** : Chevron Phillips Chemical Company LP  
Specialty Chemicals  
10001 Six Pines Drive  
The Woodlands, TX 77380

**Emergency telephone:****Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

**Transport:**

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

Responsible Department : Product Safety and Toxicology Group  
E-mail address : SDS@CPChem.com  
Website : www.CPChem.com

**SECTION 2: Hazards identification****Classification of the substance or mixture**

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

**Classification**

: Flammable liquids, Category 2  
Skin irritation, Category 2  
Reproductive toxicity, Category 2  
Specific target organ toxicity - single exposure, Category 3,  
Central nervous system  
Specific target organ toxicity - repeated exposure, Category 2,

**Toluene Reference, Fuel Grade**

Version 1.7

Revision Date 2020-08-10

Inhalation, Auditory organs, color vision  
Aspiration hazard, Category 1

**Labeling**

Symbol(s)

:



Signal Word

:

Danger

Hazard Statements

:

H225: Highly flammable liquid and vapor.  
H304: May be fatal if swallowed and enters airways.  
H315: Causes skin irritation.  
H336: May cause drowsiness or dizziness.  
H361d: Suspected of damaging the unborn child.  
H373: May cause damage to organs (Auditory organs, color vision) through prolonged or repeated exposure if inhaled.

Precautionary Statements

:

**Prevention:**

P201 Obtain special instructions before use.  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.  
P264 Wash skin thoroughly after handling.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P331 Do NOT induce vomiting.  
P362 Take off contaminated clothing and wash before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Toluene Reference, Fuel Grade**

Version 1.7

Revision Date 2020-08-10

**Carcinogenicity:****IARC**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**NTP**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**SECTION 3: Composition/information on ingredients**

Synonyms : Toluol  
Toluene (Reference Fuel)

Molecular formula : C<sub>7</sub>H<sub>8</sub>

Component	CAS-No.	Weight %
Toluene	108-88-3	99.95

**SECTION 4: First aid measures**

- General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.
- If inhaled : Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

**SECTION 5: Firefighting measures**

- Flash point : 4.4°C (39.9°F)  
Method: closed cup
- Autoignition temperature : 529°C (984°F)
- Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical.
- Unsuitable extinguishing media : High volume water jet.

**Toluene Reference, Fuel Grade**

Version 1.7

Revision Date 2020-08-10

- |  |   |  |
|--|---|--|
| Specific hazards during fire fighting          | : | Do not allow run-off from fire fighting to enter drains or water courses.  |
| Special protective equipment for fire-fighters | : | Wear self-contained breathing apparatus for firefighting if necessary.   |
| Further information                            | : | Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers. |
| Fire and explosion protection                  | : | Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.  |
| Hazardous decomposition products               | : | Carbon oxides.   |

**SECTION 6: Accidental release measures**

- |                           |   |   |
|---------------------------|---|---|
| Personal precautions      | : | Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. |
| Environmental precautions | : | Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.   |
| Methods for cleaning up   | : | Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).       |

**SECTION 7: Handling and storage****Handling**

- |   |   |   |
|---|---|---|
| Advice on safe handling                         | : | Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. |
| Advice on protection against fire and explosion | : | Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames,   |

**Toluene Reference, Fuel Grade**

Version 1.7

Revision Date 2020-08-10

hot surfaces and sources of ignition.

**Storage**

Requirements for storage : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Use : Reference Fuel

**SECTION 8: Exposure controls/personal protection****Ingredients with workplace control parameters**

US

Components	Basis	Value	Control parameters	Note
Toluene	ACGIH	TWA	20 ppm,	A4,
	OSHA Z-2	TWA	200 ppm,	
	OSHA Z-2	CEIL	300 ppm,	
	OSHA Z-2	Peak	500 ppm,	
	OSHA Z-1-A	TWA	100 ppm, 375 mg/m3	
	OSHA Z-1-A	STEL	150 ppm, 560 mg/m3	

A4 Not classifiable as a human carcinogen

**Immediately Dangerous to Life or Health Concentrations (IDLH)**

Substance name	CAS-No.	Control parameters	Update
Toluene	108-88-3	Immediately Dangerous to Life or Health Concentration Value 500 parts per million	1995-03-01

**Biological exposure indices**

US

Substance name	CAS-No.	Control parameters	Sampling time	Update
Toluene	108-88-3	Toluene: 0.02 mg/l (In blood)	Prior to last shift of workweek	2010-03-01
		Toluene: 0.03 mg/l (Urine)	End of shift (As soon as possible after exposure ceases)	2010-03-01
		o-Cresol: 0.3 mg/g Creatinine Background (Urine) With hydrolyses ()	End of shift (As soon as possible after exposure ceases)	2010-03-01

**Engineering measures**

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

**Personal protective equipment**

Respiratory protection : Wear a supplied-air NIOSH approved respirator unless

**Toluene Reference, Fuel Grade**

Version 1.7

Revision Date 2020-08-10

ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as:. Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**SECTION 9: Physical and chemical properties****Information on basic physical and chemical properties****Appearance**

- Form : Non-viscous
- Physical state : Liquid
- Color : Clear
- Odor : Strong gasoline

**Safety data**

- Flash point : 4.4°C (39.9°F)  
Method: closed cup
- Lower explosion limit : 1.2 %(V)
- Upper explosion limit : 7.1 %(V)
- Oxidizing properties : No
- Autoignition temperature : 529°C (984°F)
- Molecular formula : C<sub>7</sub>H<sub>8</sub>
- Molecular weight : 92.15 g/mol
- pH : Not applicable

**Toluene Reference, Fuel Grade**

Version 1.7

Revision Date 2020-08-10

Pour point	: No data available
Freezing point	-94.5°C (-138.1°F)
Boiling point/boiling range	: 110.6°C (231.1°F)
Vapor pressure	: 1.10 PSI at 37.8°C (100.0°F)
Relative density	: 0.870 at 15.6 °C (60.1 °F)
Density	: 0.870 kg/m3
Water solubility	: Soluble in alcohol, benzene, and ether; insoluble in water.
Partition coefficient: n-octanol/water	: No data available
Viscosity, kinematic	: No data available
Relative vapor density	: 2.8 (Air = 1.0)
Evaporation rate	: 4.5
Percent volatile	: > 99 %
Conductivity	: 8 pSm at 20 °C Method: ASTM D4308

**SECTION 10: Stability and reactivity**

<b>Reactivity</b>	: Stable under recommended storage conditions.
<b>Chemical stability</b>	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
<b>Possibility of hazardous reactions</b>	
<b>Hazardous reactions</b>	: Hazardous reactions: Hazardous polymerization does not occur.  Hazardous reactions: Vapors may form explosive mixture with air.  Further information: No decomposition if stored and applied as directed.

**Toluene Reference, Fuel Grade**

Version 1.7

Revision Date 2020-08-10

- Conditions to avoid** : Heat, flames and sparks.
- Materials to avoid** : May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
- Hazardous decomposition products** : Carbon oxides
- Other data** : No decomposition if stored and applied as directed.

**SECTION 11: Toxicological information****Acute oral toxicity**

Toluene : LD50: 6,500 mg/kg  
Species: Rat  
Sex: Not Specified

**Acute inhalation toxicity**

Toluene : LC50: 25.7 - 30 mg/l  
Exposure time: 4 h  
Species: Rat  
Test atmosphere: vapor

**Acute dermal toxicity**

Toluene : LD50: 12,400 mg/kg  
Species: Rabbit  
Sex: Not Specified

**Skin irritation**

Toluene : Skin irritation

**Eye irritation**

Toluene : slight irritation. Not classified due to data which are conclusive although insufficient for classification.

**Sensitization**

Toluene : Did not cause sensitization on laboratory animals.

**Repeated dose toxicity**

Toluene : Species: Rat  
Application Route: Inhalation  
Dose: 0, 100, 625, 1250, 3000 ppm  
Exposure time: 15 wk  
Number of exposures: 6.5 h/d, 5 d/wk  
NOEL: 625 ppm



**Toluene Reference, Fuel Grade**

Version 1.7

Revision Date 2020-08-10

Species: Mouse  
Application Route: Inhalation  
Dose: 0, 100, 625, 1250, 3000 ppm  
Exposure time: 14 wk  
Number of exposures: 6.5 h/d, 5 d/wk  
NOEL: 100 ppm

**Genotoxicity in vitro**

Toluene

: Test Type: Ames test  
Result: negative

Test Type: Sister Chromatid Exchange Assay  
Result: negative

Test Type: Mouse lymphoma assay  
Result: negative

Test Type: Cytogenetic assay  
Result: negative

**Genotoxicity in vivo**

Toluene

: Test Type: Cytogenetic assay  
Result: negative

Test Type: Mouse micronucleus assay  
Result: negative

**Carcinogenicity**

Toluene

: Species: Rat  
Dose: 0, 600, 1200 ppm  
Exposure time: 2 yrs  
Number of exposures: 6.5 h/d, 5 d/wk  
Remarks: No evidence of carcinogenicity

Species: Mouse  
Dose: 0, 600, 1200 ppm  
Exposure time: 2 yrs  
Number of exposures: 6.5 h/d, 5 d/wk  
Remarks: No evidence of carcinogenicity

**Reproductive toxicity**

Toluene

: Species: Rat  
Application Route: Inhalation  
Dose: 0, 100, 500, 2000 ppm  
Test period: 95 d  
NOAEL Parent: 2000 ppm

**Developmental Toxicity**

Toluene

: Species: Rat  
Application Route: Inhalation  
Dose: 0, 100, 500, 2000 ppm  
Test period: 95 d

**Toluene Reference, Fuel Grade**

Version 1.7

Revision Date 2020-08-10

NOAEL Teratogenicity: 400-750 ppm

**Toluene Reference, Fuel Grade****Aspiration toxicity** : May be fatal if swallowed and enters airways.**CMR effects**

**Toluene** : Carcinogenicity: Not classifiable as a human carcinogen.  
Mutagenicity: Animal testing did not show any mutagenic effects.  
Teratogenicity: Some evidence of adverse effects on development, based on animal experiments.  
Reproductive toxicity: Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

**Toluene Reference, Fuel Grade****Further information** : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents may degrease the skin.**SECTION 12: Ecological information****Toxicity to fish**

**Toluene** : LC50: 18 - 36 mg/l  
Exposure time: 96 h  
Species: Pimephales promelas (fathead minnow)

**Toxicity to daphnia and other aquatic invertebrates**

**Toluene** : EC50: 3.78 mg/l  
Exposure time: 48 h  
Species: Daphnia magna (Water flea)

**Toxicity to algae**

**Toluene** : EC50: 134 mg/l  
Exposure time: 72 h  
Species: Chlamydomonas angulosa (Green algae)

**Biodegradability**

**Toluene** : This material is expected to be readily biodegradable.

**Results of PBT assessment**

**Toluene** : Non-classified vPvB substance, Non-classified PBT substance

**Additional ecological information** : Toxic to aquatic life., Harmful to aquatic life with long lasting effects.

**Toluene Reference, Fuel Grade**

Version 1.7

Revision Date 2020-08-10

**Ecotoxicology Assessment**

Short-term (acute) aquatic hazard

Toluene : Toxic to aquatic life.

Long-term (chronic) aquatic hazard

Toluene : Harmful to aquatic life with long lasting effects.

**SECTION 13: Disposal considerations**

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14: Transport information**

**The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).**

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

**US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)**

UN1294, TOLUENE, 3, II, RQ (TOLUENE)

**IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)**

UN1294, TOLUENE, 3, II, (4.4°C)

**IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)**

UN1294, TOLUENE, 3, II

**ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))**

UN1294, TOLUENE, 3, II, (D/E)

**Toluene Reference, Fuel Grade**

Version 1.7

Revision Date 2020-08-10

**RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))**

UN1294, TOLUENE, 3, II

**ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)**

UN1294, TOLUENE, 3, II

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code****SECTION 15: Regulatory information****National legislation**

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)  
Aspiration hazard  
Skin corrosion or irritation

**CERCLA Reportable Quantity** : 1000 lbs  
Toluene

**SARA 302 Reportable Quantity** : This material does not contain any components with a SARA 302 RQ.

**SARA 302 Threshold Planning Quantity** : This material does not contain any components with a section 302 EHS TPQ.

**SARA 304 Reportable Quantity** : This material does not contain any components with a section 304 EHS RQ.

**SARA 313 Components** : The following components are subject to reporting levels established by SARA Title III, Section 313:

: Toluene - 108-88-3

**Clean Air Act**

**Toluene Reference, Fuel Grade**

Version 1.7

Revision Date 2020-08-10

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):  
 : Toluene - 108-88-3  
 Benzene - 71-43-2

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):  
 : Toluene - 108-88-3  
 Benzene - 71-43-2

**US State Regulations****Pennsylvania Right To Know**

: Toluene - 108-88-3  
 Benzene - 71-43-2

**California Prop. 65 Components**

: WARNING: This product can expose you to chemicals including [listed below], which is [are] known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov/food](http://www.P65Warnings.ca.gov/food).

Benzene 71-43-2

WARNING: This product can expose you to chemicals including [listed below], which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Toluene 108-88-3  
 Benzene 71-43-2

**Notification status**

Europe REACH : This product is in full compliance according to REACH regulation 1907/2006/EC.  
 Switzerland CH INV : On the inventory, or in compliance with the inventory  
 United States of America (USA) : On or in compliance with the active portion of the  
 TSCA TSCA inventory

**Toluene Reference, Fuel Grade**


Version 1.7

Revision Date 2020-08-10

Canada DSL	:	All components of this product are on the Canadian DSL
Australia AICS	:	On the inventory, or in compliance with the inventory
New Zealand NZIoC	:	On the inventory, or in compliance with the inventory
Japan ENCS	:	On the inventory, or in compliance with the inventory
Korea KECI	:	A substance(s) in this product was not registered, notified to be registered, or exempted from registration by CPChem according to K-REACH regulations. Importation or manufacture of this product is still permitted provided the Korean Importer of Record has themselves notified the substance.
Philippines PICCS	:	On the inventory, or in compliance with the inventory
China IECSC	:	On the inventory, or in compliance with the inventory
Taiwan TCSI	:	On the inventory, or in compliance with the inventory

**SECTION 16: Other information**

**NFPA Classification** : Health Hazard: 2  
Fire Hazard: 3  
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : 3476

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Key or legend to abbreviations and acronyms used in the safety data sheet**

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure	OSHA	Occupational Safety & Health

**Toluene Reference, Fuel Grade**

Version 1.7

Revision Date 2020-08-10

	Scenario Tool		Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		