

SAFETY DATA SHEET

FRJ-551

Version 1.0 Revision Date: 09/16/2020

Date of last issue: -
Date of first issue: 09/16/2020

SECTION 1. IDENTIFICATION

Product identifier

Product name : FRJ-551

Recommended use of the chemical and restrictions on use

Recommended use : Industrial uses: Uses of substances as such or in preparations at industrial sites
Restrictions on use : For industrial use only.

Manufacturer or supplier's details

Supplier

Company : SI Group, Inc.
Address : 2750 Balltown Rd.,
Schenectady, NY
United States
12309
E-mail address : sds.info@siigroup.com

Emergency telephone

Emergency Phone Number : +1 703-741-5970 (CHEMTREC/US)
+44 (0) 1235 239 670 (NCEC/EU)
0 512 8090 3042 (NRCC/CHINA)

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin sensitization : Category 1
Specific target organ systemic toxicity - repeated exposure : Category 2 (Central nervous system, Kidney, Liver, hearing organs)

GHS label elements

Hazard pictograms : 

Signal Word : Warning

FRJ-551

 Version 1.0
 Revision Date: 09/16/2020

 Date of last issue: -
 Date of first issue: 09/16/2020

- Hazard Statements : H317 May cause an allergic skin reaction.
 H373 May cause damage to organs (Central nervous system, Kidney, Liver, hearing organs) through prolonged or repeated exposure.
- Precautionary Statements : **Prevention:**
 P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P280 Wear protective gloves.
- Response:**
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P363 Wash contaminated clothing before reuse.
 P314 Get medical advice/ attention if you feel unwell.
- Disposal:**
 P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

May cause leucodermia [HNOC]
 May form combustible dust concentrations in air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Polymer

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol	25085-50-1	>= 90 - <= 100
Xylene	1330-20-7	>= 5 - < 10
Para-tert-butylphenol (PTBP)	98-54-4	>= 0.25 - < 1

The exact percentage concentrations of components are being withheld as a trade secret in accordance with paragraph (i) of §1910.120

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
 Show this material safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.
- If inhaled : Move to fresh air.
 If unconscious, place in recovery position and seek medical

SAFETY DATA SHEET



FRJ-551

Version 1.0
Revision Date: 09/16/2020

Date of last issue: -
Date of first issue: 09/16/2020

-
- | | |
|---|---|
| In case of skin contact | : advice.
If symptoms persist, call a physician.
If on skin, rinse well with water. |
| In case of eye contact | : If skin irritation persists, call a physician.
If on clothes, remove clothes.
Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician. |
| Most important symptoms and effects, both acute and delayed | : Product dust may be irritating to eyes, skin and respiratory system.
Causes mild skin irritation.
May cause damage to organs through prolonged or repeated exposure.
May cause an allergic skin reaction. |
| Notes to physician | : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine. |

SECTION 5. FIRE-FIGHTING MEASURES

- | | |
|--|--|
| Suitable extinguishing media | : Water fog, Dry chemical, Foam, Carbon dioxide |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during fire fighting | : Do not allow run-off from fire fighting to enter drains or water courses.
Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard. |
| Hazardous combustion products | : Carbon oxides |
| Further information | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
| Special protective equipment for fire-fighters | : Wear self-contained breathing apparatus for firefighting if necessary. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|--|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.
Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.
Avoid dispersal of dust in the air (i.e., clearing dust surfaces) |
|---|--|

FRJ-551

Version 1.0
 Revision Date: 09/16/2020

Date of last issue: -
 Date of first issue: 09/16/2020

- with compressed air).
 Non-sparking tools should be used.
 Use personal protective equipment.
 Avoid dust formation.
 Avoid breathing dust.
- Environmental precautions : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
- Advice on safe handling : Minimize dust generation and accumulation.
 Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces.
 Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations.
 Keep away from heat and sources of ignition.
 Avoid formation of respirable particles.
 Do not breathe vapors/dust.
 Avoid contact with skin and eyes.
 For personal protection see section 8.
 Smoking, eating and drinking should be prohibited in the application area.
 Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Xylene	1330-20-7	TWA8-hour	100 ppm	OSHA Z-1USA.

SAFETY DATA SHEET



FRJ-551

Version 1.0 Revision Date: 09/16/2020

Date of last issue: -
Date of first issue: 09/16/2020

		time weighted average	435 mg/m ³	Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA8-hour, time-weighted average	100 ppm	ACGIHUSA. ACGIH Threshold Limit Values (TLV)
		STELShort-term exposure limit	150 ppm	ACGIHUSA. ACGIH Threshold Limit Values (TLV)
		STELShort-term exposure limit	150 ppm 655 mg/m ³	OSHA POUSA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		TWA8-hour time weighted average	100 ppm 435 mg/m ³	OSHA POUSA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000

Engineering measures

: It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen deficient environment.
Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate ventilation, especially in confined areas.

Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk

FRJ-551

Version 1.0
 Revision Date: 09/16/2020

Date of last issue: -
 Date of first issue: 09/16/2020

assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m³ - total dust, 5 mg/m³ - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m³ - respirable particles, 10 mg/m³ - inhalable particles.

Personal protective equipment

- Respiratory protection : If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
 In the absence of engineering controls sufficient to maintain airborne limit values, appropriate respiratory protection should be utilized.
- Hand protection
- Material : Impervious gloves
- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water
 Tightly fitting safety goggles
- Skin and body protection : Dust impervious protective suit
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.
 When using do not smoke.
 Wash hands before breaks and at the end of workday.

Environmental exposure controls

- Water : Do not let product enter drains.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : solid, flakes
- Color : off-white to yellow
- Odor : characteristic
- Odor Threshold : No data available
- pH : No data available
- Melting point : 105 °C / 105 °C
- Boiling point/boiling range : No data available
- Flash point : No data available
- Evaporation rate : <Ether
- Flammability (solid, gas) : No data available
- Upper explosion limit : No data available

SAFETY DATA SHEET



FRJ-551

Version 1.0 Revision Date: 09/16/2020

Date of last issue: -
Date of first issue: 09/16/2020

Lower explosion limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	Heavier than air
Relative density	:	1.1 (25 °C / 25 °C)
Bulk density	:	No data available
Solubility(ies)	:	
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Surface tension	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong oxidizing agents, Strong acids and strong bases
Hazardous decomposition products	:	This product may release the following: Carbon dioxide (CO ₂) Carbon monoxide Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 200 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method

FRJ-551

Version 1.0
Revision Date: 09/16/2020

Date of last issue: -
Date of first issue: 09/16/2020

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:**Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

Xylene:

Acute oral toxicity : LD50 (Rat): 3,523 mg/kg

Acute inhalation toxicity : LC50 (Rat): 21.71 mg/l
Exposure time: 4 h
Test atmosphere: vapor

LC50 (Rat): 29.08 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 Dermal (Rabbit): > 4,350 mg/kg

LD50 Dermal (Rabbit): > 1,700 mg/kg

Para-tert-butylphenol (PTBP):

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 5.6 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg
Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

SAFETY DATA SHEET



FRJ-551

Version 1.0
Revision Date: 09/16/2020

Date of last issue: -
Date of first issue: 09/16/2020

mg/l
Exposure time: 96 h
Test Type: static test

LC50 (Lepomis macrochirus (Bluegill sunfish)): 13.1 - 16.5 mg/l
Exposure time: 96 h
Test Type: flow-through test

LC50 (Oncorhynchus mykiss (rainbow trout)): 13.5 - 17.3 mg/l
Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): 2.661 - 4.093 mg/l
Exposure time: 96 h
Test Type: static test

LC50 (Pimephales promelas (fathead minnow)): 13.4 mg/l
Exposure time: 96 h
Test Type: flow-through test

LC50 (Pimephales promelas (fathead minnow)): 23.53 - 29.97 mg/l
Exposure time: 96 h
Test Type: static test

LC50 (Poecilia reticulata (guppy)): 30.26 - 40.75 mg/l
Exposure time: 96 h
Test Type: static test

Para-tert-butylphenol (PTBP):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 1.0 mg/l
Exposure time: 96 h
Test Type: semi-static test

LC50 (Pimephales promelas (fathead minnow)): 5.14 mg/l
Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3.9 - 4.8 mg/l
Exposure time: 48 h
Test Type: static test

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (algae)): 14 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : 0.1 mg/l

Toxicity to daphnia and other : 0.73 mg/l

SAFETY DATA SHEET



FRJ-551

Version 1.0 Revision Date: 09/16/2020

Date of last issue: -
Date of first issue: 09/16/2020

aquatic invertebrates (Chronic toxicity)

Persistence and degradability

Product:

Biodegradability : Remarks: Not readily biodegradable.

Bioaccumulative potential

Components:

Xylene:

Partition coefficient: n-octanol/water : log Pow: 3.16 (20 °C / 20 °C)

Para-tert-butylphenol (PTBP):

Partition coefficient: n-octanol/water : log Pow: 3.31 (25 °C / 25 °C)

Mobility in soil

Product:

Stability in soil : Remarks: Adsorbs on soil.

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

FRJ-551

 Version 1.0
 Revision Date: 09/16/2020

 Date of last issue: -
 Date of first issue: 09/16/2020
SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	1666
Xylene	1330-20-7	100	100 (F003)

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Formaldehyde	50-00-0	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : See section 2 for classified hazards based on component information

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Xylene	1330-20-7	>= 5 - < 10 %
--------	-----------	---------------

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Xylene	1330-20-7	>= 5 - < 10 %
--------	-----------	---------------

SAFETY DATA SHEET



FRJ-551

Version 1.0
Revision Date: 09/16/2020

Date of last issue: -
Date of first issue: 09/16/2020

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

Xylene	1330-20-7	>= 5 - < 10 %
--------	-----------	---------------

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

Xylene	1330-20-7	>= 5 - < 10 %
Formaldehyde	50-00-0	>= 0 - < 0.1 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Xylene	1330-20-7	>= 5 - < 10 %
Formaldehyde	50-00-0	>= 0 - < 0.1 %

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

US State Regulations

Massachusetts Right To Know

Xylene	1330-20-7
Formaldehyde	50-00-0

Maine Chemicals of High Concern

Product does not contain any listed chemicals


Vermont Chemicals of High Concern

Product does not contain any listed chemicals

Washington Chemicals of High Concern

Product does not contain any listed chemicals

California Prop. 65

 **WARNING:** This product can expose you to chemicals including Formaldehyde, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Xylene	1330-20-7
--------	-----------

California Permissible Exposure Limits for Chemical Contaminants

Xylene	1330-20-7
--------	-----------

The ingredients of this product are reported in the following inventories:

REACH	: Not in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
NZIoC	: All components of this product are on the Canadian DSL

SAFETY DATA SHEET

FRJ-551

Version 1.0
Revision Date: 09/16/2020

Date of last issue: -
Date of first issue: 09/16/2020

ENCS	:	On the inventory, or in compliance with the inventory
ISHL	:	On the inventory, or in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
TCSI	:	On the inventory, or in compliance with the inventory
TSCA	:	All components of this product are on the Canadian DSL

TSCA list


No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	*	2
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Haz-

SAFETY DATA SHEET



FRJ-551

Version 1.0 Revision Date: 09/16/2020

Date of last issue: -
Date of first issue: 09/16/2020

ardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.

Revision Date : 09/16/2020

The information and recommendations contained in this safety data sheet are, to the best of SI Group's knowledge, belief and experience, accurate and reliable as of the date of its publication and describe the product only with regard to safety requirements. It is the user's responsibility to confirm that it is using the most current available version of this safety data sheet. The information and recommendations herein are offered for the user's consideration and examination. Identified uses in this safety data sheet do neither represent an agreement on the quality of the Product nor a designated use. For the avoidance of doubt, nothing herein shall be construed as relieving the user of its responsibility to ensure that the product is suitable for the intended use and that any proprietary rights, existing laws and legislation are observed. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING THE PRODUCT DESCRIPTIONS, DATA OR INFORMATION HEREIN. This safety data sheet is neither a Certificate of Analysis (CoA) nor a technical data sheet and shall not be mistaken for a description of the product's specifications. If user repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the packaging. Appropriate warnings and safe-handling procedures should be provided to handlers and further

SAFETY DATA SHEET



FRJ-551

Version 1.0 Revision Date:
09/16/2020

Date of last issue: -
Date of first issue: 09/16/2020

users of the product. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted.

US / Z8