



Product Data Sheet

Product Name: POLYOX WSR N3000

Page 1/2

The following specifications apply to sealed, unopened containers stored under the recommended conditions for the duration of the shelf life.

MATERIAL DATA, PHS

| | |
|-------------------------------|---------------------------|
| MATERIAL NUMBER | 166195 |
| MATERIAL DESCRIPTION | WSR POLYOX N3000 DRF140LB |
| SPECIFICATION NAME | POLYOX(TM) WSR N3000 |
| SPECIFICATION TYPE | SALES SPECIFICATION |
| SPECIFICATION EFFECTIVE DATE | November 28, 2022 |
| SPECIFICATION SUPERSEDES DATE | July 22, 2019 |

VISCOSITY, PHS

| | |
|---------------------------|---|
| VISCOSITY, BROOKFIELD. 5% | 2,250 - 4,500 mPa.s <i>PSM 101962 5%AQUEOUS SOLUTION</i> |
|---------------------------|---|

SCREENING, PHS

| | |
|---------------------|--|
| SCREEN <840 MICRON | 96 - 100 % <i>PSM 102261 THRU 20 MESH</i> |
| SCREEN <2000 MICRON | >= 100 % <i>PSM 102261 THRU 10 MESH</i> |

COMPOSITION, PHS

| | |
|-----------------|--|
| SILICON DIOXIDE | 0.8 - 3.0 % <i>PSM 101992</i> |
| BHT MG/KG | 100 - 1,000 mg/kg <i>PSM 102192</i> |

METALS, PHS

| | |
|-----------------------|----------------------------------|
| ALKALINE EARTH METALS | 0.0 - 1.0 % <i>PSM 102225</i> |
|-----------------------|----------------------------------|

Alkaline earth metals as CaO.

Viscosity - Brookfield RVF, spindle 1, speed 2 rpm, 25 deg C.

Document ID 3057093
Profile 6632

DISCLAIMER: The information contained herein is based on data known to IFF at the time of preparation. **It is subject to change pending the accumulation of additional data.** This is business-to-business information not intended for a consumer. The information is provided "AS IS" and its use is at the recipient's sole risk. It is the recipient's sole responsibility to determine the suitability and legality of its proposed use of IFF products for its specific purposes. Information herein shall not be construed as licenses to practice, or recommendations to infringe, any patents or other intellectual property rights of IFF or others. **TO THE FULLEST EXTENT PERMITTED UNDER APPLICABLE LAW, IFF hereby expressly disclaims (I) any and all liability in connection with such information, and (II) any and all representations or warranties, express or implied, with respect to such information, including of title, noninfringement of third-party rights, merchantability or fitness, and WARRANTIES ARISING UNDER APPLICABLE LAW.**



Product Data Sheet

Product Name: POLYOX WSR N3000

Page 2/2

METALS, PHS

The following properties are characteristic of this product: However, these properties are not determined on shipments and are not reported on the Certificate of Analysis: pH, 5.0% aq. soln. at 25 C: 8.0 to 10.0; Volatiles, 45 min, at 105 C: 1.0% by weight (max).

This is a computer generated document and is therefore not signed.

Document ID 3057093
Profile 6632

DISCLAIMER: The information contained herein is based on data known to IFF at the time of preparation. **It is subject to change pending the accumulation of additional data.** This is business-to-business information not intended for a consumer. The information is provided "AS IS" and its use is at the recipient's sole risk. It is the recipient's sole responsibility to determine the suitability and legality of its proposed use of IFF products for its specific purposes. Information herein shall not be construed as licenses to practice, or recommendations to infringe, any patents or other intellectual property rights of IFF or others. **TO THE FULLEST EXTENT PERMITTED UNDER APPLICABLE LAW, IFF hereby expressly disclaims (i) any and all liability in connection with such information, and (ii) any and all representations or warranties, express or implied, with respect to such information, including of title, noninfringement of third-party rights, merchantability or fitness, and WARRANTIES ARISING UNDER APPLICABLE LAW.**