


Technical Data Sheet**FireGard[®] LT**
Antimony Trioxide

FireGard[®] ATO is a high purity and low tint grade of antimony trioxide, manufactured under controlled conditions and from high purity raw materials.

CAS Reg. Number: [1309-64-4]

Typical Properties	
Appearance	Fine White Powder
Specific Gravity	5.5
Average Particle Size	2 to 3 Microns
Sieve Residue < 325 Mesh	≤ 0.10%
Typical Composition Sb₂O₃	
Antimony Trioxide	≥ 99.8%
Arsenic	≤ 0.10%
Lead	≤ 0.10%
Iron	≤ 0.004%

Applications

FireGard[®] LT is an effective flame retardant synergist when used in conjunction with suitable halogenated compounds or resins.

Packaging

Standard packages include 25 kg bags or 1,000 kg super sacks.

Health and Safety

The use of proper protective equipment is recommended. Excess exposure to the product should be avoided. Please wash thoroughly after handling. Store the product in a cool, dry, well-ventilated area, away from incompatible materials. For additional handling and toxicological information, consult the St. Louis Group Material Safety Data Sheet.

This information is believed to be an accurate and reliable representation of the products average properties and it is offered in good faith, but without guarantee and may be modified by later findings. This document does not constitute a specification. The manufacturer makes no warranties, express or implied, regarding the accuracy, completeness, or adequacy of the information contained herein. Any recommendations or suggestions are also made without warranty or guarantee, since the conditions of use are beyond our control. It is the obligation of the customer/user to make its own assessment to determine suitability of use for any purpose, including, the appropriate health, safety, disposal, and environmental precautions necessary in each products intended use(s).

8888 Keystone Crossing, Suite 650 • Indianapolis, IN 46240 • Phone (317) 975-3121

www.thestlouisgroup.com

Effective Date: 9/1/17