

Eastman AQ(TM) 48 Ultra Polymer

Version Revision Date: SDS Number: Date of last issue: 08/27/2014
3.0 04/25/2017 150000001940 Date of first issue: 07/14/2011
SDSCA / PRD / 0001

SECTION 1. IDENTIFICATION

Product name : Eastman AQ(TM) 48 Ultra Polymer

Product code : P15318F8

Manufacturer or supplier's details

Company name of supplier : Eastman Chemical Company

Address : 200 South Wilcox Drive
 Kingsport TN 37660-5280

Telephone : (423) 229-2000

Emergency telephone number : CHEMTREC: +1-800-424-9300, +1-703-527-3887 CCN7321

Recommended use of the chemical and restrictions on use

Recommended use : Cosmetic.

Restrictions on use : None known.

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance name : not applicable

Components

SECTION 4. FIRST AID MEASURES

If inhaled : Move to fresh air.
 Treat symptomatically.
 If symptoms persist, call a physician.

In case of skin contact : Wash off with soap and water.
 If symptoms persist, call a physician.
 Cool skin rapidly with cold water after contact with molten

Eastman AQ(TM) 48 Ultra Polymer

Version	Revision Date:	SDS Number:	Date of last issue: 08/27/2014
3.0	04/25/2017	150000001940	Date of first issue: 07/14/2011
SDSCA / PRD / 0001			

material.
Do not peel solidified product off the skin.
Burns must be treated by a physician.

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

If swallowed : Seek medical advice.

Most important symptoms and effects, both acute and delayed : The molten product can cause serious burns.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray
Dry chemical
Carbon dioxide (CO₂)

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

Specific hazards during fire-fighting : Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.

Hazardous combustion products : No hazardous combustion products are known

Further information : Minimize dust generation and accumulation.

Special protective equipment for firefighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Wear appropriate personal protective equipment.
Local authorities should be advised if significant spillages cannot be contained.

Environmental precautions : Avoid release to the environment.

Methods and materials for containment and cleaning up : Sweep up and shovel into suitable containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against : Minimize dust generation and accumulation.

Eastman AQ(TM) 48 Ultra Polymer

Version	Revision Date:	SDS Number:	Date of last issue: 08/27/2014
3.0	04/25/2017	150000001940	Date of first issue: 07/14/2011
SDSCA / PRD / 0001			

fire and explosion

Advice on safe handling : Wash thoroughly after handling.
Use only in area provided with appropriate exhaust ventilation.
Minimize dust generation and accumulation.

Conditions for safe storage : Keep tightly closed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Contains no substances with occupational exposure limit values.

Engineering measures : Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Wear respiratory protection when its use is identified for certain contributing scenario.

Hand protection

Remarks : Wear suitable gloves. When handling hot material, use heat resistant gloves.

Eye protection : Safety glasses
Wear a face shield when working with molten material.

Skin and body protection : Wear suitable protective clothing.

Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : pellets

Colour : amber

Eastman AQ(TM) 48 Ultra Polymer

Version	Revision Date:	SDS Number:	Date of last issue: 08/27/2014
3.0	04/25/2017	150000001940	Date of first issue: 07/14/2011
SDSCA / PRD / 0001			

Odour	: ester-like
Odour Threshold	: not determined
Softening point	: 48 °C
Flash point	: not applicable, combustible solid
Evaporation rate	: not determined
Vapour pressure	: not determined
Relative density	: > 1 (estimated)
Solubility(ies)	
Water solubility	: negligible
Decomposition temperature	: Thermal stability not tested. Low stability hazard expected at normal operating temperatures.
Viscosity	
Viscosity, dynamic	: 5,000,000 mPa.s (200 °C)
Viscosity, kinematic	: not determined

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: None reasonably foreseeable.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Stable
Conditions to avoid	: Minimize dust generation and accumulation.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: Carbon monoxide Carbon dioxide (CO ₂)

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Eastman AQ(TM) 48 Ultra Polymer

Version	Revision Date:	SDS Number:	Date of last issue: 08/27/2014
3.0	04/25/2017	150000001940	Date of first issue: 07/14/2011

SDSCA / PRD / 0001

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Information on likely routes of exposure**Product:**

Inhalation : Remarks: None known.

Skin contact : Remarks: The molten product can cause serious burns.

Eye contact : Remarks: The molten product can cause serious burns.

Ingestion : Remarks: None known.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Eastman AQ(TM) 48 Ultra Polymer

Version	Revision Date:	SDS Number:	Date of last issue: 08/27/2014
3.0	04/25/2017	150000001940	Date of first issue: 07/14/2011
SDSCA / PRD / 0001			

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**TDG**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**The components of this product are reported in the following inventories:**

CH INV	: On the inventory, or in compliance with the inventory
DSL	: On the inventory, or in compliance with the inventory
AICS	: On the inventory, or in compliance with the inventory
NZIoC	: On the inventory, or in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TCSI	: On the inventory, or in compliance with the inventory
TSCA	: On the inventory, or in compliance with the inventory

Canadian lists

No substances are subject to a Significant New Activity Notification.

Eastman AQ(TM) 48 Ultra Polymer

Version	Revision Date:	SDS Number:	Date of last issue: 08/27/2014
3.0	04/25/2017	150000001940	Date of first issue: 07/14/2011

SDSCA / PRD / 0001

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 04/25/2017

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN