



DOWTHERM™ • SYLTHERM† • DOWFROST™ • DOWCAL™

Heat Transfer Fluids

Product Line

# Guide

*The Industry's Broadest Range of  
Performance and Economic Options*

™Trademark of The Dow Chemical Company (Dow) or an affiliated company of Dow.

†SYLTHERM Heat Transfer Fluids are manufactured by Dow Corning Corporation and distributed by The Dow Chemical Company.

There's a DOWTHERM,<sup>™</sup>

SYLTHERM,<sup>†</sup>

DOWFROST<sup>™</sup> or

DOWCAL<sup>™</sup> Fluid To Meet

Your Needs

Learn More at  
[www.dowtherm.com](http://www.dowtherm.com)

Visit our website for complete information about the full family of heat transfer fluids available from Dow, including fluid selection assistance, product technical data, application information and technical support resources.

Dow is a diversified chemical company that harnesses the power of innovation, science and technology to constantly improve what is essential to human progress. The Company offers a broad range of products and services to customers, helping them to provide everything from fresh water, food and pharmaceuticals to paints, packaging and personal care products.

The family of DOWTHERM,<sup>™</sup> SYLTHERM,<sup>†</sup> DOWFROST,<sup>™</sup> and DOWCAL<sup>™</sup> heat transfer fluids available from Dow consists of nineteen high performance products. The line includes three distinct fluid chemistries – synthetic organic, silicone, and inhibited glycol – providing you with the industry's broadest range of performance and economic options.

You'll find an overview description of our full line of fluids, plus a summary of performance characteristics and recommended applications on page 15 of this brochure.

Because Dow offers the most comprehensive range of fluid options, we are uniquely equipped to thoroughly and fairly assess your performance and economic requirements, and then recommend the best fluid to meet your needs.

### We're equipped to supply you globally

As the world's premier supplier of heat transfer fluids, we're positioned to serve you globally. So whether your project is in Asia-Pacific, Europe, Latin America, the Middle East, Africa, India, North America, or anywhere else in the world, we can supply the fluid you need to make it a success. Our synthetic organic and silicone fluids are available globally. While you also have global access to a wide range of Dow glycol-based fluids worldwide, availability of grades may vary by region. See the table on page 7 for the geographic availability of Dow glycol-based fluids.

<sup>™</sup>Trademark of The Dow Chemical Company (Dow) or an affiliated company of Dow.

<sup>†</sup>SYLTHERM Heat Transfer Fluids are manufactured by Dow Corning Corporation and distributed by The Dow Chemical Company.

## Fluids for high temperature process heating and single fluid process heating and cooling

### DOWTHERM™ Synthetic Organic Fluids Offer Excellent Stability

Each of our seven DOWTHERM™ Synthetic Organic Fluids offers exceptional thermal stability. This stability can translate into more efficient heat transfer, longer fluid life, and optimum operating economics. For example, DOWTHERM™ A Fluid has set the industry standard for over 70 years — precisely because of its excellent thermal stability in applications up to 400°C (750°F).

All DOWTHERM™ Fluids feature vapor pressures lower than steam. Three DOWTHERM™ Fluids — DOWTHERM™ RP, DOWTHERM™ MX, and DOWTHERM™ T — are designed to operate in non-pressurized or low-pressure heat transfer systems. DOWTHERM™ RP Fluid in particular has been shown to be more thermally stable than partially hydrogenated terphenyl and dibenzyl toluene fluids.

DOWTHERM™ J Fluid can be used in batch processing applications for single fluid process heating and cooling. And DOWTHERM™ Q Fluid offers long-term advantages as an economical replacement for hot oils in applications with moderate temperature requirements above 260°C (500°F).

### SYLTHERM† Silicone Fluids Are Long-lasting, Odorless Options

SYLTHERM† 800, SYLTHERM XLT†, and SYLTHERM HF Silicone Fluids are low viscosity fluids that offer excellent heat transfer performance and can provide exceptionally long service life (often more than 10 years) without periodic reclaiming. In addition, SYLTHERM 800 Fluid has the broadest operating range of any heat transfer fluid.

SYLTHERM Fluids are essentially odorless, are low in acute oral toxicity, and, in the U.S., are not listed as reportable under SARA Title III, Section 313¹.

## Applications for DOWTHERM™ Synthetic Organic Fluids and SYLTHERM† Silicone Fluids: -100°C (-150°F) to 400°C (750°F)

- Indirect heating of process liquids and polymers
- Single fluid process heating and cooling (particularly pharmaceutical batch processing)
- Pipeline tracing to maintain process temperatures
- Energy recovery
- Low pressure cogeneration systems
- Drying and heating of bulk materials
- Solar energy collection and storage
- Gas processing
- Ebullient cooling
- LNG Liquification

### Oil and Gas Processing



™Trademark of The Dow Chemical Company (Dow) or an affiliated company of Dow.

†SYLTHERM Heat Transfer Fluids are manufactured by Dow Corning Corporation and distributed by The Dow Chemical Company.

¹You may need to comply with similar or additional legislation in other countries. Contact your Dow representative for information.





**Food & Beverage  
Chilling/Freezing**



**HVAC System Freeze/Burst/  
Corrosion Protection, TES Systems**

## Low temperature fluids for protection of water-based process circuits and HVAC systems, plus food processing applications

### **DOWTHERM™, DOWFROST™ and DOWCAL™ Inhibited Glycol-based Fluids Provide Freeze and Corrosion Protection**

DOWTHERM™, DOWFROST™ and DOWCAL™ Inhibited Glycol-based Fluids are widely used for freeze/burst and corrosion protection in closed-loop, water-based heating and air conditioning systems, as well as in water-based process heating/cooling circuits. Solutions of these fluids offer fluid freeze protection to -50°C (-60°F) and system burst protection below -73°C (-100°F). DOWTHERM™, DOWFROST™ and DOWCAL™ Fluids contain specially formulated corrosion inhibitor packages which provide protection for metals commonly used in heat transfer systems.

The food processing industry also takes advantage of the low temperature performance and corrosion protection properties of these glycol-based fluids. Applications include food product chilling and freezing, as well as coil defrosting and cold room dehumidifying.

Low temperature pumpability down to -50°C (-60°F) and high temperature operation up to 175°C (350°F) can make these fluids useful in single fluid process heating and cooling applications (batch processing).

### **Applications for DOWTHERM™, DOWFROST™ and DOWCAL™ Inhibited Glycol-based Fluids: -50°C (-60°F) to 175°C (350°F)**


- HVAC system freeze/burst/corrosion protection
- Thermal energy storage (TES)
- Ground source heat pumps
- Hydronic heating systems
- Immersion freezing or chilling of solid, wrapped foods
- Batch processing
- Refrigeration coil defrosting
- Conveyor roller defrosting
- Process chilling
- Sidewalk snow melting systems
- Refrigeration warehouse floor heating

- Liquid food cooling
- Fermentation cooling
- Cold room dehumidifying
- Heat recovery
- Solar heating
- Ice skating rinks
- Grocery store secondary loop refrigeration systems

### **You not only get more fluid options, you get more support**

Dow is more than just a supplier of heat transfer fluids; we are also a leading source of heat transfer expertise. No other company can match Dow's more than 70 years' experience as a fluid supplier. In addition, our fluids are used every day in Dow processing plants all over the world. This combination of fluid knowledge and applications expertise has made Dow the industry's leading source of technical support. Call on our experienced staff of fluid specialists. They can consult with you on the design, operation, and maintenance of your heat transfer system to help you achieve optimum performance and economy.

The FLUIDFILE™ Program makes evaluating and selecting heat transfer fluids faster, easier, and more precise. To use FLUIDFILE™ visit [www.fluidfile.com](http://www.fluidfile.com).




**Ice Rink Cooling**

<sup>™</sup>Trademark of The Dow Chemical Company (Dow) or an affiliated company of Dow.

<sup>†</sup>SYLTHERM Heat Transfer Fluids are manufactured by Dow Corning Corporation and distributed by The Dow Chemical Company.

## Choose From Our Family of Nineteen Fluids



Solar Heating



Pharmaceutical Batch  
Processing



Synthetic Fiber Processing

### DOWTHERM™ Synthetic Organic Fluids

#### DOWTHERM™ A

With excellent thermal stability at 400°C (750°F), this fluid's maximum recommended film temperature is 427°C (800°F). Its recommended use temperature range in liquid phase operations is from 15°C (60°F) to 400°C (750°F) and in vapor phase from 257°C (495°F) to 400°C (750°F). With low viscosity to minimize start-up problems, and a freezing point of 12°C (54°F), DOWTHERM™ A Fluid can be used without steam tracing in installations protected from the weather.


#### DOWTHERM™ G

As the most stable, low pressure liquid-phase fluid, DOWTHERM™ G Fluid offers low vapor pressure with high thermal stability and pumpability at moderately low temperatures. This efficient, medium-range heat transfer fluid has a recommended use temperature range of -7°C (20°F) to 360°C (680°F).

#### DOWTHERM™ J

DOWTHERM™ J Heat Transfer Fluid can be used in liquid phase as low as -80°C (-110°F) and up to 315°C (600°F). In vapor phase, the range is from 181°C (358°F) to 315°C (600°F). This is the fluid of choice for the most demanding single fluid heating and cooling applications (batch processing). Thermal stability is excellent in both liquid and vapor phase.

### DOWTHERM™ Synthetic Organic and SYLTHERM™ Silicone Heat Transfer Fluids



#### DOWTHERM™ MX

DOWTHERM™ MX Heat Transfer Fluid is a mixture of alkylated aromatics designed for use as an alternative to hot oils in liquid phase heat transfer systems. The normal operating temperature range for DOWTHERM™ MX Fluid is -23°C (-10°F) to 330°C (625°F).

#### DOWTHERM™ Q

Introduced as an alternative to hot oils, DOWTHERM™ Q Fluid has a recommended use temperature range of -35°C (-30°F) to 330°C (625°F). It combines high temperature stability with low temperature pumpability and superior heat transfer – a combination hot oils can't match. Because of its superior thermal stability, this fluid can offer substantial economic savings over the life of your heat transfer project. It is ideally suited for waste heat recovery and LNG liquification.

#### DOWTHERM™ RP

DOWTHERM™ RP Heat Transfer Fluid is a liquid phase fluid used in pressureless or low-pressure systems. It can be used in systems operating up to a maximum bulk temperature of 350°C (660°F) and a maximum film temperature of 375°C (710°F). DOWTHERM™ RP Fluid degrades primarily to low molecular weight products, reducing the need to remove high molecular weight material from the system. In some cases, DOWTHERM™ RP Fluid can also be used to top up other low pressure fluids.

#### DOWTHERM™ T

This mixture of alkyl benzenes is intended for liquid phase operation in non-pressurized systems. DOWTHERM™ T Fluid has an optimum maximum use temperature of 288°C (550°F). It can be used to an extended bulk temperature of 316°C (600°F). It has good low temperature properties that allow for low temperature start-up, and good thermal stability at the maximum use temperature.

™Trademark of The Dow Chemical Company (Dow) or an affiliated company of Dow.

†SYLTHERM Heat Transfer Fluids are manufactured by Dow Corning Corporation and distributed by The Dow Chemical Company.

## SYLTHERM<sup>†</sup> Silicone Fluids

### SYLTHERM<sup>†</sup> 800

SYLTHERM<sup>†</sup> 800 Fluid is a highly stable, long-lasting, silicone fluid with a recommended operating temperature range of -40°C (-40°F) to 400°C (750°F), the broadest range of any heat transfer fluid. Operating continuously at the upper end of this range, SYLTHERM 800 Fluid exhibits low potential for fouling and can often remain in service for 10 years or more. The fluid is essentially odorless and is very low in acute oral toxicity. Silicone heat transfer fluids such as SYLTHERM 800 Fluid are not listed as reportable in the U.S. under SARA Title III, Section 313<sup>‡</sup>.

### Radiant Heating

### SYLTHERM XLT<sup>†</sup>

SYLTHERM XLT<sup>†</sup> Fluid will operate as low as -100°C (-150°F) and up to 260°C (500°F). This wide operating temperature range makes this silicone fluid especially well-suited for single fluid process heating and cooling (batch processing) systems in the pharmaceutical and fine chemical industries. In addition, SYLTHERM XLT Fluid has essentially no odor, is very low in acute oral toxicity, and is not listed as reportable in the U.S. under SARA Title III, Section 313<sup>‡</sup>.

### SYLTHERM<sup>†</sup> HF

SYLTHERM<sup>†</sup> HF Fluid is a specially formulated silicone polymer designed for use as a low temperature, liquid phase heat transfer medium. With a similar recommended use temperature range [-73°C (-100°F) to 260°C (500°F)] as SYLTHERM XLT<sup>†</sup> Fluid, SYLTHERM HF Fluid also offers a closed-cup flash point above 63°C (145°F). In addition, SYLTHERM HF Fluid has essentially no odor, is very low in acute oral toxicity, and is not listed as reportable in the U.S. under SARA Title III, Section 313<sup>‡</sup>.

## DOWTHERM<sup>™</sup>, DOWFROST<sup>™</sup>, and DOWCAL<sup>™</sup> Inhibited Glycol-based Heat Transfer Fluids

### DOWTHERM<sup>™</sup> SR-1

This ethylene glycol-based fluid is suitable for use in closed-loop, water-based HVAC, process heating and cooling, and food industry applications operating from -50°C (-60°F) to 120°C (250°F). A specially formulated inhibitor package provides excellent corrosion protection for common metals. The inhibitor package is easily maintained, long-lasting, and replenishable. That means fluid replacement intervals are extended and long-term fluid costs are reduced. DOWTHERM<sup>™</sup> SR-1 Fluid has lasted more than 20 years in properly maintained heat transfer systems.

### DOWFROST<sup>™</sup>

DOWFROST<sup>™</sup> Fluid's recommended use temperature range is -45°C (-50°F) to 120°C (250°F). This propylene glycol-based fluid is used in solution with water in food processing applications. It is also used in freeze protection of building sprinkler systems where incidental contact with potable water is possible (e.g., when connected by a back-flow preventer to a city water supply), or where state regulations require the use of a propylene glycol-based fluid. A specially formulated industrial inhibitor package provides outstanding corrosion protection.

### DOWTHERM<sup>™</sup> 4000

This ethylene glycol-based fluid features the highest maximum use temperature of any glycol. Operating in water-based systems between -50°C (-60°F) and 175°C (350°F), this fluid is specially formulated with inhibitors to offer greater thermal stability and corrosion protection. The fluid is suitable for thermally demanding operations, as well as for applications where long fluid life and extended maintenance intervals are desired. The fluid's wide temperature range also makes it suitable for single fluid process heating and cooling.


<sup>™</sup>Trademark of The Dow Chemical Company (Dow) or an affiliated company of Dow.

<sup>†</sup>SYLTHERM Heat Transfer Fluids are manufactured by Dow Corning Corporation and distributed by The Dow Chemical Company.

<sup>‡</sup>You may need to comply with similar or additional legislation in other countries. Contact your Dow representative for information.



## DOWTHERM™, DOWFROST™, and DOWCAL™ Inhibited Glycol-based Heat Transfer Fluids



### DOWFROST™ HD

This propylene glycol-based fluid has a recommended use temperature range of -45°C (-50°F) to 160°C (325°F). It is suited for thermally demanding applications or where long fluid life and extended maintenance intervals are desired. Specially formulated inhibitors provide higher reserve alkalinity for improved long-term corrosion protection. Solutions of this fluid are used in closed-loop, water-based HVAC applications where customers prefer propylene glycol solutions or where regulations require the use of propylene glycol solutions. Excellent copper corrosion protection makes DOWFROST™ HD Fluid the preferred propylene glycol option for HVAC applications. The fluid may also be used for single fluid process heating and cooling.

### DOWCAL™ 10 DOWTHERM™ 10

DOWCAL™ 10 and DOWTHERM™ 10 Fluids are ethylene glycol-based fluids with specially formulated inhibitor packages to prevent corrosion of materials commonly used in the construction of water-based systems, including aluminum components. These fluids are used in HVAC systems to provide freeze and corrosion protection. They can also be used for freeze point depression in other applications from -50°C (-60°F) to 175°C (350°F).

### DOWCAL™ N DOWFROST™ N

Like DOWFROST™ Fluid, DOWCAL™ N and DOWFROST™ N Fluids are propylene glycol-based fluids that are low in acute oral toxicity and widely used to depress freeze points in food and beverage processing and in other applications between -45°C (-50°F) and 120°C (250°F). They feature a specially formulated corrosion inhibitor package.

### DOWFROST™ 20 G

These fluids are capable of operating at higher temperatures than other propylene glycol-based fluids. They are low in acute oral toxicity and may be used in applications ranging from -45°C (-50°F) to 160°C (325°F). A specially formulated inhibitor package prevents corrosion of common materials of construction (including protection of aluminum components) in HVAC, food and beverage processing, and other applications.

### Geographic Availability of Glycol-based Fluids

Dow Glycol-based Fluids	North America	Latin America	Western Europe	Eastern and Central Europe, India, Middle East, Africa	Asia-Pacific	
DOWTHERM™ SR-1	•	•		•	•	Ethylene Glycol
DOWTHERM™ 4000	•	•		•	•	Ethylene Glycol
DOWFROST™	•	•		•	•	Propylene Glycol
DOWFROST™ HD	•	•		•	•	Propylene Glycol
DOWCAL™ 10			•			Ethylene Glycol
DOWTHERM™ 10				•		Ethylene Glycol
DOWCAL™ N			•			Propylene Glycol
DOWFROST™ N				•		Propylene Glycol
DOWCAL™ 20 G			•			Propylene Glycol
DOWFROST™ 20 G				•		Propylene Glycol

™Trademark of The Dow Chemical Company (Dow) or an affiliated company of Dow.

†SYLTHERM Heat Transfer Fluids are manufactured by Dow Corning Corporation and distributed by The Dow Chemical Company.

# Typical Properties of DOWTHERM™ Synthetic Organic and SYLTHERM† Silicone Heat Transfer Fluids<sup>1</sup>



Process Heating and Cooling

## English Units

		<b>DOWTHERM™ A</b> Diphenyl Oxide/ Biphenyl Blend	<b>DOWTHERM™ G</b> Mixture of Di- and Tri-Aryl Ethers	<b>DOWTHERM™ J</b> Alkylated Aromatic
Composition				
Temperature Use	liquid	60 to 750	20 to 680	-110 to 600
Range, °F	vapor	495 <sup>3</sup> to 750		358 <sup>3</sup> to 600
Vapor Pressure, psia	at max. use temp.	152.02	49.12	174.52
Thermal Conductivity, Btu/(hr · ft <sup>2</sup> )(°F/ft)	at min. use temp.	0.081	0.074	0.086
	at max. use temp.	0.045	0.049	0.038
Specific Heat, Liquid, Btu/(lb · °F)	at min. use temp.	0.373	0.363	0.365
	at max. use temp.	0.644	0.606	0.72
Viscosity, cps	at min. use temp.	4.91	64.3	9.67
	at max. use temp.	0.13	0.21	0.164
Density, Liquid, lb/ft <sup>3</sup>	at min. use temp.	66.37	70.34	58.31
	at max. use temp.	42.57	46.19	35.46
Freezing Point, °F		53.6	<20	<-100
Flash Point, °F, Closed Cup		236	≥80	136
Autoignition Temperature, °F, ASTM E659-78		1139	810	788

## SI Units

		<b>DOWTHERM™ A</b> Diphenyl Oxide/ Biphenyl Blend	<b>DOWTHERM™ G</b> Mixture of Di- and Tri-Aryl Ethers	<b>DOWTHERM™ J</b> Alkylated Aromatic
Composition				
Temperature Use	liquid	15 to 400	-7 to 360	-80 to 315
Range, °C	vapor	257 <sup>3</sup> to 400		181 <sup>3</sup> to 315
Vapor Pressure, Bar Abs	at max. use temp.	10.6	3.5	11.9
Thermal Conductivity, W/(m)(K)	at min. use temp.	0.139	0.130	0.15
	at max. use temp.	0.078	0.087	0.066
Specific Heat, Liquid, kJ/(kg)(K)	at min. use temp.	1.558	1.451	0.1485
	at max. use temp.	2.702	2.735	2.983
Viscosity, mPa(s)	at min. use temp.	5.0	66.2	8.43
	at max. use temp.	0.13	0.208	0.16
Density, Liquid, kg/m <sup>3</sup>	at min. use temp.	1063.5	1067.8	931.3
	at max. use temp.	680.2	783.4	568.2
Freezing Point, °C		12	<4	<-81
Flash Point, °C, Closed Cup		113	137	57
Autoignition Temperature, °C, ASTM E659-78		615	432	420

<sup>1</sup>Properties shown are typical and should not be considered specifications.

<sup>2</sup>Properties for Aged fluid except flash point, viscosity.

<sup>3</sup>Boiling Point at atmospheric pressure.

<sup>4</sup>Properties of fluid as supplied. Properties may differ after extended use.

<sup>5</sup>ASTM D2155

™Trademark of The Dow Chemical Company (Dow) or an affiliated company of Dow.

†SYLTHERM Heat Transfer Fluids are manufactured by Dow Corning Corporation and distributed by The Dow Chemical Company.



DOWTHERM™ Q Mixture of Diphenyl- ethane and Alkylated Aromatics	DOWTHERM™ RP Diaryl Alkyl	DOWTHERM™ MX Mixture of Alkylated Aromatics	DOWTHERM™ T C <sub>14</sub> to C <sub>30</sub> Alkyl Benzene Derivatives	SYLTHERM† 800 <sup>2</sup> Polydimethyl- siloxane	SYLTHERM XLT† Polydimethyl- siloxane	SYLTHERM HF Polydimethyl- siloxane
-30 to 625	-30 to 660	-10 to 625	14 to 550	-40 to 750	-150 to 500	-100 to 500
44.42	13.63	15.1	2.6	197.32	75.46	39.76
0.074 0.044	0.0775 0.0513	0.0735 0.0523	0.077 0.056	0.085 0.037	0.078 0.0295	0.0752 0.0274
0.353 0.618	0.372 0.621	0.351 0.625	0.446 0.659	0.360 0.539	0.363 0.544	0.347 0.543
29.0 0.169	249 0.32	282 0.20	252 0.39	51.0 0.25	90.17 0.18	16.65 0.22
62.84 45.66	65.25 49.12	61.9 44.8	55.81 43.03	61.9 34.3	61.2 38.1	60.31 39.28
<-30	<-30	-13	<14	<-40	-158	<-115
249	381	329	370	320 <sup>a</sup>	116	145
773	725	788	707 <sup>b</sup>	725 <sup>b</sup>	662 <sup>b</sup>	671 <sup>b</sup>

DOWTHERM™ Q Mixture of Diphenyl- ethane and Alkylated Aromatics	DOWTHERM™ RP Diaryl Alkyl	DOWTHERM™ MX Mixture of Alkylated Aromatics	DOWTHERM™ T C <sub>14</sub> to C <sub>30</sub> Alkyl Benzene Derivatives	SYLTHERM 800 <sup>2</sup> Polydimethyl- siloxane	SYLTHERM XLT† Polydimethyl- siloxane	SYLTHERM HF Polydimethyl- siloxane
-35 to 330	-20 to 350	-23 to 330	-10 to 288	-40 to 400	-100 to 260	-73 to 260
3.1	0.96	1.05	0.2	13.7	5.2	2.7
0.128 0.077	0.134 0.089	0.127 0.090	0.133 0.098	0.146 0.064	0.134 0.051	0.13 0.048
1.476 2.586	1.561 2.602	1.47 2.617	1.87 2.761	1.506 2.257	1.520 2.276	1.453 2.273
29.7 0.17	221.1 0.31	274 0.20	252 0.39	51.0 0.25	78.63 0.18	16.46 0.22
1006.9 731.0	1043.2 785.0	991.9 717.8	893.9 688.6	990.6 547.0	978.5 608.8	965.8 629.1
<-35	0	-25	<-10	<-40	<-111	<-82
120	194	165	188	160 <sup>a</sup>	47	63
411	385	420	375 <sup>b</sup>	385 <sup>b</sup>	350 <sup>b</sup>	355 <sup>b</sup>

™Trademark of The Dow Chemical Company (Dow) or an affiliated company of Dow.

†SYLTHERM Heat Transfer Fluids are manufactured by Dow Corning Corporation and distributed by The Dow Chemical Company.

## How To Select The Right Heat Transfer Fluid

LNG Liquification

### First choose between high temperature and low temperature fluids

The decision to choose a synthetic organic fluid, a silicone fluid, or an inhibited glycol-based fluid is largely based on application temperature requirements. If your heat transfer application has a maximum use temperature requirement above 175°C (350°F), you should investigate “high temperature” synthetic organic and silicone fluids.

However, if your maximum use temperature will be lower than 175°C (350°F), or if you need freeze protection for a water-based system, consider using a “low temperature” inhibited glycol-based fluid.

Synthetic organic and silicone fluids are engineered to be thermally stable at temperatures up to 400°C (750°F). While operating at these elevated temperatures, these fluids exhibit vapor pressures much lower than steam, making them much more practical and less expensive to use. Some high temperature fluids, such as DOWTHERM™ J and SYLTHERM† Fluids, have broad operating temperature ranges. These fluids offer high temperature stability, as well as low temperature pumpability and excellent heat transfer characteristics.

Inhibited glycol-based fluids are actually solutions of water and inhibited glycols. The concentration of glycol in the fluid directly affects its performance properties and is specified by the user to meet specific application (typically minimum temperature) requirements.

### What to consider when selecting a high temperature synthetic organic or silicone fluid

#### Maximum Recommended Use Temperature/Thermal Stability

For efficient performance and longer fluid life, choose a fluid with a maximum recommended use temperature above your system’s anticipated bulk fluid temperature. A synthetic organic or silicone fluid’s maximum recommended operating temperature is an indication of the high temperature thermal stability properties of that fluid. Selection of a DOWTHERM™ or SYLTHERM Fluid with a maximum recommended use temperature above your highest anticipated operating temperature will provide optimum heat transfer efficiency, fluid life, and operating economy. All DOWTHERM™ and SYLTHERM Fluids exhibit excellent thermal stability within their recommended operating temperature ranges. Silicone fluids, in particular, exhibit low potential for fouling at elevated temperatures and, depending on service conditions, can last 10 years or longer when operating continuously at their recommended maximum operating temperatures.

™Trademark of The Dow Chemical Company (Dow) or an affiliated company of Dow.

†SYLTHERM Heat Transfer Fluids are manufactured by Dow Corning Corporation and distributed by The Dow Chemical Company.

**Low Temperature Pumpability**

If your system will be operated while exposed to cold winter weather, you'll need a fluid offering low viscosity and, therefore, low temperature pumpability. Low temperature pumpability is especially critical if your system is subject to shutdown – whether planned or unplanned. If the heat transfer fluid in the system is not pumpable, system start-up can be difficult if not impossible.

SYLTHERM† Silicone Fluids offer excellent low temperature pumpability characteristics, experiencing little viscosity change down to the lower end of their recommended operating ranges. Some DOWTHERM™ Synthetic Organic Fluids have very low crystal points so the fluids remain pumpable in extreme cold and the potential for prolonged costly system shutdown is minimized.

**Flammability and Fire Hazards**

Heat transfer systems occasionally experience vapor leaks to the atmosphere. Experience has shown that leaking vapors have usually cooled below the heat transfer fluid's fire point.

**Vapor Pressure**

Certain applications require the high operating range of a synthetic organic or silicone fluid – but combined with low vapor pressure. While all DOWTHERM™ and SYLTHERM Fluids have vapor pressures lower than steam, DOWTHERM™ G and DOWTHERM™ RP Fluids are especially effective in systems with specific low vapor pressure requirements. Another reason for selecting a fluid that offers low vapor pressure is the potentially lower initial investment in expansion tanks and other specialized equipment.

**Project Economics and Fluid Recoverability**

It is wise to look beyond initial cost when choosing your heat transfer fluid. Some fluids...such as hot oils...are less expensive at the outset – but those savings diminish significantly in the face of high yearly operating costs.

In evaluating potential long-term fluid cost, you'll want to consider two factors: 1) What effect will degradation and normal operational leakage have on annual fluid makeup requirements? 2) How often will a complete fluid change-out be necessary?

In choosing a high temperature fluid from our line, you'll also want to take into account the differences in the degradation and fouling potential of synthetic organic and silicone fluids.

**Long-term economics of synthetic organic fluids** – While synthetic organic fluids are highly stable within their recommended operating ranges, some degradation can be expected over time. A fluid's tendency to degrade under your system's operating conditions has a direct impact on the fluid's long-term cost (due to fluid makeup and replacement expense over time). To maximize fluid life, select a synthetic organic fluid offering sufficient thermal stability to both accommodate your maximum planned operating temperature and allow for unplanned excursions above that level...even if the initial cost of the fluid is higher than that of a less stable fluid (see "Maximum Recommended Use Temperature/ Thermal Stability" on page 10).

**Long-term economics of silicone fluids** – In terms of initial purchase cost, silicone fluids are typically more expensive than synthetic organic fluids. However, in many cases, the use of silicone fluids can result in lower long-term expenses because they do not degrade in the same manner as other fluids or require top-off refills. Although silicone polymers exhibit some thermally induced changes over time, a balanced, steady-state equilibrium composition is eventually attained. Depending on service conditions, this can reduce or eliminate the need for makeup fluid and extend fluid life to ten years or longer.

**Fluid analysis can also reduce long-term expense** – Regardless of which type of high temperature fluid you choose, for maximum long-term economy it is wise to participate in a regular fluid testing program such as Dow's fluid analysis service. Dow provides free annual fluid analysis to qualifying customers to help them periodically assess fluid condition and help ensure that system problems are avoided.

™Trademark of The Dow Chemical Company (Dow) or an affiliated company of Dow.

†SYLTHERM Heat Transfer Fluids are manufactured by Dow Corning Corporation and distributed by The Dow Chemical Company.



## How to Choose the Right Inhibited Glycol-based Heat Transfer Fluid

### Ethylene vs. Propylene Glycol

Early in your fluid selection process, local regulations or a specific application may require that you decide between the use of an ethylene or a propylene glycol-based fluid.

In most heat transfer applications, ethylene glycol-based fluids are your best choice because of their superior heat transfer efficiency.

This efficiency is largely due to the lower viscosity of ethylene glycol solutions. Another benefit of this viscosity advantage is the somewhat lower minimum operating temperatures ethylene glycols offer.

Propylene glycols are most commonly used in applications in which low acute oral toxicity is required, or for freeze protection where incidental contact with drinking water is possible. In some areas, use of propylene glycols is required by local regulation.

Both ethylene and propylene glycol-based fluids are used in food processing applications. The ingredients in DOWFROST™, DOWFROST™ N and DOWCAL™ N Inhibited Propylene Glycol-based Fluids are generally recognized as safe by the U.S. FDA<sup>1</sup>. Since these products also have the appropriate approvals, they can be used in immersion freezing of wrapped foods and other food applications where ethylene glycol is not permitted. (See "Food Product Chilling/Freezing" on page 13.)

### Glycol Concentration

Glycol-based fluids are solutions of glycol and water. The amount of glycol in a particular solution directly affects the fluid's performance. Therefore, the anticipated or desired glycol concentration should be considered when designing a system.

### Freeze and Burst Protection

Closed-loop, water-based heat transfer systems are vulnerable to sudden freezes and extended cold weather. Solutions of glycol-based fluids provide two different kinds of cold weather protection:

**Burst Protection:** If your system does not operate during the winter and cold weather start-up will not be required, you will want to specify a glycol concentration sufficient to prevent bursting but not necessarily high enough to maintain the fluid in a pumpable state. Solutions of all nine Dow inhibited glycol-based fluids can provide burst protection to below -73°C (-100°F).

**Freeze Protection:** If your system must remain operational in cold weather, or if cold weather start-ups may be required, freeze protection will be needed. As indicated by their minimum recommended operating temperatures, the freeze protection capabilities of DOWTHERM™, DOWFROST™ and DOWCAL™ Fluids vary slightly. Choose a solution concentration that will prevent the formation of ice crystals at 3°C (5°F) below the lowest anticipated system temperature.



Sidewalk Snow Melt Systems



Grocery Store Secondary Loop Refrigeration Systems

<sup>™</sup>Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow.

<sup>1</sup>You may need to comply with similar or additional legislation in other countries.

Contact your Dow representative for information.

## Concentrations of DOWTHERM™, DOWFROST™, and DOWCAL™ Fluids Required to Provide Freeze Protection and Burst Protection at Various Temperatures

Volume Percent Glycol Concentration Required

		For Freeze Protection		For Burst Protection	
		DOWTHERM™ SR-1 DOWTHERM™ 4000 DOWTHERM™ 10 DOWCAL™ 10	DOWFROST™ HD DOWFROST™ N DOWFROST™ 20 G DOWCAL™ N DOWCAL™ 20 G	DOWTHERM™ SR-1 DOWTHERM™ 4000 DOWTHERM™ 10 DOWCAL™ 10	DOWFROST™ HD DOWFROST™ N DOWFROST™ 20 G DOWCAL™ N DOWCAL™ 20 G
Temp., °C	(°F)	Fluids	Fluids	Fluids	Fluids
-7	(20)	16%	18%	11%	12%
-12	(10)	25	29	17	20
-18	(0)	33	36	22	24
-23	(-10)	39	42	26	28
-29	(-20)	44	46	30	30
-34	(-30)	48	50	30	33
-40	(-40)	52	54	30	35
-46	(-50)	56	57	30	35
-51	(-60)	60	60	30	35

Note: These figures are examples only and may not be appropriate to your situation. Generally, for an extended margin of protection, you should select a temperature in this table that is at least 3°C (5°F) lower than the expected lowest ambient temperature. Inhibitor levels should be adjusted for solutions of less than 30% glycol. Contact Dow for information on specific cases or further assistance.

### Corrosion Protection

It is important to specify an *inhibited* glycol-based fluid because, without inhibitors, glycol fluids can be more corrosive than water. All nine DOWTHERM™, DOWFROST™, and DOWCAL™ Inhibited Glycol-based Fluids contain specially formulated industrial inhibitor packages designed to prevent corrosion.

Corrosion is a major contributor to maintenance and operating expense in water-based HVAC, food, and process systems. Effective corrosion prevention can improve system efficiency, extend equipment life, and improve overall operating economy.

### Food Product Chilling/Freezing or Coil Defrosting/Dehumidifying

The low acute oral toxicity of DOWFROST™, DOWFROST™ N, DOWCAL™ N, DOWCAL™ 20 G and DOWFROST™ 20 G Propylene Glycol-based Fluids and the moderate acute oral toxicity of DOWTHERM™ SR-1, DOWCAL™ 10 and DOWTHERM™ 10 Ethylene Glycol-based Fluids make them highly useful fluids in many food industry applications. Selection of the proper glycol-based fluid in food processing applications depends largely on government regulatory requirements.

DOWFROST™ Fluid is the fluid of choice for immersion freezing of wrapped meat or poultry products in food processing plants operated under U.S. federal inspection. The ingredients in DOWFROST™ Fluid are listed as chemically acceptable by the U.S. Department of Agriculture (U.S.D.A.)<sup>1</sup>. A supporting letter from Dow is available upon request. The ingredients in DOWFROST™, DOWFROST™ N and DOWCAL™ N Fluids are generally recognized as safe by the U.S. Food and Drug Administration (FDA)<sup>1</sup>. DOWFROST™, DOWFROST™ N and DOWCAL™ N Fluids are also used in chilling or freezing applications where incidental fluid contact with food or beverage products is possible.

Both DOWFROST™ and DOWTHERM™ SR-1 Fluids are listed as chemically acceptable by the U.S.D.A.<sup>1</sup> for defrosting refrigeration coils in establishments operating under the U.S. federal meat and poultry products inspection program. The compounds must be used in a manner that prevents direct or indirect contamination of edible products.

### Glycol-based Fluid Maintenance

Fluid maintenance should be a major consideration in your choice of a glycol-based heat transfer fluid. A properly maintained inhibited glycol-based fluid should provide years of effective service. (DOWTHERM™ SR-1 Fluid has lasted over 20 years in some applications.)

Branded inhibited glycol-based fluids (such as DOWTHERM™, DOWFROST™, and DOWCAL™ Fluids) have a maintenance advantage over unbranded products. These Dow fluids can be periodically analyzed for inhibitor concentration, freeze point, and any significant changes in fluid quality. Unbranded glycol-based fluids, on the other hand, often can't be analyzed because their precise content is unknown. That means you are forced to guess about fluid condition and may replace fluid unnecessarily just to be sure system protection is maintained.

Dow provides annual fluid analysis to customers with systems containing 950 liters (250 gallons) or more of DOWTHERM™, DOWFROST™, or DOWCAL™ Glycol-based Fluid. Self-testing instruments are also available for use by operators of smaller systems.

<sup>TM</sup>Trademark of The Dow Chemical Company (Dow) or an affiliated company of Dow.

<sup>†</sup>SYLTHERM Heat Transfer Fluids are manufactured by Dow Corning Corporation and distributed by The Dow Chemical Company.

<sup>1</sup>You may need to comply with similar or additional legislation in other countries. Contact your Dow representative for information.

## Typical Properties<sup>†</sup> of Aqueous Solutions of DOWTHERM<sup>™</sup>, DOWFROST<sup>™</sup>, and DOWCAL<sup>™</sup> Inhibited Glycol-based Heat Transfer Fluids (glycol concentrations 50% by volume)

		DOWTHERM <sup>™</sup> SR-1	DOWTHERM <sup>™</sup> 4000	DOWCAL <sup>™</sup> 10 DOWTHERM <sup>™</sup> 10	DOWFROST <sup>™</sup>	DOWFROST <sup>™</sup> HD	DOWCAL <sup>™</sup> 20 G DOWFROST <sup>™</sup> 20 G	DOWCAL <sup>™</sup> N DOWFROST <sup>™</sup> N
Max. Operating Temp., °C (°F)		121 (250)	175 (350)	175 (350)	121 (250)	160 (320)	160 (325)	120 (250)
Freezing Point, °C (°F)	-37 (-34)	-37 (-34)	-37 (-34)	-34 (-28)	-34 (-28)	-34 (-28)	-34 (-28)	
Physical Property	Temp. °C (°F)							
Thermal Conductivity	5 (40)	0.3682 (0.212)	0.3682 (0.212)	0.369 (0.212)	0.3528 (0.204)	0.3528 (0.204)	0.354 (0.204)	0.354 (0.204)
W/(m)(K)	80 (180)	0.4114 (0.238)	0.4114 (0.238)	0.413 (0.238)	0.3815 (0.221)	0.3815 (0.221)	0.383 (0.221)	0.383 (0.221)
[Btu/(hr · ft <sup>2</sup> )(°F/ft)]	120 (250)	0.4168 (0.241)	0.4168 (0.241)	0.418 (0.241)	0.3792 (0.219)	0.3792 (0.219)	0.380 (0.219)	0.381 (0.219)
	175 (350)	NA	0.4043 (0.233)	0.406 (0.233)	NA	0.3645 <sup>††</sup> (0.210 <sup>††</sup> )	0.366 (0.210 <sup>††</sup> )	NA
Specific Heat	5 (40)	3.225 (0.770)	3.190 (0.762)	3.218 (0.762)	3.474 (0.830)	3.323 (0.794)	3.465 (0.794)	3.484 (0.830)
kJ/(kg)(K)	80 (180)	3.515 (0.842)	3.486 (0.835)	3.510 (0.835)	3.763 (0.902)	3.662 (0.878)	3.757 (0.878)	3.771 (0.902)
[Btu/(lb · °F)]	120 (250)	3.670 (0.878)	3.644 (0.872)	3.665 (0.872)	3.918 (0.937)	3.843 (0.920)	3.913 (0.920)	3.925 (0.937)
	175 (350)	NA	3.862 (0.925)	3.880 (0.925)	NA	4.024 <sup>††</sup> (0.965 <sup>††</sup> )	4.068 (0.965 <sup>††</sup> )	NA
Viscosity	5 (40)	6.63 (6.8)	6.63 (6.8)	6.54 (6.8)	13.77 (14.0)	13.77 (14.0)	13.6 (14.0)	13.6 (14.0)
mPa(s)	80 (180)	0.98 (0.94)	0.98 (0.94)	0.97 (0.94)	1.12 (1.1)	1.12 (1.1)	1.12 (1.1)	1.12 (1.1)
(cps)	120 (250)	0.53 (0.52)	0.53 (0.52)	0.52 (0.52)	0.60 (0.59)	0.60 (0.59)	0.60 (0.59)	0.60 (0.59)
	175 (350)	NA	0.28 (0.27)	0.28 (0.27)	NA	0.40 <sup>††</sup> (0.40 <sup>††</sup> )	0.40 (0.40 <sup>††</sup> )	NA
Density	5 (40)	1080 (67.47)	1092 (68.32)	1081 (68.32)	1051 (65.67)	1067 (66.68)	1052 (66.68)	1051 (65.67)
kg/m <sup>3</sup>	80 (180)	1039 (64.80)	1047 (65.30)	1040 (65.30)	1002 (62.45)	1019 (63.50)	1002 (63.50)	1002 (62.45)
(lb/ft <sup>3</sup> )	120 (250)	1006 (62.78)	1015 (63.36)	1007 (63.36)	964 (60.11)	982 (61.27)	964 (61.27)	964 (60.11)
	175 (350)	NA	964 (60.10)	950 (60.10)	NA	939 <sup>††</sup> (58.42 <sup>††</sup> )	918 (58.42 <sup>††</sup> )	NA

<sup>†</sup>Properties shown are typical and should not be considered specifications.

<sup>††</sup>At 160°C (325°F)

## Product Descriptions for DOWTHERM<sup>™</sup>, DOWFROST<sup>™</sup>, and DOWCAL<sup>™</sup> Inhibited Glycol-based Heat Transfer Fluids

	DOWTHERM <sup>™</sup> SR-1	DOWTHERM <sup>™</sup> 4000	DOWCAL <sup>™</sup> 10 DOWTHERM <sup>™</sup> 10	DOWFROST <sup>™</sup>	DOWFROST <sup>™</sup> HD	DOWCAL <sup>™</sup> 20 G DOWFROST <sup>™</sup> 20 G	DOWCAL <sup>™</sup> N DOWFROST <sup>™</sup> N
	Inhibited	Inhibited	Inhibited	Inhibited	Inhibited	Inhibited	Inhibited
	Ethylene	Ethylene	Ethylene	Propylene	Propylene	Propylene	Propylene
	Glycol	Glycol	Glycol	Glycol	Glycol	Glycol	Glycol
Composition, % by weight							
Glycols	95.4	92.4	93.5	95.5	94.0	93.5	95.5
Inhibitors & Water	4.6	7.6	6.5	4.5	6.0	6.5	4.5
Color	Fluorescent Pink	Fluorescent Orange	Pale Yellow*	Colorless	Fluorescent Yellow	Pale Yellow*	Pale Yellow*
Specific Gravity at 15/15°C (60/60°F)	1.1250–1.1350	1.130–1.144	1.125–1.135	1.050–1.060	1.053–1.063	1.050–1.060	1.050–1.060
pH of Solution Containing 50% Glycol	9.0–9.6	8.5–9.0	7.6–8.2	9.0–10.0	9.5–10.5	7.2–8.2	9.0–10.0
Reserve Alkalinity, Minimum	11.0 ml	25.0 ml	10.0 ml	10.0 ml	15.0 ml	8.0 ml	10.0 ml

\*Color available on request



## Heat Transfer

### Assistance From Dow

Dow fluid specialists can help you design, operate, and maintain your heat transfer system for optimum performance and economy. For assistance and answers to your questions, just contact the Dow representative in your area. Here are just a few of the services we offer:

- System Design Consultation
- Piping Specs and Equipment Information
- Operational Troubleshooting
- Industrial Hygiene Service
- System Leak Detection
- Fluid Consumption Reports
- Fluid Analysis
- Health & Safety Presentations

### FLUIDFILE™ Helps You Evaluate and Select the Right Fluid

To streamline and improve the accuracy of your fluid selection process, FLUIDFILE™ provides complete facts about the entire family of DOWTHERM™, DOWFROST™, and SYLTHERM† Heat Transfer Fluids. To use FLUIDFILE™ visit [www.fluidfile.com](http://www.fluidfile.com).

## The Full Family of Heat Transfer Fluids

Performance & Recommended Applications\*

Fluid Type	Fluid	Temp. Range, °C** (°F**)	High Temperature Thermal Stability	Low Temperature Pumpability	Low Vapor Pressure	Vapor Phase Operation Possible	Low Viscosity	Freeze/Corrosion Protection in Water-based Systems	Long-term Economy	Hot/Cold Cycle Operation for Batch Processing	Acute Oral Toxicity***
Synthetic Organic Fluids	DOWTHERM™ A	15 to 400 (60 to 750)	▲			▲	▲		▲		■
	DOWTHERM™ G	-7 to 370 (20 to 680)	▲	■	▲		▲		▲		■
	DOWTHERM™ Q	-35 to 330 (-30 to 625)	▲	●	▲		▲		▲	●	■
	DOWTHERM™ RP	-4 to 350 (-20 to 660)	▲	■	▲		▲		▲		
	DOWTHERM™ MX	-23 to 330 (-10 to 625)	▲	●	▲		▲		▲	●	■
	DOWTHERM™ T	-10 to 288 (14 to 550)	■	●	▲		●		●		
	DOWTHERM™ J	-80 to 315 (-110 to 600)	▲	▲		▲	▲		▲	▲	■
Silicone Fluids	SYLTHERM† 800	-40 to 400 (-40 to 750)	▲	●			▲		▲	●	▲
	SYLTHERM XLT†	-100 to 260 (-150 to 500)	▲	▲	■		▲		▲	▲	▲
	SYLTHERM HF	-73 to 260 (-100 to 500)	▲	▲	■		▲		▲	▲	
Glycol-based Fluids	DOWTHERM™ 4000	-50 to 175 (-60 to 350)	▲	▲			▲	▲	▲	●	■
	DOWFROST™ HD	-45 to 160 (-50 to 325)	▲	●			●	▲	▲	■	
	DOWTHERM™ SR-1	-50 to 121 (-60 to 250)	▲	▲			▲	▲	▲	●	■
	DOWFROST™	-45 to 121 (-50 to 250)	▲	●			●	▲	▲	■	▲
	DOWCAL™ 10	-50 to 175 (-60 to 350)	▲	▲			▲	▲	▲	●	■
	DOWTHERM™ 10	-50 to 175 (-60 to 350)	▲	▲			▲	▲	▲	●	■
	DOWCAL™ N	-45 to 120 (-50 to 250)	▲	●			●	▲	▲	■	▲
	DOWFROST™ N	-45 to 120 (-50 to 250)	▲	●			●	▲	▲	■	▲
	DOWCAL™ 20 G	-45 to 160 (-50 to 325)	▲	●			●	▲	▲	■	▲
	DOWFROST™ 20 G	-45 to 160 (-50 to 325)	▲	●			●	▲	▲	■	▲

▲ Outstanding

● Excellent

■ Good

\* Performance within fluid operating range.

\*\* Liquid phase temperature range. Vapor phase operating range for DOWTHERM™ A Fluid is 257°C (495°F) to 400°C (750°F). For DOWTHERM™ J Fluid, 181°C (358°F) to 315°C (600°F).

\*\*\* When used in industrial applications.

™Trademark of The Dow Chemical Company (Dow) or an affiliated company of Dow.

† SYLTHERM Heat Transfer Fluids are manufactured by Dow Corning Corporation and distributed by The Dow Chemical Company.

## *Heat Transfer Fluids*



# Product Line Guide

### **To Learn More, Contact Us:**

U.S., Canada, Mexico: Tel. 1-800-447-4369 • Fax: 1-989-832-1465

Latin America: Tel: (+55)-11-5188-9222 • Fax: (+55)-11-5188-9749

Europe: Toll-Free: +800 3 694 6367 • Tel: +32 3 450 2240 • Fax: +32 3 450 2815

Pacific: Toll-free: +800 7776 7776 • Tel: (+60) 3 7958 3392 • Fax: (+60) 3 7958 5598

Or visit us at: **[www.dowtherm.com](http://www.dowtherm.com)**

NOTICE: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

†SYLTHERM Heat Transfer Fluids are manufactured by Dow Corning Corporation and distributed by The Dow Chemical Company.

Published May 2007

