according to the OSHA Hazard Communication Standard



# Krytox™ GPL 225

Version Revision Date: SDS Number: Date of last issue: 10/21/2024 7.0 04/11/2025 1788789-00019 Date of first issue: 06/26/2017

### **SECTION 1. IDENTIFICATION**

Product name : Krytox™ GPL 225

Product code : D15439155

SDS-Identcode : 130000031512

### Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street

Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-

773-2000); Transport emergency: +1-800-424-9300 (outside

the U.S. +1-703-527-3887)

#### Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

Restrictions on use : For industrial use only.

Do not use or resell Chemours<sup>™</sup> materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information,

please contact your Chemours representative.

#### **SECTION 2. HAZARDS IDENTIFICATION**

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

# Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flulike symptoms in humans, especially when smoking contaminated tobacco.

#### **GHS** label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

according to the OSHA Hazard Communication Standard



# Krytox™ GPL 225

Version Revision Date: SDS Number: Date of last issue: 10/21/2024 7.0 04/11/2025 1788789-00019 Date of first issue: 06/26/2017

#### Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Sodium nitrite	7632-00-0*	>= 1 - <= 5	TSC

<sup>\*</sup> Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.

Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

Inhalation may provoke the following symptoms:

Irritation Lung edema

Eye contact may provoke the following symptoms

Blurred vision Discomfort Lachrymation

Skin contact may provoke the following symptoms:

Irritation Redness

Inhalation may provoke the following symptoms:

Irritation

Shortness of breath

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Treat symptomatically and supportively.

### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Not applicable

Will not burn

Unsuitable extinguishing

media

Not applicable Will not burn

according to the OSHA Hazard Communication Standard



# Krytox™ GPL 225

Version Revision Date: SDS Number: Date of last issue: 10/21/2024 7.0 04/11/2025 1788789-00019 Date of first issue: 06/26/2017

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Hydrogen fluoride carbonyl fluoride

potentially toxic fluorinated compounds

aerosolized particulates

Carbon oxides

Nitrogen oxides (NOx)

Metal oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Use personal protective equipment.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emer-

gency procedures

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

#### **SECTION 7. HANDLING AND STORAGE**

according to the OSHA Hazard Communication Standard



# Krytox™ GPL 225

Version Revision Date: SDS Number: Date of last issue: 10/21/2024 7.0 04/11/2025 1788789-00019 Date of first issue: 06/26/2017

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety

practice, based on the results of the workplace exposure as-

sessment

Take care to prevent spills, waste and minimize release to the

environment.

Do not breathe decomposition products.

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

# Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		С	2 ppm (Fluorine)	ACGIH
		TWA	3 ppm	OSHA Z-2
		С	6 ppm 5 mg/m³	NIOSH REL
		TWA	3 ppm 2.5 mg/m <sup>3</sup>	NIOSH REL
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m³	NIOSH REL
		ST	5 ppm 15 mg/m³	NIOSH REL
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m³	NIOSH REL

according to the OSHA Hazard Communication Standard



# Krytox™ GPL 225

Version Revision Date: SDS Number: Date of last issue: 10/21/2024 7.0 04/11/2025 1788789-00019 Date of first issue: 06/26/2017

		ST	30,000 ppm 54,000 mg/m³	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m³	OSHA Z-1
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m³	NIOSH REL
		С	200 ppm 229 mg/m³	NIOSH REL
		TWA	50 ppm 55 mg/m <sup>3</sup>	OSHA Z-1

Engineering measures : Processing may form hazardous compounds (see section

10).

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

### Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where

concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate

protection.

Hand protection

Remarks : Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:

Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the wor-

king place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

# **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Grease

according to the OSHA Hazard Communication Standard



# Krytox™ GPL 225

Version Revision Date: SDS Number: Date of last issue: 10/21/2024 7.0 04/11/2025 1788789-00019 Date of first issue: 06/26/2017

Color : white

Odor : odorless

Odor Threshold : No data available

pH : 7

Melting point/freezing point : 608 °F / 320 °C

Initial boiling point and boiling

range

No data available

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Will not burn

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : 1.89 - 1.93 (75 °F / 24 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

Not applicable

Autoignition temperature : No data available

Decomposition temperature : 608 °F / 320 °C

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics

according to the OSHA Hazard Communication Standard



# Krytox™ GPL 225

Version Revision Date: SDS Number: Date of last issue: 10/21/2024 7.0 04/11/2025 1788789-00019 Date of first issue: 06/26/2017

Particle size : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Hazardous decomposition products will be formed at elevated

temperatures.

Conditions to avoid : None known.

Incompatible materials : None.

### **Hazardous decomposition products**

Thermal decomposition : Hydrogen fluoride

Carbonyl difluoride Carbon dioxide Carbon monoxide

# **SECTION 11. TOXICOLOGICAL INFORMATION**

# Information on likely routes of exposure

Skin contact Ingestion Eye contact

# **Acute toxicity**

Not classified based on available information.

#### **Product:**

Acute oral toxicity : Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

# **Components:**

# Sodium nitrite:

Acute oral toxicity : LD50 (Rat): 180 mg/kg

Acute inhalation toxicity : LC50 (Rat): 5.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

according to the OSHA Hazard Communication Standard



# Krytox™ GPL 225

Version Revision Date: SDS Number: Date of last issue: 10/21/2024 7.0 04/11/2025 1788789-00019 Date of first issue: 06/26/2017

#### Skin corrosion/irritation

Not classified based on available information.

#### Components:

#### Sodium nitrite:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Components:

#### Sodium nitrite:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Method : OECD Test Guideline 405

# Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

### Respiratory sensitization

Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

# **Components:**

#### Sodium nitrite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: positive

Test Type: In vitro mammalian cell gene mutation test

Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: Intraperitoneal injection

Result: negative

according to the OSHA Hazard Communication Standard



# Krytox™ GPL 225

Version Revision Date: SDS Number: Date of last issue: 10/21/2024 7.0 04/11/2025 1788789-00019 Date of first issue: 06/26/2017

### Carcinogenicity

Not classified based on available information.

#### Components:

#### Sodium nitrite:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

IARC Group 2A: Probably carcinogenic to humans

Sodium nitrite 7632-00-0 (nitrite (ingested) under conditions that result in endogenous nitrosation)

**OSHA**No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

### Reproductive toxicity

Not classified based on available information.

### **Components:**

# Sodium nitrite:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Mouse

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

# STOT-single exposure

Not classified based on available information.

# STOT-repeated exposure

Not classified based on available information.

#### Repeated dose toxicity

# **Components:**

# Sodium nitrite:

Species: RatNOAEL: 10 mg/kgApplication Route: IngestionExposure time: 2 y

according to the OSHA Hazard Communication Standard



# Krytox™ GPL 225

Version Revision Date: SDS Number: Date of last issue: 10/21/2024 7.0 04/11/2025 1788789-00019 Date of first issue: 06/26/2017

#### **Aspiration toxicity**

Not classified based on available information.

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

#### **Components:**

Sodium nitrite:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.54 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 15.4 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Scenedesmus capricornutum (fresh water algae)): >

100 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Scenedesmus capricornutum (fresh water algae)): 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOEC (Cyprinus carpio (Carp)): 21 mg/l

Exposure time: 30 d

Method: OECD Test Guideline 210

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Penaeid Shrimp): 9.86 mg/l

Exposure time: 80 d

Toxicity to microorganisms : EC50: 281 mg/l

Exposure time: 48 h

### Persistence and degradability

No data available

# Bioaccumulative potential

No data available

# Mobility in soil

No data available

### Other adverse effects

No data available

according to the OSHA Hazard Communication Standard



# Krytox™ GPL 225

Version Revision Date: SDS Number: Date of last issue: 10/21/2024 7.0 04/11/2025 1788789-00019 Date of first issue: 06/26/2017

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

#### **SECTION 14. TRANSPORT INFORMATION**

# International Regulations

#### **UNRTDG**

Not regulated as a dangerous good

#### **IATA-DGR**

Not regulated as a dangerous good

#### **IMDG-Code**

Not regulated as a dangerous good

### Transport in bulk according to IMO instruments

Not applicable for product as supplied.

# **Domestic regulation**

**49 CFR** 

UN/ID/NA number : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Sodium nitrite)

Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 171
Marine pollutant : no

Remarks : THE ABOVE INFORMATION ONLY APPLIES TO PACKAGE

SIZES WHERE THE HAZARDOUS SUBSTANCE MEETS

THE REPORTABLE QUANTITY.

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

# **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)

according to the OSHA Hazard Communication Standard



# Krytox™ GPL 225

Version Revision Date: SDS Number: Date of last issue: 10/21/2024 7.0 04/11/2025 1788789-00019 Date of first issue: 06/26/2017

Sodium nitrite 7632-00-0 100 5050

# SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

Sodium nitrite 7632-00-0 >= 1 - < 5 %

#### **US State Regulations**

Pennsylvania Right To Know

PFPE fluid Trade secret Fluoropolymer Trade secret Sodium nitrite 7632-00-0

#### California Prop. 65

WARNING: This product can expose you to chemicals including Pentadecafluorooctanoic acid, which is/are known to the State of California to cause cancer, and Carbon monoxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. Note to User: This product is not made with PFOA nor is PFOA intentionally present in the product; however, it is possible that PFOA may be present as an impurity at background (environmental) levels.

#### **California List of Hazardous Substances**

Sodium nitrite 7632-00-0

#### Additional regulatory information

Sodium nitrite 7632-00-0

The United States Environmental Protection Agency (USEPA) has established a Significant New Use Rule (SNUR) for one of the components in this product.

See 40 CFR § 721.4740

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**


according to the OSHA Hazard Communication Standard



# Krytox™ GPL 225

Version Revision Date: SDS Number: Date of last issue: 10/21/2024 7.0 04/11/2025 1788789-00019 Date of first issue: 06/26/2017

### NFPA 704:



Special hazard

#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Krytox™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-2 : USA. Occupational Exposure Limits (OSHA) - Table Z-2

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

ACGIH / C : Ceiling limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

NIOSH REL / C : Ceiling value not be exceeded at any time.

OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-2 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC

according to the OSHA Hazard Communication Standard



# Krytox™ GPL 225

Version Revision Date: SDS Number: Date of last issue: 10/21/2024 7.0 04/11/2025 1788789-00019 Date of first issue: 06/26/2017

- International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

**Data Sheet** 

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 04/11/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8