

Safety Data Sheet

Conforms to OSHA Hazard Communication Standard (HCS)
29CFR 1910.1200

Printing date 04/05/2014

Reviewed on 04/05/2014

1 Identification of the Substances/Preparation and of the Company/Undertaking

- **Product identifier**
- **Product name:** TYZOR® BTP
- **Relevant identified uses of the substance or mixture and uses advised against**
Catalyst; Cross-linking agent in Industrial use as formulation of Coatings and paints, thinners, paint removers.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Dorf Ketal Specialty Catalysts LLC
11200 Westheimer Road
Suite 400
Houston, Texas 77042
Phone= +1 713 343 2377
Fax= +1 832 649 7615
Email: ehss@dorketal.com
- **Emergency telephone number:**
For Chemical Emergency ONLY (spill, leak, fire, exposure or accident) call Chemtrec at +1 (703) 527 3887 or Chemtrec India at 000-800-100-7141. DORF KETAL Emergency Control Room +91 22-65271001.

2 Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Liq. 3 H226 Flammable liquid and vapour.
Eye Dam. 1 H318 Causes serious eye damage.
Skin Irrit. 2 H315 Causes skin irritation.
STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
- **OSHA/HCS status**
This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

- **Label elements**
- **GHS label elements**
The substance is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS05 GHS07

- **Signal word** Danger
- **Hazard-determining components of labeling:**
1-Butanol, titanium(4+) salt (4:1), homopolymer
- **Hazard statements**
Flammable liquid and vapour.
Causes skin irritation.

(Contd. on page 2)

Safety Data Sheet
Conforms to OSHA Hazard Communication Standard (HCS)
29CFR 1910.1200

Printing date 04/05/2014

Reviewed on 04/05/2014

Product name: TYZOR® BTP

(Contd. of page 1)

Causes serious eye damage.

May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Take off contaminated clothing.

IF ON SKIN: Wash with plenty of water/...

Call a POISON CENTER/doctor if you feel unwell.

Classification system:**NFPA ratings (scale 0 - 4)**

Health = 2

Fire = 3

Reactivity = 0

HMIS-ratings (scale 0 - 4)

Health = 2

Fire = 3

Reactivity = 0

Other hazards No information available.

3 Composition/information on ingredients

Chemical characterization: Substances**Dangerous components:**

9022-96-2	1-Butanol, titanium(4+) salt (4:1), homopolymer	> 97%
	Flam. Liq. 3, H226	
	Eye Dam. 1, H318	
	Skin Irrit. 2, H315; STOT SE 3, H335-H336	

4 First-aid measures

Description of first aid measures**General information:**

Take affected persons out into the fresh air.

Do not leave affected persons unattended.

Inhalation:

Take affected persons into fresh air and keep quiet.

Loosen tight clothing such as a collar, tie, belt or waistband.

(Contd. on page 3)

Safety Data Sheet
Conforms to OSHA Hazard Communication Standard (HCS)
29CFR 1910.1200

Printing date 04/05/2014

Reviewed on 04/05/2014

Product name: TYZOR® BTP

(Contd. of page 2)

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- **Skin Contact:**

Immediately rinse with water.
 If skin irritation continues, consult a doctor.
 Remove contaminated clothing and shoes.
 Wash clothing before reuse.
 Clean shoes thoroughly before reuse.

- **Eye Contact:**

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids.
 Check for and remove any contact lenses.
 Rinse opened eye for several minutes under running water. Then consult a doctor.

- **Ingestion:**

Rinse out mouth and then drink plenty of water.
 Do not induce vomiting.
 Consult a physician if necessary.

- **Most important symptoms and effects, both acute and delayed**

Pain, watering, redness. Causes serious eye damage.
 May cause drowsiness or dizziness, nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo, unconsciousness
 May be irritating to respiratory system. Respiratory tract irritation, coughing.
 Skin irritation. Pain or irritation, redness, blistering may occur.

- **Indication of any immediate medical attention and special treatment needed**

Show this safety data sheet to the doctor in attendance. Treat symptomatically.

*

5 Fire-fighting measures

- **Extinguishing media** In case of fire use the following suitable extinguishing agent.

- **Suitable extinguishing agents:**

Foam
 Fire-extinguishing powder
 Alcohol resistant foam
 Carbon dioxide
 Sand

- **For safety reasons unsuitable extinguishing agents:**

Water with full jet
 Water spray

- **Special hazards arising from the substance or mixture**

Flammable liquid and vapour.
 In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
 Runoff to sewer may create fire or explosion hazard.
 In case of fire, the following can be released:
 Carbon monoxide (CO)
 Carbon dioxide

(Contd. on page 4)

Safety Data Sheet
Conforms to OSHA Hazard Communication Standard (HCS)
29CFR 1910.1200

Printing date 04/05/2014

Reviewed on 04/05/2014

Product name: TYZOR® BTP

(Contd. of page 3)

Metal oxides

- **Advice for firefighters**

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

- **Protective equipment:**

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective clothing.

Keep away from ignition sources

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

- **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

- **Methods and material for containment and cleaning up:**

Move containers from spill area.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Precautions for safe handling**

Put on appropriate personal protective equipment .

Do not ingest.

Avoid contact with eyes, skin and clothing.

Avoid breathing vapour or mist.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

- **Conditions for safe storage, including any incompatibilities**

- **Requirements to be met by storerooms and receptacles:**

Avoid storage near extreme heat, ignition sources or open flame.

(Contd. on page 5)

Safety Data Sheet
Conforms to OSHA Hazard Communication Standard (HCS)
29CFR 1910.1200

Printing date 04/05/2014

Reviewed on 04/05/2014

Product name: TYZOR® BTP

(Contd. of page 4)

- **Information about storage in one common storage facility:**

- Store away from oxidizing agents.

- Store away from foodstuffs.

- **Further information about storage conditions:**

- Moisture-sensitive material. Once opened, container should be kept under nitrogen blanketing to prevent decomposition.

- Keep receptacle tightly sealed.

- Store in cool, dry conditions in well sealed receptacles.

- Protect from heat and direct sunlight.

- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:** Not Established.

- **Exposure controls**

- **Appropriate engineering controls:**

- Use local exhaust ventilation or other engineering control to maintain airborne levels below exposure limit requirement or guidelines.

- If there are no applicable exposure limit requirement or guidelines, general ventilation should be sufficient for most operations.

- Local exhaust ventilation may be necessary for some operations.

- **Personal protective equipment:**

- **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.

- Immediately remove all soiled and contaminated clothing.

- Wash hands before breaks and at the end of work.

- Avoid contact with the eyes and skin.

- Do not breathe vapor or mist.

- **Breathing equipment:**

- Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

- Respiratory PPE (APF 10) is required if LEV is not in use and there is only basic general ventilation.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 6)

Safety Data Sheet
Conforms to OSHA Hazard Communication Standard (HCS)
29CFR 1910.1200

Printing date 04/05/2014

Reviewed on 04/05/2014

Product name: TYZOR® BTP

(Contd. of page 5)

- **Material of gloves** Gloves: EN374. Gloves should be worn when there is potential for dermal exposure
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**
Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.



Tightly sealed goggles

- **Body protection:** Protective work clothing

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

Appearance:	Yellow viscous liquid
Odor:	Alcohol-like
Odour threshold:	No data available.

pH-value:	No data available
Melting point/Freezing Point :	<-75 °C (<-103 °F) (OECD 102)
Boiling point/Boiling range:	Substance decomposes before boiling (OECD 103). 117 °C at 101,3 kPa (BP of main degradation product, n-butanol, used for CSA)

Flash point:	34 °C (93 °F) (ASTMD 93)
Flammability (solid, gaseous):	Not applicable.

Decomposition temperature:	No data available.
-----------------------------------	--------------------

Auto ignition temperature	No auto-flammability
----------------------------------	----------------------

· Explosion limits:

Lower:	not applicable (Substance non-explosive)
Upper:	not applicable (Substance non-explosive)

· Oxidizing properties

No

Vapor pressure:	Substance decomposes during vapour pressure testing (OECD 104). 10 hPa at 20 °C (read across data of hydrolysing product n-butanol)
Relative density at 25 °C (77 °F)	1.109 g/cm ³ (9.255 lbs/gal) (ASTM D 891)
Vapour density	No data available

(Contd. on page 7)

Safety Data Sheet
Conforms to OSHA Hazard Communication Standard (HCS)
29CFR 1910.1200

Printing date 04/05/2014

Reviewed on 04/05/2014

Product name: TYZOR® BTP

(Contd. of page 6)

· Evaporation rate	No data available
· Solubility:	Testing is not technically feasible as substance is hydrolytically unstable. 63200 mg/L at 25 °C (water solubility of degradation product n-butanol)
· Partition coefficient (n-octanol/water):	Hydrolytically unstable, Log Kow (Pow): 0,84 at 25 °C for hydrolysing product n-butanol released in water
· Viscosity:	
Dynamic at 25 °C (77 °F):	3250 mPas (DKTM101)
Kinematic:	No data available.

10 Stability and reactivity

- **Reactivity**

Under normal conditions of storage and use, hazardous reactions will not occur.

Water reactive, complete hydrolysis will take place with no significant reaction products other n-butanol and hydrated titanium dioxide when comes in contact with water or moisture

- **Chemical stability** The product is stable under storage at normal ambient temperature.

- **Possibility of hazardous reactions** No dangerous reactions known.

- **Conditions to avoid**

Avoid all possible sources of ignition (spark or flame).

Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

- **Incompatible materials:**

Hydrolyzes in water to form n-butanol and titanium dioxide.

Oxidizing material

Acids

- **Hazardous decomposition products:**

Hydrolyzes in water to form n-butanol.

Incomplete combustion and thermolysis may produce gases such as:

Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**

There is no experimental data available on toxicokinetics and the assessment has been made qualitatively on the basis of the physical and chemical properties and other relevant data obtained from the degradation products. As the substance is hydrolyzed, the hazardous degradation product is metabolized and excreted rapidly.

(Contd. on page 8)

Safety Data Sheet
Conforms to OSHA Hazard Communication Standard (HCS)
29CFR 1910.1200

Printing date 04/05/2014

Reviewed on 04/05/2014

Product name: TYZOR® BTP

(Contd. of page 7)

· **Acute toxicity:**· **LD/LC50 values that are relevant for classification:1****9022-96-2 1-Butanol, titanium(4+) salt (4:1), homopolymer**

Oral	LD50	> 2000 mg/kg bw (Rat)
Dermal	LD50	5300 mg/kg bw (Rat)
Inhalative	LC50	20100 mg/l (Rat)

· **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Respiratory/ Skin sensitization:** No sensitizing effects known.
- **Germ cell mutagenicity:** No adverse effect observed. Negative
- **Carcinogenicity:** Substance has not been classified for carcinogenicity
- **Reproductive toxicity:** Substance is not classified for reproductive toxicity.

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**

Substance is not listed.

· **NTP (National Toxicology Program)**

Substance is not listed.

· **Single dose toxicity:**

- May cause respiratory irritation.
- May cause drowsiness or dizziness.

· **Repeated Dose toxicity** Substance has not been classified for STOT RE.· **Aspiration hazard** Substance is not classified for aspiration hazard.· **Other relevant information:** No data available**12 Ecological information**· **Toxicity**

Substance is not classified as dangerous to aquatic organisms. Because this substance hydrolysis rapidly the intrinsic ecotoxicological properties are related to the most critical decomposition product n-butanol.

· **Aquatic toxicity:****9022-96-2 1-Butanol, titanium(4+) salt (4:1), homopolymer**

EC10 (96 h)	134 mg/L (Algae)
EC50 (48 h)	1300 mg/L mg/l (Daphnia)
EC50 (96h)	225 mg/L (Algae)
LC50 (96 h)	1825 mg/L mg/l (Fish)
NOEC (21 d)	4 mg/L (Daphnia)

(Contd. on page 9)

Safety Data Sheet
Conforms to OSHA Hazard Communication Standard (HCS)
29CFR 1910.1200

Printing date 04/05/2014

Reviewed on 04/05/2014

Product name: TYZOR® BTP

(Contd. of page 8)

- **Persistence and degradability**

Readily degradable. Main organic decomposition product (n-butanol) is readily biodegradable; No persistence potential.(half-life of < 2 hours, OECD Guideline 111)

- **Bioaccumulative potential** No potential for bioaccumulation (OECD Guideline 111)

- **Mobility in soil**

High mobility in soil based on high water solubility and estimated Koc 3.471 L/kg of degradation product n-butanol.

- **Results of PBT and vPvB assessment** The substance is not a PBT or a vPvB

- **Other adverse effects** No further relevant information available.

13 Disposal Information

- **Waste treatment methods**

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

- **Recommendation:**

Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

14 Transport information

- **UN-Number**

· **DOT, ADR, IMDG, IATA** UN1993

- **UN proper shipping name**

· **DOT** Flammable liquids, n.o.s.(1-Butanol, titanium(4+) salt (4:1), homopolymer)
 · **ADR** 1993 Flammable liquids, n.o.s.(1-Butanol, titanium(4+) salt (4:1), homopolymer), special provision 640E
 · **IMDG, IATA** FLAMMABLE LIQUID, N.O.S. (1-Butanol, titanium(4+) salt (4:1), homopolymer)

- **Transport hazard class(es)**

- **DOT, IMDG, IATA**

· **Class** 3 Flammable liquids.
 · **Label** 3

(Contd. on page 10)

Safety Data Sheet
Conforms to OSHA Hazard Communication Standard (HCS)
29CFR 1910.1200

Printing date 04/05/2014

Reviewed on 04/05/2014

Product name: TYZOR® BTP

(Contd. of page 9)

· ADR	
· Class	3 (F1) Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	30
· EMS Number:	F-E, <u>S-E</u>
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.

15 Regulatory information

· **Section 355 (extremely hazardous substances):**

Substance is not listed.

· **Section 313 (Specific toxic chemical listings):**

Substance is not listed.

· **TSCA (Toxic Substances Control Act):**

Substance is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

Substance is not listed.

· **Chemicals known to cause reproductive toxicity for females:**

Substance is not listed.

· **Chemicals known to cause reproductive toxicity for males:**

Substance is not listed.

· **Chemicals known to cause developmental toxicity:**

Substance is not listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

Substance is not listed.

(Contd. on page 11)

Safety Data Sheet
Conforms to OSHA Hazard Communication Standard (HCS)
29CFR 1910.1200

Printing date 04/05/2014

Reviewed on 04/05/2014

Product name: TYZOR® BTP

(Contd. of page 10)

· TLV (Threshold Limit Value established by ACGIH)

Substance is not listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

Substance is not listed.

· OSHA-Ca (Occupational Safety & Health Administration)
--

Substance is not listed.

· Chemical safety assessment: A Chemical Safety Assessment has been carried out.

16 Other information

File name: TYZOR BTP SDS US en APR-05-2014

Version: 2

Superseded SDS date: 28 September 2012

Change History: The whole SDS updated as per CSA of the product

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

APF = Assigned protection factor

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

IOELV: Indicative Occupational Exposure Limit Values

· **Disclaimer:**

The data and recommendations presented in this data sheet concerning the use of our product and the materials contain there in are believed to be accurate and are based on information which is considered reliable as of the date hereof. However, the customer should determine the suitability of much material for his purpose before adopting them on a commercial scale. Since the use our product by others is beyond our control, no guarantee, express or implied, is made and no responsibility assumed for the use of this material or the results to be obtained there from. Information on this document is furnished for the purpose of compliance with Government Health and Safety Regulations and shall not be used for any other purposes. Moreover, the recommendations contained in this Safety Data Sheet are not to be constructed as a license to operate under, or a recommendation to infringe, any existing patents, nor should they be confused with state, municipal or insurance requirements, or with national safety codes.