

SAFETY DATA SHEET

DDP SPECIALTY ELECTRONIC MATERIALS US,

INC.

Product name: KATHON™ CG II Preservative

Issue Date: 01/03/2019 **Print Date:** 04/24/2020

DDP SPECIALTY ELECTRONIC MATERIALS US, INC. encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: KATHON™ CG II Preservative

Recommended use of the chemical and restrictions on use Identified uses: Preservative

COMPANY IDENTIFICATION DDP SPECIALTY ELECTRONIC MATERIALS US, INC. 400 ARCOLA ROAD COLLEGEVILLE PA 19426-2914 UNITED STATES

Customer Information Number:

833-338-7668 SDSQuestion-NA@dupont.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 1-800-424-9300 Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with 29 CFR 1910.1200 Skin corrosion - Category 1B Serious eye damage - Category 1 Skin sensitisation - Category 1

Label elements Hazard pictograms



Signal word: DANGER!

Hazards

Causes severe skin burns and eye damage. May cause an allergic skin reaction.

Precautionary statements

Prevention

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. If skin irritation or rash occurs: Get medical advice/ attention. Wash contaminated clothing before reuse.

Storage

Store locked up.

Disposal

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Aqueous solution of organic and inorganic compounds

This product is a mixture.

Component	CASRN	Concentration
5-Chloro-2-methyl-4-isothiazolin-3-one	26172-55-4	>= 1.1 - 1.25 %
2-Methyl-4-isothiazolin-3-one	2682-20-4	>= 0.3 - 0.45 %
Magnesium Chloride	7786-30-3	<= 0.6 %
Magnesium dinitrate	10377-60-3	>= 1.4 - 2.7 %
Copper (II) nitrate	3251-23-8	>= 0.15 - 0.17 %

Water

7732-18-5

>= 95.5 - 96.2 %

4. FIRST AID MEASURES

Description of first aid measures

Inhalation: Move to fresh air. Give artificial respiration if breathing has stopped. If symptoms persist, call a physician.

Skin contact: IMMEDIATELY get under a safety shower. Remove contaminated clothing. Wash off with soap and water. Immediate medical attention is required. Wash contaminated clothing before reuse. Do not take clothing home to be laundered. Discard contaminated shoes, belts, and other articles made of leather.

Eye contact: Rinse immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.

Ingestion: Drink 1 or 2 glasses of water. IMMEDIATELY see a physician. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: MATERIAL IS CORROSIVE. It may not be advisable to induce vomiting. Possible mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock and convulsions maybe necessary.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media: No data available

Special hazards arising from the substance or mixture Hazardous combustion products: No data available

Unusual Fire and Explosion Hazards: Combustion generates toxic fumes of the following: hydrogen chloride Nitrogen oxides (NOx) sulfur oxides

Advice for firefighters

Fire Fighting Procedures: Cool containers/tanks with water spray. Minimize exposure. Do not breathe fumes. Contain run-off.

Special protective equipment for firefighters: Wear self-contained breathing apparatus and protective suit.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Wear a NIOSH approved (or equivalent) respirator (with organic vapor/acid gas cartridge and a dust/mist filter) during spill clean-ups and deactivation of this material. MATERIAL IS CORROSIVE. Protective clothing, including chemical splash goggles, nitrile or butyl rubber full length gloves, rubber apron, or clothing made of nitrile or butyl rubber, and rubber overshoes must be worn during spill clean-ups and deactivation of this material comes in contact with the skin during clean-up operations, IMMEDIATELY remove all contaminated clothing and wash exposed skin areas with soap and water. See SECTION 4, First Aid Measures, for further information.

Environmental precautions: Do not allow material to contaminate ground water system. Prevent product from entering drains.

Methods and materials for containment and cleaning up: WARNING: KEEP SPILLS AND CLEAN-UP RESIDUALS OUTOF MUNICIPAL SEWERS AND OPEN BODIES OF WATER. Adsorb the spill with spill pillows or inert solids such as clay or vermiculite, and transfer contaminated materials to suitable containers for disposal. Deactivate spill area with freshly prepared solution of 5% sodium bicarbonate and 5% sodium hypochlorite in water. Apply solution to the spill area at a ratio of 10 volumes deactivation solution per estimated volume of residual spill to deac tivate any residual active ingredient. Let stand for 30 minutes. Flush the spill area with copious amounts of water to chemical sewer (if in accordance with local procedures, permits and regulations). DO NOT add deactivation solution to the waste pail to deactivate the adsorbed material. See Section 13, "Disposal Considerations", for information regarding the disposal of contained materials.

7. HANDLING AND STORAGE

Precautions for safe handling: This material is corrosive. For personal protection see section 8. Do not handle material near food, feed or drinking water.

Conditions for safe storage: Keep in a well-ventilated place. The product as supplied may evolve gas (largely carbon dioxide) slowly. To prevent the buildup of pressure the product is packaged in specially vented containers, where necessary. Keep this product in the original container when not in use. Container must be stored and transported in an upright position to prevent spilling the contents through the vent, where fitted. Do not store this material in containers made of the following: steel Do not store this material near food, feed or drinking water.

CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied. Expiration date based only on retention of >95% actives during storage at 20°C-25°C (68°F-77°F).

Storage stability

Storage temperature: 1 - 55 °C (34 - 131 °F) **Other data:** Store in a cool and shaded area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value/Notation

5-Chloro-2-methyl-4- isothiazolin-3-one	Dow IHG	TWA	0.075 mg/m3
2-Methyl-4-isothiazolin-3-one	Dow IHG	STEL	0.23 mg/m3
	Dow IHG	TWA	1.5 mg/m3
	Dow IHG	STEL	4.5 mg/m3

Exposure controls

Engineering controls: Use local exhaust ventilation with a minimum capture velocity of 150 ft/min. (0.75 m/sec.) at the point of dust or mist evolution. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

Protective measures: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Individual protection measures

Eye/face protection: Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent). Eye protection worn must be compatible with respiratory protection system employed.

Skin protection

Hand protection: Chemical-resistant gloves should be worn whenever this material is handled. The glove(s) listed below may provide protection against permeation. (Gloves of other chemically resistant materials may not provide adequate protection): butyl-rubber Nitrile rubber PVC gloves >1 mm thickness Gloves should be removed and replaced immediately if there is any indication of degradation or chemical breakthrough. Rinse and remove gloves immediately after use. Wash hands with soap and water. NOTE: Material is a possible skin sensitizer.

Other protection: Wear as appropriate: Chemical resistant apron complete suit protecting against chemicals

Respiratory protection: Typical use of this material does not result in workplace exposures that exceed the exposure limits listed in the Exposure Limit Information Section. For those special workplace conditions where the listed exposure limits are exceeded, a respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements must be followed. For concentrations up to 10 times the exposure limit, wear a properly fitted NIOSH approved (or equivalent) half-mask or full facepiece air purifying respirator equipped with organic vapor cartridges and N95 filters. If oil mist is present, use R95 or P95 filters. For those unlikely situations where exposure may greatly exceed the listed exposure limits (i.e. greater than 10-fold), or in any emergency situation, wear a properly fitted NIOSH approved (or equivalent) self-contained breathing apparatus in the pressure demand mode or a full facepiece airline respirator in the pressure demand mode with emergency escape provision. See SECTION 6, Accidental Release Measures, for respirator and protective clothing requirements for spill clean-up and decontamination of this material.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state Color Odor liquid light blue clear Mild odor

Odor Threshold	No data available
рН	1.7 - 3.7
Melting point/range	-3.00 °C (26.60 °F)
Freezing point	No data available
Boiling point (760 mmHg)	ca.100.00 °C (212.00 °F)
Flash point	Noncombustible
Evaporation Rate (Butyl Acetate = 1)	<1.00
Flammability (solid, gas)	Not Applicable
Lower explosion limit	Not applicable
Upper explosion limit	Not applicable
Vapor Pressure	No data available
Relative Vapor Density (air = 1)	ca.0.6200
Relative Density (water = 1)	1.0200
Water solubility	completely soluble
Partition coefficient: n- octanol/water	No data available
Auto-ignition temperature	Not applicable
Decomposition temperature	No data available
Dynamic Viscosity	3.000 mPa.s at 25.00 °C (77.00 °F)
Kinematic Viscosity	No data available
Explosive properties	No data available
Oxidizing properties	No data available
Molecular weight	No data available
Percent volatility	95.00 - 96.00 % Water

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: No data available

Chemical stability: No data available

Possibility of hazardous reactions: Stable under recommended storage conditions. Product will not undergo polymerization.

Conditions to avoid: No data available

Incompatible materials: Avoid contact with the following: Oxidizing agents Amines Reducing agents Mercaptans.

Hazardous decomposition products: Nitric acid.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity LD50, Rat, female, 3,310 mg/kg LD50, Rat, male, > 5,000 mg/kg

Acute dermal toxicity LD50, Rabbit, > 5,000 mg/kg

Acute inhalation toxicity LC50, Rat, 4 Hour, dust/mist, > 5 mg/l Estimated.

Skin corrosion/irritation

This material is corrosive.

Serious eye damage/eye irritation

Corrosive

Sensitization

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization: No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure) Product test data not available. Refer to component data.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Product test data not available. Refer to component data.

Carcinogenicity

Did not cause cancer in laboratory animals.

Teratogenicity

Did not show teratogenic effects in animal experiments.

Reproductive toxicity

In animal studies, did not interfere with reproduction.

Mutagenicity

Not mutagenic when tested in bacterial or mammalian systems.

Aspiration Hazard

Product test data not available. Refer to component data.

COMPONENTS INFLUENCING TOXICOLOGY:

5-Chloro-2-methyl-4-isothiazolin-3-one

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Aspiration Hazard

Aspiration into the lungs may occur during ingestion or vomiting, causing tissue damage or lung injury.

2-Methyl-4-isothiazolin-3-one

Specific Target Organ Systemic Toxicity (Single Exposure)

May cause respiratory irritation. Route of Exposure: Inhalation Target Organs: Respiratory Tract

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on available data, repeated exposures are not anticipated to cause additional significant adverse effects.

Aspiration Hazard

Aspiration into the lungs may occur during ingestion or vomiting, causing tissue damage or lung injury.

Magnesium Chloride

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on available data, repeated exposures are not anticipated to cause additional significant adverse effects.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

Magnesium dinitrate

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

For similar material(s):

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Aspiration Hazard

Based on available information, aspiration hazard could not be determined.

Copper (II) nitrate

Specific Target Organ Systemic Toxicity (Single Exposure)

Material is corrosive. Material is not classified as a respiratory irritant; however, upper respiratory tract irritation or corrosivity may be expected.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

General Information

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity

5-Chloro-2-methyl-4-isothiazolin-3-one

Acute toxicity to fish

Material is highly toxic to aquatic organisms on an acute basis (LC50/EC50 between 0.1 and 1 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, 0.19 mg/l, OECD Test Guideline 203 or Equivalent

LC50, Bluegill sunfish (Lepomis macrochirus), 96 Hour, 0.28 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, 0.16 mg/l

Acute toxicity to algae/aquatic plants

NOEC, Selenastrum capricornutum (green algae), Growth rate, 0.0099 mg/l EC50, Algae (Selenastrum capricornutum), 72 Hour, Growth rate, 0.018 mg/l

Toxicity to bacteria

EC50, Bacteria, 16 Hour, 5.7 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 21 d, number of offspring, 0.172000 mg/l LOEC, Daphnia magna (Water flea), 21 d, number of offspring, 0.572000 mg/l

2-Methyl-4-isothiazolin-3-one

Acute toxicity to fish

Material is highly toxic to aquatic organisms on an acute basis (LC50/EC50 between 0.1 and 1 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, 4.77 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

LC50, Daphnia magna (Water flea), 48 Hour, 0.93 - 1.9 mg/l

Acute toxicity to algae/aquatic plants

EC50, Algae (Selenastrum capricornutum), 72 Hour, Growth rate, 0.158 mg/l, OECD Test Guideline 201

Chronic toxicity to fish

NOEC, Pimephales promelas (fathead minnow), 33 d, 2.1 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna, 21 d, 0.04 mg/l

Magnesium Chloride

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested). LC50, Gambusia affinis (Mosquito fish), static test, 96 Hour, 16,500 mg/l, Method Not Specified.

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 24 Hour, 3,190 mg/l, Directive 84/449/EEC, C.2

Acute toxicity to algae/aquatic plants

EC50, alga Scenedesmus sp., 72 Hour, Biomass, 2,200 mg/l, OECD Test Guideline 201 or Equivalent

Chronic toxicity to aquatic invertebrates EC10, Daphnia magna (Water flea), 21 d, 321 mg/l

Magnesium dinitrate

Acute toxicity to fish Not expected to be acutely toxic to aquatic organisms. For similar material(s): LC50, Poecilia reticulata (guppy), 96 Hour, > 100 mg/l

Acute toxicity to aquatic invertebrates

For similar material(s): EC50, Daphnia magna, 48 Hour, > 100 mg/l

Acute toxicity to algae/aquatic plants

For similar material(s): ErC50, Algae, 72 Hour, Growth rate, > 100 mg/l

Toxicity to bacteria

Based on data from similar materials EC50, 3 Hour, > 1,000 mg/l, OECD Test Guideline 209

Copper (II) nitrate

Acute toxicity to fish

Material is very highly toxic to aquatic organisms on an acute basis (LC50/EC50 <0.1 mg/L in the most sensitive species). LC50, Pimephales promelas (fathead minnow), 96 Hour, > 0.01 - 0.1 mg/l

Acute toxicity to aquatic invertebrates

LC50, Daphnia magna, 48 Hour, 0.033 mg/l

Acute toxicity to algae/aquatic plants

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, 0.035 mg/l, Other guidelines NOEC, Raphidocelis subcapitata (freshwater green alga), Static, 72 Hour, 0.015 - 0.164 mg/l, OECD Test Guideline 201

Toxicity to bacteria

IC50, 3 Hour, 44.6 mg/l

Chronic toxicity to fish

NOEC, Pimephales promelas (fathead minnow), flow-through, 28 d, 0.016 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Other, semi-static test, 27 d, 0.021 mg/l

Persistence and degradability

5-Chloro-2-methyl-4-isothiazolin-3-one

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.
10-day Window: Not applicable
Biodegradation: 98 %
Exposure time: 2 d
Method: OECD Test Guideline 302B or Equivalent

2-Methyl-4-isothiazolin-3-one

Biodegradability: Material is expected to be readily biodegradable.

Biodegradation: 98 % Exposure time: 48 d Method: Simulation study

Magnesium Chloride

Biodegradability: Biodegradation is not applicable.

Magnesium dinitrate

Biodegradability: No relevant data found.

Copper (II) nitrate

Biodegradability: Material is expected to be readily biodegradable.

Bioaccumulative potential

5-Chloro-2-methyl-4-isothiazolin-3-one

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3). **Partition coefficient: n-octanol/water(log Pow):** -0.71 - 0.75 Measured

2-Methyl-4-isothiazolin-3-one

Bioaccumulation: Does not bioaccumulate. Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): -0.75 Measured

Magnesium Chloride

Bioaccumulation: No bioconcentration is expected because of the relatively high water solubility. Partitioning from water to n-octanol is not applicable.

Magnesium dinitrate

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3). **Partition coefficient:** n-octanol/water(log Pow): -0.61 Estimated.

Copper (II) nitrate

Bioaccumulation: The product may be accumulated in organisms. No relevant data found.

Mobility in soil

5-Chloro-2-methyl-4-isothiazolin-3-one

No relevant data found.

2-Methyl-4-isothiazolin-3-one No relevant data found.

Magnesium Chloride

Potential for mobility in soil is very high (Koc between 0 and 50). **Partition coefficient (Koc):** 23.7

Magnesium dinitrate

Potential for mobility in soil is very high (Koc between 0 and 50). Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process. **Partition coefficient (Koc):** 24

Copper (II) nitrate

No relevant data found.

13. DISPOSAL CONSIDERATIONS

Disposal methods: Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations. (See 40 CFR 268)

Contaminated packaging: Empty containers retain product residues. Follow label warnings even after container is emptied. Improper disposal or reuse of this container may be dangerous and illegal. Refer to applicable federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT

Proper shipping name	Corrosive liquid, acidic, organic, n.o.s.(5-Chloro-2-methyl-4-isothiazolin-3-one)
UN number	UN 3265
Class	8
Packing group	II

Classification for SEA transport (IMO-IMDG):

Proper shipping name	CORROŚIVE LIQUID, ACIDIC, ORGANIC, N.O.S.(5-Chloro- 2-methyl-4-isothiazolin-3-one)
UN number	UN 3265
Class	8
Packing group	II
Marine pollutant	5-Chloro-2-methyl-4-isothiazolin-3-one
Transport in bulk	Consult IMO regulations before transporting ocean bulk

according to Annex I or II of MARPOL 73/78 and the **IBC or IGC Code**

Classification for AIR transport (IATA/ICAO):

Proper shipping name	Corrosive liquid, acidic, organic, n.o.s.(5-Chloro-2-methyl-4-
	isothiazolin-3-one)
UN number	UN 3265
Class	8
Packing group	I

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Skin corrosion or irritation Serious eye damage or eye irritation Respiratory or skin sensitisation

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This product contains a chemical which is listed in Section 313 at or above de minimis concentrations. The following listed chemicals are present: (Quantity present is found elsewhere on this MSDS.) **Components** CASRN 10377-60-3

Magnesium nitrate (10377-60-3) as nitrate compound

Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

This material is regulated under the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) and the Superfund Amendments and Reauthorization Act (SARA) Title III Section 304. This material is or contains chemical(s) listed in 40 CFR Table 302.4 or nondesignated RCRA ICR substance(s). (Nondesignated ICR substances apply to materials that will not be reused.) The Reportable Quantity(s) (RQ) are listed below. Releases in excess of its reportable quantity must be reported to the National Response Center (1-800-424-8802) and to the appropriate state and local emergency response organizations.

D002, 100lbs.

Pennsylvania Right To Know

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components	
Magnesium dinitrate	

CASRN 10377-60-3

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

United States TSCA Inventory (TSCA)

This product contains chemical substance(s) exempt from U.S. EPA TSCA Inventory requirements. It is regulated as a pesticide subject to Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA) requirements.

16. OTHER INFORMATION

Hazard Rating System

HMIS

Health	Flammability	Physical Hazard
3	0	0

Revision

Identification Number: 10081121 / A749 / Issue Date: 01/03/2019 / Version: 4.1 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

Dow IHG	Dow Industrial Hygiene Guideline
STEL	Short term exposure limit
TWA	Time weighted average

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan): ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice: HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution

Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DDP SPECIALTY ELECTRONIC MATERIALS US, INC. urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDS sobtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US