

**Hydrocarbon Fluid Type III**

Version 1.6

Revision Date 2018-11-27

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product information**

Product Name : Hydrocarbon Fluid Type III
Material : 1024838, 1024839, 1024841, 1024840

Use : Fuel

Company : Chevron Phillips Chemical Company LP
Specialty Chemicals
10001 Six Pines Drive
The Woodlands, TX 77380

Emergency telephone:**Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

Responsible Department : Product Safety and Toxicology Group
E-mail address : SDS@CPChem.com
Website : www.CPChem.com

SECTION 2: Hazards identification**Classification of the substance or mixture**

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

Classification

: Flammable liquids, Category 2
Skin irritation, Category 2
Eye irritation, Category 2A
Reproductive toxicity, Category 2
Specific target organ systemic toxicity - single exposure,
Category 3, Central nervous system

Hydrocarbon Fluid Type III

Version 1.6

Revision Date 2018-11-27

Specific target organ systemic toxicity - repeated exposure,
Category 2, Inhalation, Auditory organs, color vision
Aspiration hazard, Category 1

Labeling

Symbol(s)



Signal Word

: Danger

Hazard Statements

: H225: Highly flammable liquid and vapor.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.
H361d: Suspected of damaging the unborn child.
H373: May cause damage to organs (Auditory organs, color vision) through prolonged or repeated exposure if inhaled.

Precautionary Statements

: **Prevention:**
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapor/spray.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Hydrocarbon Fluid Type III

Version 1.6

Revision Date 2018-11-27

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity:**IARC**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3: Composition/information on ingredients

Synonyms : Rubber Swelling Test Fluid Type III

Molecular formula : Mixture

Component	CAS-No.	Weight %
2,2,4-Trimethylpentane (Isooctane)	540-84-1	69 - 71
Toluene	108-88-3	29 - 31

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

If inhaled : Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

SECTION 5: Firefighting measures

Flash point : -12.1 °C (10.2 °F)
Method: Tag closed cup

Autoignition temperature : No data available

Suitable extinguishing : Alcohol-resistant foam. Carbon dioxide (CO₂). Dry chemical.

Hydrocarbon Fluid Type III

Version 1.6

Revision Date 2018-11-27

media

Unsuitable extinguishing media : High volume water jet.

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

Fire and explosion protection : Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hazardous decomposition products : Carbon oxides.

SECTION 6: Accidental release measures

Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7: Handling and storage**Handling**

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Hydrocarbon Fluid Type III

Version 1.6

Revision Date 2018-11-27

Advice on protection against fire and explosion : Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Use : Fuel

SECTION 8: Exposure controls/personal protection**Ingredients with workplace control parameters****US**

Components	Basis	Value	Control parameters	Note
2,2,4-Trimethylpentane (Isooctane)	ACGIH	TWA	300 ppm,	URT irr,
Toluene	ACGIH	TWA	20 ppm,	visual impair, female repro, pregnancy loss, BEI, A4,
	OSHA Z-2	TWA	200 ppm,	
	OSHA Z-2	CEIL	300 ppm,	
	OSHA Z-2	Peak	500 ppm,	
	OSHA Z-1-A	TWA	100 ppm, 375 mg/m3	
	OSHA Z-1-A	STEL	150 ppm, 560 mg/m3	

A4 Not classifiable as a human carcinogen
 BEI Substances for which there is a Biological Exposure Index or Indices (see BEI® section)
 female repro Female reproductive
 pregnancy loss Pregnancy loss
 URT irr Upper Respiratory Tract irritation
 visual impair Visual impairment

Immediately Dangerous to Life or Health Concentrations (IDLH)

Substance name	CAS-No.	Control parameters	Update
Toluene	108-88-3	Immediately Dangerous to Life or Health Concentration Value 500 parts per million	1995-03-01

Biological exposure indices**US**

Substance name	CAS-No.	Control parameters	Sampling time	Update
Toluene	108-88-3	Toluene: 0.02 mg/l (In blood)	Prior to last shift of workweek	2010-03-01
		Toluene: 0.03 mg/l (Urine)	End of shift (As soon as possible after exposure ceases)	2010-03-01
		o-Cresol: 0.3 mg/g Creatinine (Urine)	End of shift (As soon as possible after exposure ceases)	2010-03-01

Engineering measures

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits.

Hydrocarbon Fluid Type III

Version 1.6

Revision Date 2018-11-27

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

- | | | |
|--------------------------|---|---|
| Respiratory protection | : | Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as: Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection. |
| Hand protection | : | The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. |
| Eye protection | : | Eye wash bottle with pure water. Tightly fitting safety goggles. |
| Skin and body protection | : | Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate: Flame retardant antistatic protective clothing. Workers should wear antistatic footwear. |
| Hygiene measures | : | When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday. |

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

- | | | |
|----------------|---|-------------------|
| Form | : | Liquid |
| Physical state | : | Liquid |
| Color | : | Colorless |
| Odor | : | Mild, Hydrocarbon |

Safety data

- | | | |
|-----------------------|---|--|
| Flash point | : | -12.1 °C (10.2 °F)
Method: Tag closed cup |
| Lower explosion limit | : | 1 %(V) |
| Upper explosion limit | : | 6.5 %(V) |

Hydrocarbon Fluid Type III

Version 1.6

Revision Date 2018-11-27

Oxidizing properties	: No
Autoignition temperature	: No data available
Molecular formula	: Mixture
Molecular weight	: Not applicable
pH	: Not applicable
Freezing point	: No data available
Pour point	No data available
Boiling point/boiling range	: 99 °C (210 °F)
Vapor pressure	: 1.50 PSI at 37.8 °C (100.0 °F)
Relative density	: 0.75 at 15.6 °C (60.1 °F)
Water solubility	: Negligible
Partition coefficient: n-octanol/water	: No data available
Viscosity, kinematic	: No data available
Relative vapor density	: 3.69 (Air = 1.0)
Evaporation rate	: 1
Percent volatile	: > 99 %

SECTION 10: Stability and reactivity

Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous reactions	
Hazardous reactions	: Hazardous reactions: Hazardous polymerization does not occur. Further information: No decomposition if stored and applied as directed. Hazardous reactions: Vapors may form explosive mixture with air.

Hydrocarbon Fluid Type III

Version 1.6

Revision Date 2018-11-27

- Conditions to avoid** : Heat, flames and sparks.
- Materials to avoid** : May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
- Hazardous decomposition products** : Carbon oxides
- Other data** : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

- Hydrocarbon Fluid Type III**
Acute oral toxicity : LD50: > 5,000 mg/kg
Method: Acute toxicity estimate
- Hydrocarbon Fluid Type III**
Acute inhalation toxicity : LC50: > 40 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Acute toxicity estimate
- Hydrocarbon Fluid Type III**
Acute dermal toxicity : LD50: > 5,000 mg/kg
Method: Acute toxicity estimate
- Hydrocarbon Fluid Type III**
Skin irritation : Skin irritation
largely based on animal evidence.
- Hydrocarbon Fluid Type III**
Eye irritation : Eye irritation
largely based on animal evidence.
- Hydrocarbon Fluid Type III**
Sensitization : Not a skin sensitizer.
largely based on animal evidence.
- Hydrocarbon Fluid Type III**
Repeated dose toxicity : Method: Based on product or component testing, long term repeated exposure may cause damage to the following organs:
Target Organs: Auditory organs
Estimated based on individual component values.
- Genotoxicity in vitro**
2,2,4-Trimethylpentane (Isooctane) : Test Type: Ames test
Method: Mutagenicity (Escherichia coli - reverse mutation assay)
Result: negative

Hydrocarbon Fluid Type III

Version 1.6

Revision Date 2018-11-27

Toluene

Test Type: Mouse lymphoma assay
Method: OECD Guideline 476
Result: negative

Test Type: Sister Chromatid Exchange Assay
Result: negative

Test Type: Unscheduled DNA synthesis assay
Result: negative

Test Type: Ames test
Result: negative

Test Type: Sister Chromatid Exchange Assay
Result: negative

Test Type: Mouse lymphoma assay
Result: negative

Test Type: Cytogenetic assay
Result: negative

Genotoxicity in vivo

2,2,4-Trimethylpentane (Isooctane) : Test Type: Unscheduled DNA synthesis assay
Species: Mouse
Dose: 500 mg/kg
Result: negative

Test Type: Unscheduled DNA synthesis assay
Species: Rat
Dose: 500 mg/kg
Result: negative

Toluene : Test Type: Cytogenetic assay
Result: negative

Test Type: Mouse micronucleus assay
Result: negative

**Hydrocarbon Fluid Type III
Carcinogenicity**

: Remarks: Not expected to be carcinogenic based on individual component data.

**Hydrocarbon Fluid Type III
Reproductive toxicity**

: Suspected of damaging fertility or the unborn child.

**Hydrocarbon Fluid Type III
Developmental Toxicity**

: Suspected of damaging fertility or the unborn child.

**Hydrocarbon Fluid Type III
Aspiration toxicity**

: May be fatal if swallowed and enters airways.

CMR effects

2,2,4-Trimethylpentane : Mutagenicity: Tests on bacterial or mammalian cell cultures

Hydrocarbon Fluid Type III

Version 1.6

Revision Date 2018-11-27

(Isooctane)	<p>did not show mutagenic effects.</p> <p>Teratogenicity: Animal testing did not show any effects on fetal development.</p> <p>Reproductive toxicity: Animal testing did not show any effects on fertility.</p>
Toluene	<p>Carcinogenicity: Not classifiable as a human carcinogen.</p> <p>Mutagenicity: Animal testing did not show any mutagenic effects.</p> <p>Teratogenicity: Some evidence of adverse effects on development, based on animal experiments.</p> <p>Reproductive toxicity: Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.</p>
Hydrocarbon Fluid Type III Further information	: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents may degrease the skin.

SECTION 12: Ecological information**Ecotoxicity effects**

Toxicity to fish	: LC50: 1 - 10 mg/l Species: Fish
Toxicity to daphnia and other aquatic invertebrates	: LC50: 1 - 10 mg/l Species: Daphnia
Toxicity to algae	: EC50: 1 - 10 mg/l Species: algae
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Biodegradability	: This material is not expected to be readily biodegradable.
Elimination information (persistence and degradability)	
Results of PBT assessment	
2,2,4-Trimethylpentane (Isooctane)	: Non-classified PBT substance, Non-classified vPvB substance
Toluene	: Non-classified vPvB substance, Non-classified PBT substance
Additional ecological information	: Very toxic to aquatic life with long lasting effects.
Ecotoxicology Assessment	
Short-term (acute) aquatic hazard	
2,2,4-Trimethylpentane	: Very toxic to aquatic life.

Hydrocarbon Fluid Type III

Version 1.6

Revision Date 2018-11-27

(Isooctane)
Toluene : Toxic to aquatic life.

Long-term (chronic) aquatic hazard
2,2,4-Trimethylpentane : Very toxic to aquatic life with long lasting effects.
(Isooctane)
Toluene : Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, MARINE POLLUTANT, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, (-12.1 °C), MARINE POLLUTANT, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

Hydrocarbon Fluid Type III

Version 1.6

Revision Date 2018-11-27

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**SECTION 15: Regulatory information****National legislation**

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Skin corrosion or irritation
Serious eye damage or eye irritation
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard

CERCLA Reportable Quantity : 1428 lbs
2,2,4-Trimethylpentane (Isooctane)

Toluene

SARA 302 Reportable Quantity : This material does not contain any components with a SARA 302 RQ.

SARA 302 Threshold Planning Quantity : This material does not contain any components with a section 302 EHS TPQ.

SARA 304 Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

Hydrocarbon Fluid Type III

Version 1.6

Revision Date 2018-11-27

SARA 313 Components : The following components are subject to reporting levels established by SARA Title III, Section 313:

: Toluene - 108-88-3

Clean Air Act

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

: 2,2,4-Trimethylpentane (Isooctane) - 540-84-1

: Toluene - 108-88-3

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

: Toluene - 108-88-3

US State Regulations

Pennsylvania Right To Know

: 2,2,4-Trimethylpentane (Isooctane) - 540-84-1

: Toluene - 108-88-3

California Prop. 65 Components : WARNING This product can expose you to chemicals including [listed below], which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Toluene 108-88-3

Notification status

Europe REACH : This mixture contains only ingredients which have been registered according to Regulation (EU) No. 1907/2006 (REACH).

United States of America (USA) TSCA : On the inventory, or in compliance with the inventory

Canada DSL : On the inventory, or in compliance with the inventory

Hydrocarbon Fluid Type III


Version 1.6

Revision Date 2018-11-27

Australia AICS	:	On the inventory, or in compliance with the inventory
New Zealand NZIoC	:	On the inventory, or in compliance with the inventory
Japan ENCS	:	On the inventory, or in compliance with the inventory
Korea KECI	:	On the inventory, or in compliance with the inventory
Philippines PICCS	:	On the inventory, or in compliance with the inventory
China IECSC	:	On the inventory, or in compliance with the inventory

SECTION 16: Other information

NFPA Classification : Health Hazard: 2
Fire Hazard: 3
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : 40490

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act

Hydrocarbon Fluid Type III

Version 1.6

Revision Date 2018-11-27

>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		