



# SAFETY DATA SHEET

In accordance with OSHA 29 CFR 1910.1200

**SUPERTAK 807120 GENERAL PURPOSE AEROSOL**  
Revision Number 3

Revision date 14-Sep-2021  
Supersedes Date: 02-Jan-2018

## 1. Identification

### 1.1. Product identifier

**Product Name** SUPERTAK 807120 GENERAL PURPOSE AEROSOL

### Other means of identification

**Other information** Not applicable

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Adhesive  
**Restrictions on use** No information available

### 1.3. Details of the supplier of the safety data sheet

#### Responsible Party

Bostik Inc.  
11320 W. Watertown Plank Road  
Wauwatosa, Wisconsin 53226 USA  
Phone: +1 (800) 843-0844 (Domestic Toll Free)  
Phone: +1 (414) 774-2250 (International)  
Fax: +1 (414) 774-8075

**E-mail** msds@bostik.com

### 1.4. Emergency telephone number

**Emergency Telephone** Chemtrec (Transport/Environmental): 1-800-424-9300  
1-703-527-3887 (Outside U.S.)  
Rocky Mountain Poison Center: 1-866-767-5089

## 2. Hazard(s) identification

### 2.1. Classification of the substance or mixture

Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Aspiration hazard	Category 1
Flammable aerosols	Category 1

### Hazards not otherwise classified (HNOC)

Not applicable

### 2.2. Label elements

#### EMERGENCY OVERVIEW

**Danger**

#### Hazard statements

Causes serious eye irritation  
May cause drowsiness or dizziness  
May be fatal if swallowed and enters airways  
Extremely flammable aerosol

# SAFETY DATA SHEET

SUPERTAK 807120 GENERAL PURPOSE AEROSOL  
Revision Number 3

Revision date 14-Sep-2021  
Supersedes Date: 02-Jan-2018



**Appearance** Aerosol Liquefied gas      **Physical state** Gas      **Odor** Solvent

## Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling  
Wear protective gloves/protective clothing/eye protection/face protection  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
Pressurized container: Do not pierce or burn, even after use  
Do not spray on an open flame or other ignition source

## Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
IF INHALED: Remove person to fresh air and keep comfortable for breathing  
Call a POISON CENTER or doctor/physician if you feel unwell  
IF SWALLOWED: Immediately call a POISON CENTER or doctor  
Do NOT induce vomiting

## Precautionary Statements - Storage

Store locked up  
Store in a well-ventilated place. Keep container tightly closed  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

## Precautionary Statements - Disposal

Dispose of contents/ container to an approved waste disposal plant

6 % of the mixture consists of ingredient(s) of unknown toxicity

## 2.3. Other Information

Causes mild skin irritation.

## 3. Composition/information on ingredients

### 3.1. Substances

Not applicable.

### Mixture

Chemical name	CAS No	Weight-%
Methyl acetate	79-20-9	20 - 40
Propane	74-98-6	10 - 20
Acetone	67-64-1	10 - 20
1,1-Difluoroethane	75-37-6	2.5 - 10
Dimethyl ether	115-10-6	2.5 - 10
Heptane	142-82-5	2.5 - 10

# SAFETY DATA SHEET

SUPERTAK 807120 GENERAL PURPOSE AEROSOL  
Revision Number 3

Revision date 14-Sep-2021  
Supersedes Date: 02-Jan-2018

Methylcyclohexane	108-87-2	0.1 - <1
-------------------	----------	----------

*\*The exact percentage (concentration) of composition has been withheld as a trade secret*

## 4. First-aid measures

### 4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention immediately if symptoms occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with plenty of water. In case of contact with liquefied gas, thaw frosted parts with lukewarm water. If skin irritation persists, call a physician.
Ingestion	If swallowed, call a poison control center or physician immediately. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
Self-protection of the first aider	Wear personal protective clothing (see section 8). Avoid contact with skin, eyes or clothing. Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May cause redness and tearing of the eyes. Burning sensation. Prolonged contact may cause redness and irritation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
----------	--

### 4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians	Aspiration hazard. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Aspiration may cause pulmonary edema and pneumonitis. Keep victim under observation. Symptoms may be delayed. Treat symptomatically.
--------------------	---

## 5. Fire-fighting measures

### 5.1. Extinguishing media

Suitable Extinguishing Media Large Fire	Alcohol resistant foam. Carbon dioxide (CO <sub>2</sub> ). Dry chemical. CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.

### 5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Extremely flammable. Risk of ignition. Will be easily ignited by heat, sparks or flames. Containers may explode when heated. In the event of fire, cool tanks with water spray. In the event of fire and/or explosion do not breathe fumes. Keep product and empty container away from heat and sources of ignition.
--	--

# SAFETY DATA SHEET

SUPERTAK 807120 GENERAL PURPOSE AEROSOL  
Revision Number 3

Revision date 14-Sep-2021  
Supersedes Date: 02-Jan-2018

**Hazardous combustion products** Carbon oxides.

**Explosion data**

**Sensitivity to mechanical impact** None.

**Sensitivity to static discharge** May be ignited by friction, heat, sparks or flames.

**5.3. Advice for firefighters**

**Special protective equipment for fire-fighters**

In the event of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do it without risk. As in any fire, wear pressure-demand, self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear. Cool containers with flooding quantities of water until well after fire is out. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible withdraw from area and let fire burn.

## 6. Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions**

Contents under pressure. Use personal protective equipment as required. Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation. Avoid breathing vapors or mists. Stop leak if you can do it without risk. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling.

**Other information**

Refer to protective measures listed in Sections 7 and 8. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc) away from spilled material.

**6.2. Environmental precautions**

**Environmental precautions**

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Prevent entry into waterways, sewers, basements or confined areas. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

**6.3. Methods and material for containment and cleaning up**

**Methods for containment**

Prevent further leakage or spillage if safe to do so. Isolate area until gas has dispersed. Cover with plastic sheet to prevent spreading.

**Methods for cleaning up**

Use personal protective equipment as required. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Clean contaminated surface thoroughly. Following product recovery, flush area with water.

**Reference to other sections**

See section 8 for more information. See section 13 for more information.

## 7. Handling and storage

**7.1. Precautions for safe handling**

**Advice on safe handling**

Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Keep

# SAFETY DATA SHEET

SUPERTAK 807120 GENERAL PURPOSE AEROSOL  
Revision Number 3

Revision date 14-Sep-2021  
Supersedes Date: 02-Jan-2018

away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Do not breathe gas. Ensure adequate ventilation. Use only with adequate ventilation and in closed systems. In case of insufficient ventilation, wear suitable respiratory equipment. Contents under pressure. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling.

## 7.2. Conditions for safe storage, including any incompatibilities

### Storage Conditions

Store locked up. Keep out of the reach of children. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Protect from sunlight. Keep at temperatures below 50°C / 122°F. Keep at temperatures between 50 and 95 °F / 10 and 35 °C.

## 7.3 References to other sections

### Reference to other sections

Section 10: STABILITY AND REACTIVITY  
Section 13: DISPOSAL CONSIDERATIONS

## 8. Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Methyl acetate 79-20-9	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 610 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 610 mg/m <sup>3</sup> (vacated) STEL: 250 ppm (vacated) STEL: 760 mg/m <sup>3</sup>	IDLH: 3100 ppm TWA: 200 ppm TWA: 610 mg/m <sup>3</sup> STEL: 250 ppm STEL: 760 mg/m <sup>3</sup>
Propane 74-98-6	: See Appendix F: Minimal Oxygen Content, explosion hazard	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup>	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) STEL: 2400 mg/m <sup>3</sup> The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>
Heptane 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m <sup>3</sup>	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 85 ppm TWA: 350 mg/m <sup>3</sup>
Methylcyclohexane 108-87-2	TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m <sup>3</sup> (vacated) TWA: 400 ppm	IDLH: 1200 ppm TWA: 400 ppm TWA: 1600 mg/m <sup>3</sup>

# SAFETY DATA SHEET

**SUPERTAK 807120 GENERAL PURPOSE AEROSOL**  
Revision Number 3

Revision date 14-Sep-2021  
Supersedes Date: 02-Jan-2018

	(vacated) TWA: 1600 mg/m <sup>3</sup>
--	---------------------------------------

Chemical name	Argentina	Brazil	Chile	Colombia
Methyl acetate 79-20-9	TWA: 200 ppm STEL: 250 ppm	TWA: 200 ppm STEL: 250 ppm	LPP: 175 ppm LPP: 530 mg/m <sup>3</sup> LPT: 250 ppm LPT: 757 mg/m <sup>3</sup>	STEL: 250ppm TWA: 200ppm
Propane 74-98-6	TWA: 2500 ppm	Simple asphyxiant	-	:
Acetone 67-64-1	TWA: 500 ppm STEL: 750 ppm	TWA: 780 ppm TWA: 1870 mg/m <sup>3</sup> STEL: 500 ppm	LPP: 438 ppm LPP: 1040 mg/m <sup>3</sup> LPT: 750 ppm LPT: 1782 mg/m <sup>3</sup>	STEL: 500ppm TWA: 250ppm
Heptane 142-82-5	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm STEL: 500 ppm Heptane, all isomers STEL: 500 ppm	-	STEL: 500ppm TWA: 400ppm
Methylcyclohexane 108-87-2	TWA: 400 ppm	TWA: 400 ppm	-	TWA: 400ppm

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Methyl acetate 79-20-9	TWA: 200ppm STEL: 250ppm	STEL: 250ppm STEL: 798mg/m <sup>3</sup> TWA: 200ppm TWA: 638mg/m <sup>3</sup>	250 ppm STEL 200 ppm TWA	STEL: 250 ppm TWA: 200 ppm
Propane 74-98-6	:	-	See Appendix F: Minimal Oxygen Content, explosion hazard	TWA: 1000 mg/m <sup>3</sup> TWA: 1000 ppm
Acetone 67-64-1	TWA: 250ppm STEL: 500ppm	STEL: 750ppm STEL: 1781mg/m <sup>3</sup> TWA: 500ppm TWA: 1187mg/m <sup>3</sup>	500 ppm STEL 250 ppm TWA	STEL: 750 ppm TWA: 500 ppm
Dimethyl ether 115-10-6	-	TWA: 1000ppm TWA: 1888mg/m <sup>3</sup>	-	TWA: 1000 ppm TWA: 1920 mg/m <sup>3</sup>
Heptane 142-82-5	TWA: 400ppm STEL: 500ppm	TWA: 400ppm TWA: 1639mg/m <sup>3</sup>	500 ppm STEL (listed under Heptane, all isomers) 500 ppm STEL 400 ppm TWA (listed under Heptane, all isomers) 400 ppm TWA	STEL: 500 ppm TWA: 400 ppm
Methylcyclohexane 108-87-2	TWA: 400ppm	TWA: 400ppm TWA: 1606mg/m <sup>3</sup>	400 ppm TWA	TWA: 400 ppm

## 8.2. Exposure controls

### Appropriate engineering controls

#### Engineering controls

Showers  
Eyewash stations  
Ventilation systems. Provide a good standard of controlled ventilation (10 to 15 air changes

# SAFETY DATA SHEET

SUPERTAK 807120 GENERAL PURPOSE AEROSOL  
Revision Number 3

Revision date 14-Sep-2021  
Supersedes Date: 02-Jan-2018

per hour).

## Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles). Avoid contact with eyes.
Hand protection	Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.
Skin and body protection	Wear suitable protective clothing.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General hygiene considerations	Wear suitable gloves and eye/face protection. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Keep away from food, drink and animal feeding stuffs. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin, eyes or clothing. Wash hands before breaks and after work. Regular cleaning of equipment, work area and clothing is recommended.

## **9. Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state	Gas
Appearance	Aerosol Liquefied gas
Color	White
Odor	Solvent
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	Not applicable Insoluble in water
pH (as aqueous solution)	No data available	None known
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	50.4 °C / 122.8 °F	None known
Flash point	PROPELLANT -104.4 °C / -155.9 °F	Estimated
Evaporation rate	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	10.7	
Lower flammability or explosive limits	2.1	
Vapor pressure	No data available	None known
Relative vapor density	No data available	None known
Relative density	No data available	None known
Water solubility	No data available	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known

# SAFETY DATA SHEET

SUPERTAK 807120 GENERAL PURPOSE AEROSOL  
Revision Number 3

Revision date 14-Sep-2021  
Supersedes Date: 02-Jan-2018

Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

## 9.2. Other information

Explosive properties	No information available	
Oxidizing properties	No information available	
Solvent content (%)	No information available	
Solid content (%)	No information available	
Softening Point	No information available	
Molecular weight	No information available	
VOC Content (%)	27.7 %	No information available
Density	No information available	
Bulk density	No information available	

## 10. Stability and reactivity

### 10.1. Reactivity

Reactivity No information available.

### 10.2. Chemical stability

Chemical stability Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Hazardous polymerization Hazardous polymerization does not occur.

### 10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Risk of explosion by shock or heating under confinement. Incompatible materials.

### 10.5. Incompatible materials

Incompatible materials Strong oxidizing agents. Nitrate compounds.

### 10.6. Hazardous decomposition products

Hazardous decomposition products Carbon oxides Formaldehyde Carbon monoxide Carbon dioxide (CO<sub>2</sub>)

## 11. Toxicological information

### 11.1. Information on toxicological effects

#### Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause drowsiness or dizziness.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. Based on available data, the classification criteria are not met.



# SAFETY DATA SHEET

SUPERTAK 807120 GENERAL PURPOSE AEROSOL  
Revision Number 3

Revision date 14-Sep-2021  
Supersedes Date: 02-Jan-2018

## Ingestion

Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

## Symptoms related to the physical, chemical and toxicological characteristics

### Symptoms

May cause redness and tearing of the eyes. Prolonged contact may cause redness and irritation. Vapors may cause drowsiness and dizziness.

## Acute toxicity

### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 91,603.10 mg/kg  
ATEmix (inhalation-gas) 7,365,319.90

## Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl acetate 79-20-9	>5 g/kg (Rattus)	> 5 g/kg (Oryctolagus cuniculus)	>49000 mg/m <sup>3</sup> (Rattus) 4 h
Propane 74-98-6	-	-	>800000 ppm (Rattus) 15 min
Acetone 67-64-1	=5800 mg/kg (Rattus)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
1,1-Difluoroethane 75-37-6	-	-	= 437500 ppm ( Rat ) 4 h
Dimethyl ether 115-10-6	-	-	=164000 ppm (Rattus) 4 h
Heptane 142-82-5	LD50 > 5000 mg/Kg (rattus)	= 3000 mg/kg (Oryctolagus cuniculus)	=103 g/m <sup>3</sup> (Rattus) 4 h
Methylcyclohexane 108-87-2	>3200 mg/kg (Rattus)	>2920 mg/Kg bw (Rattus) 24 hour	>23 mg/l (vapour) (Rat- OECD 403)

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

### Serious eye damage/eye irritation

Classification based on data available for ingredients. Causes serious eye irritation.

### Respiratory or skin sensitization

Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

### Carcinogenicity

Based on available data, the classification criteria are not met.

### Reproductive toxicity

Based on available data, the classification criteria are not met.

### STOT - single exposure

May cause drowsiness or dizziness.

# SAFETY DATA SHEET

SUPERTAK 807120 GENERAL PURPOSE AEROSOL  
Revision Number 3

Revision date 14-Sep-2021  
Supersedes Date: 02-Jan-2018

<b>STOT - repeated exposure</b>	Based on available data, the classification criteria are not met.
<b>Target organ effects</b>	Heart, Central nervous system, Eyes, Respiratory system, Skin.
<b>Aspiration hazard</b>	Risk of serious damage to the lungs (by aspiration). May be fatal if swallowed and enters airways.
<b>Other adverse effects</b>	No information available.
<b>Interactive effects</b>	No information available.

## 12. Ecological information

### 12.1. Toxicity

**Ecotoxicity** Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Methyl acetate 79-20-9	EC50: >120mg/L (72h, <i>Desmodesmus subspicatus</i> )	LC50: 295 - 348mg/L (96h, <i>Pimephales promelas</i> ) LC50: 250 - 350mg/L (96h, <i>Brachydanio rerio</i> )	EC50 = 6000 mg/L 16 h EC50 = 6100 mg/L 30 min	EC50: =1026.7mg/L (48h, <i>Daphnia magna</i> )
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L ( <i>Oncorhynchus mykiss</i> )	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L ( <i>Daphnia magna</i> Static)
Dimethyl ether 115-10-6	-	LC50: >4.1g/L (96h, <i>Poecilia reticulata</i> )	-	> 4400 mg/L ( <i>Daphnia</i> ) (NEN 6501)
Heptane 142-82-5	-	LC50: =375.0mg/L (96h, <i>Cichlid</i> )	-	EC50: >10mg/L (24h, <i>Daphnia magna</i> )
Methylcyclohexane 108-87-2	10 mg/l ( <i>Pseudokirchneriella subcapitata</i> - OECD 201)	2.07 mg/l ( <i>Oryzias latipes</i> )	-	3 mg/l ( <i>Daphnia magna</i> - OECD 202)

### 12.2. Persistence and degradability

**Persistence and degradability** No information available.

### 12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

#### Component Information

Chemical name	Partition coefficient
Methyl acetate 79-20-9	0.18
Propane 74-98-6	2.3
Acetone 67-64-1	-0.24
Dimethyl ether 115-10-6	-0.18
Heptane	4.66

# SAFETY DATA SHEET

SUPERTAK 807120 GENERAL PURPOSE AEROSOL  
Revision Number 3

Revision date 14-Sep-2021  
Supersedes Date: 02-Jan-2018

142-82-5

## 12.4. Mobility in soil

Mobility No information available.

## Other adverse effects

Other adverse effects No information available.

## 13. Disposal considerations

### 13.1. Waste treatment methods

**Waste from residues/unused products** It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

**Contaminated packaging** Dispose of in accordance with federal, state and local regulations.

## 14. Transport information

**Note:** The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition) The information shown here, may not always agree with the bill of lading shipping description for the material

### DOT

UN/ID No UN1950  
Proper Shipping Name Aerosols  
Transport hazard class(es) 2.1  
DOT reportable quantity - lbs Acetone: RQ (lb)= 5000.00  
Reportable Quantity (RQ) (Acetone: RQ (kg)= 2270.00)  
Special Provisions N82  
Marine Pollutant I  
DOT Marine Pollutant Name Heptane, Methylcyclohexane  
Description UN1950, Aerosols, 2.1, Marine Pollutant (Heptane, Methylcyclohexane)  
Emergency Response Guide Number 126

### IATA

UN number or ID number UN1950  
UN proper shipping name Aerosols, flammable  
Transport hazard class(es) 2.1  
Special Provisions A145, A167, A802  
Description UN1950, Aerosols, flammable, 2.1

### IMDG

UN number or ID number UN1950  
UN proper shipping name Aerosols  
Transport hazard class(es) 2.1  
EmS-No F-D, S-U  
Special Provisions 63,190, 277, 327, 344, 381, 959  
Marine pollutant P  
IMDG Marine Pollutant Name Heptane, Methylcyclohexane  
Description UN1950, Aerosols(Heptane, Methylcyclohexane), 2.1, Marine Pollutant

# SAFETY DATA SHEET

SUPERTAK 807120 GENERAL PURPOSE AEROSOL  
Revision Number 3

Revision date 14-Sep-2021  
Supersedes Date: 02-Jan-2018

## 15. Regulatory information

### International Inventories

TSCA	Listed
DSL	Listed

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL** - Canadian Domestic Substances List

**Listed** - The components of this product are either listed or exempt from listing on inventory.

**Not Listed** - One or more components of this product are not listed on inventory.

### US Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

#### **SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

### Europe

#### **Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU**

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation. This document is based on the information given to us by our own suppliers at the date of this document.

#### **SVHC: Substances of Very High Concern for Authorization:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## 16. Other information

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### **Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation

**Prepared By** Product Safety & Regulatory Affairs.

**Revision date** 14-Sep-2021

**Revision note** SDS sections updated. 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 12. 14. 15.

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the

# SAFETY DATA SHEET

SUPERTAK 807120 GENERAL PURPOSE AEROSOL  
Revision Number 3

Revision date 14-Sep-2021  
Supersedes Date: 02-Jan-2018

---

date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**