

**UCON Lubricant 75-H-110,000-X**

UCON Fluids and Lubricants

**Product  
Description**

UCON Lubricant 75-H-110,000-X is a viscous, ethylene oxide/propylene oxide polymer based product specially formulated with additives for high temperature use.

**Typical Physical Properties†**

Appearance	Amber colored, viscous liquid
Viscosity, SUS, 37.8°C (100°F), ASTM D 445	110,000 – 130,000
Specific Gravity, 20/20°C, ASTM D 4052	1.097
Pour Point, °C (°F), ASTM D 97	<25 (<77)
Flash Point, Open Cup, °C (°F), ASTM D 92	279 (535)
Water, wt%, ASTM E 203	0.30 max

†Typical physical properties. Not to be construed as specifications.

**Product  
Stewardship**

Dow encourages its customers and potential users to review their applications from the standpoint of human health and environmental aspects. To help ensure that Dow products are not used in ways for which they are not intended or tested, Dow personnel will assist customers in dealing with environmental and product safety considerations. Dow literature, including Material Safety Data Sheets, should be consulted prior to the use.

**For More Information:**

North America: toll-free 1-800-447-4369  
fax 1-989-832-1465  
Europe: toll-free +800 3 694 6367  
call +32 3 450 2240  
fax +32 3 450 2815  
Pacific: call +852 2879 7260  
fax +852 2827 5881  
Other Areas: call 1-989-823-1560  
fax 1-989-832-1465

<http://www.dow.com>

NOTICE: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.