

ULTRANOX™ 626 phosphite

Phosphite Antioxidant

Description

ULTRANOX[™] **626 phosphite** is a high performance solid organophosphite antioxidant that contains no more than 1.0% by weight of Triisopropanolamine (CAS Number: 122-20-3).

Chemical Structure

Bis (2,4-di-t-butylphenyl) Pentaerythritol Diphosphite

Formula: $C_{33}H_{50}O_6P_2$

Chemical Abstract Number: 26741-53-7

$$(CH_{3})_{3}C$$
 $CCH_{3})_{3}$ $CCH_{3})_{3}C$ $CH_{2}C$ $CH_{2}C$ $CH_{2}C$ $CH_{3}C$ $CCH_{3}C$ $CCH_{3}C$

Applications

- Polyolefins
- Polyesters
- Styrenics
- Engineering thermoplastics
- PVC
- Elastomers
- Adhesives

Product Features

- Excellent color stability during compounding, fabrication and end use
- Reduction in polymer degradation during processing
- Improved gas fading performance in many applications
- High performance at low loading levels for more cost-effective formulations
- Higher phosphorous content than competitive phosphite antioxidants
- Synergism when used with light stabilizers such as benzophenones and benzotriazoles

SI Group Inc., 2750 Balltown Road, Schenectady, NY 12309 PH: +1 518.347.4200 www.siigroup.com

Page 1 of 3

The foregoing product brand is a trademark of one or more SI Group, Inc. affiliated companies. SI Group, The Substance Inside and the SI Group logo are Reg. U.S. Pat. & Tm Off. and additional countries, to SI Group, Inc.

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of SI Group, Inc. and its affiliated companies to ensure the accuracy or reliability of the information. Customers should contact SI Group account representatives for current information. It is the responsibility of the user to comply with all applicable laws and regulations relating to use of the product and to provide for a safe workplace. The user should consider all information contained herein only as a guide, and should take precautions that the user considers necessary or prudent to promote a safe work environment, such as considering all applicable health and safety hazards, developing safe work practice procedures and properly instructing employees, and reviewing the Safety Data Sheet (SDS) and product label for safety information.



Typical physical properties of ULTRANOX[™] 626 phosphite

Appearance	White Powder
Melt Point (capillary)	170-180°C (338-356°F)
Acid No. (mg KOH/g)	1.0 max.
Free 2, 4-di-t-butylphenol (%)	1.0 max
Phosphorous Content (%)	10.0-10.3
Triisopropanolamine Content (%)	0.5-1.0
Molecular Weight (g/mol)	604
Flash Point (Pensky-Martens Closed Cup)	168°C (335°F)
Bulk Density @ 20°C (68°F) lbs/ft³ (g/ml)	27.0 (0.43)
Particle Size Distribution 200	10% greater than 60 mesh, 50% less than mesh

Solubility @ 25°C / 77°F g/100 g solvent

Acetone	8.5	Hexane	4.8
Heptane	4.5	Methanol	1.9
Dichloro-Methane	43.0	Mineral Oil	10.0
Perchloroethylene	15.0	THF	35.0
Toluene	35.7	Water	Insoluble

^{*}Note: Solutions may be cloudy.

Dust Explosion Hazard

Minimum Ignition Temp. Dust Cloud	421°C / 790°F
Minimum Ignition Energy	200 mJ
Minimum Explosion Dust Cloud Concentration	0.035 oz/ft ³ 35 g/m ³
Index of Explosibility	0.37

Food Contact Regulatory Status

For details please contact SI Group Regulatory Affairs Group

SI Group Inc., 2750 Balltown Road, Schenectady, NY 12309 PH: +1 518.347.4200 www.siigroup.com

Page 2 of 3


The foregoing product brand is a trademark of one or more SI Group, Inc. affiliated companies. SI Group, The Substance Inside and the SI Group logo are Reg. U.S. Pat. & Tm Off. and additional countries, to SI Group, Inc.

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of SI Group, Inc. and its affiliated companies to ensure the accuracy or reliability of the information. Customers should contact SI Group account representatives for current information. It is the responsibility of the user to comply with all applicable laws and regulations relating to use of the product and to provide for a safe workplace. The user should consider all information contained herein only as a guide, and should take precautions that the user considers necessary or prudent to promote a safe work environment, such as considering all applicable health and safety hazards, developing safe work practice procedures and properly instructing employees, and reviewing the Safety Data Sheet (SDS) and product label for safety information.



Volatility By Thermal Gravimetric Analysis

Conditions: Nitrogen atmosphere @ 36°F (20°C)/minute



Storage and Handling

ULTRANOXTM **626 phosphite** is stable in excess of one (1) year when stored under normal conditions in a cool, dry place away from any direct sources of heat and moisture.

For additional handling and toxicological information consult the SI Group Material Safety Data Sheet.

Page 3 of 3

The foregoing product brand is a trademark of one or more SI Group, Inc. affiliated companies. SI Group, The Substance Inside and the SI Group logo are Reg. U.S. Pat. & Tm Off. and additional countries, to SI Group, Inc.

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of SI Group, Inc. and its affiliated companies to ensure the accuracy or reliability of the information. Customers should contact SI Group account representatives for current information. It is the responsibility of the user to comply with all applicable laws and regulations relating to use of the product and to provide for a safe workplace. The user should consider all information contained herein only as a guide, and should take precautions that the user considers necessary or prudent to promote a safe work environment, such as considering all applicable health and safety hazards, developing safe work practice procedures and properly instructing employees, and reviewing the Safety Data Sheet (SDS) and product label for safety information.