

Technical Data Sheet

Eastek™ 1100 Polymer Dispersion

Applications

- Commercial printing inks
- General industrial coatings
- Graphic arts
- Packaging components non food contact
- Packaging inks non food contact
- Paints & coatings
- Wood coatings

Product Description

Eastek™ 1100 polymer is a film forming polyester polymer supplied as an aqueous dispersion containing 33% polymer solids. Eastek™ 1100 provides excellent alcohol resistance, fast drying rates, low odor, low foaming, good adhesion to aluminum, and neutral pH. Eastek™ 1100 polymer dispersion is amine, surfactant and co-solvent free.

Typical Properties

Property	Typical Value, Units
General	
Form	Liquid (dispersion)
Color	Translucent
Odor	Odorless
Specific Gravity (water = 1)	>1
Vapor Pressure	Negligible
Boiling Point	100 °C (212 °F)
Solubility in Water	Negligible (dispersible)

Comments

Properties reported here are typical of average lots. Eastman makes no representation that the material in any particular shipment will conform exactly to the values given.

Eastman and its marketing affiliates shall not be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability of fitness of any product, and nothing herein waives any of the Seller's conditions of sale.

3/28/2018 7:53:03 AM