

Date Printed:	2022-09-07
---------------	------------

Effective Date:	2019-07-22
Supersedes Date:	2018-01-18

Name: UCARFLOC<sup>™</sup> 309CP Polymer

Specification Number:	000000484306
Previous Specified Material:	00126158

Final Testing Requirements						
Test and Test Condition	Limit	Unit	Method	Note		
Viscosity, 1% aqueous solution	13000 Min	сР	DOWM 101962			
Particle Size, THRU 10 MESH, < 2000 MICRON	100 Min	%	DOWM 102261			
Particle Size, THRU 200 MESH, < 74 MICRON	0 — 15	%	DOWM 102261			

## **General Notes**

- 1 Alkaline earth metals as CaO. Viscosity Brookfield RVF, spindle 2, speed 2 rpm, 25 deg C. The following properties are characteristic of this product. However, these properties are not determined on shipments and are not reported on the Certificate of Analysis: pH, 1.0% aq soln at 25 C: 8.0 to 10.0; Volatiles, 45 min, at 105 C: 1.0% by weight (max).
- 2 'CP' has been added to TP 484306 name to define it as Coarse Particle

READ PRECAUTIONARY INFORMATION AND MATERIAL SAFETY SHEETS. THIS PRODUCT IS SHIPPED IN COMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS REGARDING CLASSIFICATION, PACKAGING, SHIPPING AND LABELING.