

MP90 – m,p-Cresols

Technical Data Sheet



Typical Properties*:

m,p-Cresols	91%
m-Cresol	47%
p-Cresol	44%
Phenol	<1%
o-Cresol	<1%
Moisture	< 0.05%
Total Sulfur	< 0.005%
Nitrogen Bases	< 0.005%
Color, APHA	< 100

*At loading

Additional Information:

Boiling point:	202° C
Melting point:	10 °C (May supercool)
UN #:	2076 Cresols, liquid

Packaging: Available in railcar, tank truck, isocontainer, 450 lb drum, 200 kg drum

Shelf life: Cresols are stable and have an indefinite shelf-life with regard to composition. Depending upon storage conditions, they may absorb moisture from the air, darken in color over time, or leach low level metals from the storage vessel. This will be minimized, however, if the container remains sealed and the product is not exposed to air or excessive heating.

Applications: Phenolic resins, wire enamel and other solvents, surfactants, chemical intermediates.

Contact Information:

For sales and pricing information contact a sales representative at:
Telephone: +1(281)588-3000

info@us.sasol.com

This document is not a sales specification; it is intended for general information purposes only. Please contact your local sales representative for up-to-date product and specification information. Sasol expressly disclaims any liability whatsoever for damage or injury which results from use of the preceding data and nothing therein shall constitute a guarantee, warranty or representation (including freedom from patent liability) with respect to the data, the product described, or its fitness for any specific purpose, even if that purpose is known to Sasol.

For detailed safety and handling information, please refer to the respective Sasol Chemicals safety data sheet.

21-Jun-2018