



## Product Data Sheet

### *Epolene*® N-30 Polymer

#### Application/Uses

- Automotive
- Building and Construction
- Hot Melt Adhesives
- Packaging
- Solventborne Adhesives
- Wax Modification

#### Key Attributes

- Aids in pigment dispersion
- Easy to melt blend with natural or synthetic waxes
- Improves physical properties of paper coatings
- Increases scuff and rub off resistance in inks
- Low density polyethylene (PE)

#### Product Description

*Epolene* N-30 is a polyethylene (PE) homopolymer that can easily be melt blended with natural or synthetic waxes to increase the tensile strength of wax blends, improve the gloss of paper coatings, aid in pigment dispersion and mold release, and improve scuff and rub off resistance in printing inks. For these applications, six *Epolene* N-types, differing mainly in viscosity, are available to choose from (*Epolene* N-10, N-11, N-14, N-30, N-34, and N-35).

#### Typical Properties

Property	Test Method	Typical Value, Units
Polymer Type		PE
Ring and Ball Softening Point	ASTM E 28	110°C
Penetration Hardness <sup>a</sup>	ASTM D 5	2 dmm
Viscosity, Brookfield @ 125°C (257°F)		1,050 cP
Molecular Weight <sup>b</sup> M <sub>w</sub>		9,200

<sup>a</sup> Needle under 100-g load for 5s @ 25 deg C, tenths of mm

<sup>b</sup> Molecular weight measured via Gel Permeation Chromatography (GPC) using polystyrene standards

#### Comments

Properties reported here are typical of average lots. Westlake makes no representation that the material in any particular shipment will conform exactly to the values given.

*Westlake and its marketing affiliates shall not be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability or fitness of any product, and nothing herein waives any of the Seller's conditions of sale.*

**Compatibility and Solubility**

*Epolene* polymers are compatible with many polymers, resins, and natural and synthetic waxes.

**Packaging**

*Epolene* N-30 polymer is supplied as free-flowing pellets, packaged in multiwall paper bags with a polyethylene coated inner liner [22.67 kg (50 lb) net weight]. The bags are palletized and stretch wrapped to prevent contamination during storage and shipment. Many *Epolene* polymers are also shipped in a variety of bulk containers.

**Storage**

The useful life of this product can be affected by storage and handling conditions. When stored in the original unopened container in an enclosed area and protected from moisture, extreme temperatures and contamination, this product is estimated to continue to meet applicable sales specifications for more than 2 years from the date of manufacture. First in first out (FIFO) inventory control is recommended.