## Material Safety Data Sheet

Version: 1. 10/10/2007

# COATOSIL 3573 - SGS sample (250g) Polyalkyleneoxide Modified Polydimethylsiloxane

#### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufactured By: Momentive Performance Materials

3500 South State Route 2 FRIENDLY WV 26146

**Revised:** 10/10/2007

Preparer: PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS

**CHEMTREC** 1-800-424-9300

Chemical Family/Use: Siloxane Polyalkyleneoxide Copolymer

Formula: Polyalkyleneoxide Modified Polydimethylsiloxane

**HMIS** 

Flammability: 1 Reactivity: 0 Health: 0

**NFPA** 

Flammability: 1 Reactivity: 0 Health: 0

#### 2. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

Normal precautions common to safe manufacturing practice should be followed in handling and storage.

Form: Liquid Color: Clear, pale yellow Odor: Mild

#### **POTENTIAL HEALTH EFFECTS**

#### INGESTION

No evidence of harmful effects from available information.

#### SKIN

May cause minor irritation. May cause the following effects: - itching - slight local redness

#### **INHALATION**

Short-term harmful health effects are not expected from vapor generated at ambient temperature. Prolonged or repeated overexposure to mist or vapor generated at high temperatures may result in the inhalation of harmful amounts of material.

#### **EYES**

No evidence of harmful effects from available information.

#### **MEDICAL CONDITIONS AGGRAVATED**

A knowledge of the available toxicology information and of the physical and chemical properties of the material suggests that overexposure is unlikely to aggravate existing medical conditions.

#### SUBCHRONIC (TARGET ORGAN)

None known.

## Material Safety Data Sheet

Version: 1. 10/10/2007

# COATOSIL 3573 - SGS sample (250g) Polyalkyleneoxide Modified Polydimethylsiloxane

#### **CHRONIC EFFECTS / CARCINOGENICITY**

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

#### **ROUTES OF EXPOSURE**

No anticipated routes of exposure.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

#### A. HAZARDOUS

**B. NON-HAZARDOUS** 

Siloxane Polyalkyleneoxide Trade secret > 90 %

Copolymer

Polyalkylene Glycol Trade secret 5 - 10 %

#### 4. FIRST AID MEASURES

#### **INGESTION**

Do NOT induce vomiting. If victim is conscious, give 2-4 glasses of water. Never give anything by mouth to an unconscious person. Obtain medical attention.

#### **SKIN**

Wash off with soap and water. Get medical attention if symptoms occur.

#### **INHALATION**

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

#### **EYES**

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

#### **NOTE TO PHYSICIAN**

Treatment is symptomatic and supportive.

## Material Safety Data Sheet

Version: 1. 10/10/2007

## COATOSIL 3573 - SGS sample (250g) Polyalkyleneoxide Modified Polydimethylsiloxane

### 5. FIRE-FIGHTING MEASURES

**FLASH POINT:** 110 °C; 230 °F

METHOD: Pensky-Martens closed cup ASTM D 93

FLAMMABLE LIMITS IN AIR - LOWER (%): Not available FLAMMABLE LIMITS IN AIR - UPPER (%): Not available

SENSITIVITY TO MECHANICAL IMPACT: No

#### SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected.

#### **EXTINGUISHING MEDIA**

All standard extinguishing agents are suitable.

#### SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

#### 6. ACCIDENTAL RELEASE MEASURES

#### **ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED**

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

#### 7. HANDLING AND STORAGE

#### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Avoid contact with skin and eyes. Keep away from children. Attention: Not for injection into humans. May generate formaldehyde at temperatures greater than 150 C (300 F). See Section 10 of MSDS for details.

#### **STORAGE**

Keep container closed. Store in original container.

#### **FURTHER INFORMATION ON STORAGE CONDITIONS**

To assure uniform quality, mix well before using. Protect from freezing. Store above 0'C (32'F).

# performance materials

## Material Safety Data Sheet

Version: 1. 10/10/2007

### COATOSIL 3573 - SGS sample (250g) Polyalkyleneoxide Modified Polydimethylsiloxane

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **ENGINEERING CONTROLS**

Eyewash stations; Showers; Ventilation and other forms of engineering controls are preferred for controlling exposures. Respiratory protection may be needed for non-routine or emergency situations.

#### RESPIRATORY PROTECTION

May be needed if product is used in a confined or poorly ventilated area. If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

#### PROTECTIVE GLOVES

Impermeable or chemical resistant gloves.

#### **EYE AND FACE PROTECTION**

Safety glasses

#### OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

#### **Exposure Guidelines**

Component CAS R	N Source	<u>Value</u>
-----------------	----------	--------------

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

**BOILING POINT - C & F:** > 150 °C; > 302 °F; Copolymer

VAPOR PRESSURE (20 C) (MM HG): < 1

**VAPOR DENSITY (AIR=1):** Heavier than air **FREEZING POINT:** < -29 °C; < -20 °F < -29 °C; < -20 °F **MELTING POINT:** 

**PHYSICAL STATE:** Liquid ODOR: Mild

COLOR: Clear, pale yellow

**EVAPORATION RATE (BUTYL ACETATE=1):** < 1

**DENSITY:** 1.0200 g/cm3 **VOLATILE ORGANIC CONTENT (VOL):** Not determined **SOLUBILITY IN WATER (20 C):** Dispersible 13.90

VOC EXCL. H2O & EXEMPTS (G/L):

## Material Safety Data Sheet

Version: 1. 10/10/2007

## COATOSIL 3573 - SGS sample (250g) Polyalkyleneoxide Modified Polydimethylsiloxane

#### 10. STABILITY AND REACTIVITY

#### **STABILITY**

Stable

#### HAZARDOUS POLYMERIZATION

Will not occur.

#### HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Burning can produce the following combustion products:; Oxides of carbon.; Oxides of silicon.; Formaldehyde.; Carbon monoxide is highly toxic if inhaled; carbon dioxide in sufficient concentrations can act as an asphyxiant.; Acute overexposure to the products of combustion may result in irritation of the respiratory tract.; This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 degrees Fahrenheit (150'C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. A MSDS for formaldehyde is available from Momentive.

#### **INCOMPATIBILITY (MATERIALS TO AVOID)**

None currently known.

#### CONDITIONS TO AVOID

None known.

#### 11. TOXICOLOGICAL INFORMATION

#### OTHER EFFECTS OF OVEREXPOSURE

No adverse effects anticipated from available information.

#### 12. ECOLOGICAL INFORMATION

#### **ECOTOXICOLOGY**

All available ecological data have been taken into account for the development of the hazard and precautionary information contained in this Safety Data Sheet.

#### 13. DISPOSAL CONSIDERATIONS

#### **DISPOSAL METHOD**

Disposal should be made in accordance with federal, state and local regulations.

#### 14. TRANSPORT INFORMATION

## Material Safety Data Sheet

Version: 1. 10/10/2007

# COATOSIL 3573 - SGS sample (250g) Polyalkyleneoxide Modified Polydimethylsiloxane

Further Information: This product is not regarded as dangerous goods according to the

national and international regulations on the transport of dangerous

goods.

#### 15. REGULATORY INFORMATION

#### **Inventories**

Korea Existing Chemicals y (Positive listing)

Inventory (KECI)

Japan Inventory of Existing & y (Positive listing)

New Chemical Substances

(ENCS)

EU list of existing chemical y (Positive listing)

substances

Australia Inventory of Chemical y (Positive listing)

Substances (AICS)

Philippines Inventory of y (Positive listing)

Chemicals and Chemical

Substances (PICCS)

TSCA list y (Positive listing)
China Inventory of Existing y (Positive listing)

**Chemical Substances** 

Canada DSL Inventory y (Positive listing)

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

#### **US Regulatory Information**

SARA (311,312) HAZARD CLASS

No SARA Hazards

SARA (313) CHEMICALS

#### **Canadian Regulatory Information**

#### **CALIFORNIA PROPOSITION 65**

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects.



### Material Safety Data Sheet

Version: 1. 10/10/2007

# COATOSIL 3573 - SGS sample (250g) Polyalkyleneoxide Modified Polydimethylsiloxane

#### **16. OTHER INFORMATION**

#### **OTHER**

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate., C = ceiling limit NEGL = negligible EST = estimated NF = none found UNKN = unknown NE = none established REC = recommended ND = NA = not applicable none determined = recommended by vendor SKN = skin TS = trade secret R = recommended MST = mist NT = not tested STEL = short term exposure limit ppm = ppb = parts per billion By-product= reaction by-product, TSCA inventory status parts per million not required under 40 CFR part 720.30(h-2).