

# SAFETY DATA SHEET

# DDP SPECIALTY ELECTRONIC MATERIALS US,

INC.

# Product name: ROZONE™ 2000 Mildewcide

Issue Date: 01/15/2020 Print Date: 04/24/2020

DDP SPECIALTY ELECTRONIC MATERIALS US, INC. encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

# **1. IDENTIFICATION**

Product name: ROZONE™ 2000 Mildewcide

Recommended use of the chemical and restrictions on use Identified uses: Biocidal product

COMPANY IDENTIFICATION DDP SPECIALTY ELECTRONIC MATERIALS US, INC. 400 ARCOLA ROAD COLLEGEVILLE PA 19426-2914 UNITED STATES

**Customer Information Number:** 

833-338-7668 SDSQuestion-NA@dupont.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 1-800-424-9300 Local Emergency Contact: 800-424-9300

# 2. HAZARDS IDENTIFICATION

# Hazard classification

GHS classification in accordance with 29 CFR 1910.1200 Acute toxicity - Category 4 - Oral Acute toxicity - Category 3 - Inhalation Skin corrosion - Category 1 Serious eye damage - Category 1 Skin sensitisation - Category 1

Label elements Hazard pictograms



## Signal word: DANGER!

## Hazards

Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Toxic if inhaled.

#### **Precautionary statements**

#### Prevention

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/ protective clothing/ eye protection/ face protection.

#### Response

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. If skin irritation or rash occurs: Get medical advice/ attention. Wash contaminated clothing before reuse.

# Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

# Disposal

Dispose of contents/ container to an approved waste disposal plant.

#### Other hazards

No data available

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Chemical nature:** Solution of organic and inorganic compounds This product is a mixture.

Component	CASRN	Concentration
4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one	64359-81-5	>= 19.5 - 20.5 %
Propylene glycol phenyl ether	770-35-4	>= 60.0 - 65.0 %
Dipropylene glycol phenyl ether	51730-94-0	<= 5.0 %
Propanediol	57-55-6	>= 6.0 - 10.0 %
Copper stabilizer	Trade Secret	>= 1.0 - 1.5 %
C10-16-Alkylbenzene sulfonic acid	68584-22-5	>= 7.0 - 8.0 %

# 4. FIRST AID MEASURES

# Description of first aid measures

**Inhalation:** Move to fresh air. Give artificial respiration if breathing has stopped. If symptoms persist, call a physician.

**Skin contact:** IMMEDIATELY get under a safety shower. Remove contaminated clothing. Wash off with soap and water. Immediate medical attention is required. Wash contaminated clothing before reuse. Do not take clothing home to be laundered. Discard contaminated shoes, belts, and other articles made of leather.

**Eye contact:** Rinse immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.

**Ingestion:** Drink 1 or 2 glasses of water. IMMEDIATELY see a physician. Never give anything by mouth to an unconscious person.

# Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

# Indication of any immediate medical attention and special treatment needed

**Notes to physician:** MATERIAL IS CORROSIVE. It may not be advisable to induce vomiting. Possible mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock and convulsions maybe necessary.

# 5. FIREFIGHTING MEASURES

# Extinguishing media

Suitable extinguishing media: Use extinguishing media appropriate for surrounding fire..

Unsuitable extinguishing media: No data available

# Special hazards arising from the substance or mixture

Hazardous combustion products: No data available

**Unusual Fire and Explosion Hazards:** Combustion generates toxic fumes of the following:. hydrogen chloride. Nitrogen oxides (NOx). sulfur oxides.

# Advice for firefighters

**Fire Fighting Procedures:** Cool containers/tanks with water spray.. Minimize exposure.. Do not breathe fumes.. Contain run-off..

**Special protective equipment for firefighters:** Wear self-contained breathing apparatus and protective suit..

# 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures:** Wear a NIOSH approved (or equivalent) respirator (with organic vapor/acid gas cartridge and a dust/mist filter) during spill clean-ups and deactivation of this material. MATERIAL IS CORROSIVE. Protective clothing, including chemical splash goggles, nitrile or butyl rubber full length gloves, rubber apron, or clothing made of nitrile or butyl rubber, and rubber overshoes must be worn during spill clean-ups and deactivation of this material comes in contact with the skin during clean-up operations, IMMEDIATELY remove all contaminated clothing and wash exposed skin areas with soap and water. See SECTION 4, First Aid Measures, for further information.

**Environmental precautions:** Do not allow material to contaminate ground water system. Prevent product from entering drains.

**Methods and materials for containment and cleaning up:** WARNING: KEEP SPILLS AND CLEAN-UP RESIDUALS OUT OF MUNICIPAL SEWERS AND OPEN BODIES OF WATER. Adsorb the spill with spill pillows or inert solids such as clay or vermiculite, and transfer contaminated materials to suitable containers for recovery or disposal. Wipe contaminated area with TEXANOL<sup>®</sup> (2,2,4-trimethyl-1,3-pentanediol monoisobutyrate) or butyl CARBITOL<sup>®</sup> (diethylene glycol monobutyl ether) using a clean rag(s) or disposable pad(s) or mop(s). Isopropanol can also be used, but special care should be taken due to the flammability of this solvent. Discard contaminated wiping materials into suitable containers for recovery or disposal. Decontaminate spill area with a freshly prepared aqueous solution of 10% sodium thiosulfate. Let stand for 30 minutes. Rinse decontamination solution to chemical sewer (if in accordance with local procedures, permits and regulations). DO NOT add decontamination solution to the waste pail to deactivate the adsorbed product. See SECTION 13, Disposal Considerations, for information regarding the disposal of contained spills. TEXANOL<sup>®</sup> is a trademark of Eastman Chemical Co. CARBITOL<sup>®</sup> is a trademark of Union Carbide Co.

# 7. HANDLING AND STORAGE

**Precautions for safe handling:** This material is corrosive. For personal protection see section 8. Do not handle material near food, feed or drinking water.

**Conditions for safe storage:** Keep from freezing. Keep in a well-ventilated place. Do not store this material in containers made of the following: steel Do not store this material near food, feed or drinking water.

CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied. Expiration date based only on retention of >95% actives during storage at 20°C-25°C (68°F-77°F).

# Storage stability

**Storage temperature:** 10 - 43 °C (50 - 109 °F)

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
4,5-Dichloro-2-n-octyl-4-	Dow IHG	TWA	0.06 mg/m3
isothiazolin-3-one			
	Dow IHG	STEL	0.1 mg/m3
Propanediol	US WEEL	TWA	10 mg/m3

# Exposure controls

**Engineering controls:** Use local exhaust ventilation with a minimum capture velocity of 150 ft/min. (0.75 m/sec.) at the point of dust or mist evolution. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

**Protective measures:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

# Individual protection measures

**Eye/face protection:** Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent). Eye protection worn must be compatible with respiratory protection system employed. **Skin protection** 

**Hand protection:** Chemical-resistant gloves should be worn whenever this material is handled. The glove(s) listed below may provide protection against permeation. (Gloves of other chemically resistant materials may not provide adequate protection): butyl-rubber Nitrile rubber Gloves should be removed and replaced immediately if there is any indication of degradation or chemical breakthrough. Rinse and remove gloves immediately after use. Wash hands with soap and water. NOTE: Material is a possible skin sensitizer.

**Other protection:** Wear as appropriate: Chemical resistant apron complete suit protecting against chemicals

**Respiratory protection:** A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements or equivalent must be followed whenever workplace conditions warrant a respirator's use. None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Up to 10 times the exposure limit: Wear a properly fitted NIOSH approved (or equivalent) half-mask, air-purifying respirator. Up to 1000 ppm organic vapor: Wear a properly fitted NIOSH approved (or equivalent) full-facepiece, air-purifying respirator, OR full-facepiece, airline respirator in the pressure demand mode. Above 1000 ppm organic vapor or Unknown: Wear a properly fitted NIOSH approved (or equivalent) self-contained breathing appartus in the pressure demand mode, OR full-facepiece, airline respirator in the pressure demand mode with emergency escape provision. Air-purifying respirators should be equipped with NIOSH approved (or equivalent) organic vapor cartridges and R95 or P95 filters.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	
Physical state	liquid clear
Color	green
Odor	Mild odor
Odor Threshold	No data available
рН	2.8 Aqueous solution
Melting point/range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	243.00 °C (469.40 °F) Solvent
Flash point	116.00 °C (240.80 °F) TCC (Solvent)
Evaporation Rate (Butyl Acetate	No data available
= 1)	
Flammability (solid, gas)	Not Applicable
Lower explosion limit	ca.0.70 % vol
Upper explosion limit	ca.9.40 % vol
Vapor Pressure	0.1 mmHg
Relative Vapor Density (air = 1)	ca.53.0000
Relative Density (water = 1)	1.09 at 25 °C (77 °F)
Water solubility	slightly soluble
Partition coefficient: n- octanol/water	log Pow: 2.8 OECD Test Guideline 107 or Equivalent
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Dynamic Viscosity	58 mPa.s at 25 °C (77 °F)
Kinematic Viscosity	No data available
Explosive properties	No data available
Oxidizing properties	No data available
Molecular weight	No data available
Percent volatility	60 - 70 %
-	

NOTE: The physical data presented above are typical values and should not be construed as a specification.

# **10. STABILITY AND REACTIVITY**

Reactivity: No data available

Chemical stability: No data available

**Possibility of hazardous reactions:** Stable under recommended storage conditions. Product will not undergo polymerization.

Conditions to avoid: No data available

**Incompatible materials:** Avoid contact with the following: Oxidizing agents Amines Reducing agents Mercaptans.

Hazardous decomposition products: Nitrogen oxides (NOx). Sulphur oxides. hydrogen chloride.

# 11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

# Acute toxicity

Acute oral toxicity LD50, Rat, 978 mg/kg

Acute dermal toxicity LD50, Rabbit, > 2,000 mg/kg

Acute inhalation toxicity LC50, Rat, 4 Hour, dust/mist, 0.758 mg/l

**Skin corrosion/irritation** This material is corrosive.

Serious eye damage/eye irritation Corrosive

**Sensitization** Causes sensitisation.

For respiratory sensitization: No relevant data found.

# Specific Target Organ Systemic Toxicity (Single Exposure)

Contains component(s) which are classified as specific target organ toxicant, single exposure, category 3.

Specific Target Organ Systemic Toxicity (Repeated Exposure) Product test data not available. Refer to component data.

# Carcinogenicity

Contains component(s) which did not cause cancer in laboratory animals.

# Teratogenicity

Did not show teratogenic effects in animal experiments. Active ingredient

# **Reproductive toxicity**

This product is not a reproductive hazard. Active ingredient

# Mutagenicity

Non-mutagenic Active ingredient

# **Aspiration Hazard**

Product test data not available. Refer to component data.

## COMPONENTS INFLUENCING TOXICOLOGY:

## 4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one

# Specific Target Organ Systemic Toxicity (Repeated Exposure)

In animals, effects have been reported on the following organs: Stomach.

#### **Aspiration Hazard**

Aspiration into the lungs may occur during ingestion or vomiting, causing tissue damage or lung injury.

#### Propylene glycol phenyl ether

#### Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on available data, repeated exposures are not anticipated to cause additional significant adverse effects.

# Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

# Dipropylene glycol phenyl ether

# Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

#### **Aspiration Hazard**

Based on physical properties, not likely to be an aspiration hazard.

#### **Propanediol**

# Specific Target Organ Systemic Toxicity (Repeated Exposure)

In rare cases, repeated excessive exposure to propylene glycol may cause central nervous system effects.

#### Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

#### Copper stabilizer

# Specific Target Organ Systemic Toxicity (Repeated Exposure)

For similar material(s):

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

#### **Aspiration Hazard**

Aspiration into the lungs may occur during ingestion or vomiting, causing tissue damage or lung injury.

# C10-16-Alkylbenzene sulfonic acid

# **Specific Target Organ Systemic Toxicity (Repeated Exposure)** For similar material(s):

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

# **Aspiration Hazard**

Aspiration into the lungs may occur during ingestion or vomiting, causing tissue damage or lung injury.

# 12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

# **General Information**

Very toxic to aquatic organisms.

# Toxicity

# 4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one

# Acute toxicity to fish

Material is very highly toxic to aquatic organisms on an acute basis (LC50/EC50 <0.1 mg/L in the most sensitive species).

LC50, Oncorhynchus mykiss (rainbow trout), flow-through, 96 Hour, 0.0027 mg/l, OECD Test Guideline 203 or Equivalent

LC50, Bluegill sunfish (Lepomis macrochirus), flow-through, 96 Hour, 0.014 mg/l, OECD Test Guideline 203 or Equivalent

# Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, 0.0057 mg/l

# Acute toxicity to algae/aquatic plants

EbC50, Pseudokirchneriella subcapitata (green algae), static test, 72 Hour, 0.048 mg/l, OECD Test Guideline 201 ErC50, Pseudokirchneriella subcapitata (green algae), static test, 72 Hour, 0.077 mg/l, OECD Test Guideline 201

# Toxicity to bacteria

EC50, activated sludge, Respiration rates., 5.70 mg/l

# Chronic toxicity to fish

NOEC, Oncorhynchus mykiss (rainbow trout), flow-through, 97 d, growth, 0.00056 mg/l

# Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 21 d, 0.00063 mg/l

# Propylene glycol phenyl ether

# Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested). LC50, Pimephales promelas (fathead minnow), static test, 96 Hour, 280 mg/l, OECD Test Guideline 203 or Equivalent

# Acute toxicity to aquatic invertebrates

LC50, Daphnia magna (Water flea), static test, 48 Hour, 370 mg/l, OECD Test Guideline 202 or Equivalent

# Acute toxicity to algae/aquatic plants

EC50, Desmodesmus subspicatus (green algae), static test, 72 Hour, Growth rate inhibition, > 100 mg/l, EU Method C.3 (Algal Inhibition test)

# Toxicity to bacteria

EC50, 30 min, > 1,000 mg/l, OECD Test Guideline 209

# Dipropylene glycol phenyl ether

# Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested). LC50, Oncorhynchus mykiss (rainbow trout), static test, 96 Hour, 204 mg/l, OECD Test Guideline 203 or Equivalent

#### Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, 336 mg/l, OECD Test Guideline 202 or Equivalent

#### Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), 96 Hour, Growth rate inhibition, 188 mg/l, OECD Test Guideline 201 or Equivalent

# **Propanediol**

# Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested). LC50, Oncorhynchus mykiss (rainbow trout), static test, 96 Hour, 40,613 mg/l, OECD Test Guideline 203

## Acute toxicity to aquatic invertebrates

LC50, Ceriodaphnia dubia (water flea), static test, 48 Hour, 18,340 mg/l, OECD Test Guideline 202

# Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), 96 Hour, Growth rate inhibition, 19,000 mg/l, OECD Test Guideline 201

# Toxicity to bacteria

NOEC, Pseudomonas putida, 18 Hour, > 20,000 mg/l

#### Chronic toxicity to aquatic invertebrates

NOEC, Ceriodaphnia dubia (water flea), semi-static test, 7 d, number of offspring, 13,020 mg/l

# Copper stabilizer

Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

# Acute toxicity to aquatic invertebrates

For this family of materials: EC50, Daphnia magna (Water flea), 48 Hour, 5.2 mg/l, OECD Test Guideline 202 or Equivalent

# Acute toxicity to algae/aquatic plants

For this family of materials:

ErC50, Desmodesmus subspicatus (green algae), 72 Hour, Growth rate, 36 mg/l NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, 1,000 mg/l

# Toxicity to bacteria

EC10, Bacteria, 16 Hour, 51 mg/l

# C10-16-Alkylbenzene sulfonic acid

# Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

# Acute toxicity to aquatic invertebrates

For this family of materials: EC50, Daphnia magna (Water flea), 48 Hour, 5.2 mg/l, OECD Test Guideline 202 or Equivalent

#### Acute toxicity to algae/aquatic plants

For this family of materials: ErC50, Desmodesmus subspicatus (green algae), 72 Hour, Growth rate, 36 mg/l NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, 1,000 mg/l

# Toxicity to bacteria

EC10, Bacteria, 16 Hour, 51 mg/l

# Persistence and degradability

#### 4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one

**Biodegradability:** Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions. Considered to be rapidly degradable. Biodegradation (Aquatic metabolism) CAS # 64359-81-5 t 1/2 anaerobic = < 1hr. CAS # 64359-81-5 t 1/2 aerobic = < 1hr.

# Propylene glycol phenyl ether

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Biodegradation rate may increase in soil and/or water with acclimation.
10-day Window: Fail
Biodegradation: 72 %
Exposure time: 28 d
Method: OECD Test Guideline 301F or Equivalent

Theoretical Oxygen Demand: 2.31 mg/mg

#### Photodegradation Atmospheric half-life: 3.5 Hour Method: Estimated.

# Dipropylene glycol phenyl ether

Biodegradability: Material is expected to be readily biodegradable. 10-day Window: Pass Biodegradation: 100 % Exposure time: 28 d Method: OECD Test Guideline 301F or Equivalent

# **Propanediol**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Biodegradation may occur under anaerobic conditions (in the absence of oxygen). 10-day Window: Pass

Biodegradation: 81 % Exposure time: 28 d Method: OECD Test Guideline 301F or Equivalent 10-day Window: Not applicable Biodegradation: 96 % Exposure time: 64 d Method: OECD Test Guideline 306 or Equivalent

Theoretical Oxygen Demand: 1.68 mg/mg

Chemical Oxygen Demand: 1.53 mg/mg

# **Biological oxygen demand (BOD)**

Incubation Time	BOD
5 d	69.000 %
10 d	70.000 %
20 d	86.000 %

#### Photodegradation Atmospheric half-life: 10 Hour Method: Estimated.

# Copper stabilizer

Biodegradability: For similar material(s): Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. 10-day Window: Pass Biodegradation: 84 % Exposure time: 28 d Method: OECD Test Guideline 301E or Equivalent 10-day Window: Pass Biodegradation: 80 % Exposure time: 28 d Method: OECD Test Guideline 301B or Equivalent

# C10-16-Alkylbenzene sulfonic acid

Biodegradability: For similar material(s): Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.
10-day Window: Pass
Biodegradation: 84 %
Exposure time: 28 d
Method: OECD Test Guideline 301E or Equivalent
10-day Window: Pass
Biodegradation: 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301B or Equivalent

#### **Bioaccumulative potential**

Partition coefficient: n-octanol/water(log Pow): 2.8 OECD Test Guideline 107 or Equivalent

# Mobility in soil

# 4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one

Expected to be relatively immobile in soil (Koc > 5000). **Partition coefficient (Koc):** 5662 - 7865 Measured

# Propylene glycol phenyl ether

Potential for mobility in soil is very high (Koc between 0 and 50). **Partition coefficient (Koc):** 19 - 21 Estimated.

# Dipropylene glycol phenyl ether

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process. Potential for mobility in soil is very high (Koc between 0 and 50). **Partition coefficient (Koc):** 12.36 Estimated.

# **Propanediol**

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process. Potential for mobility in soil is very high (Koc between 0 and 50). **Partition coefficient (Koc):** < 1 Estimated.

#### Copper stabilizer

No relevant data found.

# C10-16-Alkylbenzene sulfonic acid

No relevant data found.

# **13. DISPOSAL CONSIDERATIONS**

**Disposal methods:** Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations. (See 40 CFR 268)

**Contaminated packaging:** Empty containers retain product residues. Follow label warnings even after container is emptied. Improper disposal or reuse of this container may be dangerous and illegal. Refer to applicable federal, state and local regulations.

# **14. TRANSPORT INFORMATION**

DOT

Proper shipping name	Corrosive liquids, toxic, n.o.s.(4,5-Dichloro-2-n-octyl-4- isothiazolin-3-one, C10-16-Alkylbenzene sulfonic acid)
UN number	UN 2922
Class	8 (6.1)
Packing group	

Classification for SEA transport (I Proper shipping name	<b>MO-IMDG):</b> CORROSIVE LIQUID, TOXIC, N.O.S.(4,5-Dichloro-2-n-octyl- 4-isothiazolin-3-one, C10-16-Alkylbenzene sulfonic acid)
UN number	UN 2922
Class	8 (6.1)
Packing group	II
Marine pollutant	4,5-Dichloro-2-n-octyl-4-isothiazolin-3-one
Transport in bulk	Consult IMO regulations before transporting ocean bulk
according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	
Classification for AIR transport (I	ATA/ICAO):
Proper shipping name	Corrosive liquid, toxic, n.o.s.(4,5-Dichloro-2-n-octyl-4- isothiazolin-3-one, C10-16-Alkylbenzene sulfonic acid)
UN number	UN 2922
Class	8 (6.1)
Packing group	

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

# **15. REGULATORY INFORMATION**

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Acute toxicity (any route of exposure) Skin corrosion or irritation Serious eye damage or eye irritation Respiratory or skin sensitisation

# Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

The following components are subject to reporting levels established by SARA Title III, Section 313:ComponentsCASRNCopper hydroxide20427-59-2

# Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

This material does not contain any components with a CERCLA RQ.

Pennsylvania

Any material listed as "Not Hazardous" in the CAS REG NO. column of SECTION 2, Composition/Information On Ingredients, of this MSDS is a trade secret under the provisions of the Pennsylvania Worker and Community Right-to-Know Act.

# California Prop. 65

WARNING: This product can expose you to chemicals including Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

# **United States TSCA Inventory (TSCA)**

This product contains chemical substance(s) exempt from U.S. EPA TSCA Inventory requirements. It is regulated as a pesticide subject to Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA) requirements.

# Federal Insecticide, Fungicide and Rodenticide Act

EPA Registration Number: 707-262

This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label:

# DANGER

Corrosive Causes irreversible eye damage and skin burns May cause allergic skin reaction Harmful if swallowed May be fatal if inhaled May be fatal if absorbed through skin This product is a dermal sensitizer. This product is toxic to fish and aquatic invertebrates.

# **16. OTHER INFORMATION**

# Hazard Rating System

#### HMIS

Health	Flammability	Physical Hazard
3*	1	0

\* = Chronic Effects (See Hazards Identification)

# Revision

Identification Number: 6025845 / A749 / Issue Date: 01/15/2020 / Version: 6.4 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

# Legend

Dow IHG	Dow Industrial Hygiene Guideline
STEL	Short term exposure limit

TWA	8	8-hr TWA
US WEEI	[	USA. Workplace Environmental Exposure Levels (WEEL)

# Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response: ERG - Emergency Response Guide: GHS - Globally Harmonized System: GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA -Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA -Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

# Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DDP SPECIALTY ELECTRONIC MATERIALS US, INC. urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDS sobtained from any source other than ourselves. If you have obtained an (M)SDS from

another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US