



Chevron Phillips Chemical Company Issued Sales Specification

Name of Product

SOLTROL* 125 ISOPARAFFIN

Revision Date

11/18/2011

Chevron Phillips Chemical Company LP

10001 Six Pines Drive

The Woodlands, TX 77380

800-858-4327

Technical Service: 832-813-4862

Chevron Phillips Chemicals International N.V.

Brusselsesteenweg 355

B-3090 Overijse, Belgium

+32 (0) 2 689 12 11

Chevron Phillips Chemicals Asia PTE Ltd.

5 Temasek Boulevard

05-01 Suntec Tower Five

Singapore 038985

+65 6337 9700

Test	Units	Method	Typical	Minimum	Maximum	Qualitative	Note
Acidity of Dist Residue	---	ASTM D-1093	Neutral	---	---	---	Neutral
Appearance	---	Visual	Clear with no particulate matter	---	---	Clear with no particulate matter	---
Corrosion (3 hrs @212F)	---	ASTM D-130	1A	---	---	---	1B Max
Distillation - DP	FAH	ASTM D-86	373	---	395	---	---
Distillation - IBP	FAH	ASTM D-86	348	330	---	---	---
Flash Point, TCC	FAH	ASTM D-56	127	115	---	---	---
Odor	---	Smell	Pass	---	---	Pass	---
Saybolt Color	SAY	ASTM D-6045	30	30	---	---	---
Specific Gravity 60/60F	---	ASTM D-4052	0.7562	0.740	0.770	---	---
Aromatics	ppm	ASTM E-169	25	---	200	---	---
Other	Units	Method	Typical	Minimum	Maximum	Qualitative	Note
Aniline Point	FAH	ASTM D-611	184	---	---	---	---
API Gravity	---	ASTM D-287	55.2	---	---	---	---
Density @ 60 F	LB/GAL	ASTM D-4052	6.31	---	---	---	---
Kauri Butanol	---	ASTM D-1133	27	---	---	---	---
Purity, wt% Isoparaaffins	---	---	99+	---	---	---	---

Notes

Soltrol* is a registered trademark of Chevron Phillips Chemical Company LP

Printed Versions of this document are uncontrolled

Notice: Before using this product, the user is advised and cautioned to make its own determination and assessment of the safety and suitability of the product for the specific use in question and is further advised against relying on the information contained herein as it may relate to any specific use or application. It is the ultimate responsibility of the user to ensure that the product is suited and the information is applicable to the user's specific application. Chevron Phillips Chemical Company LP does not make and expressly disclaims, all warranties, including warranties of merchantability or fitness for a particular purpose, regardless of whether oral or written, express or implied, or allegedly arising from any usage of any trade or from any course of dealing in connection with the use of the information contained herein or the product itself. The user expressly assumes all risk and liability, whether based in contract, or otherwise, in connection with the use of the information contained herein or the product itself. Further, information contained herein is given without reference to any intellectual property issues, as well as federal, state or local laws which may be encountered in the use thereof. Such questions should be investigated by the user.