

LOWINOX[™] 1790 stabilizer

Phenolic Antioxidant

Description

LOWINOX[™] 1790 stabilizer is a high performance sterically hindered phenolic antioxidant of the trisphenol class with a cyanuric acid central moiety.

Chemical Name

1,3,5-tris(4-tert.-butyl-3-hydroxy-2,6-dimethylbenzyl)-1,3,5-triazine-2,4,6-(1H,3H,5H)-trione

CAS-Number:

40601-76-1

EINECS-Number:

254-996-9

Formula LOWINOX[™] 1790 stabilizer



SI Group Inc., 2750 Balltown Road, Schenectady, NY 12309 PH: +1 518.347.4200 www.siigroup.com

Page 1 of 3

The foregoing product brand is a trademark of one or more SI Group, Inc. affiliated companies. SI Group, The Substance Inside and the SI Group logo are Reg. U.S. Pat. & Tm Off. and additional countries, to SI Group, Inc.

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of SI Group, Inc. and its affiliated companies to ensure the accuracy or reliability of the information. Customers should contact SI Group account representatives for current information. It is the responsibility of the user to comply with all applicable laws and regulations relating to use of the product and to provide for a safe workplace. The user should consider all information contained herein only as a guide, and should take precautions that the user considers necessary or prudent to promote a safe work environment, such as considering all applicable health and safety hazards, developing safe work practice procedures and properly instructing employees, and reviewing the Safety Data Sheet (SDS) and product label for safety information.

Typical physical properties of LOWINOX[™] 1790 stabilizer

Appearance	White free flowing powder or granules
Granular Bulk density, g/l	534
Powder Bulk density, g/l	405
Molecular weight [g/mol]	700
Melting range, °C	159-163

Solubility (g/100g solvent) @ 25°C

Water	<0.1	Toluene	75
Methanol	<0.1	Dimethylacetamide	>100
Ethyl Acetate	>100	<i>n</i> -Hexane	1.5
Acetone	60	Chloroform	>100

Thermogravimetric Analysis (10 mg @ 10°C/minute under N₂)

Weight Loss [%]	1	5	10
Temperature [°C]	202	333	349

Application

LOWINOX[™] 1790 stabilizer is especially suited for polyurethane, polypropylene, polyester and polyamide fibers where it provides at unusually low load levels excellent gas fading resistance. In addition, the molecular structure and the relatively high molecular weight results in a high extraction resistance in highly demanding applications like hot water conducting polypropylene pipes. For more detailed advice on applications and load levels please contact SI Group Technical Service.

Features

- Excellent gas fading resistance
- High molecular weight, high extraction resistance
- Excellent process stabilizer
- Exceptional heat stabilization in combination with secondary antioxidants (exceptional synergism with NAUGARD[™] DLTDP thioester) provides excellent processing stability at load levels of 50% - 75% of conventional phenolic antioxidants in rotomolding applications.

SI Group Inc., 2750 Balltown Road, Schenectady, NY 12309 PH: +1 518.347.4200 www.siigroup.com

Page 2 of 3

The foregoing product brand is a trademark of one or more SI Group, Inc. affiliated companies. SI Group, The Substance Inside and the SI Group logo are Reg. U.S. Pat. & Tm Off. and additional countries, to SI Group, Inc.

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of SI Group, Inc. and its affiliated companies to ensure the accuracy or reliability of the information. Customers should contact SI Group account representatives for current information. It is the responsibility of the user to comply with all applicable laws and regulations relating to use of the product and to provide for a safe workplace. The user should consider all information contained herein only as a guide, and should take precautions that the user considers necessary or prudent to promote a safe work environment, such as considering all applicable health and safety hazards, developing safe work practice procedures and properly instructing employees, and reviewing the Safety Data Sheet (SDS) and product label for safety information.

Mar 2019

Physical Forms

LOWINOX[™] 1790 stabilizer is a white to off-white powder. For applications in polyurethane fibers it is available in organic solvents (e.g. Dimethylacetamide). Utilizing SI Group proprietary technology [US 5240642 (31.8.1993), EP 0565184 (1.4.1993)] LOWINOX[™] 1790 stabilizer can be offered also in the form of tailor made NDBs (No Dust Blends) containing LOWINOX[™] 1790 stabilizer alone or together with costabilizers, specific phenolic antioxidants, synergistic light stabilizers of the HALS type, thio or phosphorus synergists. For additional information on the above-mentioned physical forms please contact SI Group Technical Service.

Food Contact

For details please contact SI Group Regulatory Affairs.

Handling and Storage

The use of proper protective equipment is recommended. Excess exposure to the product should be avoided. Wash thoroughly after handling. Store the product in a cool, dry, well-ventilated area away from incompatible materials. Unless otherwise stated, the shelf life of the product is 1 year when it is properly stored.

For additional handling and toxicological information consult the SI Group Material Safety Data Sheet.

SI Group Inc., 2750 Balltown Road, Schenectady, NY 12309 PH: +1 518.347.4200 www.siigroup.com

Page 3 of 3

The foregoing product brand is a trademark of one or more SI Group, Inc. affiliated companies. SI Group, The Substance Inside and the SI Group logo are Reg. U.S. Pat. & Tm Off. and additional countries, to SI Group, Inc.

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of SI Group, Inc. and its affiliated companies to ensure the accuracy or reliability of the information. Customers should contact SI Group account representatives for current information. It is the responsibility of the user to comply with all applicable laws and regulations relating to use of the product and to provide for a safe workplace. The user should consider all information contained herein only as a guide, and should take precautions that the user considers necessary or prudent to promote a safe work environment, such as considering all applicable health and safety hazards, developing safe work practice procedures and properly instructing employees, and reviewing the Safety Data Sheet (SDS) and product label for safety information.