

SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Name ELVACITE® 4170

Product Description Polymer based on Methyl methacrylate.

CAS No. 9011-14-7

Identified use(s)

Manufacture of inks, paints and varnishes.

Uses advised against None known.

Manufacturer Lucite International, Inc., 7275 Goodlett Farms Parkway, Cordova, TN 38016-4909

Phone: 1-800-4-LUCITE msdsinfo@lucite.com

Emergency Phone No. 1-800-424-9300 (Transport Emergency)

1-877-886-2143 (Medical Emergency)

2. HAZARDS IDENTIFICATION

Hazard classification Combustible dust

Label elements

Signal word Warning

Hazard statement(s) May form combustible dust concentrations in air.

Other hazards Low toxicity under normal conditions of handling and use.

COMPOSITION/INFORMATION ON INGREDIENTS

Chemical identity of the substance Poly(Methyl methacrylate)

CAS No. 9011-14-7

Substances in the product which may present a health or environmental hazard, or which have been assigned occupational exposure limits, are detailed below.

Substance identity	%W/W	CAS No.
No classifiable hazardous ingredient(s).		

4. FIRST AID MEASURES

Description of first aid measures

Inhalation IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Skin Contact IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Ingestion IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Obtain medical attention if ill effects

occur

Most important symptoms and effects, both acute and delayed

Not applicable.

Indication of any immediate medical attention and special treatment needed

None necessary.

FIRE-FIGHTING MEASURES

Suitable extinguishing media Water spray, foam, dry powder or CO2.

Unsuitable Extinguishing Media

Special hazards arising from the substance Combustible but not readily ignited. By analogy with similar materials, the product may or mixture

Do not use water jet.

decompose if heated to temperatures above 392°F (200°C). Combustion or thermal

decomposition will evolve toxic, irritant and flammable vapors.

Special protective equipment and A self contained breathing apparatus and suitable protective clothing should be worn in fire

conditions.

ACCIDENTAL RELEASE MEASURES

Caution - spillages may be slippery.

precautions for fire fighters

Methods and materials for containment and

cleaning up

STORAGE

Sweep up and shovel into waste drums or plastic bags. Wash the spillage area with water.

HANDLING AND STORAGE

HANDLING Product as supplied: Avoid contact with eyes. Avoid prolonged skin contact. Unlikely to

represent a dust hazard under normal handling conditions.

Process Hazards The product may be suitable for a wide range of industrial applications and therefore it is

impossible to make detailed recommendations regarding all process hazards. Thermal processing requires adequate ventilation to remove any monomer decomposition products, and use of inert atmosphere may be required in some processes to safely decompose the

resin when it is used as a binder. Any thermal processing must consider the time-

temperature decomposition of the resin. If the product is to be used in applications for which the hazards are not fully understood it is recommended to consult the supplier before use. Acrylic polymers are supplied in either bags or bulk containers. Keep containers in a clean,

cool and dry area away from heat sources. Natural ventilation is adequate.

Storage temperature (°C): Ambient. Incompatible materials: None known.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Substance	CAS No.	OSHA PEL	ACGIH	ACGIH	Company Std.	Company
		TWA	TWA	STEL	TWA	Std.
						STEL
Particulates (Total dust)		15 mg/m³	Not			
(Respirable dust)		5 mg/m³	established.			
The following values apply to substances						
which may be evolved during thermal						
processing.						
Methyl methacrylate	80-62-6	100 ppm	50 ppm	100 ppm	50 ppm	100 ppm
		410 mg/m ³	(205 mg/m ³)	(410 mg/m³)		
				(SEN;A4)		

Appropriate engineering controls Do not eat, drink or smoke at the work place. Provide adequate ventilation, including

> appropriate local extraction, to ensure that the occupational exposure limit is not exceeded. Consideration should be given to the work procedures involved and the potential extent of

exposure as they may determine whether a higher level of protection is required.

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection



Wear eye/face protection. Safety spectacles/goggles/full face shield.

Skin protection



Not normally required.

Respiratory protection



A suitable dust mask or dust respirator with filter type P may be appropriate. In the unlikely event of formation of particularly high levels of dust a self contained breathing apparatus may be appropriate.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Beads. Color. White

Odor Typically methacrylate.

pH (Value)

Boiling Point (°C)

Not available.

Not applicable.

Flash Point (°C) 300

Relative Evaporation Rate (Ether = 1) Not applicable. Not applicable. Flammable Limits Vapour pressure (Pascal) Not applicable. Not applicable. Vapor Density (Air=1) Specific Gravity 1.18 Solubility (Water) Negligible Solubility (Other) Not available. Partition Coefficient (n-Octanol/water) Not applicable. Viscosity (mPa. s) Not available. **Explosive Properties** Not applicable. Oxidizing Properties Not applicable.

10. STABILITY AND REACTIVITY

Reactivity Non-reactive material.

Chemical stability Stable under normal conditions.

Hazardous Reactions None known.

Conditions to avoid Keep away from heat.

Materials to avoid None known.

Hazardous decomposition product(s) Methyl methacrylate, Carbon dioxide, Carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Ingestion Low oral toxicity.

Inhalation Unlikely to be hazardous by inhalation.

Skin Contact Unlikely to cause skin irritation.

Contains greater than 0.1% residual (Methyl methacrylate). During normal handling this will not constitute a hazard. If the polymer matrix is destroyed e.g. when the product is dissolved in organic solvent, chemical residues will be released from the polymer matrix. Under these

conditions, they may produce an allergic reaction in persons already sensitised.

Eye Contact Dust may cause irritation

Repeated exposure toxicity

Chronic exposure This type of material has been in use for many years with no evidence of adverse effects.

CHEMICALS	IARC	NTP	OSHA	ACGIH
None				

12. ECOLOGICAL INFORMATION

Ecotoxicity The product is predicted to have low toxicity to aquatic organisms.

Persistence and degradability The product is non-biodegradable in soil. There is no evidence of degradation in soil and

water.

Bioaccumulative potential The product has low potential for bioaccumulation.

Mobility The product is predicted to have low mobility in soil.

13. DISPOSAL CONSIDERATIONS

The waste is considered to be non hazardous. Clean scrap may be reprocessed. Certain packages are returnable. Please consult your local office for further details. Ensure that all packaging is disposed of safely.

Disposal methods May be disposed of by landfill in accordance with local regulations. Incineration may be used

to recover energy value.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF Not Classified as Dangerous for Transport.

TRANSPORTATION)

UN No.
Proper Shipping Name
Not applicable.
Packing group
Not applicable.
Environmental hazards
Special precautions for user
Transport in bulk according to Annex II of
Not applicable.
Not applicable.
Not applicable.

MARPOL 73/78 and the IBC Code

15. REGULATORY INFORMATION

US Federal Regulations

SARA 302 - Extremely Hazardous Not applicable.

Substances

US State Regulations

California SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS

OR OTHER REPRODUCTIVE HARM None known.

SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER None

known.

Canadian Regulations

WHMIS Classification Not classified.

16. OTHER INFORMATION

The following sections contain revisions or

new statements:

4, 8, 10, 13, 14

Date of preparation: 16 -August- 2013

Inventory Status

European Union To the best of our knowledge all chemicals in this product comply with REACH regulations.

United States (TSCA)

Canada (DSL/NDSL)

Japan (ENCS)

Philippines (PICCS)

Australia (AICS)

South Korea (KECI)

China (IECSC)

Listed in TSCA

Listed in DSL

Listed in PICCS

Listed in PICCS

Listed in AICS

Listed in KECI

Listed in IECSC

Compliance with other Regulatory Chemical Inventories cannot be assumed, please contact supplier for further information.

LEGEND

Note: Not all of the following are necessarily contained in this Safety Data Sheet:

LTEL: Long Term Exposure Limit STEL: Short Term Exposure Limit TWA: Time Weighted Average PEL: Permissible Exposure Levels

OSHA: Occupational Safety and Health Administration SARA: Superfund Amendments and Reauthorisation Act WHMIS: Worker Hazardous Materials Information System

ELVACITE® is the Registered Trade Mark of companies within the Lucite International Limited Group of companies.

MEDICAL USE: CAUTION: DO NOT USE IN MEDICAL APPLICATIONS INVOLVING IMPLANTATION IN THE HUMAN BODY. Lucite International Inc. has performed no clinical testing on the use of this product in any medical application. Lucite International Inc. has no data to support the use of this product in any medical application. This product was not designed or manufactured for use in implantation in the human body or in contact with internal body fluids or tissues. Lucite International Inc. has neither sought, nor received, approval from any regulatory agency for the use of this product in implantation in the human body or in contact with internal body fluids or tissues.

It is the responsibility of the end-product manufacturer to identify all market and use-specific regulations and to ensure compliance with these regulations.

Subject to the exclusions and limitations set out below the Information contained in this publication or as otherwise supplied to the User is believed to be accurate and has been given in good faith. It is for the User to use the Information contained in this publication or as otherwise supplied to the User with care and satisfy itself of the suitability of the product for their intended use and the applicability of the advice given. Except to the extent that exclusion is prevented by applicable law Lucite International Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded and accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.