Ashland always solving ™	Page: 1
SAFETY DATA SHEET	Revision Date: 02/22/2018
	Print Date: 5/30/2018
	SDS Number: R0718450
PVP/VA™ I-335 pvp/va copolymer ™ Trademark, Ashland or its subsidiaries, registered in various countries 831297	Version: 1.2

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : $PVP/VA^{TM} I-335$

pvp/va copolymer

™ Trademark, Ashland or its subsidiaries, registered in

various countries

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Cosmetics

Details of the supplier of the safety data sheet Emergency telephone number 1-800-ASHLAND (1-800-274-5263)

Ashland P.O. Box 2219

Columbus, OH 43216

United States of America (USA)

+1-614-790-3333

Regulatory Information Number 1-800-325-3751

Product Information +1-614-790-3333

EHSProductSafety@ashland.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2

Eye irritation : Category 2A

Specific target organ systemic toxicity - single

exposure

: Category 3 (Central nervous system)

GHS label elements

Hazard pictograms





Signal Word : Danger

PAshland always solving	Page: 2
SAFETY DATA SHEET	Revision Date: 02/22/2018
	Print Date: 5/30/2018
	SDS Number: R0718450
PVP/VA™ I-335 pvp/va copolymer	Version: 1.2
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
831297	

Hazard Statements : Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Precautionary Statements : Prevention:

Keep away from heat/sparks/open flames/hot surfaces. No

smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/ eye protection/ face protection.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/ attention.

In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name CAS-No. Classification Concentration (76)	Chemical name	CAS-No.	Classification	Concentration (%)
---	---------------	---------	----------------	-------------------

P Ashland always solving	Page: 3
SAFETY DATA SHEET	Revision Date: 02/22/2018
	Print Date: 5/30/2018
	SDS Number: R0718450
PVP/VA™ I-335 pvp/va copolymer	Version: 1.2
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
831297	

ISOPROPANOL	67-63-0	Flam. Liq. 2; H225	51.999
		Eye Irrit. 2A; H319	
		STOT SE 3; H336	

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Call a POISON CENTRE or doctor/physician if exposed or

you feel unwell.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Move to fresh air.

If unconscious, place in recovery position and seek medical

advice.

Consult a physician after significant exposure.

In case of skin contact : If on skin, rinse well with water.

First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: Administration of high doses of isopropanol in combination with known hepatotoxic chemicals resulted in enhanced liver

toxicity in experimental animals.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through

the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

confusion

lung edema (fluid buildup in the lung tissue)

Causes serious eye irritation.

PAshland always solving ™	Page: 4
SAFETY DATA SHEET	Revision Date: 02/22/2018
	Print Date: 5/30/2018
	SDS Number: R0718450
PVP/VA™ I-335 pvp/va copolymer	Version: 1.2
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
831297	

May cause drowsiness or dizziness.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray

Foam

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Never use welding or cutting torch on or near drum (even

empty) because product (even just residue) can ignite

explosively.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Specific extinguishing

methods

Product is compatible with standard fire-fighting agents.

Further information Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, : Evacuate personnel to safe areas.

PAshland always solving ™	Page: 5
SAFETY DATA SHEET	Revision Date: 02/22/2018
	Print Date: 5/30/2018
	SDS Number: R0718450
PVP/VA™ I-335 pvp/va copolymer ™ Trademark, Ashland or its subsidiaries, registered in various countries	Version: 1.2
831297	

protective equipment and emergency procedures

Remove all sources of ignition. Ensure adequate ventilation.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

Other information

: Comply with all applicable federal, state, and local regulations. Suppress (knock down) gases/vapours/mists with a water

spray jet.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Open drum carefully as content may be under pressure.

Avoid formation of aerosol.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Container hazardous when empty.

Take precautionary measures against static discharges. Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

No smoking.

Electrical installations / working materials must comply with

Ashland always solving Solving	Page: 6
SAFETY DATA SHEET	Revision Date: 02/22/2018
	Print Date: 5/30/2018
	SDS Number: R0718450
PVP/VA™ I-335 pvp/va copolymer ™ Trademark, Ashland or its subsidiaries, registered in various countries 831297	Version: 1.2

the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
•		(Form of	parameters /	
		exposure)	Permissible	
			concentration	
ISOPROPANOL	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1
		TWA	400 ppm 980 mg/m3	OSHA P0
		STEL	500 ppm 1,225 mg/m3	OSHA P0
		PEL	400 ppm 980 mg/m3	CAL PEL
		STEL	500 ppm 1,225 mg/m3	CAL PEL

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentrati on	Basis
ISOPROPANOL	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ZUS_A CGIHB

Engineering measures : Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an

approved filter.

A NIOSH-approved air-purifying respirator with an appropriate

Ashland always solving ™	Page: 7
SAFETY DATA SHEET	Revision Date: 02/22/2018
	Print Date: 5/30/2018
	SDS Number: R0718450
PVP/VA™ I-335 pvp/va copolymer	Version: 1.2
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
831297	

cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by airpurifying respirators is limited. Use a positive pressure, airsupplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for

exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Wear as appropriate:

Impervious clothing

Safety shoes

Flame-resistant clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.

When using do not eat or drink. When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : light yellow

Odour : pleasant, alcohol-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 181.0 °F / 82.8 °C

Value for Component

Ashland always solving ™	Page: 8
SAFETY DATA SHEET	Revision Date: 02/22/2018
	Print Date: 5/30/2018
	SDS Number: R0718450
PVP/VA™ I-335 pvp/va copolymer	Version: 1.2
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
831297	

Flash point : 10 °C

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.945 - 0.965 g/cm3

Solubility(ies)

Water solubility : dispersible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : 1,000 cps

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

PAshland always solving ™	Page: 9
SAFETY DATA SHEET	Revision Date: 02/22/2018
	Print Date: 5/30/2018
	SDS Number: R0718450
PVP/VA™ I-335 pvp/va copolymer	Version: 1.2
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
831297	

Incompatible materials : Acids

Aldehydes alkalis Amines Ethylene oxide

halogenated hydrocarbons

halogens isocyanates

Strong oxidizing agents

Do not use with aluminum equipment at temperatures above

49C or 120 degrees F.

Hazardous decomposition

products carbon dioxide and carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

exposure Skin contact

Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Remarks: Based on similar product.

Components:

ISOPROPANOL:

Acute oral toxicity : LD50 (Rat): 5.84 g/kg

Acute inhalation toxicity : LC50 (Rat): > 10000 ppm

Exposure time: 4 h
Test atmosphere: vapour

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 12,800 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: Slight, transient irritation Remarks: Based on similar product.

Ashland always solving ™	Page: 10
SAFETY DATA SHEET	Revision Date: 02/22/2018
	Print Date: 5/30/2018
	SDS Number: R0718450
PVP/VA™ I-335 pvp/va copolymer	Version: 1.2
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
831297	

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation in susceptible persons.

Components:

ISOPROPANOL: Species: Rabbit

Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Result: Irritating to eyes.

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

ISOPROPANOL: Species: Rabbit

Result: Irritating to eyes.

Method: OECD Test Guideline 405

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Components: ISOPROPANOL:

Test Type: Buehler Test Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components: ISOPROPANOL:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Test species: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Carcinogenicity

Not classified based on available information.

PAshland always solving Solving	Page: 11
SAFETY DATA SHEET	Revision Date: 02/22/2018
	Print Date: 5/30/2018
	SDS Number: R0718450
PVP/VA™ I-335 pvp/va copolymer	Version: 1.2
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
831297	

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

ISOPROPANOL:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components:

ISOPROPANOL:

Remarks: Central nervous system

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 48 h

Remarks: Based on similar product.

Ecotoxicology Assessment

aquatic invertebrates

Acute aquatic toxicity : Not classified based on available information.

Ashland always solving ™	Page: 12
SAFETY DATA SHEET	Revision Date: 02/22/2018
	Print Date: 5/30/2018
	SDS Number: R0718450
PVP/VA™ I-335 pvp/va copolymer	Version: 1.2
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
831297	

Chronic aquatic toxicity : Not classified based on available information.

Components: ISOPROPANOL:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 10,000 mg/l

Exposure time: 96 h

Test Type: flow-through test

Toxicity to daphnia and other

aquatic invertebrates

: LC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 24 h Test Type: static test

Persistence and degradability

Product:

Biodegradability : Biodegradation: 27 %

Exposure time: 28 d

Remarks: Based on a similar product formulation.

Components:

No data available

Bioaccumulative potential

Components: ISOPROPANOL:

Partition coefficient: n-

octanol/water

: log Pow: 0.05

No data available **Mobility in soil Components:**

No data available

Other adverse effects

No data available

Product:

Additional ecological

: No data available

information

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

S Ashland always solving	Page: 13
SAFETY DATA SHEET	Revision Date: 02/22/2018
	Print Date: 5/30/2018
	SDS Number: R0718450
PVP/VA™ I-335 pvp/va copolymer ™ Trademark, Ashland or its subsidiaries, registered in various countries 831297	Version: 1.2

Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

_	_	\sim 1	 Α.	-1	$\hat{}$	
×	-		 Δ			N

REG	ULATION					
ID NU	JMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
U.S. I	DOT - RO	AD				
UN	1866	Resin solution	3		II	
CFR_R	AIL_C					
UN	1866	Resin solution	3		II	
U.S. DO	OT - INLAI	ND WATERWAYS				
UN	1866	Resin solution	3		II	
TDG_R	OAD_C					
UN	1866	RESIN SOLUTION	3		II	
TDG_R	AIL_C					
UN	1866	RESIN SOLUTION	3		II	

RESIN SOLUTION

TDG INWT C

1866

UN

ļ	NTERNA	TIONAL	MARITIME DANGER	OUS GOODS		
	UN	1866	RESIN SOLUTION	3	II	

Ш

3

Ashland always solving Solving	Page: 14
SAFETY DATA SHEET	Revision Date: 02/22/2018
	Print Date: 5/30/2018
	SDS Number: R0718450
PVP/VA™ I-335 pvp/va copolymer ™ Trademark, Ashland or its subsidiaries, registered in various countries 831297	Version: 1.2

NTERNATIONA	_ AIR	TRANSPORT	ASSOCIATION	- CARGO
--------------------	-------	-----------	--------------------	---------

UN	1866	Resin solution	3	II	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

UN	1866	Resin solution	3	II	

MX DG

UN	1866	RESINA, SOLUCIONES DE	3	II

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
VINYL ACETATE MONOMER	108-05-4	5000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
VINYL ACETATE MONOMER	108-05-4	5000	*
VINYL ACETATE MONOMER	108-05-4		*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 302 : This material does not contain any components with a section

302 EHS TPQ.

Ashland always solving ™	Page: 15
SAFETY DATA SHEET	Revision Date: 02/22/2018
	Print Date: 5/30/2018
	SDS Number: R0718450
PVP/VA™ I-335 pvp/va copolymer	Version: 1.2
™ Trademark, Ashland or its subsidiaries, registered	
in various countries	
831297	

SARA 313 The following components are subject to reporting levels

established by SARA Title III, Section 313:

ISOPROPANOL 67-63-0 51.99 %

Pennsylvania Right To Know

1-VINYL-2-PYRROLIDONE, - VINYL 25086-89-9

ACETATE POLYMER

ISOPROPANOL 67-63-0

New Jersey Right To Know

1-VINYL-2-PYRROLIDONE, - VINYL 25086-89-9

ACETATE POLYMER

ISOPROPANOL 67-63-0

California Prop 65 This product does not contain any chemicals known to State

of California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

NZIOC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

Inventories


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 02/22/2018

Ashland always solving	Page: 16
SAFETY DATA SHEET	Revision Date: 02/22/2018
	Print Date: 5/30/2018
	SDS Number: R0718450
PVP/VA™ I-335 pvp/va copolymer ™ Trademark, Ashland or its subsidiaries, registered in various countries 831297	Version: 1.2



NFPA Flammable and Combustible Liquids Classification

Flammable Liquid Class IB

Full text of H-Statements

H225 Highly flammable liquid and vapor.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Sources of key data used to compile the Safety Data Sheet
Ashland internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -

Ashland always solving	Page: 17
SAFETY DATA SHEET	Revision Date: 02/22/2018
	Print Date: 5/30/2018
	SDS Number: R0718450
PVP/VA™ I-335 pvp/va copolymer ™ Trademark, Ashland or its subsidiaries, registered in various countries 831297	Version: 1.2

Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL -Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS -Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA -National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD -Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS -Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative