



ERAPOL E93A

Chemwatch GHS Safety Data Sheet
Nov-30-2009
C614LP

Hazard Alert Code: MODERATE

CHEMWATCH 22-5949
Version No:2.0
Page 1 of 17

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

ERAPOL E93A

PRODUCT USE

■ Used according to manufacturer's directions.
Polyurethane prepolymer.

SUPPLIER

Company: Era Polymers Pty Ltd

Address:

25- 27 Green Street

Banksmeadow

NSW, 2019

Australia

Telephone: +61 2 9666 3788

Emergency Tel:1800 039 008 (AUS)


Emergency Tel: +61 3 9573 3112 ; +800 2436

2255(INTL)

Fax: +61 2 9666 4805

Section 2 - HAZARDS IDENTIFICATION

NFPA



GHS Classification

Acute Toxicity Category 4

Eye Irritation Category 2A

Respiratory Sensitizer Category 1

Skin Corrosion/Irritation Category 2

Skin Sensitizer Category 1

STOT - SE Category 3

continued...

ERAPOL E93A

Chemwatch GHS Safety Data Sheet

Nov-30-2009

C614LP

Hazard Alert Code: MODERATE

CHEMWATCH 22-5949

Version No:2.0

Page 2 of 17

Section 2 - HAZARDS IDENTIFICATION



EMERGENCY OVERVIEW

HAZARD

DANGER

Determined by Chemwatch using GHS criteria

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.

PRECAUTIONARY STATEMENTS

Prevention

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash ... thoroughly after handling.
P271	Use only outdoors or in a well- ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P285	In case of inadequate ventilation wear respiratory protection.

Response

P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P304+P341	IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P363	Wash contaminated clothing before reuse.

Storage

P403+P233	Store in a well- ventilated place. Keep container tightly closed.
P405	Store locked up.

Disposal

P501	Dispose of contents/container to ...
------	--------------------------------------

continued...

ERAPOL E93A

Chemwatch GHS Safety Data Sheet

Nov-30-2009

C614LP

Hazard Alert Code: MODERATE

CHEMWATCH 22-5949

Version No:2.0

Page 3 of 17

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
polyurethane prepolymer		>60
toluene- 2, 4- diisocyanate	584-84-9	<1

Section 4 - FIRST AID MEASURES

SWALLOWED

- If poisoning occurs, contact a doctor or Poisons Information Centre.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

- For sub-chronic and chronic exposures to isocyanates:
- This material may be a potent pulmonary sensitiser which causes bronchospasm even in patients without prior airway hyperreactivity.
- Clinical symptoms of exposure involve mucosal irritation of respiratory and gastrointestinal tracts.
- Conjunctival irritation, skin inflammation (erythema, pain vesiculation) and gastrointestinal disturbances occur soon after exposure.
- Pulmonary symptoms include cough, burning, substernal pain and dyspnoea.
- Some cross-sensitivity occurs between different isocyanates.
- Noncardiogenic pulmonary oedema and bronchospasm are the most serious consequences of exposure. Markedly

continued...

ERAPOL E93A

Chemwatch GHS Safety Data Sheet

Nov-30-2009

C614LP

Hazard Alert Code: MODERATE

CHEMWATCH 22-5949

Version No:2.0

Page 4 of 17

Section 4 - FIRST AID MEASURES

symptomatic patients should receive oxygen, ventilatory support and an intravenous line.

- Treatment for asthma includes inhaled sympathomimetics (epinephrine [adrenalin], terbutaline) and steroids.
- Activated charcoal (1 g/kg) and a cathartic (sorbitol, magnesium citrate) may be useful for ingestion.
- Mydriatics, systemic analgesics and topical antibiotics (Sulamyd) may be used for corneal abrasions.
- There is no effective therapy for sensitised workers. [Ellenhorn and Barceloux; Medical Toxicology]

NOTE: Isocyanates cause airway restriction in naive individuals with the degree of response dependant on the concentration and duration of exposure. They induce smooth muscle contraction which leads to bronchoconstrictive episodes. Acute changes in lung function, such as decreased FEV1, may not represent sensitivity.

[Karol & Jin, Frontiers in Molecular Toxicology, pp 56-61, 1992]

Personnel who work with isocyanates, isocyanate prepolymers or polyisocyanates should have a pre-placement medical examination and periodic examinations thereafter, including a pulmonary function test. Anyone with a medical history of chronic respiratory disease, asthmatic or bronchial attacks, indications of allergic responses, recurrent eczema or sensitisation conditions of the skin should not handle or work with isocyanates. Anyone who develops chronic respiratory distress when working with isocyanates should be removed from exposure and examined by a physician. Further exposure must be avoided if a sensitivity to isocyanates or polyisocyanates has developed.

Toluene diisocyanate is a known pulmonary sensitiser. Annual medical surveillance should be conducted including pulmonary history, examination of the heart and lungs, 14 x 17 inch (35 x 47 cm) x-ray and pulmonary function testing (FCV, FEV1).

In normal commercial preparations of toluene diisocyanate, the 2,4-isomer dominates in the ratio 4:1. However it is also hydrolysed, in air, more rapidly than the 2,6-isomer. Airway sensitivities may result from the appearance of immunoglobulins in the blood. Frequent inability to detect antibodies to TDI in clinical cases may result from the routine use of diagnostic antigens containing predominantly 2,4-TDI, whereas individuals may have been exposed to atmospheres in which 2,6-TDI was the predominant isomer. [Karol & Jin, Frontiers of Molecular Toxicology, pp 55-61, 1992].

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

FIRE/EXPLOSION HAZARD

- Combustible.
- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.

continued...

ERAPOL E93A

Chemwatch GHS Safety Data Sheet

Nov-30-2009

C614LP

Hazard Alert Code: MODERATE

CHEMWATCH 22-5949

Version No:2.0

Page 5 of 17

Section 5 - FIRE FIGHTING MEASURES

- Mists containing combustible materials may be explosive.

Combustion products include: carbon dioxide (CO₂), isocyanates, and minor amounts of, hydrogen cyanide, nitrogen oxides (NO_x), other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable, labelled container for waste disposal.

MAJOR SPILLS

- For isocyanate spills of less than 40 litres (2 m²):
- Evacuate area from everybody not dealing with the emergency, keep them upwind and prevent further access, remove ignition sources and, if inside building, ventilate area as well as possible.
- Notify supervision and others as necessary.
- Put on personal protective equipment (suitable respiratory protection, face and eye protection, protective suit, gloves and impermeable boots).
- Control source of leakage (where applicable).
- Dike the spill to prevent spreading and to contain additions of decontaminating solution.
- Prevent the material from entering drains.
- Estimate spill pool volume or area.
- Absorb and decontaminate. - Completely cover the spill with wet sand, wet earth, vermiculite or other similar absorbent. - Add neutraliser (for suitable formulations: see below) to the adsorbent materials (equal to that of estimated spill pool volume). Intensify contact between spill, absorbent and neutraliser by carefully mixing with a rake and allow to react for 15 minutes
- Shovel absorbent/decontaminant solution mixture into a steel drum.
- Decontaminate surface. - Pour an equal amount of neutraliser solution over contaminated surface. - Scrub area with a stiff bristle brush, using moderate pressure. - Completely cover decontaminant with vermiculite or other similar absorbent. - After 5 minutes, shovel absorbent/decontamination solution mixture into the same steel drum used above.
- Monitor for residual isocyanate. If surface is decontaminated, proceed to next step. If contamination persists, repeat decontaminate procedure immediately above
- Place loosely covered drum (release of carbon dioxide) outside for at least 72 hours. Label waste-containing drum appropriately. Remove waste materials for incineration.
- Decontaminate and remove personal protective equipment.
- Return to normal operation.
- Conduct accident investigation and consider measures to prevent reoccurrence.

Decontamination:

Treat isocyanate spills with sufficient amounts of isocyanate decontaminant preparation ("neutralising fluid"). Isocyanates and polyisocyanates are generally not miscible with water. Liquid surfactants are necessary to allow better dispersion of isocyanate and neutralising fluids/ preparations. Alkaline

continued...

ERAPOL E93A

Hazard Alert Code: MODERATE

Chemwatch GHS Safety Data Sheet

Nov-30-2009

C614LP

CHEMWATCH 22-5949

Version No:2.0

Page 6 of 17

Section 6 - ACCIDENTAL RELEASE MEASURES

neutralisers react faster than water/surfactant mixtures alone.

Typically, such a preparation may consist of:

Sawdust: 20 parts by weight Kieselguhr 40 parts by weight plus a mixture of {ammonia (s.g. 0.880) 8% v/v non-ionic surfactant 2% v/v water 90% v/v}.

Let stand for 24 hours

Three commonly used neutralising fluids each exhibit advantages in different situations.

Formulation A :

liquid surfactant	0.2-2%
sodium carbonate	5-10%
water to	100%

Formulation B

liquid surfactant	0.2-2%
concentrated ammonia	3-8%
water to	100%

Formulation C

ethanol, isopropanol or butanol	50%
concentrated ammonia	5%
water to	100%

After application of any of these formulae, let stand for 24 hours.

Formulation B reacts faster than Formulation A. However, ammonia-based neutralisers should be used only under well-ventilated conditions to avoid overexposure to ammonia or if members of the emergency team wear suitable respiratory protection. Formulation C is especially suitable for cleaning of equipment from unreacted isocyanate and neutralizing under freezing conditions. Regard has to be taken to the flammability of the alcoholic solution.

- Avoid contamination with water, alkalies and detergent solutions.
- Material reacts with water and generates gas, pressurises containers with even drum rupture resulting.
- DO NOT reseal container if contamination is suspected.
- Open all containers with care.

Moderate hazard.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

ACUTE EXPOSURE GUIDELINE LEVELS (AEGl) (in ppm)

toluene-

2, 4-

diisocyanate

te

AEGl Type	10 min	30 min	60 min	4 hr	8 hr
-----------	--------	--------	--------	------	------

continued...

ERAPOL E93A

Hazard Alert Code: MODERATE

Chemwatch GHS Safety Data Sheet

Nov-30-2009

C614LP

CHEMWATCH 22-5949

Version No:2.0

Page 7 of 17

Section 6 - ACCIDENTAL RELEASE MEASURES

1	0.020	0.020	0.020	0.010	CAS_CHECK~
2	0.24	0.17	0.083	0.021	CAS_CHECK~
3	0.65	0.65	0.51	0.32	CAS_CHECK~

AEGL 1: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience notable discomfort, irritation, or certain asymptomatic nonsensory effects. However, the effects are not disabling and are transient and reversible upon cessation of exposure.

AEGL 2: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience irreversible or other serious, long-lasting adverse health effects or an impaired ability to escape.

AEGL 3: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience life-threatening health effects or death.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- DO NOT allow clothing wet with material to stay in contact with skin.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

SUITABLE CONTAINER

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

- Segregate from alcohol, water.
- Avoid reaction with oxidising agents.
- NOTE: May develop pressure in containers; open carefully. Vent periodically.

STORAGE REQUIREMENTS

- for commercial quantities of isocyanates:

continued...

ERAPOL E93A

Chemwatch GHS Safety Data Sheet

Nov-30-2009

C614LP

Hazard Alert Code: MODERATE

CHEMWATCH 22-5949

Version No:2.0

Page 8 of 17

Section 7 - HANDLING AND STORAGE

- Isocyanates should be stored in adequately banded areas. Nothing else should be kept within the same banding. Pre-polymers need not be segregated. Drums of isocyanates should be stored under cover, out of direct sunlight, protected from rain, protected from physical damage and well away from moisture, acids and alkalis.
- Where isocyanates are stored at elevated temperatures to prevent solidifying, adequate controls should be installed to prevent the high temperatures and precautions against fire should be taken.
- Where stored in tanks, the more reactive isocyanates should be blanketed with a non-reactive gas such as nitrogen and equipped with absorptive type breather valve (to prevent vapour emissions)..
- Transfer systems for isocyanates in bulk storage should be fully enclosed and use pump or vacuum systems. Warning signs, in appropriate languages, should be posted where necessary.
- Areas in which polyurethane foam products are stored should be supplied with good general ventilation. Residual amounts of unreacted isocyanate may be present in the finished foam, resulting in hazardous atmospheric concentrations.
- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: May be stored together

O: May be stored together with specific preventions

X: Must not be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC	Notes
US ACGIH Threshold Limit Values (TLV)	(Toluene- 2, 4- or 2, 6-diisocyanate (or as a mixture))	0.005		0.02					TLV® Basis: (Resp sens) , See Notice of Intended Changes (NIC)

continued...

ERAPOL E93A

Hazard Alert Code: MODERATE

Chemwatch GHS Safety Data Sheet

Nov-30-2009

C614LP

CHEMWATCH 22-5949

Version No:2.0

Page 9 of 17

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

MATERIAL DATA

ERAPOL E93A:

Not available

TOLUENE-2,4-DIISOCYANATE:

■ for toluene diisocyanate:

NOTE: Detector tubes for toluene diisocyanate, measuring in excess of 0.02 ppm, are commercially available.

The odour recognition threshold, 0.05-0.4 ppm in air, is not reliable and being above exposure standard, gives no warning of exposure.

A substantial proportion of the working population (4.3% to 25%) can be sensitised to TDI at the ES-TWA. Such sensitisation was not limited to highly susceptible individuals and workers often developed symptoms early. Preplacement exams have been unsuccessful in identifying those who may develop sensitisation. Allergy, bronchial asthma and chronic bronchitis sufferers should be excluded from exposure to TDI. Chronic low level exposures below 0.02 ppm have been reported to cause sensitisation. Workers complained of cough, phlegm production, breathlessness and wheezing 2 to 17 years after the last exposure and it is reported that several workers developed chronic bronchitis 40 months after removal from exposure. Effects of TDI appear to be dose-related and there is a threshold (0.005 ppm) below which no respiratory effects are produced by at least the isomer 2,4-TDI. It should be noted that some polyurethane production facilities also emit amines which are the most important cause of respiratory symptoms and occupational asthma.

Odour Safety Factor(OSF)

OSF=0.029 ("2,4-TOLUENEDIISOCYANATE").

PERSONAL PROTECTION



EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

HANDS/FEET

- Wear chemical protective gloves, eg. PVC.
- Wear safety footwear or safety gumboots, eg. Rubber.

NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves

continued...

ERAPOL E93A

Hazard Alert Code: MODERATE

Chemwatch GHS Safety Data Sheet

Nov-30-2009

C614LP

CHEMWATCH 22-5949

Version No:2.0

Page 10 of 17

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

include:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly.

Application of a non-perfumed moisturiser is recommended.

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

RESPIRATOR

- Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area.

continued...

ERAPOL E93A

Chemwatch GHS Safety Data Sheet

Nov-30-2009

C614LP

Hazard Alert Code: MODERATE

CHEMWATCH 22-5949

Version No:2.0

Page 11 of 17

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Clear light amber viscous liquid; reacts with water.

PHYSICAL PROPERTIES

Liquid.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°F)	Not Available	Viscosity	Not Available
Boiling Range (°F)	>572	Solubility in water (g/L)	Reacts
Flash Point (°F)	>392	pH (1% solution)	Not Available
Decomposition Temp (°F)	Not Available	pH (as supplied)	Not Available
Autoignition Temp (°F)	Not Available	Vapour Pressure (mmHG)	Not Available
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	1.05
Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ The material is not thought to produce adverse health effects following ingestion (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum.

EYE

■ This material can cause eye irritation and damage in some persons.

SKIN

- This material can cause inflammation of the skin on contact in some persons.
- The material may accentuate any pre-existing dermatitis condition.
- Open cuts, abraded or irritated skin should not be exposed to this material.

INHALED

■ Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.

continued...

ERAPOL E93A

Hazard Alert Code: MODERATE

Chemwatch GHS Safety Data Sheet

Nov-30-2009

C614LP

CHEMWATCH 22-5949

Version No:2.0

Page 12 of 17

Section 11 - TOXICOLOGICAL INFORMATION

- Inhalation hazard is increased at higher temperatures.

CHRONIC HEALTH EFFECTS

- Inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.
- Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.
- With most allergens, removal of the offending material results in resolution of symptoms. Asthma caused by toluene diisocyanate (TDI) continues for months or even years after exposure ceases. This may be due to a non-allergenic condition called reactive airway dysfunction syndrome (RADS). Animal testing with mice has shown commercial grade TDI may cause a range of benign and malignant tumours.
- Sensitisation may result in allergic dermatitis responses including rash, itching, hives or swelling of extremities.
- Sensitisation may give severe responses to very low levels of exposure, i.e. hypersensitivity. Sensitised persons should not be allowed to work in situations where exposure may occur.

TOXICITY AND IRRITATION

ERAPOL E93A:

- Not available. Refer to individual constituents.

TOLUENE-2,4-DIISOCYANATE:

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Inhalation (human) TCLO: 20 ppb/2 yr
Inhalation (human) TCLO: 80 ppb
Inhalation (human) TCLO: 500 ppb
Oral (rat) LD50: 5800 mg/kg
Inhalation (rat) LC50: 14 ppm/14 hr
Inhalation (rat) LC50: 600 ppm/6 hr

IRRITATION

Skin (rabbit): 500 mg(open)- SEVERE
Skin (rabbit):500 mg/24hr- Moderate
Eye (rabbit): 100 mg - SEVERE

■ Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. Allergic reactions involving the respiratory tract are usually due to interactions between IgE antibodies and allergens and occur rapidly. Allergic potential of the allergen and period of exposure often determine the severity of symptoms. Some people may be genetically more prone than others, and exposure to other irritants may aggravate symptoms. Allergy causing activity is due to interactions with proteins.

continued...

ERAPOL E93A

Hazard Alert Code: MODERATE

Chemwatch GHS Safety Data Sheet

Nov-30-2009

C614LP

CHEMWATCH 22-5949

Version No:2.0

Page 13 of 17

Section 11 - TOXICOLOGICAL INFORMATION

Attention should be paid to atopic diathesis, characterised by increased susceptibility to nasal inflammation, asthma and eczema.

Exogenous allergic alveolitis is induced essentially by allergen specific immune-complexes of the IgG type; cell-mediated reactions (T lymphocytes) may be involved. Such allergy is of the delayed type with onset up to four hours following exposure.

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.

Aromatic and aliphatic diisocyanates may cause airway toxicity and skin sensitization. Monomers and prepolymers exhibit similar respiratory effect. Of the several members of diisocyanates tested on experimental animals by inhalation and oral exposure, some caused cancer while others produced a harmless outcome. This group of compounds has therefore been classified as cancer-causing.

Isocyanate vapours are irritating to the airways and can cause their inflammation, with wheezing, gasping, severe distress, even loss of consciousness and fluid in the lungs. Nervous system symptoms that may occur include headache, sleep disturbance, euphoria, inco-ordination, anxiety, depression and paranoia. Digestive effects include nausea and vomiting. Breathing difficulties may occur unpredictably after a period of tolerance and after skin contact. Allergic inflammation of the skin can occur, with rash, itching, blistering, and swelling of the hands and feet. Sensitive people can react to very low levels and should not be exposed to this material.

WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.

Tenth Annual Report on Carcinogens: Substance anticipated to be Carcinogen

[National Toxicology Program: U.S. Dep. of Health & Human Services 2002].

CARCINOGEN

Toluene diisocyanates	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	2B
Toluene- 2, 4- or 2, 6- diisocyanate (or as a mixture)	US ACGIH Threshold Limit Values (TLV) - Carcinogens	Carcinogen Category	A4
toluene- 2, 4- diisocyanate	US - Rhode Island Hazardous Substance List	IARC	
TOLUENE- 2, 4- DIISOCYANATE	US Environmental Defense Scorecard Recognized Carcinogens	Reference(s)	P65- MC
TOLUENE DIISOCYANATE (MIXED ISOMERS)	US Environmental Defense Scorecard Recognized Carcinogens	Reference(s)	P65
2, 4- Toluene diisocyanate	US Air Toxics Hot Spots TSD for Describing Available Cancer Potency Factors	IARC Class	2B
toluene- 2, 4- diisocyanate	US - Maine Chemicals of High Concern List	Carcinogen	CA Prop 65; NTP 11th ROC

continued...

ERAPOL E93A

Hazard Alert Code: MODERATE

Chemwatch GHS Safety Data Sheet

Nov-30-2009

C614LP

CHEMWATCH 22-5949

Version No:2.0

Page 14 of 17

Section 11 - TOXICOLOGICAL INFORMATION

toluene- 2, 4-diisocyanate	Canada - Prince Edward Island Occupational Exposure Limits - Carcinogens	Notes	TLV Basis: respiratory sensitization; asthma; eye irritation
TDI; 2, 4- TDI; 2, 4-Toluene diisocyanate	US NIOSH Recommended Exposure Limits (RELs) - Carcinogens	Notes	Ca See Appendix A

Section 12 - ECOLOGICAL INFORMATION

TOLUENE-2,4-DIISOCYANATE:

! Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

For Isocyanate Monomers:

Environmental Fate: Isocyanates, (di- and polyfunctional isocyanates), are commonly used to make various polymers, such as polyurethanes. Polyurethanes find significant application in the manufacture of rigid and flexible foams. They are also used in the production of adhesives, elastomers, and coatings.

Atmospheric Fate: These substances are not expected to be removed from the air via precipitation washout or dry deposition.

Terrestrial Fate: These substances are expected to sorb strongly to soil. Migration to groundwater and surface waters is not expected to occur.

Aquatic Fate: Breakdown by water, (hydrolysis), is the primary fate mechanism for the majority of commercial isocyanate monomers, however; the low solubility of these substances will generally lessen the effectiveness of hydrolysis as a fate pathway. But hydrolysis should be considered one of the two major fate processes for the isocyanates. These substances strongly sorb to suspended particulates in water. In the absence of hydrolysis, sorption to solids, (e.g., sludge and sediments), will be the primary mechanism of removal.

Biological breakdown is minimal for most compounds and evaporation is negligible. Evaporation from surface water is expected to take years. In wastewater treatment this process is not expected to be significant.

Isocyanates will react with water producing carbon dioxide and forming a solid mass, which is insoluble.

Biodegradation: Breakdown of these substances in oxygenated and low oxygen environments is not expected to occur. Most of the substances take several months to degrade. Degradation of the hydrolysis products will occur at varying rates.

Ecotoxicity: These substances are not expected to accumulate/biomagnify in the environment. These substances are toxic if inhaled. These substances are harmful to aquatic organisms and may cause long-term adverse effects in the aquatic environment.

DO NOT discharge into sewer or waterways.

Half-life (hr) air: 3.3

Toxicity Fish: LC50(96)0.0045-57.68mg/L

Toxicity invertebrate: cell mult. inhib.26-456mg/L

Bioaccumulation: low-moderate

Nitrif. inhib.: inhib at 350mg/L

Effects on algae and plankton: cell mult. inhib. algae 105->400mg/L

Degradation Biological: sig

processes Abiotic: nophotol&hydrol,sig oxid,RxnOH*

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
------------	----------------------------	------------------	-----------------	----------

continued...

ERAPOL E93A

Chemwatch GHS Safety Data Sheet

Nov-30-2009

C614LP

Hazard Alert Code: MODERATE

CHEMWATCH 22-5949

Version No:2.0

Page 15 of 17

Section 12 - ECOLOGICAL INFORMATION

toluene- 2, 4- diisocyanate	HIGH	No Data Available	LOW	MED
-----------------------------	------	----------------------	-----	-----

Section 13 - DISPOSAL CONSIDERATIONS

■ Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- DO NOT recycle spilled material.
- Consult State Land Waste Management Authority for disposal.
- Neutralise spill material carefully and decontaminate empty containers and spill residues with 10% ammonia solution plus detergent or a proprietary decontaminant prior to disposal.
- DO NOT seal or stopper drums being decontaminated as CO₂ gas is generated and may pressurise containers.
- Puncture containers to prevent re-use.
- Bury or incinerate residues at an approved site.

Section 14 - TRANSPORTATION INFORMATION

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: DOT, IATA, IMDG

Section 15 - REGULATORY INFORMATION

REGULATIONS

Regulations for ingredients

toluene-2,4-diisocyanate (CAS: 584-84-9) is found on the following regulatory lists;

"Canada - Alberta Occupational Exposure Limits", "Canada - Alberta Substances and processes requiring a code of practice", "Canada - British Columbia Occupational Exposure Limits", "Canada - Northwest Territories Occupational Exposure Limits (English)", "Canada - Nova Scotia Occupational Exposure Limits", "Canada - Ontario Occupational Exposure Limits", "Canada - Prince Edward Island Occupational Exposure Limits", "Canada - Prince Edward Island Occupational Exposure Limits - Carcinogens", "Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)", "Canada - Saskatchewan Industrial Hazardous Substances", "Canada -

continued...

ERAPOL E93A

Hazard Alert Code: MODERATE

Chemwatch GHS Safety Data Sheet

Nov-30-2009

C614LP

CHEMWATCH 22-5949

Version No:2.0

Page 16 of 17

Section 15 - REGULATORY INFORMATION

Saskatchewan Occupational Health and Safety Regulations - Contamination Limits", "Canada - Saskatchewan Occupational Health and Safety Regulations - Designated Chemical Substances", "Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances", "Canada ARET (Accelerated Reduction / Elimination of Toxics) Substance List", "Canada CEPA Environmental Registry Substance Lists - List of substances on the DSL that meet the human health criteria for categorization (English)", "Canada CEPA Environmental Registry Substance Lists - Other DSL substances that are priorities for human health (English)", "Canada Domestic Substances List (DSL)", "Canada Ingredient Disclosure List (SOR/88-64)", "Canada List of Prohibited and Restricted Cosmetic Ingredients (The Cosmetic Ingredient ""Hotlist""", "Canada National Pollutant Release Inventory (NPRI)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (English)", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD List of High Production Volume (HPV) Chemicals", "US - Alaska Limits for Air Contaminants", "US - California Air Toxics ""Hot Spots"" List (Assembly Bill 2588) Substances for Which Emissions Must Be Quantified", "US - California Occupational Safety and Health Regulations (CAL/OSHA) - Hazardous Substances List", "US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)", "US - California Permissible Exposure Limits for Chemical Contaminants", "US - California Proposition 65 - Carcinogens", "US - California Proposition 65 - No Significant Risk Levels (NSRLs) for Carcinogens", "US - California Toxic Air Contaminant List Category II", "US - Connecticut Hazardous Air Pollutants", "US - Delaware Pollutant Discharge Requirements - Reportable Quantities", "US - Hawaii Air Contaminant Limits", "US - Idaho - Limits for Air Contaminants", "US - Louisiana Minimum Emission Rates Toxic Air Pollutants", "US - Louisiana Toxic Air Pollutant Ambient Air Standards", "US - Maine Chemicals of High Concern List", "US - Massachusetts Oil & Hazardous Material List", "US - Michigan Exposure Limits for Air Contaminants", "US - Minnesota Hazardous Substance List", "US - New Jersey Right to Know Hazardous Substances (English)", "US - North Dakota Air Pollutants - Guideline Concentrations", "US - North Dakota Air Pollutants - Unit Risk Factors", "US - Oregon Permissible Exposure Limits (Z-1)", "US - Oregon Permissible Exposure Limits (Z-2)", "US - Pennsylvania - Hazardous Substance List", "US - Rhode Island Hazardous Substance List", "US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants", "US - Vermont Hazardous Constituents", "US - Vermont Hazardous wastes which are Discarded Commercial Chemical Products or Off-Specification Batches of Commercial Chemical Products or Spill Residues of Either", "US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants", "US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants", "US - Washington Dangerous waste constituents list", "US - Washington Discarded Chemical Products List - ""U"" Chemical Products", "US - Washington Permissible exposure limits of air contaminants", "US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values", "US - Wisconsin Control of Hazardous Pollutants - Emission Thresholds, Standards and Control Requirements (Hazardous Air Contaminants)", "US - Wisconsin Control of Hazardous Pollutants - Substances of Concern for Sources of Incidental Emissions of Hazardous Air Contaminants", "US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants", "US ACGIH Threshold Limit Values (TLV)", "US ACGIH Threshold Limit Values (TLV) - Carcinogens", "US ACGIH Threshold Limit Values (TLV) - Notice of Intended Changes", "US CAA (Clean Air Act) - HON Rule - Organic HAPs (Hazardous Air Pollutants)", "US Clean Air Act - Hazardous Air Pollutants", "US Department of Transportation (DOT) List of Hazardous Substances and Reportable Quantities - Hazardous Substances Other Than Radionuclides", "US DOE Temporary Emergency Exposure Limits (TEELs)", "US EPA Acute Exposure Guideline Levels (AEGs) - Final", "US EPA High Production Volume Program Chemical List", "US EPCRA Section 313 Chemical List", "US FDA Indirect Food Additives: Adhesives and Components of Coatings - Substances for Use Only as Components of Adhesives - Adhesives", "US FDA List of ""Indirect"" Additives Used in Food Contact Substances", "US List of Lists - Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112(r) of the Clean Air Act", "US National Toxicology Program (NTP) 12th Report Part A Known to be Human Carcinogens", "US National Toxicology Program (NTP) 12th Report Part B. Reasonably Anticipated to be a Human Carcinogen", "US NIOSH Recommended Exposure Limits (RELs)", "US OSHA Permissible Exposure Levels (PELs) - Table Z1", "US RCRA (Resource Conservation & Recovery Act) - Hazardous Constituents - Appendix VIII to 40 CFR 261", "US RCRA (Resource Conservation & Recovery Act) - List of Hazardous Wastes", "US SARA Section 302 Extremely Hazardous Substances", "US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory", "US TSCA Section 8 (d) - Health and Safety Data Reporting", "USA: Chemical Facility Anti-Terrorism Standards - List Appendix A - 6CFR 27"

continued...

ERAPOL E93A

Chemwatch GHS Safety Data Sheet

Nov-30-2009

C614LP

Hazard Alert Code: MODERATE

CHEMWATCH 22-5949

Version No:2.0

Page 17 of 17

Section 15 - REGULATORY INFORMATION

No data for ERAPOL E93A (CW: 22-5949)

Section 16 - OTHER INFORMATION

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

■ For detailed advice on Personal Protective Equipment, refer to the following U.S. Regulations and Standards:

OSHA Standards - 29 CFR:

1910.132 - Personal Protective Equipment - General requirements

1910.133 - Eye and face protection

1910.134 - Respiratory Protection

1910.136 - Occupational foot protection

1910.138 - Hand Protection

Eye and face protection - ANSI Z87.1

Foot protection - ANSI Z41

Respirators must be NIOSH approved.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Nov-30-2009

Print Date: Mar-8-2012