



ERAPOL EMP83A

Erapol EMP95A
For Domestic Use Only.
Mar-23-2011
NC614TDP

Hazard Alert Code: MODERATE

CHEMWATCH 24-3814
Version No:2.0
CD 2011/2 Page 1 of 18

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME
ERAPOL EMP83A

PRODUCT USE

■ Used according to manufacturer's directions.
Polyurethane prepolymer.

SUPPLIER

Company: Era Polymers Pty Ltd
Address:
25- 27 Green Street
Banksmeadow
NSW, 2019
Australia
Telephone: +61 2 9666 3788
Emergency Tel: **1800 039 008 (AUS)**
Emergency Tel: **+61 3 9573 3112; +800 243 62255**
Fax: +61 2 9666 4805
Website: www.erapol.com.au

Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Acute Toxicity Category 4
Eye Irritation Category 2A
Respiratory Sensitizer Category 1
Skin Corrosion/Irritation Category 2
Skin Sensitizer Category 1
STOT - SE Category 3



continued...

ERAPOL EMP83A

Hazard Alert Code: MODERATE

Erapol EMP95A
For Domestic Use Only.
Mar-23-2011
NC614TDP

CHEMWATCH 24-3814

Version No:2.0

CD 2011/2 Page 2 of 18

Section 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HAZARD

DANGER

Determined by Chemwatch using GHS criteria

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.

PRECAUTIONARY STATEMENTS

Prevention

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash ... thoroughly after handling.
P271	Use only outdoors or in a well- ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P285	In case of inadequate ventilation wear respiratory protection.

Response

P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P304+P341	IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P363	Wash contaminated clothing before reuse.

Storage

P403+P233	Store in a well- ventilated place. Keep container tightly closed.
P405	Store locked up.

Disposal

P501	Dispose of contents/container to ...
------	--------------------------------------

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
polyurethane prepolymer		>60
toluene diisocyanate	26471-62-5	1-10

continued...

ERAPOL EMP83A

Hazard Alert Code: MODERATE

Erapol EMP95A
For Domestic Use Only.
Mar-23-2011
NC614TDP

CHEMWATCH 24-3814
Version No:2.0
CD 2011/2 Page 3 of 18

Section 4 - FIRST AID MEASURES

SWALLOWED

- If poisoning occurs, contact a doctor or Poisons Information Centre.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

- For sub-chronic and chronic exposures to isocyanates:
- This material may be a potent pulmonary sensitiser which causes bronchospasm even in patients without prior airway hyperreactivity.
- Clinical symptoms of exposure involve mucosal irritation of respiratory and gastrointestinal tracts.
- Conjunctival irritation, skin inflammation (erythema, pain vesication) and gastrointestinal disturbances occur soon after exposure.
- Pulmonary symptoms include cough, burning, substernal pain and dyspnoea.
- Some cross-sensitivity occurs between different isocyanates.
- Noncardiogenic pulmonary oedema and bronchospasm are the most serious consequences of exposure. Markedly symptomatic patients should receive oxygen, ventilatory support and an intravenous line.
- Treatment for asthma includes inhaled sympathomimetics (epinephrine [adrenalin], terbutaline) and steroids.
- Activated charcoal (1 g/kg) and a cathartic (sorbitol, magnesium citrate) may be useful for ingestion.
- Mydriatics, systemic analgesics and topical antibiotics (Sulamyd) may be used for corneal abrasions.
- There is no effective therapy for sensitised workers. [Ellenhorn and Barceloux; Medical Toxicology]

NOTE: Isocyanates cause airway restriction in naive individuals with the degree of response dependant on the

continued...

ERAPOL EMP83A

Hazard Alert Code: MODERATE

Erapol EMP95A

For Domestic Use Only.

Mar-23-2011

NC614TDP

CHEMWATCH 24-3814

Version No:2.0

CD 2011/2 Page 4 of 18

Section 4 - FIRST AID MEASURES

concentration and duration of exposure. They induce smooth muscle contraction which leads to bronchoconstrictive episodes. Acute changes in lung function, such as decreased FEV1, may not represent sensitivity.

[Karol & Jin, Frontiers in Molecular Toxicology, pp 56-61, 1992]

Personnel who work with isocyanates, isocyanate prepolymers or polyisocyanates should have a pre-placement medical examination and periodic examinations thereafter, including a pulmonary function test. Anyone with a medical history of chronic respiratory disease, asthmatic or bronchial attacks, indications of allergic responses, recurrent eczema or sensitisation conditions of the skin should not handle or work with isocyanates. Anyone who develops chronic respiratory distress when working with isocyanates should be removed from exposure and examined by a physician. Further exposure must be avoided if a sensitivity to isocyanates or polyisocyanates has developed.

Toluene diisocyanate is a known pulmonary sensitiser. Annual medical surveillance should be conducted including pulmonary history, examination of the heart and lungs, 14 x 17 inch (35 x 47 cm) x-ray and pulmonary function testing (FCV, FEV1).

In normal commercial preparations of toluene diisocyanate, the 2,4-isomer dominates in the ratio 4:1. However it is also hydrolysed, in air, more rapidly than the 2,6-isomer. Airway sensitivities may result from the appearance of immunoglobulins in the blood. Frequent inability to detect antibodies to TDI in clinical cases may result from the routine use of diagnostic antigens containing predominantly 2,4-TDI, whereas individuals may have been exposed to atmospheres in which 2,6-TDI was the predominant isomer. [Karol & Jin, Frontiers of Molecular Toxicology, pp 55-61, 1992].

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE/EXPLOSION HAZARD

- Combustible.
- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.
- Mists containing combustible materials may be explosive.

Combustion products include: carbon dioxide (CO₂), isocyanates, and minor amounts of, hydrogen cyanide, nitrogen oxides (NO_x), other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

Personal Protective Equipment

Breathing apparatus.

Gas tight chemical resistant suit.

Limit exposure duration to 1 BA set 30 mins.

continued...

ERAPOL EMP83A

Hazard Alert Code: MODERATE

Erapol EMP95A
For Domestic Use Only.
Mar-23-2011
NC614TDP

CHEMWATCH 24-3814
Version No:2.0
CD 2011/2 Page 5 of 18

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable, labelled container for waste disposal.

ACUTE EXPOSURE GUIDELINE LEVELS (AEGL) (in ppm)

toluene

diisocyanate

AEGL Type	10 min	30 min	60 min	4 hr	8 hr
1	0.020	0.020	0.020	0.010	CAS_CHECK~
2	0.24	0.17	0.083	0.021	CAS_CHECK~
3	0.65	0.65	0.51	0.32	CAS_CHECK~
1	0.020	0.020	0.020	0.010	CAS_CHECK~
2	0.24	0.17	0.083	0.021	CAS_CHECK~
3	0.65	0.65	0.51	0.32	CAS_CHECK~

AEGL 1: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience notable discomfort, irritation, or certain asymptomatic nonsensory effects. However, the effects are not disabling and are transient and reversible upon cessation of exposure.

AEGL 2: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience irreversible or other serious, long-lasting adverse health effects or an impaired ability to escape.

AEGL 3: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience life-threatening health effects or death.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

toluene diisocyanate 0.6ppm

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

toluene diisocyanate 0.15ppm

other than mild, transient adverse effects without perceiving a clearly defined odour is:

toluene diisocyanate 0.01ppm

continued...

ERAPOL EMP83A

Hazard Alert Code: MODERATE

Erapol EMP95A
For Domestic Use Only.
Mar-23-2011
NC614TDP

CHEMWATCH 24-3814

Version No:2.0

CD 2011/2 Page 6 of 18

Section 6 - ACCIDENTAL RELEASE MEASURES

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	$\geq 0.1\%$	Toxic (T)	$\geq 3.0\%$
R50	$\geq 0.25\%$	Corrosive (C)	$\geq 5.0\%$
R51	$\geq 2.5\%$		
else	$\geq 10\%$		

where percentage is percentage of ingredient found in the mixture

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- DO NOT allow clothing wet with material to stay in contact with skin.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

SUITABLE CONTAINER

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE REQUIREMENTS

- for commercial quantities of isocyanates:
 - Isocyanates should be stored in adequately bunded areas. Nothing else should be kept within the same bunding. Pre-polymers need not be segregated. Drums of isocyanates should be stored under cover, out of direct sunlight, protected from rain, protected from physical damage and well away from moisture, acids and alkalis.
 - Where isocyanates are stored at elevated temperatures to prevent solidifying, adequate controls should be installed to prevent the high temperatures and precautions against fire should be taken.
 - Where stored in tanks, the more reactive isocyanates should be blanketed with a non-reactive gas such as nitrogen and equipped with absorptive type breather valve (to prevent vapour emissions)..
 - Transfer systems for isocyanates in bulk storage should be fully enclosed and use pump or vacuum systems. Warning signs, in appropriate languages, should be posted where necessary.
 - Areas in which polyurethane foam products are stored should be supplied with good general ventilation. Residual amounts of unreacted isocyanate may be present in the finished foam, resulting in hazardous

continued...

ERAPOL EMP83A

Hazard Alert Code: MODERATE

Erapol EMP95A
For Domestic Use Only.
Mar-23-2011
NC614TDP

CHEMWATCH 24-3814
Version No:2.0
CD 2011/2 Page 7 of 18
Section 7 - HANDLING AND STORAGE

- atmospheric concentrations.
- Store in original containers.
 - Keep containers securely sealed.
 - No smoking, naked lights or ignition sources.
 - Store in a cool, dry, well-ventilated area.
 - Store away from incompatible materials and foodstuff containers.
 - Protect containers against physical damage and check regularly for leaks.
 - Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



- +: May be stored together
O: May be stored together with specific precautions
X: Must not be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m³	STEL ppm	STEL mg/m³	Peak ppm	Peak mg/m³	TWA F/CC	Notes
Canada - Nova Scotia Occupational Exposure Limits	toluene diisocyanate (Toluene diisocyanate - Mixed isomers)	0.005		0.02					TLV Basis: respiratory sensitization; asthma; eye irritation
Canada - Alberta Occupational Exposure Limits	toluene diisocyanate (Toluene- 2, 4 or 2, 6diisocyanate (or as mixture) (TDI))	0.005	0.04			0.02	0.1		
Canada - British Columbia Occupational Exposure Limits	toluene diisocyanate (Toluene- 2, 4-diisocyanate (2, 4- TDI))	0.005				0.01			2B; S

continued...

ERAPOL EMP83A

Hazard Alert Code: MODERATE

Erapol EMP95A
For Domestic Use Only.
Mar-23-2011
NC614TDP

CHEMWATCH 24-3814
Version No:2.0
CD 2011/2 Page 8 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC	Notes
US ACGIH Threshold Limit Values (TLV)	toluene diisocyanate (Toluene- 2, 4- diisocyanate [2, 4- TDI])	0.005		0.02					TLV Basis: respira tory sensiti zation; asthma; eye irritat ion
US - Vermont Permissible Exposure Limits Table Z- 1- A Transitional Limits for Air Contaminants	toluene diisocyanate (Toluene- 2, 4- diisocyanate (TDI))	(C)0.02	(C)0.14						
US - Vermont Permissible Exposure Limits Table Z- 1- A Final Rule Limits for Air Contaminants	toluene diisocyanate (Toluene- 2, 4- diisocyanate (TDI))	0.005	0.04	0.02	0.15				
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	toluene diisocyanate (Toluene- 2, 4- diisocyanate (TDI))	0.005	0.04	0.02	0.15				
US - California Permissible Exposure Limits for Chemical Contaminants	toluene diisocyanate (Toluene- 2, 4- diisocyanate; TDI)	0.005	0.04	0.02	0.15	0.02			
US - Idaho - Limits for Air Contaminants	toluene diisocyanate (Toluene- 2, 4- diisocyanate (TDI))					0.02	0.14		
US - Hawaii Air Contaminant Limits	toluene diisocyanate (Toluene di- isocyanate (TDI))	0.005	0.04	0.02	0.15				
US - Alaska Limits for Air Contaminants	toluene diisocyanate (Toluene- 2, 4- diisocyanate (TDI))	0.005	0.04	0.02	0.15				

continued...

ERAPOL EMP83A

Hazard Alert Code: MODERATE

Erapol EMP95A
For Domestic Use Only.
Mar-23-2011
NC614TDP

CHEMWATCH 24-3814
Version No:2.0
CD 2011/2 Page 9 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m³	STEL ppm	STEL mg/m³	Peak ppm	Peak mg/m³	TWA F/CC	Notes
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	toluene diisocyanate (Toluene- 2, 4- or 2, 6- diisocyanate (TDI))	0.005		0.02					SEN
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	toluene diisocyanate (Toluene- 2, 4- diisocyanate (TDI))	0.02	0.14	-	-				
US - Washington Permissible exposure limits of air contaminants	toluene diisocyanate (TDI (Toluene- 2, 4- diisocyanate))	0.005		0.02					
US - Michigan Exposure Limits for Air Contaminants	toluene diisocyanate (Toluene- 2, 4- diisocyanate(TDI))	0.005	0.04	0.02	0.15				
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	toluene diisocyanate (Toluene- 2, 4- diisocyanate (TDI))					0.02	0.14		
US OSHA Permissible Exposure Levels (PELs) - Table Z1	toluene diisocyanate (Toluene- 2, 4- diisocyanate (TDI))					0.02	0.14		
Canada - Prince Edward Island Occupational Exposure Limits	toluene diisocyanate (Toluene- 2, 4- diisocyanate [2, 4- TDI])	0.005		0.02					TLV Basis: respiratory sensitization; asthma; eye irritation

continued...

ERAPOL EMP83A

Hazard Alert Code: MODERATE

Erapol EMP95A
For Domestic Use Only.
Mar-23-2011
NC614TDP

CHEMWATCH 24-3814

Version No:2.0

CD 2011/2 Page 10 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC	Notes
Canada - Northwest Territories Occupational Exposure Limits (English)	toluene diisocyanate (Toluene- 2, 4-diisocyanate)					0.02	0.14		
Canada - Alberta Occupational Exposure Limits	toluene diisocyanate (Toluene- 2, 4 or 2, 6diisocyanate (or as mixture) (TDI))	0.005				0.02	0.1		
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	toluene diisocyanate (Toluene diisocyanate (TDI) (isomers mixture))	0.005	0.036	0.02	0.14				
Canada - Ontario Occupational Exposure Limits	toluene diisocyanate (Toluene diisocyanate (TDI) / Diisocyanate de toluène (TDI))	0.005				0.02			
US - Oregon Permissible Exposure Limits (Z- 2)	toluene diisocyanate (Toluene diisocyanate (TDI))	0.005	0.035			0.140	0.02		

MATERIAL DATA

ERAPOL EMP83A:
Not available

TOLUENE DIISOCYANATE:

■ for toluene diisocyanate:

NOTE: Detector tubes for toluene diisocyanate, measuring in excess of 0.02 ppm, are commercially available.

The odour recognition threshold, 0.05-0.4 ppm in air, is not reliable and being above exposure standard, gives no warning of exposure.

A substantial proportion of the working population (4.3% to 25%) can be sensitised to TDI at the ES-TWA. Such sensitisation was not limited to highly susceptible individuals and workers often developed symptoms early. Preplacement exams have been unsuccessful in identifying those who may develop sensitisation. Allergy, bronchial asthma and chronic bronchitis sufferers should be excluded from exposure to TDI. Chronic low level exposures below 0.02 ppm have been reported to cause sensitisation. Workers complained of cough, phlegm production, breathlessness and wheezing 2 to 17 years after the last exposure and it is reported that several workers developed chronic bronchitis 40 months after removal from exposure. Effects of TDI appear to be dose-related and there is a threshold (0.005 ppm) below which no respiratory effects are produced by at least the isomer 2,4-TDI. It should be noted that some polyurethane production facilities also emit amines which are

continued...

ERAPOL EMP83A

Hazard Alert Code: MODERATE

Erapol EMP95A
For Domestic Use Only.
Mar-23-2011
NC614TDP

CHEMWATCH 24-3814

Version No:2.0

CD 2011/2 Page 11 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

the most important cause of respiratory symptoms and occupational asthma.

Odour Safety Factor(OSF)

OSF=0.029 ("2,4-TOLUENEDIISOCYANATE").

PERSONAL PROTECTION



EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

HANDS/FEET

- Wear chemical protective gloves, eg. PVC.
- Wear safety footwear or safety gumboots, eg. Rubber.

NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
 - Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.
- Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

continued...

ERAPOL EMP83A

Hazard Alert Code: MODERATE

Erapol EMP95A
For Domestic Use Only.
Mar-23-2011
NC614TDP

CHEMWATCH 24-3814

Version No:2.0

CD 2011/2 Page 12 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

RESPIRATOR

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:

solvent, vapours, degreasing etc., evaporating from tank (in still air).

aerosols, fumes from pouring operations,

intermittent container filling, low speed

conveyer transfers, welding, spray drift,

plating acid fumes, pickling (released at low velocity into zone of active generation)

direct spray, spray painting in shallow booths,

drum filling, conveyer loading, crusher dusts,

gas discharge (active generation into zone of rapid air motion)

grinding, abrasive blasting, tumbling, high

speed wheel generated dusts (released at high

initial velocity into zone of very high rapid

air motion).

Air Speed:

0.25- 0.5 m/s (50- 100 f/min.)

0.5- 1 m/s (100- 200 f/min.)

1- 2.5 m/s (200- 500 f/min.)

2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

continued...

ERAPOL EMP83A

Hazard Alert Code: MODERATE

Erapol EMP95A
For Domestic Use Only.
Mar-23-2011
NC614TDP

CHEMWATCH 24-3814
Version No:2.0
CD 2011/2 Page 13 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Clear light amber liquid; reacts with water liberating carbon dioxide.

PHYSICAL PROPERTIES

Liquid.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°F)	Not Available	Viscosity	Not Available
Boiling Range (°F)	>572	Solubility in water (g/L)	Reacts
Flash Point (°F)	>392	pH (1% solution)	Not Available
Decomposition Temp (°F)	Not Available	pH (as supplied)	Not Available
Autoignition Temp (°F)	Not Available	Vapour Pressure (mmHG)	Not Available
Upper Explosive Limit (%)	Not Applicable	Specific Gravity (water=1)	1.02 @ 25C
Lower Explosive Limit (%)	Not Applicable	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

continued...

ERAPOL EMP83A

Erapol EMP95A
For Domestic Use Only.
Mar-23-2011
NC614TDP

Hazard Alert Code: MODERATE

CHEMWATCH 24-3814
Version No:2.0
CD 2011/2 Page 14 of 18

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ The material is not thought to produce adverse health effects following ingestion (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum.

EYE

■ This material can cause eye irritation and damage in some persons.

SKIN

- This material can cause inflammation of the skin on contact in some persons.
- The material may accentuate any pre-existing dermatitis condition.
- Open cuts, abraded or irritated skin should not be exposed to this material.

INHALED

- If inhaled, this material can irritate the throat and lungs of some persons.
- Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.

CHRONIC HEALTH EFFECTS

■ Inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.
Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.
With most allergens, removal of the offending material results in resolution of symptoms. Asthma caused by toluene diisocyanate (TDI) continues for months or even years after exposure ceases. This may be due to a non-allergenic condition called reactive airway dysfunction syndrome (RADS). Animal testing with mice has shown commercial grade TDI may cause a range of benign and malignant tumours.
Sensitisation may result in allergic dermatitis responses including rash, itching, hives or swelling of extremities.
Sensitisation reactions may appear suddenly after repeated symptom free exposures.
Sensitisation may give severe responses to very low levels of exposure, i.e. hypersensitivity. Sensitised persons should not be allowed to work in situations where exposure may occur.

TOXICITY AND IRRITATION

ERAPOL EMP83A:

- Not available. Refer to individual constituents.

TOLUENE DIISOCYANATE:

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.
- Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger

continued...

ERAPOL EMP83A

Hazard Alert Code: MODERATE

Erapol EMP95A
For Domestic Use Only.
Mar-23-2011
NC614TDP

CHEMWATCH 24-3814

Version No:2.0

CD 2011/2 Page 15 of 18

Section 11 - TOXICOLOGICAL INFORMATION

sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. Allergic reactions involving the respiratory tract are usually due to interactions between IgE antibodies and allergens and occur rapidly. Allergic potential of the allergen and period of exposure often determine the severity of symptoms. Some people may be genetically more prone than others, and exposure to other irritants may aggravate symptoms. Allergy causing activity is due to interactions with proteins.

Attention should be paid to atopic diathesis, characterised by increased susceptibility to nasal inflammation, asthma and eczema.

Exogenous allergic alveolitis is induced essentially by allergen specific immune-complexes of the IgG type; cell-mediated reactions (T lymphocytes) may be involved. Such allergy is of the delayed type with onset up to four hours following exposure.

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.

Aromatic and aliphatic diisocyanates may cause airway toxicity and skin sensitization. Monomers and prepolymers exhibit similar respiratory effect. Of the several members of diisocyanates tested on experimental animals by inhalation and oral exposure, some caused cancer while others produced a harmless outcome. This group of compounds has therefore been classified as cancer-causing.

Isocyanate vapours are irritating to the airways and can cause their inflammation, with wheezing, gasping, severe distress, even loss of consciousness and fluid in the lungs. Nervous system symptoms that may occur include headache, sleep disturbance, euphoria, inco-ordination, anxiety, depression and paranoia. Digestive effects include nausea and vomiting. Breathing difficulties may occur unpredictably after a period of tolerance and after skin contact. Allergic inflammation of the skin can occur, with rash, itching, blistering, and swelling of the hands and feet. Sensitive people can react to very low levels and should not be exposed to this material.

CARCINOGEN

Toluene diisocyanates	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	2B
Toluene- 2, 4- diisocyanate [2, 4- TDI]	US ACGIH Threshold Limit Values (TLV) - Carcinogens	Carcinogen Category	A4
toluene diisocyanate	US - Rhode Island Hazardous Substance List	IARC	

continued...

ERAPOL EMP83A

Hazard Alert Code: MODERATE

Erapol EMP95A
For Domestic Use Only.
Mar-23-2011
NC614TDP

CHEMWATCH 24-3814

Version No:2.0

CD 2011/2 Page 16 of 18

Section 11 - TOXICOLOGICAL INFORMATION

TOLUENE DIISOCYANATE (MIXED ISOMERS)	US Environmental Defense Scorecard Recognized Carcinogens	Reference(s)	P65
TOLUENE- 2, 4- DIISOCYANATE	US Environmental Defense Scorecard Recognized Carcinogens	Reference(s)	P65- MC
TOLUENE DIISOCYANATE (MIXED ISOMERS)	US Environmental Defense Scorecard Suspected Carcinogens	Reference(s)	P65
TOLUENE- 2, 4- DIISOCYANATE	US Environmental Defense Scorecard Suspected Carcinogens	Reference(s)	P65- MC
2, 4- Toluene diisocyanate	US Air Toxics Hot Spots TSD for Describing Available Cancer Potency Factors	IARC Class	2B
Toluene- 2, 4- diisocyanate [2, 4- TDI]	US NIOSH Recommended Exposure Limits (RELs) - Carcinogens	Carcinogen	Ca
TWAPPM~	US - Maine Chemicals of High Concern List	Carcinogen	A4
VPVB_(VERY~	US - Maine Chemicals of High Concern List	Carcinogen	CA Prop 65; NTP 11th ROC
PBIT_(PERS~	US - Maine Chemicals of High Concern List	Carcinogen	

Section 12 - ECOLOGICAL INFORMATION

TOLUENE DIISOCYANATE:

■ Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.
Wastes resulting from use of the product must be disposed of on site or at approved waste sites.
Hydrolysis would represents the primary fate mechanism for the majority of the commercial isocyanate monomers, but, is tempered somewhat by the lack of water solubility. In the absence of hydrolysis, sorption to solids (e.g., sludge and sediments) will be the primary mechanism of removal. Biodegradation is minimal for most compounds and volatilisation is negligible. Atmospheric degradation is not expected with removal from air occurring by washout or dry deposition. Volatilisation from surface waters (e.g., lakes and rivers) is expected to take years. In wastewater treatment this process is not expected to be significant.
Review of the estimated properties of the isocyanates suggest that sorption is the primary removal mechanism in the ambient environment and in wastewater treatment in the absence of significant hydrolysis. Sorption to solids in wastewater treatment is considered strong to very strong for most compounds. Sorption to sediments and soils in the ambient environment is very strong in most instances. Migration to groundwater and surface waters is not expected due to sorption or hydrolysis.
Hydrolysis of the $N=C=O$ will occur in less than hours in most instances and within minutes for more than 90% of the commercial isocyanates. However, the low to very low solubility of these substances will generally lessen the effectiveness of hydrolysis as a fate pathway. But hydrolysis should be considered one of the two major fate processes for the isocyanates.
Aerobic and/or anaerobic biodegradation of the isocyanates is not expected to occur at significant levels. Most of the substances take several months to degrade.
Degradation of the hydrolysis products will occur at varying rates depending on the moiety formed.

continued...

ERAPOL EMP83A

Hazard Alert Code: MODERATE

Erapol EMP95A
For Domestic Use Only.
Mar-23-2011
NC614TDP

CHEMWATCH 24-3814

Version No:2.0

CD 2011/2 Page 17 of 18

Section 12 - ECOLOGICAL INFORMATION

DO NOT discharge into sewer or waterways.

Water pollution class (WGK): 2 - impairment of water quality

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
ERAPOL EMP83A	No Data	No Data		
toluene diisocyanate	Available LOW	Available LOW	LOW	MED

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle where possible
Otherwise ensure that:
- licenced contractors dispose of the product and its container.
- disposal occurs at a licenced facility.

Section 14 - TRANSPORTATION INFORMATION

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: DOT, IATA, IMDG

Section 15 - REGULATORY INFORMATION

REGULATIONS

Regulations for ingredients

toluene diisocyanate (CAS: 26471-62-5,584-84-9,91-08-7) is found on the following regulatory lists;

"Canada - Nova Scotia Occupational Exposure Limits", "Canada - Saskatchewan Industrial Hazardous Substances", "Canada Ingredient Disclosure List (SOR/88-64)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (English)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "US - California Proposition 65 - No Significant Risk Levels (NSRLs) for Carcinogens", "US - Pennsylvania - Hazardous Substance List", "US - Vermont Hazardous Constituents", "US - Vermont Hazardous wastes which are Discarded Commercial Chemical Products or Off-Specification Batches of Commercial Chemical Products or Spill Residues of Either", "US - Washington Dangerous waste constituents list", "US - Washington Discarded Chemical Products List - ""U"" Chemical Products", "US Department of Transportation (DOT) List of Hazardous Substances and Reportable Quantities - Hazardous Substances Other Than Radionuclides", "US DOE Temporary Emergency Exposure Limits (TEELs)", "US EPA High Production Volume Program Chemical List", "US List of Lists - Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112(r) of the Clean Air Act", "US National Toxicology Program (NTP) 11th Report Part B. Reasonably Anticipated to be a Human Carcinogen", "US RCRA (Resource Conservation & Recovery Act) - Hazardous Constituents - Appendix VIII to 40 CFR 261", "US RCRA (Resource Conservation & Recovery Act) - List of Hazardous Wastes", "US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory", "US TSCA Section 8 (d) - Health and Safety Data Reporting", "USA: Chemical Facility Anti-Terrorism Standards - List Appendix A - 6CFR 27"

continued...

ERAPOL EMP83A

Hazard Alert Code: MODERATE

Erapol EMP95A
For Domestic Use Only.
Mar-23-2011
NC614TDP

CHEMWATCH 24-3814
Version No:2.0
CD 2011/2 Page 18 of 18
Section 15 - REGULATORY INFORMATION

No data for ERAPOL EMP83A (CW: 24-3814)

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
toluene diisocyanate	26471-62-5, 584-84-9, 91-08-7

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

■ For detailed advice on Personal Protective Equipment, refer to the following U.S. Regulations and Standards:

OSHA Standards - 29 CFR:

1910.132 - Personal Protective Equipment - General requirements

1910.133 - Eye and face protection

1910.134 - Respiratory Protection

1910.136 - Occupational foot protection

1910.138 - Hand Protection

Eye and face protection - ANSI Z87.1

Foot protection - ANSI Z41

Respirators must be NIOSH approved.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Mar-23-2011

Print Date: Sep-13-2011