

**PRODUCT DESCRIPTION**

Aristonate® S-4000 is a low molecular weight first-intent sodium sulfonate with excellent emulsification and lubricity characteristics. Aristonate® S-4000 is a clear to slightly hazy amber custom tailored sulfonate with unsurpassed handling and storage properties.

**CHEMICAL NAME**

Proprietary Sodium Alkyl Aryl Sulfonate (Synthetically Derived Petroleum Sulfonate)

**TYPICAL PROPERTIES**

Appearance @ 25°C	Viscous dark amber liquid
Odor	Slight
Active (Wt. %)	60.0 min
Sodium Sulfate (Wt. %)	0.75 max
Water (Wt. %)	1.0 max
% Volatile by Volume	<1.0
Molecular Weight	400
Density (lbs/gal)	8.5
pH (10% solution)	10.0
Solubility in Water	Dispersible

**APPLICATIONS**
**Soluble Oils**

Aristonate® S-4000 is a very efficient emulsifier when combined with oleic acid, which can be further formulated into low foaming soluble oils. These soluble oils can provide excellent ferrous corrosion inhibition.

**Semi-Synthetics**

Aristonate® S-4000 easily forms microemulsions generating the basis for semi-synthetic fluids. Additional additives, such as amides, chlorinated paraffins, sulfurized olefins and phosphate esters are easily incorporated into emulsifier packages utilizing this sulfonate.

**PERFORMANCE**

Aristonate® S-4000 offers unmatched emulsification consistency and performance; reducing the need for emulsifier package adjustments due to quality variations.

**ADVANTAGES**

Aristonate® S-4000 is compatible with a wide range of secondary emulsifiers, soaps, coupling agents, bactericides, antioxidants and corrosion inhibitors.

**STORAGE & HANDLING**

Employ normal safety precautions (i.e. gloves and safety goggles) when handling. Avoid eye and prolonged skin contact. Wash thoroughly after handling material. Material should be warmed to 110 - 120°F with agitation before using. Do not store drums near open flames or strong oxidants. Containers should be stored at temperatures above 50° F. Avoid excessive heat. Heated and agitated iron or steel tanks should be used for bulk storage. Please refer to the MSDS before handling Aristonate® S-4000.

**REGULATORY**

Aristonate® S-4000 is listed with the following country chemistry inventories: USA – TSCA, Canadian - DSL, EEC - EINECS, Japanese - ENCS, Australian - AICS, and Korean - ECL.

**PACKAGING**

Aristonate® S-4000 is available in 55-gallon open head steel drums (net weight 420lb/191kg); bulk quantities are available by tank car or tank truck.

**See starting formulas and additional product information, at [www.pilotchemical.com](http://www.pilotchemical.com)**

The information and suggestions given are drawn from data we believe to be reliable, but in all cases, the user should check and confirm the suggestions and results in his own use before proceeding further. None of the suggestions or recommendations constitute freedom from any patents that may be existent in the field or be issued.