

Eastman AQ(TM) 65S Polymer

ZSAMPLE00000194970

Version	Revision Date:	SDS Number:	Date of last issue: 06/01/2018
1.2	11/06/2019	150000072728	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	N02 / 0090242009 / 0004343309

SECTION 1. IDENTIFICATION

Product name : Eastman AQ(TM) 65S Polymer

Product code : P33109FT

Manufacturer or supplier's details

Company name of supplier : Eastman Chemical Company

Address : 200 South Wilcox Drive
Kingsport TN 37660-5280

Telephone : (423) 229-2000

Emergency telephone : CHEMTREC: +1-800-424-9300, +1-703-527-3887 CCN7321

Recommended use of the chemical and restrictions on useRecommended use : Manufacture of plastics products
Polymer

Restrictions on use : None known.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200**

Combustible dust

GHS label elements

Signal Word : Warning

Hazard Statements : If small particles are generated during further processing,
handling or by other means, may form combustible dust
concentrations in air.Precautionary Statements : **Disposal:**
P501 Dispose of contents/ container to an approved waste dis-
posal plant.**Other hazards**

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Components**

Chemical name	CAS-No.	Concentration (% w/w)
polyester	proprietary	100

Eastman AQ(TM) 65S Polymer

ZSAMPLE00000194970

Version	Revision Date:	SDS Number:	Date of last issue: 06/01/2018
1.2	11/06/2019	150000072728	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	N02 / 0090242009 / 0004343309

SECTION 4. FIRST AID MEASURES

- If inhaled : Move to fresh air.
Treat symptomatically.
If symptoms persist, call a physician.
- In case of skin contact : Wash off with soap and water.
If symptoms persist, call a physician.
Cool skin rapidly with cold water after contact with molten material.
Do not peel solidified product off the skin.
Burns must be treated by a physician.
- In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- If swallowed : Seek medical advice.
- Most important symptoms and effects, both acute and delayed : The molten product can cause serious burns.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Dry chemical
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.
- Specific hazards during fire fighting : Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
- Hazardous combustion products : No hazardous combustion products are known
- Further information : Minimize dust generation and accumulation.
- Special protective equipment for fire-fighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Wear appropriate personal protective equipment.
Local authorities should be advised if significant spillages cannot be contained.
- Environmental precautions : Avoid release to the environment.

Eastman AQ(TM) 65S Polymer

ZSAMPLE00000194970

Version	Revision Date:	SDS Number:	Date of last issue: 06/01/2018
1.2	11/06/2019	150000072728	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	N02 / 0090242009 / 0004343309

Methods and materials for containment and cleaning up : Sweep up and shovel into suitable containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Minimize dust generation and accumulation.

Advice on safe handling : Wash thoroughly after handling.
Use only in area provided with appropriate exhaust ventilation.
Minimize dust generation and accumulation.

Conditions for safe storage : Keep tightly closed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Contains no substances with occupational exposure limit values.

Engineering measures : Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Wear respiratory protection when its use is identified for certain contributing scenario.

Hand protection

Remarks : Wear suitable gloves. When handling hot material, use heat resistant gloves.

Eye protection : Safety glasses
Wear a face shield when working with molten material.

Skin and body protection : Wear suitable protective clothing.

Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.

Eastman AQ(TM) 65S Polymer

ZSAMPLE00000194970

Version	Revision Date:	SDS Number:	Date of last issue: 06/01/2018
1.2	11/06/2019	150000072728	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	N02 / 0090242009 / 0004343309

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	pellets
Color	:	light yellow
Odor	:	slight, characteristic
Odor Threshold	:	not determined
pH	:	Not applicable
Softening point	:	149 °F / 65 °C
Boiling point/boiling range	:	not determined
Flash point	:	not applicable, combustible solid
Evaporation rate	:	not determined
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	not determined
Vapor pressure	:	not determined
Relative vapor density	:	not determined
Relative density	:	> 1 (estimated)
Solubility(ies) Water solubility	:	negligible
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	not determined
Decomposition temperature	:	Thermal stability not tested. Low stability hazard expected at normal operating temperatures.
Viscosity Viscosity, dynamic	:	not determined
Viscosity, kinematic	:	not determined
Explosive properties	:	No data available

Eastman AQ(TM) 65S Polymer

ZSAMPLE00000194970

Version	Revision Date:	SDS Number:	Date of last issue: 06/01/2018
1.2	11/06/2019	150000072728	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	N02 / 0090242009 / 0004343309

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : None reasonably foreseeable.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Stable

Conditions to avoid : Minimize dust generation and accumulation.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : Carbon monoxide
Carbon dioxide (CO₂)

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : No data available

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : No data available

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Eastman AQ(TM) 65S Polymer

ZSAMPLE00000194970

Version	Revision Date:	SDS Number:	Date of last issue: 06/01/2018
1.2	11/06/2019	150000072728	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	N02 / 0090242009 / 0004343309

Product:

Remarks : No data available

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Product:

Remarks : This information is not available.

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Product:

Effects on fertility : Remarks: No data available

STOT-single exposure

Not classified based on available information.

Product:

Remarks : No data available

STOT-repeated exposure

Not classified based on available information.

Product:

Remarks : No data available

Aspiration toxicity

Not classified based on available information.

Product:

No data available

Information on likely routes of exposure**Product:**

Inhalation : Remarks: None known.

Skin contact : Remarks: The molten product can cause serious burns.

Eastman AQ(TM) 65S Polymer

ZSAMPLE00000194970

Version	Revision Date:	SDS Number:	Date of last issue: 06/01/2018
1.2	11/06/2019	150000072728	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	N02 / 0090242009 / 0004343309

Eye contact : Remarks: The molten product can cause serious burns.

Ingestion : Remarks: None known.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

Eastman AQ(TM) 65S Polymer

ZSAMPLE00000194970

Version	Revision Date:	SDS Number:	Date of last issue: 06/01/2018
1.2	11/06/2019	150000072728	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	N02 / 0090242009 / 0004343309

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Combustible dust

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

WARNING: This product can expose you to chemicals including 1,4-dioxane, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

AICS : On the inventory, or in compliance with the inventory

DSL : All components of this product are on the Canadian DSL

ENCS : On the inventory, or in compliance with the inventory

ISHL : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

Eastman AQ(TM) 65S Polymer


ZSAMPLE00000194970

Version
1.2
PRDRevision Date:
11/06/2019SDS Number:
150000072728
SDSUS / Z8 / 0001Date of last issue: 06/01/2018
Date of first issue: 09/06/2016
N02 / 0090242009 / 0004343309

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	/	1
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG -

Eastman AQ(TM) 65S Polymer

ZSAMPLE00000194970

Version	Revision Date:	SDS Number:	Date of last issue: 06/01/2018
1.2	11/06/2019	150000072728	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	N02 / 0090242009 / 0004343309

United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 11/06/2019

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8