



CC50A PART A

Erapol Co. GHS Safety Data Sheet (REVIEW)
May-4-2012
B614L

Hazard Alert Code: HIGH

ERAPOL CO. 9-35001
Version No:1
Page 1 of 15

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

CC50A PART A

PROPER SHIPPING NAME

ISOCYANATES, TOXIC, N.O.S. or ISOCYANATE SOLUTION, TOXIC, N.O.S.(contains toluene diisocyanate)

PRODUCT USE

Polyurethane Prepolymer

SUPPLIER

Company: Era Polymers Pty Ltd

Address:

25- 27 Green Street, Banksmeadow, NSW 2019,
Australia

Telephone: +61 2 9666 3788

Emergency Tel:1800 039 008 (AUS)


Emergency Tel:+80024362255 (INTL)

Fax: +61 2 9666 4805

Email: erapol@erapol.com.au

Section 2 - HAZARDS IDENTIFICATION

NFPA



GHS Classification

Acute Toxicity Category 2

Carcinogen Category 2

continued...

CC50A PART A

Erapol Co. GHS Safety Data Sheet (REVIEW)

May-4-2012

B614L

Hazard Alert Code: HIGH

ERAPOL CO. 9-35001

Version No:1

Page 2 of 15

Section 2 - HAZARDS IDENTIFICATION

Respiratory Sensitizer Category 1

Skin Sensitizer Category 1



EMERGENCY OVERVIEW

HAZARD

DANGER

Determined by Chemwatch using GHS criteria

H317	May cause an allergic skin reaction.
H330	Fatal if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H351	Suspected of causing cancer.

PRECAUTIONARY STATEMENTS

Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well- ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P284	Wear respiratory protection.
P285	In case of inadequate ventilation wear respiratory protection.

Response

P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P310	Immediately call a POISON CENTER or doctor/physician.
P320	Specific treatment is urgent (see MSDS).
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P363	Wash contaminated clothing before reuse.

Storage

P403+P233	Store in a well- ventilated place. Keep container tightly closed.
P405	Store locked up.

Disposal

P501	Dispose of contents/container to ...
------	--------------------------------------

continued...

CC50A PART A

Erapol Co. GHS Safety Data Sheet (REVIEW)

May-4-2012

B614L

Hazard Alert Code: HIGH

ERAPOL CO. 9-35001

Version No:1

Page 3 of 15

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
Polyurethane prepolymer		>60
toluene diisocyanate	26471-62-5	1-7

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Center or a doctor.

EYE

- If this product comes in contact with the eyes:
- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Center or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor, without delay.

NOTES TO PHYSICIAN

- Treat symptomatically.

The material is a known pulmonary sensitizer. Annual medical surveillance should be conducted including pulmonary history, examination of the heart and lungs, 14 x 17 inch (35 x 47 cm) x-ray and pulmonary function testing (FCV, FEV1).

For sub-chronic and chronic exposures to isocyanates:

- This material may be a potent pulmonary sensitizer which causes bronchospasm even in patients without prior airway hyperreactivity.
- Clinical symptoms of exposure involve mucosal irritation of respiratory and gastrointestinal tracts.
- Conjunctival irritation, skin inflammation (erythema, pain vesication) and gastrointestinal disturbances occur soon after exposure.
- Pulmonary symptoms include cough, burning, substernal pain and dyspnea.
- Some cross-sensitivity occurs between different isocyanates.
- Noncardiogenic pulmonary edema and bronchospasm are the most serious consequences of exposure. Markedly symptomatic patients should receive oxygen, ventilatory support and an intravenous line.

continued...

CC50A PART A

Erapol Co. GHS Safety Data Sheet (REVIEW)

May-4-2012

B614L

Hazard Alert Code: HIGH

ERAPOL CO. 9-35001

Version No:1

Page 4 of 15

Section 4 - FIRST AID MEASURES

- Treatment for asthma includes inhaled sympathomimetics (epinephrine [adrenalin], terbutaline) and steroids.
- Activated charcoal (1 g/kg) and a cathartic (sorbitol, magnesium citrate) may be useful for ingestion.
- Mydriatics, systemic analgesics and topical antibiotics (Sulamyd) may be used for corneal abrasions.
- There is no effective therapy for sensitized workers. [Ellenhorn and Barceloux: Medical Toxicology]NOTE: Isocyanates cause airway restriction in naive individuals with the degree of response dependant on the concentration and duration of exposure. They induce smooth muscle contraction which lead to bronchoconstrictive episodes. Acute changes in lung function, such as decreased FEV1, may not represent sensitivity. [Karol Jin, Frontiers in Molecular Toxicology, pp 56-61, 1992].

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Alert Emergency Responders and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 2625 feet in all directions.

FIRE/EXPLOSION HAZARD

- Combustible.
- Moderate fire hazard when exposed to heat or flame.
- When heated to high temperatures decomposes rapidly generating vapor which pressures and may then rupture containers with release of flammable and highly toxic isocyanate vapor.
- Burns with acrid black smoke and poisonous fumes.
- Combustion yields traces of highly toxic hydrogen cyanide HCN, plus toxic nitrogen oxides NOx and carbon monoxide.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidizing agents i.e. nitrates, oxidizing acids, chlorine bleaches, pool chlorine etc. as ignition may result.

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapors and contact with skin and eyes.
- Control personal contact by using protective equipment.

continued...

CC50A PART A

Hazard Alert Code: HIGH

Erapol Co. GHS Safety Data Sheet (REVIEW)

May-4-2012

B614L

ERAPOL CO. 9-35001

Version No:1

Page 5 of 15


Section 6 - ACCIDENTAL RELEASE MEASURES

- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labeled container for waste disposal.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Emergency Responders and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labeled containers for recycling.
- Neutralize/decontaminate residue.
- Collect solid residues and seal in labeled drums for disposal.
- Wash area and prevent runoff into drains.
- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- If contamination of drains or waterways occurs, advise emergency services.

PROTECTIVE ACTIONS FOR SPILL



From IERG (Canada/Australia)

Isolation Distance	25 meters
Downwind Protection Distance	250 meters
IERG Number	38

FOOTNOTES

- 1 PROTECTIVE ACTION ZONE is defined as the area in which people are at risk of harmful exposure. This zone assumes that random changes in wind direction confines the vapor plume to an area within 30 degrees on either side of the predominant wind direction, resulting in a crosswind protective action distance equal to the downwind protective action distance.
- 2 PROTECTIVE ACTIONS should be initiated to the extent possible, beginning with those closest to the spill and working away from the site in the downwind direction. Within the protective action zone a level of vapor concentration may exist resulting in nearly all unprotected persons becoming incapacitated and unable to take protective action and/or incurring serious or irreversible health effects.
- 3 INITIAL ISOLATION ZONE is determined as an area, including upwind of the incident, within which a high probability of localized wind reversal may expose nearly all persons without appropriate protection to life-threatening concentrations of the material.
- 4 SMALL SPILLS involve a leaking package of 200 litres (55 US gallons) or less, such as a drum (jerrican or box with inner containers). Larger packages leaking less than 200 litres and compressed gas leaking from a

continued...

CC50A PART A

Erapol Co. GHS Safety Data Sheet (REVIEW)

May-4-2012

B614L

Hazard Alert Code: HIGH

ERAPOL CO. 9-35001

Version No:1

Page 6 of 15

Section 6 - ACCIDENTAL RELEASE MEASURES

small cylinder are also considered "small spills".

LARGE SPILLS involve many small leaking packages or a leaking package of greater than 200 litres, such as a cargo tank, portable tank or a "one-tonne" compressed gas cylinder.

5 Guide 155 is taken from the US DOT emergency response guide book.

6 IERG information is derived from CANUTEC - Transport Canada.

ACUTE EXPOSURE GUIDELINE LEVELS (AEGL) (in ppm)

toluene

diisocyanate

AEGL Type	10 min	30 min	60 min	4 hr	8 hr
1	0.020	0.020	0.020	0.010	CAS_CHECK~
2	0.24	0.17	0.083	0.021	CAS_CHECK~
3	0.65	0.65	0.51	0.32	CAS_CHECK~
1	0.020	0.020	0.020	0.010	CAS_CHECK~
2	0.24	0.17	0.083	0.021	CAS_CHECK~
3	0.65	0.65	0.51	0.32	CAS_CHECK~

AEGL 1: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience notable discomfort, irritation, or certain asymptomatic nonsensory effects. However, the effects are not disabling and are transient and reversible upon cessation of exposure.

AEGL 2: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience irreversible or other serious, long-lasting adverse health effects or an impaired ability to escape.

AEGL 3: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience life-threatening health effects or death.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Launder contaminated clothing before re-use.
- Use good occupational work practice.

continued...

CC50A PART A

Erapol Co. GHS Safety Data Sheet (REVIEW)

May-4-2012

B614L

Hazard Alert Code: HIGH

ERAPOL CO. 9-35001

Version No:1

Page 7 of 15

Section 7 - HANDLING AND STORAGE

- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Lined metal can, Lined metal pail/drum
- Plastic pail
- Polyliner drum
- Packing as recommended by manufacturer.
- Check all containers are clearly labeled and free from leaks.

For low viscosity materials

- Drums and jerricans must be of the non-removable head type.
- Where a can is to be used as an inner package, the can must have a screwed enclosure.

For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):

- Removable head packaging;
- Cans with friction closures and
- low pressure tubes and cartridges may be used.- Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages *
- In addition, where inner packagings are glass and contain liquids of packing group I and II there must be sufficient inert absorbent to absorb any spillage *. - * unless the outer packaging is a close fitting molded plastic box and the substances are not incompatible with the plastic.

All inner and sole packagings for substances that have been assigned to Packaging Groups I or II on the basis of inhalation toxicity criteria, must be hermetically sealed.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



X



X



+



X



X



+

+: May be stored together

O: May be stored together with specific preventions

X: Must not be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC	Notes

continued...

CC50A PART A

Hazard Alert Code: HIGH

Erapol Co. GHS Safety Data Sheet (REVIEW)

May-4-2012

B614L

ERAPOL CO. 9-35001

Version No:1

Page 8 of 15

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC	Notes
US ACGIH Threshold Limit Values (TLV)	toluene diisocyanate (Toluene- 2, 4- or 2, 6- diisocyanate (or as a mixture))	0.005		0.02					TLV® Basis: (Resp sens) , See Notice of Intended Changes (NIC)

The following materials had no OELs on our records

• Polyurethane prepolymer:

CAS:

MATERIAL DATA

CC50A PART A:

TOLUENE DIISOCYANATE:

CC50A PART A:

- Some jurisdictions require that health surveillance be conducted on occupationally exposed workers.
 - demography, occupational and medical history and health advice
 - completion of a standardized respiratory questionnaire
 - physical examination of the respiratory system and skin
 - standardized respiratory function tests such as FEV1, FVC and FEV1/FVC.

POLYURETHANE PREPOLYMER:

Not available

PERSONAL PROTECTION



EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them. DO NOT wear contact lenses.

HANDS/FEET

- NOTE: The material may produce skin sensitization in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

OTHER

- Overalls.
- Eyewash unit.
- Barrier cream.

continued...

CC50A PART A

Erapol Co. GHS Safety Data Sheet (REVIEW)

May-4-2012

B614L

Hazard Alert Code: HIGH

ERAPOL CO. 9-35001

Version No:1

Page 9 of 15

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

- Skin cleansing cream.

RESPIRATOR

- Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

- Spraying of material or material in admixture with other components must be carried out in conditions conforming to local state regulations. Local exhaust ventilation with full face air supplied breathing apparatus (hood or helmet type) is normally required. Unprotected personnel must vacate spraying area.
- NOTE: Isocyanate vapors will not be adequately absorbed by organic vapor respirators.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Light/Yellow/Brown Colour

PHYSICAL PROPERTIES

Liquid.

Toxic or noxious vapors/ gas.

State	Liquid	Molecular Weight	Not Available
Melting Range (°F)	Not Available	Viscosity	Not Available
Boiling Range (°F)	>572	Solubility in water (g/L)	Reacts with water liberating carbon dioxide [Reacts]
Flash Point (°F)	>392	pH (1% solution)	Not Available
Decomposition Temp (°F)	Not Available	pH (as supplied)	Not Available
Autoignition Temp (°F)	Not Available	Vapour Pressure (mmHG)	Not Available
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	1.06
Lower Explosive Limit (%)	Not Available	Relative Vapor Density (air=1)	Not Available
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerization will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

continued...

CC50A PART A

Erapol Co. GHS Safety Data Sheet (REVIEW)

May-4-2012

B614L

Hazard Alert Code: HIGH

ERAPOL CO. 9-35001

Version No:1

Page 10 of 15

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ The material is not thought to produce adverse health effects following ingestion (as classified using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum.

EYE

■ Although the liquid is not thought to be an irritant, direct contact with the eye may produce transient discomfort characterized by tearing or conjunctival redness (as with windburn).

SKIN

■ Skin contact is not thought to produce harmful health effects (as classified using animal models). Systemic harm, however, has been identified following exposure of animals by at least one other route and the material may still produce health damage following entry through wounds, lesions or abrasions. Good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

■ Open cuts, abraded or irritated skin should not be exposed to this material.

■ Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

■ Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may produce toxic effects; these may be fatal.

■ The material is not thought to produce respiratory irritation (as classified using animal models). Nevertheless inhalation of vapors, fumes or aerosols, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.

■ In addition to producing pulmonary sensitization, toluene diisocyanate (TDI) is active in contracting smooth muscle such as that found in the airway. So-called bronchoconstriction is often mistaken for sensitization and lung function tests, including measurement of forced expiratory volume (FEV1) and forced vital capacity (FCV) may distinguish acute reaction. Severe irritation is produced by inhalation of low vapor concentrations. At 0.02 ppm, TDI does not produce immediate irritation but this may become apparent after an extended period of exposure. Symptoms may include a burning sensation, coughing, wheezing, laryngitis, shortness of breath, headache, nausea and vomiting. Overexposure or repeated exposure may produce bronchial spasm and asthma which may not appear for several hours. Symptoms may persist for several weeks. Most individuals recover completely. Both allergy-prone and non allergy-prone individuals may become sensitized. Cross-sensitization to other isocyanates may occur.

CHRONIC HEALTH EFFECTS

■ There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment.

Inhaling this product is more likely to cause a sensitization reaction in some persons compared to the general population.

Skin contact with the material is more likely to cause a sensitization reaction in some persons compared to the general population.

Isocyanate vapors are irritating to the airways and can cause their inflammation, with wheezing, gasping, severe distress, even loss of consciousness and fluid in the lungs. Nervous system symptoms that may occur include headache, sleep disturbance, euphoria, inco-ordination, anxiety, depression and paranoia. Digestive effects include nausea and vomiting. Breathing difficulties may occur unpredictably after a period of

continued...

CC50A PART A

Hazard Alert Code: HIGH

Erapol Co. GHS Safety Data Sheet (REVIEW)

May-4-2012

B614L

ERAPOL CO. 9-35001

Version No:1

Page 11 of 15

Section 11 - TOXICOLOGICAL INFORMATION

tolerance and after skin contact. Allergic inflammation of the skin can occur, with rash, itching, blistering, and swelling of the hands and feet. Sensitive people can react to very low levels and should not be exposed to this material.

TOXICITY AND IRRITATION

TOLUENE DIISOCYANATE:

CC50A PART A:

■ Isocyanate vapors are irritating to the airways and can cause their inflammation, with wheezing, gasping, severe distress, even loss of consciousness and fluid in the lungs. Nervous system symptoms that may occur include headache, sleep disturbance, euphoria, inco-ordination, anxiety, depression and paranoia. Digestive effects include nausea and vomiting. Breathing difficulties may occur unpredictably after a period of tolerance and after skin contact. Allergic inflammation of the skin can occur, with rash, itching, blistering, and swelling of the hands and feet. Sensitive people can react to very low levels and should not be exposed to this material.

■ Exogenous allergic alveolitis is induced essentially by allergen specific immune-complexes of the IgG type; cell-mediated reactions (T lymphocytes) may be involved. Such allergy is of the delayed type with onset up to four hours following exposure.

■ Attention should be paid to atopic diathesis, characterized by increased susceptibility to nasal inflammation, asthma and eczema.

■ Allergic reactions involving the respiratory tract are usually due to interactions between IgE antibodies and allergens and occur rapidly. Allergic potential of the allergen and period of exposure often determine the severity of symptoms. Some people may be genetically more prone than others, and exposure to other irritants may aggravate symptoms. Allergy causing activity is due to interactions with proteins.

■ Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's edema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitization potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitizing substance which is widely distributed can be a more important allergen than one with stronger sensitizing potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

CC50A PART A:

~OTHER

POLYURETHANE PREPOLYMER:

■ None assigned. Refer to individual constituents.

TOLUENE DIISOCYANATE:

■ The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.

CARCINOGEN

Toluene- 2, 4- or 2, 6-diisocyanate (or as a mixture)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

Carcinogen Category

A4

continued...

CC50A PART A

Hazard Alert Code: HIGH

Erapol Co. GHS Safety Data Sheet (REVIEW)

May-4-2012

B614L

ERAPOL CO. 9-35001

Version No:1

Page 12 of 15

Section 11 - TOXICOLOGICAL INFORMATION

toluene diisocyanate	US - Rhode Island Hazardous Substance List	IARC	
TOLUENE DIISOCYANATE (MIXED ISOMERS)	US Environmental Defense Scorecard Recognized Carcinogens	Reference(s)	P65
TOLUENE- 2, 4- DIISOCYANATE	US Environmental Defense Scorecard Recognized Carcinogens	Reference(s)	P65- MC
MERCURY COMPOUNDS	US Environmental Defense Scorecard Suspected Carcinogens	Reference(s)	P65- MC
2, 4- Toluene diisocyanate	US Air Toxics Hot Spots TSD for Describing Available Cancer Potency Factors	IARC Class	2B
toluene diisocyanate	Canada - Prince Edward Island Occupational Exposure Limits - Carcinogens	Notes	TLV Basis: respiratory sensitization; asthma; eye irritation

Section 12 - ECOLOGICAL INFORMATION

TOLUENE DIISOCYANATE:

■ Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DO NOT discharge into sewer or waterways.

Water pollution class (WGK): 2 - impairment of water quality

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
Polyurethane prepolymer	No Data Available	No Data Available		
toluene diisocyanate	LOW	LOW	LOW	MED

Section 13 - DISPOSAL CONSIDERATIONS

■ Puncture containers to prevent re-use and bury at an authorized landfill.

DO NOT allow wash water from cleaning equipment to enter drains. Collect all wash water for treatment before disposal.

- DO NOT recycle spilled material.
- Consult Waste Management Authority for disposal.
- Neutralize spill material carefully and decontaminate empty containers and spill residues with 10% ammonia solution plus detergent or a proprietary decontaminant prior to disposal.
- DO NOT seal or stopper drums being decontaminated as CO₂ gas is generated and may pressurize containers
- Puncture containers to prevent re-use.
- Bury or incinerate residues at an approved site.

continued...

CC50A PART A

Erapol Co. GHS Safety Data Sheet (REVIEW)

May-4-2012

B614L

Hazard Alert Code: HIGH

ERAPOL CO. 9-35001

Version No:1

Page 13 of 15

Section 14 - TRANSPORTATION INFORMATION



DOT:

Symbols:	None	Hazard class or Division:	6.1
Identification Numbers:	UN2206	PG:	III
Label Codes:	6.1	Special provisions:	IB3, T7, TP1, TP13, TP28

Packaging: Exceptions:	153	Packaging: Non- bulk:	203
------------------------	-----	-----------------------	-----

Packaging: Exceptions:	153	Quantity limitations:	60 L
------------------------	-----	-----------------------	------

		Passenger aircraft/rail:	
--	--	--------------------------	--

Quantity Limitations: Cargo	220 L	Vessel stowage: Location:	E
-----------------------------	-------	---------------------------	---

aircraft only:

Vessel stowage: Other: 25, 40, 48

Hazardous materials descriptions and proper shipping names:

Isocyanates, toxic, n.o.s. or Isocyanate solutions, toxic, n.o.s., flash point

more than 61 degrees C and boiling point less than 300 degrees C

Maritime Transport IMDG:

IMDG Class:	6.1	IMDG Subrisk:	None
-------------	-----	---------------	------

UN Number:	2206	Packing Group:	III
------------	------	----------------	-----

EMS Number:	F-A,S-A	Special provisions:	223 274
-------------	---------	---------------------	---------

Limited Quantities:	5 L		
---------------------	-----	--	--

Shipping name: ISOCYANATES, TOXIC, N.O.S. or ISOCYANATE SOLUTION, TOXIC, N.O.S. (contains toluene diisocyanate)

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: IATA

Section 15 - REGULATORY INFORMATION

REGULATIONS

Regulations for ingredients

toluene diisocyanate (CAS: 26471-62-5, 584-84-9, 91-08-7) is found on the following regulatory lists;

"Canada - Alberta Occupational Exposure Limits", "Canada - Alberta Substances and processes requiring a code of practice", "Canada - Northwest Territories Occupational Exposure Limits (English)", "Canada - Nova Scotia Occupational Exposure Limits", "Canada - Ontario Occupational Exposure Limits", "Canada - Prince Edward Island Occupational Exposure Limits", "Canada - Prince Edward Island Occupational Exposure Limits - Carcinogens", "Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)", "Canada -

continued...

CC50A PART A

Hazard Alert Code: HIGH

Erapol Co. GHS Safety Data Sheet (REVIEW)

May-4-2012

B614L

ERAPOL CO. 9-35001

Version No:1

Page 14 of 15

Section 15 - REGULATORY INFORMATION

Saskatchewan Industrial Hazardous Substances", "Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits", "Canada - Saskatchewan Occupational Health and Safety Regulations - Designated Chemical Substances", "Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances", "Canada ARET (Accelerated Reduction / Elimination of Toxics) Substance List", "Canada CEPA Environmental Registry Substance Lists - List of substances on the DSL that meet the human health criteria for categorization (English)", "Canada CEPA Environmental Registry Substance Lists - Other DSL substances that are priorities for human health (English)", "Canada Environmental Protection Act (CEPA) 1999 - Schedule 3 Export Control List - Part 2 Substances Subject to Notification or Consent", "Canada National Pollutant Release Inventory (NPRI)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (English)", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "International Council of Chemical Associations (ICCA) - High Production Volume List", "US - Alaska Limits for Air Contaminants", "US - California Environmental Health Standards for the Management of Hazardous Waste - List of Inorganic Persistent and Bioaccumulative Toxic Substances and Their STLC & TTLC Values", "US - California Occupational Safety and Health Regulations (CAL/OSHA) - Hazardous Substances List", "US - California Permissible Exposure Limits for Chemical Contaminants", "US - California Proposition 65 - No Significant Risk Levels (NSRLs) for Carcinogens", "US - California Toxic Air Contaminant List Category II", "US - Connecticut Hazardous Air Pollutants", "US - Delaware Pollutant Discharge Requirements - Reportable Quantities", "US - Hawaii Air Contaminant Limits", "US - Idaho - Limits for Air Contaminants", "US - Louisiana Minimum Emission Rates Toxic Air Pollutants", "US - Louisiana Toxic Air Pollutant Ambient Air Standards", "US - Massachusetts Oil & Hazardous Material List", "US - Michigan Exposure Limits for Air Contaminants", "US - Minnesota Hazardous Substance List", "US - North Dakota Air Pollutants - Unit Risk Factors", "US - Oregon Permissible Exposure Limits (Z-1)", "US - Oregon Permissible Exposure Limits (Z-2)", "US - Pennsylvania - Hazardous Substance List", "US - Rhode Island Hazardous Substance List", "US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants", "US - Vermont Hazardous Constituents", "US - Vermont Hazardous wastes which are Discarded Commercial Chemical Products or Off-Specification Batches of Commercial Chemical Products or Spill Residues of Either", "US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants", "US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants", "US - Washington Dangerous waste constituents list", "US - Washington Discarded Chemical Products List - ""U"" Chemical Products", "US - Washington Permissible exposure limits of air contaminants", "US - Wisconsin Control of Hazardous Pollutants - Emission Thresholds, Standards and Control Requirements (Hazardous Air Contaminants)", "US - Wisconsin Control of Hazardous Pollutants - Substances of Concern for Sources of Incidental Emissions of Hazardous Air Contaminants", "US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants", "US ACGIH Threshold Limit Values (TLV)", "US ACGIH Threshold Limit Values (TLV) - Carcinogens", "US ACGIH Threshold Limit Values (TLV) - Notice of Intended Changes", "US CAA (Clean Air Act) - HON Rule - Organic HAPs (Hazardous Air Pollutants)", "US Clean Air Act - Hazardous Air Pollutants", "US CWA (Clean Water Act) - Priority Pollutants", "US CWA (Clean Water Act) - Toxic Pollutants", "US Department of Transportation (DOT) List of Hazardous Substances and Reportable Quantities - Hazardous Substances Other Than Radionuclides", "US DOE Temporary Emergency Exposure Limits (TEELs)", "US EPA Acute Exposure Guideline Levels (AEGLs) - Final", "US EPA High Production Volume Program Chemical List", "US EPA Master Testing List - Index I Chemicals Listed", "US EPA Toxic Chemical Release Inventory Persistent Bioaccumulative Toxic Chemical (PBT) List", "US EPCRA Section 313 Chemical List", "US List of Lists - Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112(r) of the Clean Air Act", "US OSHA Permissible Exposure Levels (PELs) - Table Z1", "US RCRA (Resource Conservation & Recovery Act) - Appendix IX to Part 264 Ground-Water Monitoring List 1", "US RCRA (Resource Conservation & Recovery Act) - Hazardous Constituents - Appendix VIII to 40 CFR 261", "US RCRA (Resource Conservation & Recovery Act) - List of Hazardous Inorganic and Organic Constituents 1", "US RCRA (Resource Conservation & Recovery Act) - List of Hazardous Wastes", "US SARA Section 302 Extremely Hazardous Substances", "US TSCA Section 8 (d) - Health and Safety Data Reporting", "USA: Chemical Facility Anti-Terrorism Standards - List Appendix A - 6CFR 27"

No data for CC50A PART A (CW: 9-35001)

No data for Polyurethane prepolymer (CAS: ,)

continued...

CC50A PART A

Erapol Co. GHS Safety Data Sheet (REVIEW)

May-4-2012

B614L

Hazard Alert Code: HIGH

ERAPOL CO. 9-35001

Version No:1

Page 15 of 15

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
toluene diisocyanate	26471-62-5, 584-84-9, 91-08-7

■ Classification of the preparation and its individual components has drawn on official and authoritative sources using available literature references.

■ For detailed advice on Personal Protective Equipment, refer to the following U.S. Regulations and Standards:

OSHA Standards - 29 CFR:

1910.132 - Personal Protective Equipment - General requirements

1910.133 - Eye and face protection

1910.134 - Respiratory Protection

1910.136 - Occupational foot protection

1910.138 - Hand Protection

Eye and face protection - ANSI Z87.1

Foot protection - ANSI Z41

Respirators must be NIOSH approved.

This document is copyright

Issue Date: May-4-2012

Print Date: May-4-2012