

CALCINATE ™ C-300R

Version: 1.1 Revision Date: 03/31/2015 Print Date: 04/21/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: CALCINATE ™ C-300R

Product Use Description: Additive

Company: Chemtura Corporation

199 Benson Road Middlebury, CT

06749

United States of America

Telephone: (US) +1 866-430-2775

Emergency telephone

number:

CHEMTREC: (24 hours) 800-424-9300

Chemtura Corporation Emergency Response: CHEMTURA: 800-292-5898

For additional emergency telephone numbers see section 16 of the Safety

Data Sheet.

Prepared by <u>Product Safety Department</u>

(US) +1 866-430-2775

MSDSRequest@chemtura.com

Recommended use of the chemical and restrictions on use

Recommended use : Additive

SECTION 2. HAZARDS IDENTIFICATION

Form	viscous liquid
Colour	brown
Odour	mild hydrocarbon-like

GHS Classification

Eye irritation : Category 2A Skin sensitisation : Category 1

GHS Label element

Signal word : Warning

SAP 6.0 SDS 2012-2 NA GHS 1/10 SDS Number: 400000003938



CALCINATE ™ C-300R

Version: 1.1 Revision Date: 03/31/2015 Print Date: 04/21/2015

Hazard pictograms

(!)

Hazard statements : H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

Other hazards : None

Precautionary statements : Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear eye protection/ face protection.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical Name	CAS-No.	Concentration (%)
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	>= 30 - < 50 %



CALCINATE ™ C-300R Version: 1.1 Revision Date: 03/31/2015 Print Date: 04/21/2015

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	70024-69-0	>= 10 - < 20 %
calcium carbonate	471-34-1	>= 10 - < 20 %
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	68584-23-6	>= 10 - < 20 %
Sulfonic acids, petroleum, calcium salts	61789-86-4	>= 5 - < 10 %
calcium dihydroxide	1305-62-0	>= 1 - < 5 %

SECTION 4. FIRST AID MEASURES

If inhaled : Remove to fresh air.

Aspiration may cause pulmonary oedema and pneumonitis.

If breathing is difficult, give oxygen. If symptoms persist, call a physician.

In case of skin contact : Wash off with warm water and soap.

If skin irritation persists, call a physician.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Obtain medical attention.

If swallowed : Obtain medical attention.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

Notes to physician : For specialist advice physicians should contact the Poisons

Information Service.

: irritant effects

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : (on small fires)

Carbon dioxide (CO2)

Dry chemical Dry sand

Extinguishing media - large fires

Foam Water mist

Specific hazards during

firefighting

: Do not use a solid water stream as it may scatter and spread

fire.

Specific extinguishing

methods

: Cool containers/tanks with water spray.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SAP 6.0 SDS 2012-2 NA GHS 3/10 SDS Number: 400000003938





CALCINATE ™ C-300R

Version: 1.1 Revision Date: 03/31/2015 Print Date: 04/21/2015

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Wear suitable protective equipment.

Environmental precautions : Should not be released into the environment.

Do not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up

: Clean-up methods - large spillage Dam up. Large spills should be collected mechanically (remove by pumping) for disposal. Clean-up methods - small spillage Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Shovel into suitable container for

disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Handle in accordance with good industrial hygiene and safety

practice.

Avoid contact with skin, eyes and clothing. Wear suitable protective equipment. Use only with adequate ventilation.

Protect from contamination.

Conditions for safe storage : Keep tightly closed in a dry, cool and well-ventilated place.

Materials to avoid : Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
Distillates (petroleum), solvent- refined heavy paraffinic	64741-88-4	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		TWA (Mist)	5 mg/m3	OSHA P0
calcium carbonate	471-34-1	TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
calcium dihydroxide	1305-62-0	TWA	5 mg/m3	ACGIH
_		TWA (total	15 mg/m3	OSHA Z-1



CALCINATE ™ C-300R

Version: 1.1 Revision Date: 03/31/2015 Print Date: 04/21/2015

dust)		
TWA (respirable fraction)	5 mg/m3	OSHA Z-1
TWA	5 mg/m3	OSHA P0
TWA	5 mg/m3	NIOSH REL

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

In the case of respirable dust and/or fumes, use self-contained

breathing apparatus.

Hand protection

Remarks : Impervious gloves

Eye protection : Safety glasses with side-shields

Skin and body protection : impervious clothing

Hygiene measures : Electrically bond and ground all containers and equipment.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

Color : brown

Odor : mild hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Melting point/range

No data available

Boiling point/boiling range : No data available

Evaporation rate : No data available

Flash point : > 180 °C

Method: open cup

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : < 0.0008 hPa (20 °C)

Relative vapour density : No data available

Relative density : > 1 (25 °C)

Density : No data available

SAP 6.0 SDS 2012-2 NA GHS 5 / 10 SDS Number: 400000003938



CALCINATE ™ C-300R

Version: 1.1 Revision Date: 03/31/2015 Print Date: 04/21/2015

Solubility(ies)

Water solubility : negligible
Solubility in other solvents : partly soluble

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available
Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : > 30 mm2/s (40 °C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Hazardous polymerisation does not occur.

Conditions to avoid : Exposure to moisture.

Contamination

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

Carbon oxides

Sulphur oxides Metal oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity (Product) : LD50: > 20,000 mg/kg

Species: Rat

Remarks: Information given is based on data obtained from similar

substances.

Acute dermal toxicity

Benzenesulfonic acid, mono-

alcium Species: Rat

C16-24-alkyl derivs., calcium salts (Component)

Method: OECD Test Guideline 402

Sulfonic acids, petroleum,

SAP 6.0 SDS 2012-2 NA GHS 6/10 SDS Number: 400000003938

: LD50: > 2,000 mg/kg

: LD50: > 4,000 mg/kg



CALCINATE ™ C-300R

Version: 1.1 Revision Date: 03/31/2015 Print Date: 04/21/2015

calcium salts (Component) Species: Rabbit

Method: OECD Test Guideline 402

Skin irritation

calcium carbonate

(Component) Result: No skin irritation

calcium dihydroxide

(Component)

: Result: Irritating to skin.

Species: Rabbit

Eye irritation (Product) : Result: Eye irritation

Classification: Irritating to eyes.

Sensitisation

Benzenesulfonic acid, mono-

C16-24-alkyl derivs., calcium

salts (Component)

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts

(Component)

Sulfonic acids, petroleum, calcium salts (Component)

calcium dihydroxide

(Component)

: Result: Probability or evidence of low to moderate skin sensitisation rate

in humans

: Result: Probability or evidence of low to moderate skin sensitisation rate

in humans

: Result: Probability or evidence of low to moderate skin sensitisation rate

: Classification: Did not cause sensitisation on laboratory animals.

in humans

(Component)

Reproductive toxicity calcium carbonate

calcium carbonate

(Component)

: Species: Rat

Application Route: Oral

Aspiration toxicity (Product) : No aspiration toxicity classification

CMR effects

calcium carbonate (Component)

: Teratogenicity: No effects on or via lactation Reproductive toxicity: No toxicity to reproduction

Further information (Product) : No data is available on the product itself.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity effects

Toxicity to fish (Product) : Remarks:

No data available

SAP 6.0 SDS 2012-2 NA GHS 7 / 10 SDS Number: 400000003938



CALCINATE ™ C-300R

Version: 1.1 Revision Date: 03/31/2015 Print Date: 04/21/2015

Toxicity to daphnia and other aquatic invertebrates
Sulfonic acids, petroleum, : EC50: > 100 mg/l
calcium salts (Component) Exposure time: 48 h

Species: Daphnia magna (Water flea) static test Method: OECD Test Guideline 202

Toxicity to algae

Sulfonic acids, petroleum, : EbC50: > 100 mg/l calcium salts (Component) Exposure time: 72 h

Species: Green algae (Scenedesmus subspicatus)

static test Analytical monitoring: no Method: OECD Test Guideline 201

ErC50: > 100 mg/l

Species: Green algae (Scenedesmus subspicatus)

static test Analytical monitoring: no Method: OECD Test Guideline 201

Elimination information (persistence and degradability)

Bioaccumulation (Product) : Remarks:

No data available

Mobility (Product) : Remarks:

No data available

Biodegradability (Product) : Result: No data available

Further information on ecology

Ecotoxicology Assessment

Acute aquatic toxicity

calcium dihydroxide : Harmful to aquatic life.

(Component)

calcium dihydroxide

(Component)

calcium dihydroxide (Component)

calcium dihydroxide (Component) calcium dihydroxide

(Component)

Results of PBT assessment (Product)

This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).

Additional ecological : The product itself has not been tested.

information (Product)



CALCINATE ™ C-300R

Version: 1.1 Revision Date: 03/31/2015 Print Date: 04/21/2015

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : In accordance with local and national regulations.

SECTION 14. TRANSPORT INFORMATION

ADR

Not dangerous goods

RID

Not dangerous goods

MERCOSUR

Not dangerous goods

DOT

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

Additional advice: Not classified as dangerous in the meaning of transport regulations.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
naphthalene	91-20-3	100	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard





	CALCINATE ™ C-300R	
Version: 1.1	Revision Date: 03/31/2015	Print Date: 04/21/2015

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65 WARNING! This product contains a chemical known to the

State of California to cause cancer.

naphthalene 91-20-3

The components of this product are reported in the following inventories:

US.TSCA On TSCA Inventory

All components of this product are on the Canadian DSL.

AICS
On the inventory, or in compliance with the inventory

NZIOC
On the inventory, or in compliance with the inventory

ENCS
On the inventory, or in compliance with the inventory

KECI
On the inventory, or in compliance with the inventory

PICCS
On the inventory, or in compliance with the inventory

On the inventory, or in compliance with the inventory

IECSC
On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Further information

Other Emergency Phone Number

Latin America:	Brazil	+55 113 711 9144
	All other countries	+44 (0) 1235 239 670
Mexico:		+52 555 004 8763

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.