Capstone™ ST-300 Protector



Revision Date: Date of last issue: 03/12/2021 03/12/2021 Date of first issue: 03/12/2021

SECTION 1. IDENTIFICATION

Product name : Capstone™ ST-300 Protector

Other means of identification : No data available

SDS-Identcode : 130000052151

Manufacturer or supplier's details

Company name of supplier : ChemPoint

Address : 411 108th Ave NE Suite 1050

Bellevue WA 98004

Telephone : 1-800-485-9569

Emergency telephone : 1-888-226-8832 (1-888-CAN-UTEC) (24 hours)

Recommended use of the chemical and restrictions on use

Recommended use : Stain and soil repellent

Impregnation agents

Restrictions on use : For industrial use only., Do not use this product in consumer

spray applications except in water-based coatings where the maximum concentration of active ingredient does not exceed

0.1 wt percent.

Do not use or resell materials in medical applica-tions involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a

written agreement covering such use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Acute toxicity (Inhalation) : Category 1

Skin sensitization : Sub-category 1A

Specific target organ toxicity : 0

- repeated exposure

Category 2 (Liver)

GHS label elements

Hazard pictograms







Capstone™ ST-300 Protector

Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.

H330 Fatal if inhaled.

H373 May cause damage to organs (Liver) through prolonged or

repeated exposure.

Precautionary Statements : Prevention:

P260 Do not breathe mist or vapors.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear protective gloves. P284 Wear respiratory protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER.

P314 Get medical attention if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical atten-

tion.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

Other hazards

Inhalation of decomposition products in high concentration may cause shortness of breath (lung edema).

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Partially fluorinated alcohol, reaction	Accession	
	number:	>= 10 - < 30 *
(P2O5), ammonium salts	18253-1	
2-Methyl-2H-isothiazol-3-one	2682-20-4	>= 0.0015 - < 0.1 *

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical ad-

Capstone™ ST-300 Protector

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled If inhaled, remove to fresh air.

> If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

In case of skin contact In case of contact, immediately flush skin with soap and plenty

of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

Flush eyes with water as a precaution. In case of eye contact

Get medical attention if irritation develops and persists.

If swallowed If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms

delayed

and effects, both acute and

Irritation

Shortness of breath

Cough Lung edema

Eye contact may provoke the following symptoms

Inhalation may provoke the following symptoms:

Lachrymation Redness Discomfort

May cause an allergic skin reaction.

Fatal if inhaled.

May cause damage to organs through prolonged or repeated

exposure.

Protection of first-aiders First Aid responders should pay attention to self-protection,

> and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Water spray

> Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire Exposure to combustion products may be a hazard to health.

Capstone™ ST-300 Protector

fighting

Hazardous combustion prod: :

ucts

Hydrogen fluoride carbonyl fluoride

potentially toxic fluorinated compounds

aerosolized particulates

Carbon oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

Evacuate area.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer-

gency procedures

Evacuate personnel to safe areas.

Only trained personnel should re-enter the area.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up Soak up with inert absorbent material.

For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Capstone™ ST-300 Protector

Advice on safe handling Do not get on skin or clothing.

Do not breathe mist or vapors.

Do not swallow.

Avoid contact with eyes.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Keep container tightly closed.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage Keep in properly labeled containers.

> Store locked up. Keep tightly closed.

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Materials to avoid Do not store with the following product types:

> Strong oxidizing agents Flammable liquids Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures which in contact with water emit

flammable gases **Explosives**

Gases

Recommended storage tem- :

perature

4 - 50 °C

Further information on stor- : Perishable if frozen.

age stability

Do not freeze.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrofluoric acid	7664-39-3	TWA	0.5 ppm 0.4 mg/m³ (Fluorine)	CA AB OEL
		(c)	2 ppm 1.6 mg/m³	CA AB OEL

Capstone™ ST-300 Protector

	1	1	(Fluorine)	1
		С	2 ppm (Fluorine)	CA BC OEL
		С	3 ppm 2.6 mg/m³ (Fluorine)	CA QC OEL
		TWA	0.5 ppm (Fluorine)	ACGIH
		С	2 ppm (Fluorine)	ACGIH
Carbonyl difluoride	353-50-4	TWA	2 ppm 5.4 mg/m³	CA AB OEL
		STEL	5 ppm 13 mg/m³	CA AB OEL
		TWA	2 ppm	CA BC OEL
		STEL	5 ppm	CA BC OEL
		STEV	5 ppm 13 mg/m³	CA QC OEL
		TWAEV	2 ppm 5.4 mg/m³	CA QC OEL
		TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
Carbon dioxide	124-38-9	STEL	30,000 ppm 54,000 mg/m ³	CA AB OEL
		TWA	5,000 ppm 9,000 mg/m ³	CA AB OEL
		TWA	5,000 ppm	CA BC OEL
		STEL	15,000 ppm	CA BC OEL
		TWAEV	5,000 ppm 9,000 mg/m³	CA QC OEL
		STEV	30,000 ppm 54,000 mg/m ³	CA QC OEL
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
Carbon monoxide	630-08-0	TWA	25 ppm 29 mg/m³	CA AB OEL
		TWA	25 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL
		TWAEV	35 ppm 40 mg/m ³	CA QC OEL
		STEV	200 ppm 230 mg/m³	CA QC OEL
		TWA	25 ppm	ACGIH

Engineering measures

Processing may form hazardous compounds (see section

10).

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Personal protective equipment

Respiratory protection

If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the re-

Capstone™ ST-300 Protector

commended guidelines, use respiratory protection.

Filter type : Combined particulates and acidic gas/vapor type

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks

and at the end of workday.

Eye protection : Wear the following personal protective equipment:

Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the wor-

king place.

When using do not eat, drink or smoke.

Contaminated work clothing should not be allowed out of the

workplace.

Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

Color : amber

Odor : odorless

Odor Threshold : No data available

pH : 7-9

Melting point/freezing point : No data available

Initial boiling point and boiling : 100 °C

range

Capstone™ ST-300 Protector

: does not flash Flash point

Evaporation rate No data available

Flammability (solid, gas) Not applicable

Flammability (liquids) No data available

Upper explosion limit / Upper :

flammability limit

No data available

Lower explosion limit / Lower : No data available

flammability limit

Vapor pressure : 1.1 hPa

(for a component of this mixture)

Relative vapor density No data available

Relative density 1.1

1.2 g/cm³ Density

Solubility(ies)

Water solubility soluble

Partition coefficient: n-

octanol/water

Not applicable

Autoignition temperature No data available

Decomposition temperature > 200 °C

Viscosity

Viscosity, kinematic No data available

Explosive properties Not explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

Particle size Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity Not classified as a reactivity hazard.

Chemical stability Stable under normal conditions.

Possibility of hazardous reac-

tions

Can react with strong oxidizing agents.

Hazardous decomposition products will be formed at elevated

temperatures.

Conditions to avoid None known.

Capstone™ ST-300 Protector

Incompatible materials : Oxidizing agents

Hazardous decomposition products

Thermal decomposition : Hydrofluoric acid

Carbonyl difluoride Carbon dioxide Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Fatal if inhaled.

Product:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate (Rat): 0.005 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgment

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Components:

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts:

Acute oral toxicity : LD50 (Rat): > 1,000 mg/kg

Method: OECD Test Guideline 425

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : Approximate Lethal Concentration (Rat): 0.047 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 1,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

2-Methyl-2H-isothiazol-3-one:

Acute oral toxicity : LD50 (Rat): 120 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.11 mg/l

Capstone™ ST-300 Protector

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 (Rat): 242 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Product:

Species : Rabbit

Result : No skin irritation

Components:

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

2-Methyl-2H-isothiazol-3-one:

Result : Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Species : Rabbit

Result : No eye irritation

Components:

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

2-Methyl-2H-isothiazol-3-one:

Result : Irreversible effects on the eye

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Capstone™ ST-300 Protector

Components:

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

2-Methyl-2H-isothiazol-3-one:

Routes of exposure : Skin contact
Result : positive

Assessment : Probability or evidence of high skin sensitization rate in hu-

mans

Germ cell mutagenicity

Not classified based on available information.

Components:

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Germ cell mutagenicity -

Assessment

: Weight of evidence does not support classification as a germ

cell mutagen.

2-Methyl-2H-isothiazol-3-one:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with

mammalian liver cells in vivo

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 486

Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Capstone™ ST-300 Protector

Components:

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 415

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

Reproductive toxicity - As-

sessment

Weight of evidence does not support classification for repro-

ductive toxicity

2-Methyl-2H-isothiazol-3-one:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion
Method: OECD Test Guideline 414

Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs (Liver) through prolonged or repeated exposure.

Components:

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts:

Routes of exposure : Ingestion Target Organs : Liver

Assessment : Shown to produce significant health effects in animals at con-

centrations of >10 to 100 mg/kg bw.

Capstone™ ST-300 Protector

Repeated dose toxicity

Components:

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts:

Species Rat, male and female

LOAEL 3.6 mg/kg Application Route Ingestion Exposure time 90 Days

Method **OECD Test Guideline 408**

Remarks Based on data from similar materials

Species Rat, male NOAEL : 100 mg/kg : 1,000 mg/kg LOAEL Application Route : Skin contact Exposure time : 28 Days

Method : OECD Test Guideline 410

Remarks Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to soil dwelling or-

ganisms

LC50 (Eisenia fetida (earthworms)): > 1,000 mg/kg

Exposure time: 14 d

NOEC (Eisenia fetida (earthworms)): 125 mg/kg

LOEC (Eisenia fetida (earthworms)): 250 mg/kg

Components:

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium

: LC50 (Oncorhynchus mykiss (rainbow trout)): > 36.4 mg/l Toxicity to fish

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 3.24 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): >

22.44 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Capstone™ ST-300 Protector

Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 22.44

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus mykiss (rainbow trout)): 0.88 mg/l

Exposure time: 90 d

Method: OECD Test Guideline 210

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.0093 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

2-Methyl-2H-isothiazol-3-one:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.77 - 6 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.93 - 1.9 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

ErC50 (Skeletonema costatum (marine diatom)): 0.1 mg/l

Exposure time: 72 h

ErC50 (Skeletonema costatum (marine diatom)): 0.0695 mg/l

Exposure time: 24 h

EC10 (Pseudokirchneriella subcapitata (green algae)): 0.024

mg/l

Exposure time: 24 h

Toxicity to fish (Chronic tox-

icity)

NOEC (Pimephales promelas (fathead minnow)): 2.1 mg/l

Exposure time: 33 d

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.04 mg/l

Exposure time: 21 d

Persistence and degradability

Components:

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts:

Biodegradability : Result: Not readily biodegradable.

Method: OECD Test Guideline 301D

Remarks: Based on data from similar materials

2-Methyl-2H-isothiazol-3-one:

Capstone™ ST-300 Protector

Biodegradability : Result: Not readily biodegradable.

Bioaccumulative potential

Components:

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)

Bioconcentration factor (BCF): 4

Remarks: Based on data from similar materials

2-Methyl-2H-isothiazol-3-one:

Partition coefficient: n-

octanol/water

log Pow: -0.34

Mobility in soil

No data available

Other adverse effects

Components:

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium

Additional ecological infor-

mation

Information given is based on data on the ingredients and the

ecotoxicology of similar products.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S

(Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts)

Class : 9
Packing group : III
Labels : 9

IATA-DGR

Capstone™ ST-300 Protector

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(Partially fluorinated alcohol, reaction products with phospho-

rus oxide (P2O5), ammonium salts)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo

aircraft)

Packing instruction (passen- : 964

ger aircraft)

Environmentally hazardous : yes

IMDG-Code

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

964

(Partially fluorinated alcohol, reaction products with phospho-

rus oxide (P2O5), ammonium salts)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Partially fluorinated alcohol, reaction products with phospho-

rus oxide (P2O5), ammonium salts)

Class : 9
Packing group : III
Labels : 9
ERG Code : 171

Marine pollutant : yes(Partially fluorinated alcohol, reaction products with phos-

phorus oxide (P2O5), ammonium salts)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Additional regulatory information

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts

Capstone™ ST-300 Protector

This product contains a substance subject to a Significant New Activity (SNAc) as disclosed in the Canada Gazette.

SECTION 16. OTHER INFORMATION

Capstone™ is a trademark or copyright of The Chemours Company FC, LLC. Before use read safety information.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA QC OEL : Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

ACGIH / C : Ceiling limit

CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit
CA AB OEL / (c) : ceiling occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA BC OEL / STEL : short-term exposure limit

CA BC OEL / C : ceiling limit

CA QC OEL / TWAEV : Time-weighted average exposure value

CA QC OEL / STEV : Short-term exposure value

CA QC OEL / C : Ceiling

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumu-

Capstone™ ST-300 Protector

lative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 03/12/2021 Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8