

**METHOCEL K15MS**

Cellulose Ether

**General
Description**

METHOCEL K15MS is a cold water dispersible cellulose ether for the construction industry.

**Industrial
Applications**

This product is especially suitable for use in mortars and in manual and spray plasters. The product imparts good workability to the building materials and enhances water retention considerably. Due to its cold water dispersibility, it reduces lump formation.

Typical Properties

Viscosity Ubbelohde [mPa·s] 2% in water @ 20°C	13000
Moisture Content [%]	< 5.0
Sodium Chloride [%]	< 2.0
Particle Size [%] < 70 U.S. Standard Sieve, 212 µm	> 95

Safety and Handling For specific safe use and handling information, or to obtain a Materials Safety Data Sheet, contact your local Dow representative.

Contact us:
North America: 1-800-447-4369
Europe: +800 3 694 6367
+32 3 450 2240

www.methocel.com

NOTICE: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.