



SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY*

Product name: ADCOTE™ 503E

Issue Date: 04/27/2015

Print Date: 09/18/2015

THE DOW CHEMICAL COMPANY* encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: ADCOTE™ 503E

Recommended use of the chemical and restrictions on use

Identified uses: Adhesives.

COMPANY IDENTIFICATION

THE DOW CHEMICAL COMPANY*
Agent for Rohm and Haas Chemicals LLC
100 INDEPENDENCE MALL WEST
PHILADELPHIA PA 19106-2399
UNITED STATES

Customer Information Number:

215-592-3000

SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 1 800 424 9300

Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

This material is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Flammable liquids - Category 2

Specific target organ toxicity - single exposure - Category 3

Label elements

Hazard pictograms



Signal word: **DANGER!**

Hazards

Highly flammable liquid and vapour.
May cause drowsiness or dizziness.

Precautionary statements**Prevention**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting/ equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ eye protection/ face protection.

Response

IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage

Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

no data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Polyester resin solvent based

This product is a mixture.

Component	CASRN	Concentration
Polyester resin(s)	Not Hazardous	28.0 - 30.0 %
Epoxy resin	Not Hazardous	11.0 - 13.0 %
Ethyl acetate	141-78-6	59.0 - 61.0 %

4. FIRST AID MEASURES

Description of first aid measures

Inhalation: Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. Immediate medical attention is required.

Skin contact: Take off all contaminated clothing immediately. Wash off immediately with soap and plenty of water. Consult a physician. Wash contaminated clothing before re-use.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.

Ingestion: Never give anything by mouth to an unconscious person. If a person vomits when lying on his back, place him in the recovery position. Drink 1 or 2 glasses of water. Call a physician immediately.

Most important symptoms and effects, both acute and delayed: Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Treatment should be directed at preventing absorption, administering to symptoms (if they occur), and providing supportive therapy.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Foam Carbon dioxide (CO2) Dry powder Water spray

Unsuitable extinguishing media: no data available

Special hazards arising from the substance or mixture

Hazardous combustion products: no data available

Unusual Fire and Explosion Hazards: Vapors can travel to a source of ignition and flash back. Heated material can form flammable or explosive vapors with air. Closed containers may rupture via pressure build-up when exposed to fire or extreme heat.

Advice for firefighters

Fire Fighting Procedures: For safety reasons in case of fire, containers should be stored separately in closed containments. Cool closed containers exposed to fire with water spray.

Special protective equipment for firefighters: Wear self-contained breathing apparatus and protective suit.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Remain upwind. Avoid breathing smoke. Remove all sources of ignition.

Environmental precautions: Do not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up: Evacuate personnel to safe areas. Remove all sources of ignition. Ensure adequate ventilation. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

7. HANDLING AND STORAGE

Precautions for safe handling: Provide sufficient air exchange and/or exhaust in work rooms. Avoid exceeding the given occupational exposure limits (see section 8). In case of insufficient ventilation, wear suitable respiratory equipment. Wear personal protective equipment. For personal protection see section 8. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all MSDS and label warnings even after container is emptied.

Conditions for safe storage: Material can burn; limit indoor storage to approved areas equipped with automatic sprinklers. Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Electrical installations / working materials must comply with the technological safety standards.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits are listed below, if they exist.

Component	Regulation	Type of listing	Value/Notation
Ethyl acetate	Rohm and Haas	TWA	150 ppm
	Rohm and Haas	STEL	300 ppm
	ACGIH	TWA	400 ppm
	OSHA Z-1	TWA	1,400 mg/m3 400 ppm

Exposure controls

Engineering controls: Use explosion-proof local exhaust ventilation with a minimum capture velocity of 100 ft/min (0.5 m/sec) at the point of vapor evolution. Refer to the current edition of Industrial Ventilation: A Manual of Recommended Practice published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

Hygiene measures: Wash hands before breaks and immediately after handling the product.

Protective measures: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Individual protection measures

Eye/face protection: Chemical resistant goggles must be worn. Eye protection worn must be compatible with respiratory protection system employed.

Skin protection

Hand protection: Chemical-resistant gloves should be worn whenever this material is handled. The glove(s) listed below may provide protection against permeation. (Gloves of other chemically resistant materials may not provide adequate protection): 4H Glove (Trademark of Safety 4 A/S of Denmark) Norfoil (Trademark of Siebe North, Inc.) Gloves should be removed and replaced immediately if there is any indication of

degradation or chemical breakthrough. Before removing gloves clean them with soap and water.

Respiratory protection: A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements or equivalent must be followed whenever workplace conditions warrant a respirator's use. None required under normal operating conditions. Where vapors and/or mists may occur, wear a properly fitted NIOSH approved (or equivalent) half-mask, air-purifying respirator. Air-purifying respirators should be equipped with NIOSH approved (or equivalent) organic vapor cartridges and N95 filters. If oil mist is present, use R95 or P95 filters.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	liquid
Color	amber
Odor	Solvent odor
Odor Threshold	no data available
pH	Not Applicable
Melting point/range	-84.00 °C (-119.20 °F) Ethyl acetate
Freezing point	no data available
Boiling point (760 mmHg)	77.00 °C (170.60 °F) Ethyl acetate
Flash point	closed cup -4.00 °C (24.80 °F) <i>SETAFLASH CLOSED CUP</i>
Evaporation Rate (Butyl Acetate = 1)	6.20 Ethyl acetate
Flammability (solid, gas)	Not Applicable
Lower explosion limit	2.20 % vol Ethyl acetate
Upper explosion limit	11.50 % vol Ethyl acetate
Vapor Pressure	73.0000000 mmHg at 20.00 °C (68.00 °F) Ethyl acetate
Relative Vapor Density (air = 1)	3.0400 Ethyl acetate
Relative Density (water = 1)	1.0100
Water solubility	insoluble
Partition coefficient: n-octanol/water	no data available
Auto-ignition temperature	426.00 °C (798.80 °F) Ethyl acetate
Decomposition temperature	no data available
Dynamic Viscosity	no data availableno data available
Kinematic Viscosity	no data available
Explosive properties	no data available
Oxidizing properties	no data available
Molecular weight	no data available
Percent volatility	58.00 - 62.00 %
Volatile Organic Compounds	605 g/L <i>Calculated.</i>

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: no data available

Chemical stability: no data available

Possibility of hazardous reactions: This material is considered stable. However, avoid contact with ignition sources (e.g. sparks, open flame, heated surfaces).
Product will not undergo polymerization.

Conditions to avoid: Heat, flames and sparks.

Incompatible materials: no data available

Hazardous decomposition products: no data available

11. TOXICOLOGICAL INFORMATION

Toxicological information on this product or its components appear in this section when such data is available.

Acute toxicity

Acute oral toxicity

Product test data not available.

Acute dermal toxicity

Product test data not available.

Acute inhalation toxicity

Product test data not available.

Skin corrosion/irritation

Product test data not available.

Serious eye damage/eye irritation

Product test data not available.

Sensitization

Product test data not available.

Specific Target Organ Systemic Toxicity (Single Exposure)

Product test data not available.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Product test data not available.

Carcinogenicity

Product test data not available.

Teratogenicity

Product test data not available.

Reproductive toxicity

Product test data not available.

Mutagenicity

Product test data not available.

Aspiration Hazard

Product test data not available.

Additional information

No toxicity data are available for this material.

COMPONENTS INFLUENCING TOXICOLOGY:

Polyester resin(s)

Acute oral toxicity

Single dose oral LD50 has not been determined.

Acute dermal toxicity

The dermal LD50 has not been determined.

Acute inhalation toxicity

The LC50 has not been determined.

Ethyl acetate

Acute oral toxicity

LD50, Rabbit, 4,934 mg/kg

Acute dermal toxicity

LD50, Rabbit, > 17,900 mg/kg

Acute inhalation toxicity

Prolonged excessive exposure may cause adverse effects. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness. May cause respiratory irritation and central nervous system depression.

LC50, Rat, 4 Hour, vapour, > 28.6 mg/l

Skin corrosion/irritation

Essentially nonirritating to skin.
May cause drying and flaking of the skin.

Serious eye damage/eye irritation

May cause slight eye irritation.
May cause slight temporary corneal injury.
Vapor may cause eye irritation experienced as mild discomfort and redness.

Sensitization

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

May cause drowsiness or dizziness.

Route of Exposure: Inhalation

Target Organs: Nervous system

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Symptoms of excessive exposure may be anesthetic or narcotic effects; dizziness and drowsiness may be observed.

In animals, effects have been reported on the following organs:

Liver.

Respiratory tract.

Carcinogenicity

For the hydrolysis product: Ethanol when not consumed in an alcoholic beverage is not classifiable as a human carcinogen.

Teratogenicity

Relevant data not available.

Reproductive toxicity

Relevant data not available.

Mutagenicity

In vitro genetic toxicity studies were predominantly negative. Animal genetic toxicity studies were negative.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicological information on this product or its components appear in this section when such data is available.

General Information

There is no data available for this product.

Toxicity

Polyester resin(s)

Acute toxicity to fish

No relevant data found.

Ethyl acetate

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

LC50, Pimephales promelas (fathead minnow), 96 Hour, 230 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 24 Hour, 3,090 mg/l, DIN 38412

Acute toxicity to algae/aquatic plants

NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, > 100 mg/l, OECD Test Guideline 201

EbC50, alga Scenedesmus sp., static test, 48 Hour, Biomass, 3,300 mg/l

Chronic toxicity to fish

NOEC, Pimephales promelas (fathead minnow), 32 d, < 9.65 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, 2.4 mg/l

Persistence and degradability**Polyester resin(s)**

Biodegradability: No relevant data found.

Ethyl acetate

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

Biodegradation: 100 %

Exposure time: 28 d

Method: OECD Test Guideline 301D or Equivalent

Theoretical Oxygen Demand: 1.82 mg/mg

Bioaccumulative potential**Polyester resin(s)**

Bioaccumulation: No relevant data found.

Ethyl acetate

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 0.68 Measured

Bioconcentration factor (BCF): 30 Fish. Measured

Mobility in soil**Polyester resin(s)**

No relevant data found.

Ethyl acetate

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient(Koc): 3 Estimated.

13. DISPOSAL CONSIDERATIONS

Disposal methods: For disposal, incinerate this material at a facility that complies with local, state, and federal regulations. (See 40 CFR 268)

14. TRANSPORT INFORMATION

DOT

Proper shipping name	Resin solution
UN number	UN 1866
Class	3
Packing group	II
Reportable Quantity	Ethyl acetate

Classification for SEA transport (IMO-IMDG):

Proper shipping name	RESIN SOLUTION
UN number	UN 1866
Class	3
Packing group	II
Marine pollutant	No
Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Proper shipping name	Resin solution
UN number	UN 1866
Class	3
Packing group	II

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

OSHA Hazard Communication Standard

This product is considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Fire Hazard

Acute Health Hazard

Chronic Health Hazard

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This product does not contain a chemical which is listed in Section 313 at or above de minimis concentrations.

Pennsylvania

Any material listed as "Not Hazardous" in the CAS REG NO. column of SECTION 2, Composition/Information On Ingredients, of this MSDS is a trade secret under the provisions of the Pennsylvania Worker and Community Right-to-Know Act.

California (Proposition 65)

This product contains trace levels of a component or components known to the state of California to cause cancer and birthdefects or other reproductive harm:

Components**CASRN**

Benzene

71-43-2

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System**HMIS**

Health	Flammability	Physical Hazard
2*	3	0

* = Chronic Effects (See Hazards Identification)

Revision

Identification Number: 101112018 / 1001 / Issue Date: 04/27/2015 / Version: 3.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
Rohm and Haas	Rohm and Haas OEL's
STEL	Short term exposure limit
TWA	Time weighted average

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY* urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.