

SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY

Product name: UCON™ Lubricant LB-165

Issue Date: 06/15/2018 Print Date: 09/11/2018

THE DOW CHEMICAL COMPANY encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: UCON™ Lubricant LB-165

Recommended use of the chemical and restrictions on use

Identified uses: Selection of the appropriate polyglycol product for a specific application requires knowledge of the fluid requirements of the application, awareness of the most important of these requirements, and a match-up with the properties of the various polyglycol materials. Polyglycol products can be formulated for use in numerous industry applications such as hydraulic fluids, quenchants, compressor and refrigeration lubricants, heat transfer fluids, machinery lubricants, solder assist fluids, metalworking lubricants, textile finishing, etc. We recommend that you use this product in a manner consistent with the listed use. If your intended use is not consistent with the stated use, please contact your sales or technical service representative.

COMPANY IDENTIFICATION

THE DOW CHEMICAL COMPANY 2030 DOW CENTER MIDLAND MI 48674-0000 UNITED STATES

Customer Information Number:

800-258-2436 SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: CHEMTREC +1 800-424-9300 Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with 29 CFR 1910.1200 Not a hazardous substance or mixture.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms: Polypropylene glycol

| Component | CASRN | Concentration |
|--------------------------------------|-----------|---------------|
| | | |
| Polypropylene glycol monobutyl ether | 9003-13-8 | 100.0% |

4. FIRST AID MEASURES

Description of first aid measures

General advice:

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin contact: Wash off with plenty of water.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Unsuitable extinguishing media: Do not use direct water stream. May spread fire.

Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Do not use direct water stream. May spread fire. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage.

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection. Refer to section 7, Handling, for additional precautionary measures.

Environmental precautions: Material will float on water. Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up: Contain spilled material if possible. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

7. HANDLING AND STORAGE

Precautions for safe handling: Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Conditions for safe storage: Store in the following material(s): 316 stainless steel. Carbon steel. Glass-lined container. Polypropylene. Polyethylene-lined container. Stainless steel. Teflon. This material may soften and lift certain paint and surface coatings. Use product promptly after opening. Store in original unopened container. Unopened containers of material stored beyond the recommended shelf life should be retested against the sales specifications before use. Additional storage and handling information on this product may be obtained by calling your sales or customer service contact.

Storage stability

Shelf life: Use within 24 Month

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields).

Skin protection

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Butyl rubber. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Neoprene. Natural rubber ("latex"). Polyvinyl chloride ("PVC" or "vinyl"). Nitrile/butadiene rubber ("nitrile" or "NBR"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Wear clean, body-covering clothing.

Respiratory protection: Under intended handling conditions, no respiratory protection should be needed.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

| Physical stateLiquid.ColorColorless to yellowOdorMildOdor ThresholdNo test data availablepH5.0 - 8.5 ASTM E70 (16.7% in isopropanol/water, 10:6)Melting point/rangeNo test data availableFreezing pointSee Pour PointBoiling point (760 mmHg)> 200 °C (> 392 °F) Calculated.Flash pointclosed cup 191 °C (376 °F) ASTM D 93Evaporation Rate (Butyl Acetate = 1)No test data availableFlammability (solid, gas)Not est data availableLower explosion limitNo test data availableVapor Pressure< 0.01 mmHg at 20 °C (68 °F) ASTM E1719 | Appearance | |
|--|----------------------------------|---|
| OdorMildOdor ThresholdNo test data availablepH5.0 - 8.5 ASTM E70 (16.7% in isopropanol/water, 10:6)Melting point/rangeNo test data availableFreezing pointSee Pour PointBoiling point (760 mmHg)> 200 °C (> 392 °F) Calculated.Flash pointclosed cup 191 °C (376 °F) ASTM D 93Evaporation Rate (Butyl AcetateNo test data available= 1)No test data availableFlammability (solid, gas)Not applicable to liquidsLower explosion limitNo test data availableVapor Pressure< 0.01 mmHg at 20 °C (68 °F) ASTM E1719Relative Density (water = 1).983 at 20 °C (68 °F) / 20 °C Calculated.Water solubility< 0.1 % VisualPartition coefficient: n- octanol/waterNo data available | Physical state | Liquid. |
| Odor ThresholdNo test data availablepH5.0 - 8.5 ASTM E70 (16.7% in isopropanol/water, 10:6)Melting point/rangeNo test data availableFreezing pointSee Pour PointBoiling point (760 mmHg)> 200 °C (> 392 °F) Calculated.Flash pointclosed cup 191 °C (376 °F) ASTM D 93Evaporation Rate (Butyl AcetateNo test data available= 1)No test data availableFlammability (solid, gas)Not applicable to liquidsLower explosion limitNo test data availableUpper explosion limitNo test data availableVapor Pressure< 0.01 mmHg at 20 °C (68 °F) ASTM E1719Relative Density (water = 1)0.983 at 20 °C (68 °F) / 20 °C Calculated.Water solubility< 0.1 % VisualPartition coefficient: n- octanol/waterNo data available | Color | Colorless to yellow |
| pH5.0 - 8.5 ASTM E70 (16.7% in isopropanol/water, 10:6)Melting point/rangeNo test data availableFreezing pointSee Pour PointBoiling point (760 mmHg)> 200 °C (> 392 °F) Calculated.Flash pointclosed cup 191 °C (376 °F) ASTM D 93Evaporation Rate (Butyl Acetate = 1)No test data availableFlammability (solid, gas)Not applicable to liquidsLower explosion limitNo test data availableUpper explosion limitNo test data availableVapor Pressure< 0.01 mmHg at 20 °C (68 °F) ASTM E1719 | Odor | Mild |
| Melting point/rangeNo test data availableFreezing pointSee Pour PointBoiling point (760 mmHg)> 200 °C (> 392 °F) Calculated.Flash pointclosed cup 191 °C (376 °F) ASTM D 93Evaporation Rate (Butyl Acetate = 1)No test data availableFlammability (solid, gas)Not applicable to liquidsLower explosion limitNo test data availableUpper explosion limitNo test data availableVapor Pressure< 0.01 mmHg at 20 °C (68 °F) ASTM E1719 | Odor Threshold | No test data available |
| Freezing pointSee Pour PointBoiling point (760 mmHg)> 200 °C (> 392 °F) Calculated.Flash pointclosed cup 191 °C (376 °F) ASTM D 93Evaporation Rate (Butyl Acetate = 1)No test data availableFlammability (solid, gas)Not applicable to liquidsLower explosion limitNo test data availableUpper explosion limitNo test data availableVapor Pressure< 0.01 mmHg at 20 °C (68 °F) ASTM E1719Relative Vapor Density (air = 1)>1 Calculated.Relative Density (water = 1)0.983 at 20 °C (68 °F) / 20 °C Calculated.Water solubility< 0.1 % VisualPartition coefficient: n- octanol/waterNo data available | рН | 5.0 - 8.5 ASTM E70 (16.7% in isopropanol/water, 10:6) |
| Boiling point (760 mmHg)> 200 °C (> 392 °F) Calculated.Flash pointclosed cup 191 °C (376 °F) ASTM D 93Evaporation Rate (Butyl Acetate = 1)No test data availableFlammability (solid, gas)Not applicable to liquidsLower explosion limitNo test data availableUpper explosion limitNo test data availableVapor Pressure< 0.01 mmHg at 20 °C (68 °F) ASTM E1719 | Melting point/range | No test data available |
| Flash pointclosed cup 191 °C (376 °F) ASTM D 93Evaporation Rate (Butyl Acetate = 1)No test data availableFlammability (solid, gas)Not applicable to liquidsLower explosion limitNo test data availableUpper explosion limitNo test data availableVapor Pressure< 0.01 mmHg at 20 °C (68 °F) ASTM E1719Relative Vapor Density (air = 1)>1 Calculated.Relative Density (water = 1)0.983 at 20 °C (68 °F) / 20 °C Calculated.Water solubility< 0.1 % VisualPartition coefficient: n- octanol/waterNo data available | Freezing point | See Pour Point |
| Evaporation Rate (Butyl Acetate = 1)No test data availableFlammability (solid, gas)Not applicable to liquidsLower explosion limitNo test data availableUpper explosion limitNo test data availableVapor Pressure< 0.01 mmHg at 20 °C (68 °F) ASTM E1719 | Boiling point (760 mmHg) | > 200 °C (> 392 °F) Calculated. |
| = 1)Flammability (solid, gas)Lower explosion limitUpper explosion limitVapor Pressure< 0.01 mmHg at 20 °C (68 °F) ASTM E1719Relative Vapor Density (air = 1)Relative Density (water = 1)Water solubility< 0.1 % VisualPartition coefficient: n- octanol/water | Flash point | closed cup 191 °C(376 °F) <i>ASTM D 93</i> |
| Lower explosion limitNo test data availableUpper explosion limitNo test data availableVapor Pressure< 0.01 mmHg at 20 °C (68 °F) ASTM E1719 | | No test data available |
| Upper explosion limitNo test data availableVapor Pressure< 0.01 mmHg at 20 °C (68 °F) ASTM E1719 | Flammability (solid, gas) | Not applicable to liquids |
| Vapor Pressure< 0.01 mmHg at 20 °C (68 °F) ASTM E1719 | Lower explosion limit | No test data available |
| Relative Vapor Density (air = 1)>1 Calculated.Relative Density (water = 1)0.983 at 20 °C (68 °F) / 20 °C Calculated.Water solubility< 0.1 % VisualPartition coefficient: n- octanol/waterNo data available | Upper explosion limit | No test data available |
| Relative Density (water = 1)0.983 at 20 °C (68 °F) / 20 °C Calculated.Water solubility< 0.1 % Visual | Vapor Pressure | < 0.01 mmHg at 20 °C (68 °F) ASTM E1719 |
| Water solubility< 0.1 % Visual | Relative Vapor Density (air = 1) | >1 Calculated. |
| Partition coefficient: n- No data available octanol/water No data available | Relative Density (water = 1) | 0.983 at 20 °C (68 °F) / 20 °C Calculated. |
| octanol/water | Water solubility | < 0.1 % Visual |
| Auto-ignition temperature No test data available | | No data available |
| | Auto-ignition temperature | No test data available |

| Decomposition temperature | No test data available |
|----------------------------|--|
| Kinematic Viscosity | 30.8 - 34.1 cSt at 40 °C (104 °F) ASTM D 445 |
| Explosive properties | No test data available |
| Oxidizing properties | No test data available |
| Molecular weight | 740 g/mol Calculated. |
| Pour point | -45.6 °C(-50.1 °F) <i>ASTM D</i> 97 |
| Volatile Organic Compounds | 0.00 g/L EPA Method No. 24 |

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: No data available

Chemical stability: Thermally stable at typical use temperatures.

Possibility of hazardous reactions: Polymerization will not occur.

Conditions to avoid: Exposure to elevated temperatures can cause product to decompose. Generation of gas during decomposition can cause pressure in closed systems.

Incompatible materials: Avoid contact with: Strong acids. Strong bases. Strong oxidizers.

Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Aldehydes. Alcohols. Ethers. Hydrocarbons. Ketones. Organic acids. Polymer fragments.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.

LD50, Rat, 3,815 mg/kg

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

LD50, Rabbit, > 8,000 mg/kg

Acute inhalation toxicity

At room temperature, exposure to vapor is minimal due to low volatility; single exposure is not likely to be hazardous. For respiratory irritation and narcotic effects: No relevant data found. As product: The LC50 has not been determined.

Skin corrosion/irritation

Prolonged contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation

May cause slight temporary eye irritation. Corneal injury is unlikely.

Sensitization

For skin sensitization: No relevant data found.

For respiratory sensitization: No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on available data, repeated exposures to small amounts are not anticipated to cause significant adverse effects.

Carcinogenicity No relevant data found.

Teratogenicity No relevant data found.

Reproductive toxicity

No relevant data found.

Mutagenicity

No relevant data found.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

COMPONENTS INFLUENCING TOXICOLOGY:

Polypropylene glycol monobutyl ether

Acute inhalation toxicity As product: The LC50 has not been determined.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

Acute toxicity to fish

Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested).

LC50, Pimephales promelas (fathead minnow), static test, 96 Hour, 86 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, 250 mg/l, OECD Test Guideline 202 or Equivalent

Toxicity to bacteria

IC50, Bacteria, static test, 16 Hour, Growth inhibition, 1,300 mg/l

Persistence and degradability

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.
10-day Window: Pass
Biodegradation: 99 %
Exposure time: 28 d
Method: OECD Test Guideline 301B or Equivalent

Bioaccumulative potential

Bioaccumulation: No data available for this product.

Mobility in soil

No data available.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device.

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code Not regulated for transport Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312 No SARA Hazards

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Worker and Community Right-To-Know Act:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

California Prop. 65

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System

NFPA

| Health | Flammability | Instability |
|--------|--------------|-------------|
| 0 | 1 | 0 |

Revision

Identification Number: 167551 / A001 / Issue Date: 06/15/2018 / Version: 6.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances: ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation. and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice: HMIS - Hazardous Materials Identification System: IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA -Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA -Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US