



UCON Lubricant LB-300-XY26 and LB-1800-XY26

UCON™ Fluids and Lubricants

Product Description

Water insoluble butanol-propylene oxide polymer based products specially formulated with additives for iron and copper corrosion protection, extreme pressure and high temperature use.

Typical Physical Properties†

	LB-300-XY26	LB-1800-XY26
Appearance		
Viscosity, cSt, 37.8°C (100°F), ASTM D 445	260 – 330	1745 – 1925
Specific Gravity, 20/20°C, ASTM D 4052	0.992	1.006
Pour Point, °C (°F), ASTM D 97	<-26 (<-15)	<-26 (<-15)
Flash Point, Open Cup, °C (°F), ASTM D 92	271 (520)	265 (510)
Water, wt%, ASTM E 203	0.30 max	0.30 max

†Typical physical properties. Not to be construed as specifications.

Product Stewardship

Dow encourages its customers and potential users to review their applications from the standpoint of human health and environmental aspects. To help ensure that Dow products are not used in ways for which they are not intended or tested, Dow personnel will assist customers in dealing with environmental and product safety considerations. Dow literature, including Material Safety Data Sheets, should be consulted prior to the use.

For More Information:

North America: toll-free 1-800-447-4369
 fax 1-989-832-1465
 Europe: toll-free +800 3 694 6367
 call +32 3 450 2240
 fax +32 3 450 2815
 Pacific: call +852 2879 7260
 fax +852 2827 5881
 Other Areas: call 1-989-823-1560
 fax 1-989-832-1465
<http://www.dow.com>

NOTICE: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.



*Trademark of The Dow Chemical Company

Form No. XXX-XXXX-XXX
CH XXX-XXX-E-XXX