

ROYCO LANDING GEAR FLUID YELLOW

Version: 1.1

Revision Date: 12/19/2014

Print Date: 04/14/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: ROYCO LANDING GEAR FLUID YELLOW

Product Use Description: Lubricant

Company: Manufacturer
Anderol Specialty Lubricants, a division of Chemtura Corporation
215 Merry Lane
East Hanover, NJ
07936
United States of America

Telephone: +1 203-573-4596, Toll Free: +1 888-263-3765

Emergency telephone number: CHEMTREC: (24 hours) 800-424-9300
:
: 703-527-3887

For additional emergency telephone numbers see section 16 of the Safety Data Sheet.

Prepared by Product Safety Department
(US) +1 866-430-2775

MSDSRequest@chemtura.com

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

SECTION 2. HAZARDS IDENTIFICATION

Form	liquid
Colour	yellow

GHS Classification

Eye irritation : Category 2A
Aspiration hazard : Category 1
Acute aquatic toxicity : Category 3
Chronic aquatic toxicity : Category 3

GHS Label elementSignal word : **Danger**

ROYCO LANDING GEAR FLUID YELLOW

Version: 1.1

Revision Date: 12/19/2014

Print Date: 04/14/2015

Hazard pictograms

:



Hazard statements

: H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.

Other hazards

: None

Precautionary statements

: **Prevention:**
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear eye protection/ face protection.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331 Do NOT induce vomiting.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
Storage:
P405 Store locked up.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity:

IARC

Group 3: Not classifiable as to its carcinogenicity to humans

Distillates (petroleum), 64742-46-7

hydrotreated middle

Distillates (petroleum), 64742-47-8

hydrotreated light

2,6-di-tert-butyl-p-cresol 128-37-0

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

ROYCO LANDING GEAR FLUID YELLOW

Version: 1.1

Revision Date: 12/19/2014

Print Date: 04/14/2015

Chemical Name	CAS-No.	Concentration (%)
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	>= 50 - < 70 %
Distillates (petroleum), hydrotreated middle	64742-46-7	>= 10 - < 20 %
Distillates (petroleum), hydrotreated light	64742-47-8	>= 5 - < 10 %
NJTS# 136411-5778P Polyolefins		>= 1 - < 5 %
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	68649-42-3	>= 1 - < 5 %
Phenol, isobutylenated, phosphate (3:1)	68937-40-6	>= 0.1 - < 1 %
2,6-di-tert-butyl-p-cresol	128-37-0	>= 0.1 - < 1 %

SECTION 4. FIRST AID MEASURES

- If inhaled : If inhaled
Move to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
In case of bluish discoloration (lips, ear lobes, fingernails), give oxygen as quickly as possible.
If symptoms persist, call a physician.
- In case of skin contact : In case of skin contact
Wash off with soap and water.
Remove contaminated clothing and shoes.
Wash contaminated clothing before re-use.
Get medical attention if irritation develops and persists.
- In case of eye contact : In case of eye contact
Rinse thoroughly with plenty of water, also under the eyelids.
If eye irritation persists, consult a specialist.
- If swallowed : If swallowed, DO NOT induce vomiting.
Consult a physician if necessary.
- Most important symptoms and effects, both acute and delayed : Aspiration may cause pulmonary oedema and pneumonitis.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Carbon dioxide (CO2)
Dry powder
Foam
Alcohol-resistant foam
Water mist
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Burning produces noxious and toxic fumes.
- Specific extinguishing : In the event of fire, cool tanks with water spray.

ROYCO LANDING GEAR FLUID YELLOW

Version: 1.1

Revision Date: 12/19/2014

Print Date: 04/14/2015

methods

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.

Environmental precautions : Should not be released into the environment.
Do not contaminate water.
Do not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice.
Keep container closed when not in use.
Do not use pressure to empty drums.
Ensure all equipment is electrically grounded before beginning transfer operations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

Materials to avoid : Strong acids and strong bases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
		TWA (Mist)	5 mg/m ³	OSHA P0

ROYCO LANDING GEAR FLUID YELLOW

Version: 1.1

Revision Date: 12/19/2014

Print Date: 04/14/2015

Distillates (petroleum), hydrotreated middle	64742-46-7	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		TWA (Mist)	5 mg/m3	OSHA P0
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	200 mg/m3	ACGIH
		TWA	400 ppm 1,600 mg/m3	OSHA P0
1-Decene, tetramer, mixed with 1-decene trimer, hydrogenated	68649-12-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		TWA (Mist)	5 mg/m3	OSHA P0
2,6-di-tert-butyl-p-cresol	128-37-0	TWA	10 mg/m3	OSHA P0
		TWA (Inhalable fraction and vapor)	2 mg/m3	ACGIH
		TWA (Inhalable fraction and vapor)	2 mg/m3	ACGIH
		TWA	10 mg/m3	NIOSH REL

Personal protective equipment

Respiratory protection : Breathing apparatus needed only when aerosol or mist is formed.
In the case of vapour formation use a respirator with an approved filter.

Hand protection : Neoprene gloves

Eye protection : Safety glasses with side-shields
Tightly fitting safety goggles

Skin and body protection : impervious clothing

Hygiene measures : Avoid contact with skin, eyes and clothing.
Provide adequate ventilation.
Do not breathe dust or spray mist.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

ROYCO LANDING GEAR FLUID YELLOW

Version: 1.1

Revision Date: 12/19/2014

Print Date: 04/14/2015

Appearance	: liquid
Color	: yellow
pH	: No data available
Melting point/range	: Not applicable
Boiling point/boiling range	: No data available
Flash point	: 111 °C
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Density	: 0.8698 g/cm3
<u>Solubility(ies)</u>	
Water solubility	: slightly soluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Viscosity	
Viscosity, kinematic	: 14.55 mm2/s (40 °C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use. No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions. No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: Hazardous polymerisation does not occur.
Conditions to avoid	: Heat.
Incompatible materials	: Strong acids and strong bases
Hazardous decomposition products	: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

ROYCO LANDING GEAR FLUID YELLOW

Version: 1.1

Revision Date: 12/19/2014

Print Date: 04/14/2015

Acute oral toxicity

2,6-di-tert-butyl-p-cresol
(Component): LD50: > 2,930 mg/kg
Species: Rat
Method: OECD Test Guideline 401

Acute dermal toxicity

2,6-di-tert-butyl-p-cresol
(Component): LD50: > 2,000 mg/kg
Species: Rat
Method: OECD Test Guideline 402

Skin irritation

1-Decene, tetramer, mixed
with 1-decene trimer,
hydrogenated (Component)
Phosphorodithioic acid, O,O-
di-C1-14-alkyl esters, zinc
salts (Component)
2,6-di-tert-butyl-p-cresol
(Component): Result: No skin irritation
: Result: Irritating to skin.
: Species: Rabbit
Result: No skin irritation

Eye irritation (Product)

: Remarks: Irritating to eyes.

Sensitisation

Phosphorodithioic acid, O,O-
di-C1-14-alkyl esters, zinc
salts (Component): Maximisation Test (GPMT)
Species: Guinea pig
Classification: Did not cause sensitisation on laboratory animals.2,6-di-tert-butyl-p-cresol
(Component): Species: Guinea pig
Classification: Did not cause sensitisation on laboratory animals.

CMR effects

1-Decene, tetramer, mixed
with 1-decene trimer,
hydrogenated (Component): Carcinogenicity: Animal testing did not show any carcinogenic effects.
Mutagenicity: Animal testing did not show any mutagenic effects.
Teratogenicity: No effects on or via lactation, Did not show teratogenic effects in animal experiments.
Reproductive toxicity: No toxicity to reproduction2,6-di-tert-butyl-p-cresol
(Component): Mutagenicity: Animal testing did not show any mutagenic effects.
Teratogenicity: No effects on or via lactation
Reproductive toxicity: No toxicity to reproduction

Further information (Product)

: There is no data available for this product.

ROYCO LANDING GEAR FLUID YELLOW

Version: 1.1

Revision Date: 12/19/2014

Print Date: 04/14/2015

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity effects**

Toxicity to fish (Product) : Remarks:
No data available

Toxicity to daphnia and other : Remarks:
aquatic invertebrates : No data available
(Product)

Toxicity to algae (Product) : Remarks:
No data available

Toxicity to fish (Chronic toxicity)
Phenol, isobutyleneated, : NOEC: 0.093 mg/l
phosphate (3:1) : Exposure time: 90 d
(Component)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)
Phenol, isobutyleneated, : NOEC: 0.0399 mg/l
phosphate (3:1) : Exposure time: 21 d
(Component)

Elimination information (persistence and degradability)

Bioaccumulation (Product) : Remarks:
No data available

Mobility (Product) : Remarks:
No data available

Biodegradability
2,6-di-tert-butyl-p-cresol : aerobic
(Component) : Result: According to the results of tests of biodegradability this
product is not readily biodegradable.
4.5 %

Further information on ecology**Ecotoxicology Assessment**

Results of PBT assessment (Product)
This substance is not considered to be persistent, bioaccumulating and toxic (PBT).
Additional ecological : There is no data available for this product.
information (Product)

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

ROYCO LANDING GEAR FLUID YELLOW

Version: 1.1

Revision Date: 12/19/2014

Print Date: 04/14/2015

Waste from residues : In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.**SECTION 14. TRANSPORT INFORMATION****ADR**

Not dangerous goods

RID

Not dangerous goods

MERCOSUR

Not dangerous goods

DOT

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
formaldehyde	50-00-0	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
formaldehyde	50-00-0	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Acute Health Hazard

ROYCO LANDING GEAR FLUID YELLOW

Version: 1.1

Revision Date: 12/19/2014

Print Date: 04/14/2015

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:
Phosphorodithioic acid, 68649-42-3 1.3485
O,O-di-C1-14-alkyl esters,
zinc salts

US State Regulations

California Prop 65 WARNING! This product contains a chemical known to the State of California to cause cancer.

formaldehyde 50-00-0

The components of this product are reported in the following inventories:

US.TSCA	On TSCA Inventory
DSL	All components of this product are on the Canadian DSL.
AICS	On the inventory, or in compliance with the inventory
NZIoC	Not in compliance with the inventory
ENCS	On the inventory, or in compliance with the inventory
KECI	Not in compliance with the inventory
PICCS	Not in compliance with the inventory
IECSC	Not in compliance with the inventory

SECTION 16. OTHER INFORMATION**Further information****Other Emergency Phone Number**

<u>Latin America:</u>	Brazil	+55 113 711 9144
	All other countries	+44 (0) 1235 239 670
<u>Mexico:</u>		+52 555 004 8763

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.