



SAFETY DATA SHEET

SUPERTAK HIGH PERFORMANCE
Revision Number 3

Revision date 13-Mar-2020
Supersedes Date: 15-Sep-2017

1. Identification

1.1. Product Identifier

Product Name SUPERTAK HIGH PERFORMANCE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesive.
Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Responsible Party

Bostik Inc.
11320 W. Watertown Plank Road
Wauwatosa, Wisconsin 53226 USA
Phone: +1 (800) 843-0844 (Domestic Toll Free)
Phone: +1 (414) 774-2250 (International)
Fax: +1 (414) 774-8075

E-mail msds@bostik.com

1.4. Emergency telephone number

Telephone: 1-800-227-0332
(Outside U.S.) 1-703-527-3887

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Flammable aerosols	Category 1

2.2. Label Elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Causes serious eye irritation
May cause an allergic skin reaction
May cause drowsiness or dizziness
Extremely flammable aerosol

SAFETY DATA SHEET

SUPERTAK HIGH PERFORMANCE
Revision Number 3

Revision date 13-Mar-2020
Supersedes Date: 15-Sep-2017



Appearance Aerosol

Physical State Liquid

Odor Solvent

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing should not be allowed out of the workplace
Use only outdoors or in a well-ventilated area
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Pressurized container: Do not pierce or burn, even after use
Do not spray on an open flame or other ignition source

Precautionary Statements - Response

Not applicable
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed
Store locked up
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/ container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown acute toxicity

25 % of the mixture consists of ingredient(s) of unknown toxicity

2.3. Other Information

Causes mild skin irritation.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Mixture

3.2 Mixtures

Chemical name	CAS No.	Weight-%
Acetone	67-64-1	20 - 40
Propane	74-98-6	10 - 20
Butane	106-97-8	10 - 20

SAFETY DATA SHEET

SUPERTAK HIGH PERFORMANCE
Revision Number 3

Revision date 13-Mar-2020
Supersedes Date: 15-Sep-2017

Methyl acetate	79-20-9	2.5 - 10
Parachlorobenzotrifluoride	98-56-6	2.5 - 10
n-Heptane	142-82-5	1 - 2.5

**The exact percentage (concentration) of composition has been withheld as a trade secret.*

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse. In case of contact with liquefied gas, thaw frosted parts with lukewarm water. May cause sensitization by skin contact. In the case of skin irritation or allergic reactions see a physician.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Ingestion	If swallowed, call a poison control center or physician immediately. Rinse mouth. Never give anything by mouth to an unconscious person.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Drowsiness. Dizziness. Headache. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Irritating to eyes.
-----------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically. Keep victim under observation. Symptoms may be delayed.
---------------------------	--

4.4. Reference to Other Sections

Reference to other sections	Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION See Section 12: ECOLOGICAL INFORMATION
------------------------------------	--

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Use extinguishing agent suitable for type of surrounding fire. Dry chemical or CO₂. Water spray, fog or regular foam. Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists.

Unsuitable extinguishing media

Strong water jet. Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical

Containers may explode when heated. Ruptured cylinders may rocket. Thermal decomposition can lead to release of irritating and

SAFETY DATA SHEET

SUPERTAK HIGH PERFORMANCE
Revision Number 3

Revision date 13-Mar-2020
Supersedes Date: 15-Sep-2017

toxic gases and vapors. May cause sensitization by skin contact.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO₂). Formaldehyde.

Explosion Data

Sensitivity to mechanical impact

None.

Sensitivity to static discharge

May be ignited by friction, heat, sparks or flames.

5.3. Advice for firefighters

Special protective actions for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Move containers from fire area if you can do it without risk. Cool containers with flooding quantities of water until well after fire is out. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible withdraw from area and let fire burn. In the event of fire and/or explosion do not breathe fumes.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Contents under pressure. Use personal protective equipment as required. All equipment used when handling the product must be grounded. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid breathing vapors or mists. Ensure adequate ventilation, especially in confined areas. Remove all possible sources of ignition in the surrounding area. Do not puncture or incinerate cans. Use personal protection recommended in Section 8.

Other information

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc) away from spilled material. All equipment used when handling the product must be grounded.

For emergency responders

Use personal protective equipment as required. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2. Environmental precautions

Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow into any sewer, on the ground or into any body of water. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so. Cover with plastic sheet to prevent spreading. Isolate area until gas has dispersed.

Methods for cleaning up

Use personal protective equipment as required. Use a non-combustible material like vermiculite or sand to soak up the product and place into a container for later disposal. Clean contaminated surface thoroughly. After cleaning, flush away traces with water.

6.4. Reference to other sections

Reference to other sections

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION
See Section 12: ECOLOGICAL INFORMATION

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

SAFETY DATA SHEET

SUPERTAK HIGH PERFORMANCE
Revision Number 3

Revision date 13-Mar-2020
Supersedes Date: 15-Sep-2017

Advice on safe handling

Contents under pressure. Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Do not eat, drink or smoke when using this product. Do not reuse container. Never pierce, drill, grind, cut, saw or weld any empty container. Avoid contact with skin, eyes or clothing. Do not breathe dust/fume/gas/mist/vapors/spray. Use only with adequate ventilation and in closed systems. This material can accumulate static charge by flow or agitation and can be ignited by static discharge. All equipment used when handling the product must be grounded.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Store locked up. Observe local regulations / instructions for storage of pressurized containers. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep container tightly closed in a cool, well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Recommended storage temperature. 50 - 95 °F. Store away from incompatible materials.

Incompatible materials

Strong oxidizing agents. Acid anhydrides. Strong acids. Halogens.

7.3. Specific end use(s)

Specific Use(s)

Adhesive.

Other information

Keep product and empty container away from heat and sources of ignition.

7.4. References to Other Sections

Reference to other sections

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION
See Section 12: ECOLOGICAL INFORMATION

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	NIOSH IDLH	OSHA PEL	Mexico
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³	TWA: 1000 ppm TWA: 2400 mg/m ³	TWA: 500 ppm STEL: 750 ppm
Propane 74-98-6	: See Appendix F: Minimal Oxygen Content, explosion hazard	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³	TWA: 1000 ppm TWA: 1800 mg/m ³	TWA: 1000 ppm
Butane 106-97-8	STEL: 1000 ppm explosion hazard	IDLH: 1600 ppm TWA: 800 ppm TWA: 1900 mg/m ³	-	TWA: 1000 ppm
Methyl acetate 79-20-9	STEL: 250 ppm TWA: 200 ppm	IDLH: 3100 ppm TWA: 200 ppm TWA: 610 mg/m ³ STEL: 250 ppm STEL: 760 mg/m ³	TWA: 200 ppm TWA: 610 mg/m ³	TWA: 200 ppm TWA: 610 mg/m ³ STEL: 250 ppm
Parachlorobenzotrifluoride 98-56-6	TWA: 2.5 mg/m ³ F	IDLH: 250 mg/m ³ F	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³
n-Heptane 142-82-5	STEL: 500 ppm TWA: 400 ppm	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 85 ppm	TWA: 500 ppm TWA: 2000 mg/m ³	TWA: 400 ppm TWA: 1600 mg/m ³ STEL: 500 ppm

SAFETY DATA SHEET

SUPERTAK HIGH PERFORMANCE
Revision Number 3

Revision date 13-Mar-2020
Supersedes Date: 15-Sep-2017

		TWA: 350 mg/m ³	
Chemical name	Argentina	Brazil	Chile
Acetone 67-64-1	TWA: 500 ppm STEL: 750 ppm	TWA: 780 ppm TWA: 1870 mg/m ³	TWA: 438 ppm TWA: 1040 mg/m ³
Propane 74-98-6	TWA: 2500 ppm	-	-
Butane 106-97-8	TWA: 800 ppm	TWA: 470 ppm TWA: 1090 mg/m ³	-
Methyl acetate 79-20-9	TWA: 200 ppm STEL: 250 ppm	TWA: 200 ppm	TWA: 175 ppm TWA: 530 mg/m ³
Parachlorobenzotrifluoride 98-56-6	TWA: 2.5 mg/m ³	TWA: 2.5 mg/m ³	TWA: 2.19 mg/m ³
n-Heptane 142-82-5	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm	-
			STEL: 750 ppm TWA: 500 ppm
			TWA: 1000 mg/m ³ TWA: 1000 ppm
			TWA: 1000 ppm
			STEL: 250 ppm TWA: 200 ppm
			-
			STEL: 500 ppm TWA: 400 ppm

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Ensure the ventilation system is regularly maintained and tested. Showers
Eyewash stations
Ventilation systems.

Personal protective equipment [PPE]

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General hygiene considerations Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice. When using do not eat, drink or smoke. Take off contaminated clothing and wash before reuse. Regular cleaning of equipment, work area and clothing is recommended.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Aerosol
Color White
Odor Solvent
Odor threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No data available	
Boiling point / boiling range	67.05 °C / 152.69 °F	
Flash point	-104.4 °C / -156 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability or explosive limits	11.4%	
Lower flammability or explosive	2.2%	

SAFETY DATA SHEET

SUPERTAK HIGH PERFORMANCE
Revision Number 3

Revision date 13-Mar-2020
Supersedes Date: 15-Sep-2017

limits
Vapor pressure No information available
Vapor density No information available
Relative density No information available
Water solubility No information available
Solubility in Other Solvents
Partition coefficient No information available
Autoignition temperature No information available
Decomposition temperature No information available
Kinematic viscosity No information available

Dynamic viscosity No information available

Explosive properties No information available
Oxidizing properties No information available

9.2. Other information

Softening Point No information available
Molecular weight No information available
Solvent content (%) No information available
Solid content (%) 34
Density 7.360 LB/GAL
VOC Content (%) 38.4 g/L

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

None under normal use conditions.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

None under normal processing.

Hazardous polymerization Hazardous polymerization does not occur.

10.4. Conditions to avoid

Extremes of temperature and direct sunlight. Keep away from heat, sparks and flames. Heating causes rise in pressure with risk of bursting. Incompatible materials.

10.5. Incompatible materials

Strong oxidizing agents. Acid anhydrides. Strong acids. Halogens.

10.6. Hazardous decomposition products

Formaldehyde. Carbon monoxide. Carbon dioxide (CO₂).

Section 11: TOXICOLOGY INFORMATION

11.1. Information on toxicological effects

Product Information Harmful by inhalation

SAFETY DATA SHEET

SUPERTAK HIGH PERFORMANCE
Revision Number 3

Revision date 13-Mar-2020
Supersedes Date: 15-Sep-2017

Inhalation	May cause drowsiness or dizziness. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
Eye contact	Severely irritating to eyes.
Skin contact	May cause sensitization by skin contact.
Ingestion	Not an expected route of exposure.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	=5800 mg/kg (Rattus)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Propane 74-98-6	-	-	>800000 ppm (Rattus) 15 min
Butane 106-97-8	-	-	=658 g/m ³ (Rattus) 4 h
Methyl acetate 79-20-9	>5 g/kg (Rattus)	> 5 g/kg (Oryctolagus cuniculus)	>49000 mg/m ³ (Rattus) 4 h
Parachlorobenzotrifluoride 98-56-6	=13 g/kg (Rattus)	> 2 mL/kg (Oryctolagus cuniculus)	=33 mg/L (Rattus) 4 h
n-Heptane 142-82-5	LD50 > 5000 mg/Kg (rattus)	= 3000 mg/kg (Oryctolagus cuniculus)	=103 g/m ³ (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Symptoms	No information available.
Skin corrosion/irritation	Substance may cause slight skin irritation.
Serious eye damage/eye irritation	Severe eye irritation.
Irritation	No information available.
Corrosivity	No information available.
Sensitization	May cause sensitization by skin contact.
Germ cell mutagenicity	No information available.
Reproductive toxicity	No information available.
Developmental toxicity	No information available.
Teratogenicity	No information available.
STOT - single exposure	May cause drowsiness or dizziness.
STOT - repeated exposure	No information available.
Chronic Toxicity	Prolonged exposure may cause chronic effects. Avoid repeated exposure. Repeated contact may cause allergic reactions in very susceptible persons. heart, Central nervous system, Eyes, Respiratory system, Skin.
Target organ effects	No information available.
Aspiration hazard	No information available.
Carcinogenicity	This product does not contain any carcinogens or potential carcinogens as listed by ACGIH, OSHA, IARC or NTP at or above 0.1 wt%.

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Acetone 67-64-1		LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)
Methyl acetate 79-20-9	EC50: >120mg/L (72h, Desmodesmus subspicatus)	LC50: 295 - 348mg/L (96h, Pimephales promelas)	EC50 = 6000 mg/L 16 h EC50 = 6100 mg/L 30 min	EC50: =1026.7mg/L (48h, Daphnia magna)

SAFETY DATA SHEET

SUPERTAK HIGH PERFORMANCE
Revision Number 3

Revision date 13-Mar-2020
Supersedes Date: 15-Sep-2017

		LC50: 250 - 350mg/L (96h, Brachydanio rerio)	
Parachlorobenzotrifluoride 98-56-6		LC50: 11.5 - 15.8mg/L (48h, Lepomis macrochirus) LC50: =3mg/L (96h, Danio rerio)	EC50: =3.68mg/L (48h, Daphnia magna)
n-Heptane 142-82-5		LC50: =375.0mg/L (96h, Cichlid)	EC50: >10mg/L (24h, Daphnia magna)

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

Other adverse effects

No information available

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Disposal of Wastes It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations

Contaminated packaging Dispose of in accordance with federal, state and local regulations

Section 14: TRANSPORT INFORMATION

Note: The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition)
 The information shown here, may not always agree with the bill of lading shipping description for the material

DOT

UN/ID No UN1950
Proper Shipping Name Aerosols
Hazard class 2.1
Reportable Quantity (RQ) (Acetone: RQ (kg)= 2270.00)
Special Provisions N82
Description UN1950, Aerosols, 2.1
Emergency Response Guide Number 126

IATA

UN number UN1950
Proper Shipping Name Aerosols, flammable
Transport hazard class(es) 2.1
ERG Code 10L
Special Provisions A145, A167, A802
Description UN1950, Aerosols, flammable, 2.1

SAFETY DATA SHEET

SUPERTAK HIGH PERFORMANCE
Revision Number 3

Revision date 13-Mar-2020
Supersedes Date: 15-Sep-2017

IMDG

UN number	UN1950
UN proper shipping name	Aerosols
Transport hazard class(es)	2.1
EmS-No.	F-D, S-U
Special Provisions	63,190, 277, 327, 344, 381, 959
Description	UN1950, Aerosols (n-Heptane), 2.1, (-104.4°C c.c.), Marine Pollutant

Section 15: REGULATORY INFORMATION

Global Inventories

TSCA	Listed
DSL	Listed

This product contains Parachlorobenzotrifluoride (CAS 98-56-6), which is subject to the reporting requirements of TSCA 12(b) when exported from the United States when the CAS is present at or above 1%.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

Listed - The components of this product are either listed or exempt from listing on inventory.

Not Listed - One or more components of this product are not listed on inventory.

United States of America

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Classification is shown in section 2 of this SDS

Europe

Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead (7439-92-1), Cadmium (7440-43-9), Mercury (7439-97-6), Hexavalent chromium (7440-47-3), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE) above the regulated limit mentioned in this regulation

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Section 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

No information available

Key Literature References and Sources for Data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 13-Mar-2020

SAFETY DATA SHEET

SUPERTAK HIGH PERFORMANCE
Revision Number 3

Revision date 13-Mar-2020
Supersedes Date: 15-Sep-2017

Revision note	SDS sections updated, 1, 2, 4, 5, 6, 7, 8, 9, 11, 12, 15, 16.
Training Advice	Provide adequate information, instruction, and training for operator
Further information	No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet