

Safety Data Sheet

HiTEC® 5714 Performance Additive

SDS no. H5714

Date of issue/Date of 11/15/2022 revision

Section 1. Identification

GHS product identifier : HiTEC® 5714 Performance Additive

Product use : Petrochemical industry: Pour Point Depressant

In case of emergency - Chemical

0800-70-77-022 (Brazil) 800-681-9531 (Mexico)

+1-703-527-3887 (International)

+1-703-741-5979 (Spanish language)

+1-800-424-9300 (US & Canada)

Manufacturer / Supplier

Afton Chemical Corporation

500 Spring St. Richmond, VA 23219

Afton Chemical Canada Corporation 5045 South Service Road

Suite 101

Burlington, ON L7L 5Y7

905-631-5470

Non-Emergency Telephone: +1-804-788-5800

Section 2. Hazards identification

OSHA/HCS status

: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.

Classification of the substance or mixture : Not classified.

GHS label elements

Signal word : No signal word.

Hazard statements : No known significant effects or critical hazards.

Precautionary statements

Prevention : Not applicable. Response : Not applicable.

Storage : Store in a well-ventilated place.

Disposal : Dispose of contents and container in accordance with all local, regional, national and

international regulations.

Additional hazards : None known.

Page: 2/12

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	CAS number	Conc. (% w/w)	US GHS Classification
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	≥15 - ≤25	ASPIRATION HAZARD - Category 1
n-butyl methacrylate	97-88-1	≥0.1 - ≤0.3	FLAMMABLE LIQUIDS - Category 3 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1B SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

^{*} HMIRA registration number:9578. Exemption granted date: 22/12/2015.

Any concentration shown as a range is to protect confidentiality or is due to batch variation. If specific chemical identify is withheld, it is to protect confidentiality.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Immediatel

: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical

attention if irritation occurs.

Inhalation : If inhaled, remove to fresh air. Get medical attention if symptoms occur. If not

breathing, give artificial respiration. If breathing is difficult, administer oxygen.

Skin contact: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur.

Ingestion : Wash out mouth with water. Remove victim to fresh air and keep at rest in a position

comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

Page: 3/12

Section 4. First aid measures

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: In case of fire, use water spray (fog), foam, dry chemical or CO2

Unsuitable extinguishing media

: Do not use water jet.

carbon monoxide

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products : Decomposition products may include the following materials: carbon dioxide

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8).

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated light paraffinic	ACGIH TLV (United States, 1/2022). TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 5/2018). TWA: 5 mg/m³ 8 hours.

Appropriate engineering controls

Environmental exposure controls

- : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

Skin protection Hand protection

: Hand Protection: Wear chemical resistant gloves. Nitrile gloves of minimum thickness 0.4 mm have an expected breakthrough time of 480 minutes or less when in frequent contact with the product. Due to variable exposure conditions the user must consider that the practical use of a chemical-protective glove in practice may be much shorter than the permeation time above. Manufacturer's directions for use, especially about the minimum thickness and the minimum breakthrough time, must be observed. This information does not replace suitability tests by the end user since glove protection varies depending on the conditions under which the product is used.

Section 8. Exposure controls/personal protection

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Page: 5/12

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid. [Viscous Clear to slightly hazy liquid.]

Color : Yellow. Amber.

Odor : Aromatic. Mineral oil

: Not available. **Odor threshold** : Not available. pН **Melting point** : Not available. : Not available. **Boiling point**

: Closed cup: 120°C (248°F) [Pensky-Martens Minimum] Flash point

: Not available. **Evaporation rate** : Not available. Flammability (solid, gas) : Not available. Lower and upper explosive

(flammable) limits

Vapor pressure : Not available. Vapor density : Not available.

Density : 0.928 g/cm³ [59°F (15°C)]

Relative density : 0.915

Solubility(ies) ٠

Media	Result
cold water	Not soluble

Partition coefficient: n-

: Not applicable.

octanol/water

Viscosity

Auto-ignition temperature : Not available. : Not available.

Decomposition temperature

: Kinematic (40°C (104°F)): 12000 mm²/s (12000 cSt) Minimum

860 cSt at 100°C

Explosive properties : Not available. : Not available. **Oxidizing properties**

Section 10. Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. Reactivity

Chemical stability : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : High temperatures, sparks and open flames.

Section 10. Stability and reactivity

Incompatible materials : Strong oxidizing and reducing agents.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Page: 6/12

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Test	Result	Species	Dose	Exposure	Remarks
Distillates (petroleum), hydrotreated light paraffinic	403 Acute Inhalation Toxicity	LC50 Inhalation Dusts and mists	Rat	>5.53 mg/l	4 hours	Based on data for a similar substance.
	402 Acute Dermal Toxicity	LD50 Dermal	Rabbit	>5000 mg/kg	-	Based on data for a similar substance.
	401 Acute Oral Toxicity	LD50 Oral	Rat	>5000 mg/kg	-	Based on data for a similar substance.
n-butyl methacrylate	403 Acute Inhalation Toxicity	LC50 Inhalation Vapor	Rat	29 mg/l	4 hours	-
	402 Acute Dermal Toxicity	LD50 Dermal	Rabbit	>2000 mg/kg	-	-
	401 Acute Oral Toxicity	LD50 Oral	Rat	>2000 mg/kg	-	-

Conclusion/Summary

: Not available.

Irritation/Corrosion

Product/ingredient name	Test	Species	Result	Remarks
Distillates (petroleum), hydrotreated light paraffinic	405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Not an Irritant	Based on data for a similar substance.
	404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Mild irritant	Based on data for a similar substance. WOE does not support classification
	None available.	Rabbit	Skin - Not an Irritant	Based on data for a similar substance.
n-butyl methacrylate	405 Acute Eye Irritation/Corrosion	Rabbit	Eyes - Irritant	-
	404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Irritant	-

Conclusion/Summary

Skin : Not available.

Eyes: Non-irritating to the eyes. Based on test data for this or similar products.

Respiratory: Not available.

Sensitization

Product/ingredient name	Test	Route of exposure	Species	Result	Remarks
Distillates (petroleum), hydrotreated light paraffinic	406 Skin Sensitization	skin	Guinea pig	Not sensitizing	Based on data for a similar substance.
n-butyl methacrylate	406 Skin Sensitization	skin	Guinea pig	Sensitizing	-
	429 Skin Sensitization: Local Lymph Node Assay	skin	Mouse	Sensitizing	-

Page: 7/12

HiTEC® 5714 Performance Additive

Section 11. Toxicological information

Conclusion/Summary

Skin : Not available.

Respiratory : Not available.

Mutagenicity

Product/ingredient name	Test	Experiment	Result	Remarks
Distillates (petroleum), hydrotreated light paraffinic	471 Bacterial Reverse Mutation Test	Experiment: In vitro Subject: Bacteria	Negative	Based on data for a similar substance.
	473 <i>In vitro</i> Mammalian Chromosomal Aberration Test	Experiment: In vitro Subject: Mammalian-Animal	Negative	Based on data for a similar substance.
n-butyl methacrylate	471 Bacterial Reverse Mutation Test	Experiment: In vitro Subject: Bacteria	Negative	-
	476 <i>In vitro</i> Mammalian Cell Gene Mutation Test	Experiment: In vitro Subject: Mammalian-Animal	Negative	-

Conclusion/Summary

: Not available.

Carcinogenicity

Product/ingredient name	Test	Species	Exposure	Result	Remarks
Distillates (petroleum), hydrotreated light paraffinic	451 Carcinogenicity Studies	Mouse	78 weeks	Negative - Dermal - NOAEL	Based on data for a similar substance.
n-butyl methacrylate	451 Carcinogenicity Studies	Rat	102 weeks; 5 days per week	Negative - Inhalation - NOAEL	Based on data for a similar substance.
	None available.	Rat	2 years; 7 days per week	Negative - Oral - NOAEL	Based on data for a similar substance.

Conclusion/Summary

: Not available.

Classification

Reproductive toxicity

Product/ingredient name	Test	Route of exposure	Species	Maternal toxicity	Fertility	Development toxin	Remarks
Distillates (petroleum), hydrotreated light paraffinic	421 Reproduction/ Developmental Toxicity Screening Test	Oral	Rat	Negative	Negative	Negative	Based on data for a similar substance.
n-butyl methacrylate	422 Combined Repeated Dose Toxicity Study with the Reproduction/ Developmental Toxicity Screening Test	Oral	Rat	Negative	Negative	Negative	-
	416 Two- Generation Reproduction Toxicity Study	Oral	Rat	Positive	Negative	Negative	-

Conclusion/Summary

: Not available.

Teratogenicity

Product/ingredient name	Test	Species	Result	Remarks
Distillates (petroleum), hydrotreated light paraffinic	414 Prenatal Developmental Toxicity Study	Rat	Negative - Dermal	Based on data for a similar substance.
n-butyl methacrylate	414 Prenatal Developmental Toxicity Study	Rat	Negative - Route of exposure unreported	-

HiTEC® 5714 Performance Additive

Section 11. Toxicological information

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
n-butyl methacrylate	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Distillates (petroleum), hydrotreated light paraffinic

ASPIRATION HAZARD - Category 1

Page: 8/12

Information on the likely routes of exposure

: Skin, Eyes, Ingestion, and Inhalation

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

effects

: Inhalation of oil mist or vapors at elevated temperatures may cause respiratory irritation.

Ingestion may cause gastrointestinal irritation and diarrhea.

Potential delayed effects : Not available.

Long term exposure

Potential immediate

effects

: Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

Potential delayed effects : Not available.

Potential chronic health effects

Product/ingredient name	Test	Species	Dose	Exposure	Result	Remarks
Distillates (petroleum), hydrotreated light paraffinic	410 Repeated Dose Dermal Toxicity: 21/28-day Study	Rabbit	1000 mg/kg	-	Sub-acute NOAEL Dermal	Based on data for a similar substance.
	411 Subchronic Dermal Toxicity: 90-day Study	Rat	30 mg/kg	-	Sub-chronic NOAEL Dermal	Based on data for a similar substance.
	408 Repeated Dose 90-Day Oral Toxicity Study in Rodents	Rat	125 mg/kg	-	Sub-chronic NOAEL Oral	Based on data for a similar substance.
	None available.	Rat	0.15 mg/l	13 weeks	Sub-chronic NOAEL Inhalation Dusts and mists	Based on data for a similar substance.
	None available.	Rat	0.22 mg/l	4 weeks	Sub-acute	Based on data

Page: 9/12

HiTEC® 5714 Performance Additive

Section 11. Toxicological information

						NOAEL Inhalation Dusts and	for a similar substance.
		412 Repeated Dose Inhalation Toxicity: 28-day or 14-day Study	Rat	0.05 mg/l	4 weeks	mists Sub-acute NOAEL Inhalation Dusts and	Based on data for a similar substance.
n-	butyl methacrylate	408 Repeated Dose 90-Day Oral Toxicity Study in Rodents	Rat	120 mg/kg	-	mists Sub-chronic NOAEL Oral	-
		422 Combined Repeated Dose Toxicity Study with the Reproduction/ Developmental Toxicity Screening Test	Rat	30 mg/kg	-	Sub-acute NOAEL Oral	-
		412 Repeated Dose Inhalation Toxicity: 28-day or 14-day Study	Rat	11.175 mg/l	4 weeks	Sub-acute NOAEL Inhalation Vapor	-

Conclusion/Summary

General

Carcinogenicity

Mutagenicity

Teratogenicity

Developmental effects

Fertility effects

: Not available.

: No known significant effects or critical hazards.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure	Remarks
Distillates (petroleum), hydrotreated light paraffinic	Acute EL50 >10000 mg/l	Daphnia - Daphnia magna	48 hours	Based on data for a similar substance.
	Acute LL50 >100 mg/	Fish - Pimephales promelas	96 hours	Based on data for a similar substance.
	Chronic NOEL ≥100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	Based on data for a similar substance.
	Chronic NOEL 10 mg/l	Daphnia - Daphnia magna	21 days	Based on data for a similar substance.
	Chronic NOEL 1000 mg/l	Fish - Oncorhynchus mykiss	14 days	QSAR result.
n-butyl methacrylate	Acute EC10 31.7 mg/l	Micro-organism	18 hours	-
	Acute EL50 31.2 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	-
	Acute EL50 25.4 mg/l	Daphnia - Daphnia magna	48 hours	-
	Acute LC50 5.57 mg/l	Fish - Oryzias latipes	96 hours	-
	Chronic NOEC 1.1 mg/l	Daphnia - Daphnia magna	21 days	-

HiTEC® 5714 Performance Additive	In Case of Emergency +1-800-424-9300 (US/Canada) +1-703-527-3887 (Int'I)	Page: 10/12
----------------------------------	--	-------------

Section 12. Ecological information

Chronic NOEL 24.8	Algae - Pseudokirchneriella	72 hours	-
mg/l	subcapitata		

Persistence and degradability

Product/ingredient name	Test	Result	Remarks
Distillates (petroleum), hydrotreated light paraffinic	OECD 301F Ready Biodegradability - Manometric Respirometry Test	31 % - Not readily - 28 days	Based on data for a similar substance.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
n-butyl methacrylate	2.99	-	low

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according: Not available. to IMO instruments

Notice to reader

: The above transport information is provided to assist in the proper classification of this product and may not be suitable for all shipping conditions.

Page: 11/12

Section 15. Regulatory information

U.S. Federal regulations

United States - TSCA Section 5

TSCA 5(a)2 final significant new use rules

None of the components are listed.

TSCA 5(a)2 proposed significant new use rules

None of the components are listed.

TSCA 5(e) substance consent order

None of the components are listed.

United States - TSCA Section 6

TSCA 6 final risk management

None of the components are listed.

<u>United States - TSCA 12(b) - Chemical export notification</u>

Name on list Status Ref. number

None of the components are listed.

SARA 302/304

Composition/information on ingredients

None of the components are listed.

SARA 304 RQ : Not applicable.

CERCLA: Hazardous substances.: None of the components are listed.

SARA 311/312

Classification: Not applicable.

Composition/information on ingredients

Name	%	Classification
Distillates (petroleum), hydrotreated light paraffinic n-butyl methacrylate	≥15 - ≤25 ≥0.1 - ≤0.3	ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid FLAMMABLE LIQUIDS - Category 3 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1B SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

SARA 313

No SARA 313 chemicals are present above the reporting threshold.

State - California Prop. 65

Not listed.

Canadian regulations

Canada Significant New

Activity Notice

substances

: None of the components are listed.

Canadian NPRI : None of the components are listed.
CEPA Toxic : None of the components are listed.

International Inventory Status

Australia: All components are listed or exempted.Canada: All components are listed or exempted.China: All components are listed or exempted.

Page: 12/12

Section 15. Regulatory information

: For information on compliance with this regulation please contact your Afton representative **Europe**

(EHS.CustomerVolumes@AftonChemical.com).

Japan : All components are listed or exempted. Republic of Korea : All components are listed or exempted. **New Zealand** : All components are listed or exempted. : All components are listed or exempted. **Philippines**

: For information on compliance with this regulation please contact your Afton representative **Switzerland**

(EHS.CustomerVolumes@AftonChemical.com).

: For information on compliance with this regulation please contact your Afton representative **Turkey**

(EHS.CustomerVolumes@AftonChemical.com).

: All components are listed or exempted. **Taiwan**

United Kingdom (UK) : For information on compliance with this regulation please contact your Afton representative

(EHS.CustomerVolumes@AftonChemical.com).

United States Active : All components are active or exempted.

Section 16. Other information

History

Date of issue/Date of

revision

: 11/15/2022

Prepared by

: EHS Department (Tel: +1 804 788 5800)

Key to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations WOE = Weight of Evidence

Toxicological and Ecotoxicological Test Data : CORR A15

Summary(s)

Indicates information that has changed from previously issued version.

Notice to reader

This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations. Afton makes no representation as to completeness or accuracy. In no event will Afton be responsible for damages of any nature whatsoever resulting from the use or reliance upon the information and recommendations.