SAFETY DATA SHEET



Reference Fuel A

Version 1.3

CTION 1: Identification of	of the substance/mixture and of the company/undertaking
Product information	
Product Name Material	 Reference Fuel A 1103204, 1102597, 1029651, 1029652, 1029653
Use	: Engine Testing
Company	 Chevron Phillips Chemical Company LP Specialty Chemicals 10001 Six Pines Drive The Woodlands, TX 77380
Emergency telephone:	::
Asia: CHEMWATCH EUROPE: BIG +32.1 Mexico CHEMTREC	ernational) 24.9300 or 703.527.3887(int'l) 1 (+612 9186 1132) China: 0532 8388 9090 14.584545 (phone) or +32.14583516 (telefax) 2 01-800-681-9531 (24 hours) -Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600
Responsible Departmer E-mail address Website	nt : Product Safety and Toxicology Group : SDS@CPChem.com : www.CPChem.com
CTION 2: Hazards identi	ification
	Substance or mixture classified in accordance with the hazard communication standard 29 CFR and labels contain all the information as required by the standard.
Classification	 Flammable liquids, Category 2 Skin irritation, Category 2 Specific target organ toxicity - single exposure, Category 3, Central nervous system Aspiration hazard, Category 1
S Number:100000014070	0 1/14

Version 1.3

Symbol(s)	
Signal Word	: Danger
Hazard Statements	 H225: Highly flammable liquid and vapor. H304: May be fatal if swallowed and enters airways. H315: Causes skin irritation. H336: May cause drowsiness or dizziness.
Precautionary Statements	 Prevention: P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing dust/fume/gas/mist/vapors/spray. P264 Wash skin thoroughly after handling. P280 Wear protective gloves/ eye protection/ face protection. Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P331 Do NOT induce vomiting. P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. Storage: P403 + P235 Store in a well-ventilated place. Keep cool. Disposal plant.
Carcinogenicity:	
IARC	No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
NTP	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
CTION 3: Composition/infor	mation on ingredients
Synonyms	: 2,2,4-Trimethylpentane
Molecular formula	: C8H18

SDS Number:100000014070

Version 1.3

Revision Date 2021-06-21

Component	0 ¹	20)	CAS-No.	Weight %
2,2,4-Trimethylpentane (Isoc	ctai	ne)	540-84-1	99 - 100
TION 4: First aid measures				
General advice	:	sheet t	o the doctor in att	area. Show this material safety data endance. Material may produce a oneumonia if swallowed or vomited.
If inhaled	:			significant exposure. If unconscious, n and seek medical advice.
In case of skin contact	:		rritation persists, ater. If on clothes	call a physician. If on skin, rinse well remove clothes.
In case of eye contact	:	lenses.	Protect unharme	a precaution. Remove contact ed eye. Keep eye wide open while ersists, consult a specialist.
If swallowed	:	an unc		ear. Never give anything by mouth to If symptoms persist, call a physician. to hospital.
TION 5: Firefighting measu	res			
Flash point	:	-12.2° estimat	C (10.0°F) ted	
Autoignition temperature	:	No data	a available	
Suitable extinguishing media	:	Alcoho	I-resistant foam.	Carbon dioxide (CO2). Dry chemical.
Unsuitable extinguishing media	:	High vo	olume water jet.	
Specific hazards during fire fighting	:	Do not course		fire fighting to enter drains or water
Special protective equipment for fire-fighters	:	Wear s necess		athing apparatus for firefighting if
Further information	:	must ne contarr accord of fire,	ot be discharged i ninated fire extingu ance with local re- cans should be st ments. Use a wa	e extinguishing water separately. This nto drains. Fire residues and uishing water must be disposed of in gulations. For safety reasons in case ored separately in closed ter spray to cool fully closed
Fire and explosion protection	:	Take n	ecessary action to	flame or any incandescent material. avoid static electricity discharge on of organic vapors). Use only

3/14

ference Fuel A		SAFETY DATA SH
sion 1.3		Revision Date 2021-00
		explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
Hazardous decomposition products	:	Hydrocarbons. Carbon oxides.
TION 6: Accidental release	me	asures
Personal precautions	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods for cleaning up	:	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
TION 7: Handling and stora	ge	
Handling		
Advice on safe handling	:	Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
Advice on protection against fire and explosion	:	Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge
		(which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
Storage		(which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot
	:	 (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working
Storage Requirements for storage	:	 (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working
Storage Requirements for storage areas and containers	:	 (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Version 1.3

SAFETY DATA SHEET

Revision Date 2021-06-21

SECTION 8: Exposure controls/personal protection

Ingredients with workplace control parameters

US

Components	Basis	Value	Control parameters	Note
2,2,4-Trimethylpentane (Isooctane)	ACGIH	TWA	300 ppm,	

Engineering measures

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection	: Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume unde normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material m occur, such as:. Air-Purifying Respirator for Organic Vapor Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air- purifying respirators may not provide adequate protection.	nay rs.
Hand protection	: The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough tin which are provided by the supplier of the gloves. Also take consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and contact time. Gloves should be discarded and replaced if the is any indication of degradation or chemical breakthrough.	e me into the
Eye protection	: Eye wash bottle with pure water. Tightly fitting safety gogg	les.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to specific work-place. Wear as appropriate:. Flame retardar antistatic protective clothing. Workers should wear antistat footwear.	nt
Hygiene measures	: When using do not eat or drink. When using do not smoke Wash hands before breaks and at the end of workday.	·_
SECTION 9: Physical and cher	cal properties	
Information on basic physic	cal and chemical properties	
Appearance		
Form Physical state	: liquid : liquid	
SDS Number:100000014070	5/14	

ference Fuel A	SAFETY DATA SH
sion 1.3	Revision Date 2021-0
Color Odor	: Colorless : Mild
Safety data	
Flash point	: -12.2°C (10.0°F) estimated
Lower explosion limit	: 1 %(V)
Upper explosion limit	: 7 %(V)
Oxidizing properties	: no
Autoignition temperature	: No data available
Molecular formula	: C8H18
Molecular weight	: 114.26 g/mol
рН	: Not applicable
Pour point	: No data available
Boiling point/boiling range	: 99°C (210°F)
Vapor pressure	: 1.70 PSI at 37.8°C (100.0°F)
Relative density	: 0.69 at 15.6 °C (60.1 °F)
Water solubility	: negligible
Partition coefficient: n- octanol/water	: No data available
Viscosity, kinematic	: 50 cSt at 20°C (68°F)
Relative vapor density	: 1 (Air = 1.0)
Evaporation rate	: 1
TION 10: Stability and react	tivity
Reactivity	: Stable under recommended storage conditions.
Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Number:100000014070	6/14

SAFETY DATA SHEET

Version 1.3

Possibility of hazardous rea	actions
Hazardous reactions	: Hazardous reactions: Hazardous polymerization does not occur.
	Hazardous reactions: Vapors may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Materials to avoid	: May react with oxygen and strong oxidizing agents, such as
Hazardous decomposition products	chlorates, nitrates, peroxides, etc. : Hydrocarbons Carbon oxides
Other data	: No decomposition if stored and applied as directed.
TION 11: Toxicological info	rmation
Acute oral toxicity	
2,2,4-Trimethylpentane (Isooctane)	 LD50: > 5,000 mg/kg Species: Rat Sex: male and female Method: OECD Test Guideline 401 Symptoms: Salivation
Acute inhalation toxicity	
2,2,4-Trimethylpentane (Isooctane)	: LC50: > 33.52 mg/l Exposure time: 4 h Species: Rat Sex: male and female Test atmosphere: vapor Method: OECD Test Guideline 403
Acute dermal toxicity	
2,2,4-Trimethylpentane (Isooctane)	: LD50: > 2,000 mg/kg Species: Rabbit Sex: male and female Method: OECD Test Guideline 402
Skin irritation	
2,2,4-Trimethylpentane (Isooctane)	: Skin irritation
Eye irritation 2,2,4-Trimethylpentane (Isooctane)	: No eye irritation
Sensitization	
Number:100000014070	7/14

Reference Fuel A	SAFETY DATA SHEE
/ersion 1.3	Revision Date 2021-06-2
2,2,4-Trimethylpentane (Isooctane)	: Does not cause skin sensitization.
Repeated dose toxicity	
2,2,4-Trimethylpentane (Isooctane)	 Species: Rat, Male and female Sex: Male and female Application Route: Inhalation Dose: 0, 668, 2220, 6646 ppm Exposure time: 13 weeks Number of exposures: 6 hr/day 5 d/wk NOEL: 8.117 mg/l 2220 ppm Method: OECD Guideline 413 Information given is based on data obtained from similar substances.
Genotoxicity in vitro	
2,2,4-Trimethylpentane (Isooctane)	 Test Type: Ames test Method: Mutagenicity (Escherichia coli - reverse mutation assay) Result: negative
	Test Type: Mouse lymphoma assay Method: OECD Guideline 476 Result: negative
	Test Type: Sister Chromatid Exchange Assay Result: negative
	Test Type: Unscheduled DNA synthesis assay Result: negative
Genotoxicity in vivo	
2,2,4-Trimethylpentane (Isooctane)	: Test Type: Unscheduled DNA synthesis assay Species: Mouse Dose: 500 mg/kg Result: negative
	Test Type: Unscheduled DNA synthesis assay Species: Rat Dose: 500 mg/kg Result: negative
Reproductive toxicity	
2,2,4-Trimethylpentane (Isooctane)	 Species: Rat Sex: male and female Application Route: Inhalation Dose: 0, 900, 3000, 9000 ppm Number of exposures: 6 h/d 5 d/wk Method: OECD Test Guideline 416 NOAEL Parent: 3000 ppm NOAEL F1: 3000 ppm NOAEL F2: 3000 ppm Information given is based on data obtained from similar substances.
DS Number:100000014070	8/14

Version 1.3

2,2,4-Trimethylpentane (Isooctane)	: Species: Rat Application Route: Inhalation Dose: 0, 400, 1200 ppm Number of exposures: 6h/d Test period: GD6-15 NOAEL Teratogenicity: 1200 ppm NOAEL Maternal: 1200 ppm Information given is based on data obtained from similar
	substances.
	Species: Rat Application Route: Inhalation Dose: 0, 900, 3000, 9000 ppm Number of exposures: 6h/d Test period: GD6-15 Method: OECD Guideline 414 NOAEL Teratogenicity: 9000 ppm NOAEL Maternal: 3000 ppm Information given is based on data obtained from similar substances.
Reference Fuel A Aspiration toxicity	: May be fatal if swallowed and enters airways.
CMR effects	
2,2,4-Trimethylpentane (Isooctane)	 Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects. Teratogenicity: Animal testing did not show any effects on fetal development. Reproductive toxicity: Animal testing did not show any effects on fertility.
Reference Fuel A Further information	: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents may degrease the skin.
SECTION 12: Ecological information	ation
Toxicity to fish	
2,2,4-Trimethylpentane (Isooctane)	: LC50: 0.11 mg/l Exposure time: 96 h Species: Oncorhynchus mykiss (rainbow trout) semi-static test Method: OECD Test Guideline 203 Information given is based on data obtained from similar substances.
Toxicity to daphnia and oth	ner aquatic invertebrates
	: EC50: 0.4 mg/l
2,2,4-Trimethylpentane	

eference Fuel A	SAFETY DATA SHEE
/ersion 1.3	Revision Date 2021-06-2
(Isooctane)	Exposure time: 48 h Species: Daphnia magna (Water flea) static test Information given is based on data obtained from similar substances.
Toxicity to algae	
2,2,4-Trimethylpentane (Isooctane)	: EL50: 2.943 mg/l Exposure time: 72 h Method: QSAR modeled data
Toxicity to daphnia and othe	er aquatic invertebrates (Chronic toxicity)
2,2,4-Trimethylpentane (Isooctane)	 NOEL: 0.17 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211 Information given is based on data obtained from similar substances.
Biodegradability	
2,2,4-Trimethylpentane (Isooctane)	 Result: Not readily biodegradable. Method: OECD Test Guideline 301 Expected to be inherently biodegradable. Information given is based on data obtained from similar substances.
Bioaccumulation	
2,2,4-Trimethylpentane (Isooctane)	: Bioconcentration factor (BCF): 231 Method: QSAR modeled data This material is not expected to bioaccumulate.
Mobility	
2,2,4-Trimethylpentane (Isooctane)	: Medium: Air Method: Calculation, Mackay Level I Fugacity Model After release, disperses into the air.
Results of PBT assessment 2,2,4-Trimethylpentane (Isooctane) Additional ecological information	 Non-classified PBT substance, Non-classified vPvB substance Very toxic to aquatic life with long lasting effects.
Ecotoxicology Assessment	
Short-term (acute) aquatic haz 2,2,4-Trimethylpentane (Isooctane)	zard : Very toxic to aquatic life.
Long-term (chronic) aquatic ha	azard
SDS Number:100000014070	10/14

eference Fuel A	SAFETY DATA SHEET
/ersion 1.3	Revision Date 2021-06-21
2,2,4-Trimethylpentane (Isooctane)	: Very toxic to aquatic life with long lasting effects.
ECTION 13: Disposal consider	rations
The information in this SDS r	pertains only to the product as shipped.
Use material for its intended may meet the criteria of a ha other State and local regulati regulated components may b	purpose or recycle if possible. This material, if it must be discarded, zardous waste as defined by US EPA under RCRA (40 CFR 261) or ions. Measurement of certain physical properties and analysis for be necessary to make a correct determination. If this material is liste, federal law requires disposal at a licensed hazardous waste
Product	: The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.
ECTION 14: Transport informa	ation
shipments in non-bulk pac	shown here are for bulk shipments only, and may not apply to kages (see regulatory definition).
shipments in non-bulk pac Consult the appropriate dom Goods Regulations for additionet etc.) Therefore, the informat	kages (see regulatory definition). estic or international mode-specific and quantity-specific Dangerous onal shipping description requirements (e.g., technical name or names, ion shown here, may not always agree with the bill of lading shipping
shipments in non-bulk pac Consult the appropriate dome Goods Regulations for additionet etc.) Therefore, the informat description for the material. bill of lading.	kages (see regulatory definition). estic or international mode-specific and quantity-specific Dangerous onal shipping description requirements (e.g., technical name or names, ion shown here, may not always agree with the bill of lading shipping Flashpoints for the material may vary slightly between the SDS and the DEPARTMENT OF TRANSPORTATION) , MARINE POLLUTANT, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE)
 shipments in non-bulk pac Consult the appropriate dome Goods Regulations for additional etc.) Therefore, the informat description for the material. bill of lading. US DOT (UNITED STATES UN1262, OCTANES, 3, II RQ (2,2,4-TRIMETHYLPE IMO / IMDG (INTERNATION 	kages (see regulatory definition). estic or international mode-specific and quantity-specific Dangerous onal shipping description requirements (e.g., technical name or names, ion shown here, may not always agree with the bill of lading shipping Flashpoints for the material may vary slightly between the SDS and the DEPARTMENT OF TRANSPORTATION) , MARINE POLLUTANT, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE)
 shipments in non-bulk pac Consult the appropriate dome Goods Regulations for additivetc.) Therefore, the informat description for the material. bill of lading. US DOT (UNITED STATES UN1262, OCTANES, 3, II RQ (2,2,4-TRIMETHYLPE IMO / IMDG (INTERNATION UN1262, OCTANES, 3, II (ISOOCTANE)) 	kages (see regulatory definition). estic or international mode-specific and quantity-specific Dangerous onal shipping description requirements (e.g., technical name or names, ion shown here, may not always agree with the bill of lading shipping Flashpoints for the material may vary slightly between the SDS and the DEPARTMENT OF TRANSPORTATION) , MARINE POLLUTANT, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE) ENTANE (ISOOCTANE)) IAL MARITIME DANGEROUS GOODS) I, (-12.2°C), MARINE POLLUTANT, (2,2,4-TRIMETHYLPENTANE R TRANSPORT ASSOCIATION)
 shipments in non-bulk pac Consult the appropriate dome Goods Regulations for additional etc.) Therefore, the informat description for the material. I bill of lading. US DOT (UNITED STATES UN1262, OCTANES, 3, II RQ (2,2,4-TRIMETHYLPE IMO / IMDG (INTERNATION UN1262, OCTANES, 3, II (ISOOCTANE)) IATA (INTERNATIONAL AIF UN1262, OCTANES, 3, II MOTA (AGREEMENT ON DA 	 kages (see regulatory definition). estic or international mode-specific and quantity-specific Dangerous onal shipping description requirements (e.g., technical name or names, ion shown here, may not always agree with the bill of lading shipping Flashpoints for the material may vary slightly between the SDS and the DEPARTMENT OF TRANSPORTATION) MARINE POLLUTANT, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE) ENTANE (ISOOCTANE)) MARITIME DANGEROUS GOODS) (-12.2°C), MARINE POLLUTANT, (2,2,4-TRIMETHYLPENTANE R TRANSPORT ASSOCIATION) NGEROUS GOODS BY ROAD (EUROPE)) (, (D/E), ENVIRONMENTALLY HAZARDOUS, (2,2,4-
 shipments in non-bulk pac Consult the appropriate dome Goods Regulations for additivetc.) Therefore, the informat description for the material. Ibill of lading. US DOT (UNITED STATES UN1262, OCTANES, 3, II RQ (2,2,4-TRIMETHYLPE IMO / IMDG (INTERNATION UN1262, OCTANES, 3, II (ISOOCTANE)) IATA (INTERNATIONAL AIF UN1262, OCTANES, 3, II (ISOOCTANE)) IATA (INTERNATIONAL AIF UN1262, OCTANES, 3, II UN1262, OCTANES, 3, II RIMETHYLPENTANE (I RID (REGULATIONS CONC DANGEROUS GOODS (EU) 	kages (see regulatory definition). estic or international mode-specific and quantity-specific Dangerous onal shipping description requirements (e.g., technical name or names, ion shown here, may not always agree with the bill of lading shipping Flashpoints for the material may vary slightly between the SDS and the DEPARTMENT OF TRANSPORTATION) , MARINE POLLUTANT, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE) ENTANE (ISOOCTANE)) IAL MARITIME DANGEROUS GOODS) , (-12.2°C), MARINE POLLUTANT, (2,2,4-TRIMETHYLPENTANE R TRANSPORT ASSOCIATION) NGEROUS GOODS BY ROAD (EUROPE)) , (D/E), ENVIRONMENTALLY HAZARDOUS, (2,2,4- SOOCTANE)) ERNING THE INTERNATIONAL TRANSPORT OF

SAFETY DATA SHEET

Reference Fuel A

Version 1.3

	o Annex II of MARPOL 73/78 and the IBC Code
TION 15: Regulatory info	rmation
National legislation	
SARA 311/312 Hazards	 Flammable (gases, aerosols, liquids, or solids) Aspiration hazard Skin corrosion or irritation Specific target organ toxicity (single or repeated exposure)
CERCLA Reportable Quantity	: 1000 lbs 2,2,4-Trimethylpentane (Isooctane)
SARA 302 Reportable Quantity	: This material does not contain any components with a SARA 302 RQ.
SARA 302 Threshold Planning Quantity	: This material does not contain any components with a section 302 EHS TPQ.
SARA 304 Reportable Quantity	: This material does not contain any components with a section 304 EHS RQ.
SARA 313 Components	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
Clean Air Act	

SAFETY DATA SHEET

Version 1.3

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).						
This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).						
US State Regulations						
Pennsylvania Right To Know :	2,2,4-Trimethylpentane (Isooctane) - 540-84-1					
Notification status Europe REACH	: This product is in full compliance according to REACH					
Switzerland CH INV United States of America (USA) TSCA Canada DSL	 regulation 1907/2006/EC. On the inventory, or in compliance with the inventory On or in compliance with the active portion of the TSCA inventory All components of this product are on the Canadian 					
Other AIIC New Zealand NZIoC Japan ENCS Korea KECI	 DSL On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory A substance(s) in this product was not registered, notified to be registered, or exempted from registration by CPChem according to K-REACH regulations. Importation or manufacture of this product is still permitted provided the Korean Importer of Record has themselves notified the substance or the exported amount does not exceed the minimum threshold quantity of the non-registered substance(s). 					
Philippines PICCS Taiwan TCSI China IECSC	 On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory 					
SECTION 16: Other information						
NFPA Classification : Health Hazard: 2 Fire Hazard: 3 Reactivity Hazard: 0						
SDS Number:100000014070	13/14					

SAFETY DATA SHEET

Version 1.3

Revision Date 2021-06-21

Further information

Legacy SDS Number

: 26080

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

K	ey or legend to abbreviations and a	cronyms use	d in the safety data sheet
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		

SDS Number:100000014070