

Safety Data Sheet

Afton Chemical Canada Corporation

5045 South Service Road

H543 SDS no

Section 1. Identification

GHS product identifier : HiTEC® 543 Performance Additive

Product use : Petrochemical industry: Hydraulic Additive

In case of emergency - Chemical

+1-703-527-3887 (International)

+1-703-741-5979 (Spanish language)

+1-800-424-9300 (US & Canada)

Manufacturer / Supplier

Afton Chemical Corporation 500 Spring St.

Richmond, VA 23219

USA

Afton Chemical Corporation 7201 W. 65th Street

Bedford Park, IL 60638, USA Suite 101

Burlington, ON L7L 5Y7 905-631-5470

Non-Emergency Telephone: +1-804-788-5800

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture SKIN SENSITIZATION - Category 1 TOXIC TO REPRODUCTION (Fertility) - Category 2 TOXIC TO REPRODUCTION (Unborn child) - Category 2

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 13.5%

GHS label elements

Hazard pictograms





Signal word

: Warning

Hazard statements

: May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Precautionary statements

Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Avoid breathing vapor. Contaminated work clothing must not be allowed out of the workplace.

Response

: IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical attention.

Storage Disposal : Store locked up.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Additional hazards : None known.

Page: 2/11

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

: Not available.

Other means of identification

Ingredient name	CAS number	Conc. (% w/w)	US GHS Classification
Petroleum distillates	68477-31-6	20 - 30	ASPIRATION HAZARD - Category 1
Mineral oil	Mixture	10 - 19.9	Not classified.
Alkylphosphorothioate, long-chain alkyl amine	Proprietary	5 - 9.9	EYE IRRITATION - Category 2A
Aryl amine	90-30-2	5 - 9.9	ACUTE TOXICITY (oral) - Category 4
			SKIN SENSITIZATION - Category 1B
Long-chain alkenyl amide	Proprietary	5 - 9.9	SKIN IRRITATION - Category 2 TOXIC TO REPRODUCTION (Fertility) - Category 2 TOXIC TO REPRODUCTION (Unborn child) - Category 2
Aryl triazole alkyl amine	94270-86-7	1 - 4.9	SKIN IRRITATION - Category 2 SKIN SENSITIZATION - Category 1B
Alkylphosphate, alkyl amine	Proprietary	1 - 4.9	SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1B

Any concentration shown as a range is to protect confidentiality or is due to batch variation. If specific chemical identity is withheld, it is to protect confidentiality.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Inhalation

: If inhaled, remove to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. If not breathing, give artificial respiration. If breathing is difficult, administer oxygen.

Skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 15 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Page: 3/11

Section 4. First aid measures

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

Skin contact: May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

: In case of fire, use water spray (fog), foam, dry chemical or CO₂.

Unsuitable extinguishing

media

: Do not use water jet.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides sulfur oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Page: 4/11

Section 5. Fire-fighting measures

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Elicitation of skin sensitization may be experienced at concentrations below the general classification threshold by individuals who are already sensitized.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Section 7. Handling and storage

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Page: 5/11

Section 8. Exposure controls/personal protection

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Petroleum distillates	OSHA PEL Z2 (United States).
	TWA: 500 ppm 8 hours.
Mineral Oil	ACGIH (United States).
	TWA: 5 mg/m³
	OSHA (United States).
	TWA: 5 mg/m³

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Page: 6/11

Section 8. Exposure controls/personal protection

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.

Color : Clear. Brown. [Dark] Odor : Pungent. [Slight] : Not available. **Odor threshold** : Not available. : Not available. **Melting point Boiling point** : Not available.

: Closed cup: 105°C (221°F) [Pensky-Martens. Minimum] Flash point

Open cup: >120°C (>248°F) [Cleveland.]

: Not available. **Evaporation rate** Flammability (solid, gas) : Not applicable. Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available. Vapor density : Not available.

: 0.971 g/cm³ [60.1°F (15.6°C)] **Density**

Relative density : Not available. : Not available. Solubility Partition coefficient: n-: Not available.

octanol/water

: Not available. **Auto-ignition temperature Decomposition temperature** : Not available. : 125 cSt at 40°C **Viscosity** 13 cSt @ 100°C

Aerosol product

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions

: Hazardous reactions or instability may occur under certain conditions of storage or use.

Conditions to avoid No specific data.

Incompatible materials : Strong oxidizing and reducing agents.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Page: 7/11

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
Mineral oil	LC50 Inhalation Vapor	Rat	>5000 mg/m ³	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Alkylphosphorothioate, long- chain alkyl amine	LD50 Oral	Rat	>2000 mg/kg	-
Aryl amine	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	1625 mg/kg	-
Long-chain alkenyl amide	LD50 Oral	Rat	10.4 g/kg	-
Aryl triazole alkyl amine	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	3313 mg/kg	-
Alkylphosphate, alkyl amine	LD50 Oral	Rat	>2000 mg/kg	-

Conclusion/Summary: Not available.

Irritation/Corrosion

Conclusion/Summary

Skin: Not available.Eyes: Not available.Respiratory: Not available.

Sensitization

Conclusion/Summary

Skin: May cause an allergic skin reaction.

Respiratory: Not available.

Mutagenicity

Conclusion/Summary: Not available.

Carcinogenicity

Conclusion/Summary: Not available.

Classification

Product / ingredient name	OSHA	IARC	NTP
Not available.			

Reproductive toxicity

Conclusion/Summary : Suspected of damaging fertility. Suspected of damaging the unborn child.

Teratogenicity

Conclusion/Summary: Not available.

Aspiration hazard

Name	Result
Petroleum distillates	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

: Skin, Eyes, Ingestion, and Inhalation

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

Skin contact: May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Page: 8/11

HiTEC® 543 Performance Additive

Section 11. Toxicological information

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary : - Adverse symptoms may include the following:: This product contains a component that may

cause methemoglobinemia. This product contains an aryl amine that has been shown to cause

skin sensitization in a small number of occupationally- exposed persons.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

Carcinogenicity: No known significant effects or critical hazards.

Mutagenicity: No known significant effects or critical hazards.

Teratogenicity: Suspected of damaging the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : Suspected of damaging fertility.

Section 12. Ecological information

Toxicity

Persistence and degradability

Product / ingredient name	Aquatic half-life	Photolysis	Biodegradability
Aryl amine Alkyl dithio thiadiazole	-		Not readily Not readily
Aryl triazole alkyl amine	-	-	Inherent

Bioaccumulative potential

Not available.

Page: 9/11

Section 12. Ecological information

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
DOT Classification	Not regulated.	-	-	-		-
TDG Classification	UN3082	Environmentally hazardous substance, liquid, n.o.s. (Aryl amine; Aryl triazole alkyl amine). Marine pollutant	9	III	**************************************	-
IMDG Class	UN3082	Environmentally hazardous substance, liquid, n.o.s. (Aryl amine; Aryl triazole alkyl amine). Marine pollutant	9	III		-
IATA-DGR Class	UN3082	Environmentally hazardous substance, liquid, n.o.s. (Aryl amine; Aryl triazole alkyl amine)	9	III	**************************************	-

Notice to reader

The above transport information is provided to assist in the proper classification of this product and may not be suitable for all shipping conditions.

Section 15. Regulatory information

US regulations

SARA 313 toxic chemical notification and release reporting (w/w%)

- : No SARA 313 chemicals are present above the reporting threshold.
- SARA 311/312 Hazardous Categorization
- : SARA 311/312 Hazards identification: Immediate (acute) health hazard, Delayed (chronic) health hazard

RQ (Reportable quantity)

: CERCLA: Hazardous substances.: Naphthalene: 100 lbs. (45.4 kg); 1-Naphthylamine: 100 lbs. (45.4 kg); 2-Naphthylamine: 10 lbs. (4.54 kg); Aniline: 5000 lbs. (2270 kg); Toluene: 1000 lbs. (454 kg); Phenol: 1000 lbs. (454 kg); Ethylene oxide: 10 lbs. (4.54 kg); Propylene oxide: 100 lbs. (45.4 kg); Dioxane: 100 lbs. (45.4 kg);

:

Page: 10/11

HiTEC® 543 Performance Additive

Section 15. Regulatory information

State - California Prop. 65

This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute:

Naphthalene Aniline Toluene

alpha-Naphthylamine beta-Naphthylamine Ethylene oxide Propylene oxide 1,4-Dioxane

Canadian regulations

HMIRA Registry Number: 9581

Claim granted. : December 9, 2015

International Inventory Status

United States inventory (TSCA

8b)

: All components are listed or exempted.

Canada inventory

: All components are listed or exempted.

Europe inventory

: All components are listed or exempted.

Japan inventory

All components are listed or exempted.

Australia inventory (AICS)

All components are listed or exempted.

Korea inventory (KECI)

All components are listed or exempted.

China inventory (IECSC)
Philippines inventory (PICCS)

All components are listed or exempted.

All components are listed or exempted.

New Zealand Inventory of

Chemicals (NZIoC)

All components are listed or exempted.

Taiwan Chemical Substances

Inventory (TCSI)

: All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

History

Date of issue/Date of

9/26/2017

revision

Prepared by: EHS Department (Tel: +1 804 788 5800)

Page: 11/11

Section 16. Other information

Key to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations. Afton makes no representation as to completeness or accuracy. In no event will Afton be responsible for damages of any nature whatsoever resulting from the use or reliance upon the information and recommendations.