

# SAFETY DATA SHEET

## FOR INDUSTRIAL USE ONLY

### Cascophen(TM) LT-5210Q

#### Section 1. Product and company identification

**GHS product identifier** : Cascophen(TM) LT-5210Q  
**MSDS Number** : 000000104568  
**Product type** : Phenol Resorcinol Formaldehyde Resin  
**Material uses** : Wood Adhesives, Composites, Laminates or Related Board Products

**Manufacturer/Supplier/Importer** : Hexion Inc.  
180 East Broad Street  
Columbus, Ohio  
43215 USA

**Contact person** : 4information@hexion.com

**Telephone** : For additional health and safety or regulatory information, call  
1 888 443 9466.

**Emergency telephone number** : For Emergency Medical Assistance  
Call Health & Safety Information Services  
1-866-303-6949

For Emergency Transportation Information  
CHEMTREC US Domestic (800) 424-9300  
CHEMTREC International (703) 527-3887  
CANUTEC CA Domestic (613) 996-6666

Part of the CASCO® Brand of Adhesives and Resins from Hexion Inc.

#### Section 2. Hazards identification

**Classification of the substance or mixture** : FLAMMABLE LIQUIDS - Category 4  
ACUTE TOXICITY:inhalation - Category 4  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A  
SKIN SENSITIZATION - Category 1  
GERM CELL MUTAGENICITY - Category 2  
TOXIC TO REPRODUCTION - Category 1B  
TOXIC TO REPRODUCTION - Category 1B  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)  
[central nervous system (CNS), blood system, eyes, respiratory tract] -  
Category 1  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)  
[Respiratory tract irritation] - Category 3  
SPECIFIC TARGET ORGAN TOXICITY (REPEATED  
EXPOSURE) [thyroid, liver] - Category 1

## GHS label elements

### Hazard pictograms



### Signal word

: Danger

### Hazard statements

: H227 Combustible liquid.  
H332 Harmful if inhaled.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H341 Suspected of causing genetic defects.  
H360F May damage fertility.  
H360 May damage the unborn child.  
H370 Causes damage to organs: (central nervous system (CNS), blood system, eyes, respiratory tract)  
H335 May cause respiratory irritation.  
H372 Causes damage to organs through prolonged or repeated exposure: (thyroid, liver)

## Precautionary statements

### General

: Not applicable.

### Prevention

: Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Use personal protective equipment as required.  
Wear protective gloves.  
Wear eye or face protection.  
Keep away from flames and hot surfaces. - No smoking.  
Use only outdoors or in a well-ventilated area.  
Do not breathe vapor.  
Do not eat, drink or smoke when using this product.  
Wash hands thoroughly after handling.  
Contaminated work clothing should not be allowed out of the workplace.

### Response

: Get medical attention if you feel unwell.  
IF exposed:  
Call a POISON CENTER or physician.  
**IF INHALED:**  
Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
Call a POISON CENTER or physician if you feel unwell.  
**IF ON SKIN:**  
Wash with plenty of soap and water.  
Wash contaminated clothing before reuse.  
If skin irritation or rash occurs:  
Get medical attention.  
**IF IN EYES:**  
Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists:  
Get medical attention.

- Storage** : Store locked up.  
Store in a well-ventilated place.  
Keep cool.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Other hazards which do not result in classification** : None known.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture

Ingredient name	% by weight	CAS number
Resorcinol	7 - 10	108-46-3
Phenol	5 - 7	108-95-2
Sodium Hydroxide	3 - 5	1310-73-2
Ethanol	3 - 5	64-17-5
Methanol	0.1 - 0.2	67-56-1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim

to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### **Indication of immediate medical attention and special treatment needed, if necessary**

- |  |   |   |
|--|---|---|
| <b>Notes to physician</b>                | : | Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.   |
| <b>Specific treatments</b>               | : | No specific treatment.  |
| <b>Protection of first aid personnel</b> | : | No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

See toxicological information (Section 11)

## **Section 5. Fire-fighting measures**

### **Extinguishing media**

- |   |   |  |
|---|---|--|
| <b>Suitable extinguishing media</b>                   | : | Use dry chemical, CO2, water spray (fog) or foam.  |
| <b>Unsuitable extinguishing media</b>                 | : | Do not use water jet.  |
| <b>Specific hazards arising from the chemical</b>     | : | Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.  |
| <b>Hazardous thermal decomposition products</b>       | : | Decomposition products may include the following materials:<br>carbon dioxide<br>carbon monoxide<br>metal oxide/oxides   |
| <b>Special protective actions for fire-fighters</b>   | : | Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. |
| <b>Special protective equipment for fire-fighters</b> | : | Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.  |

## **Section 6. Accidental release measures**

### **Personal precautions, protective equipment and emergency procedures**

- |                                    |   |   |
|------------------------------------|---|---|
| <b>For non-emergency personnel</b> | : | No action shall be taken involving any personal risk or without |
|------------------------------------|---|---|

- suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### **Methods and material for containment and cleaning up**

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13 of SDS). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

## **Section 7. Handling and storage**

### **Precautions for safe handling**

- Protective measures** : Put on appropriate personal protective equipment (see section 8 of SDS). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container. Take precautionary measures against

electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Follow US NFPA 30, "Flammable & Combustible Liquids Code," or other national, state and local codes on safe handling of flammable liquids. Train workers in the recognition and prevention of hazards associated with the storage, handling and transfer of flammable liquids in the plant. Store in an area designated for storage of flammable liquids (See NPFA 30, and OSHA 29 CFR 1910.106)

**Advice on general occupational hygiene**

- : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Conditions for safe storage, including any incompatibilities**

- : Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Resorcinol	<p><b>NIOSH REL (1994-06-01)</b> Time Weighted Average (TWA) 45 mg/m<sup>3</sup> 10 ppm <b>Pollutant concentration that should not be exceeded during working hours and which workers are believed to be exposed during a period of 15 minutes maximum, without experiencing: a) irritation. b) chronic or irreversible tissue damage. c) dependent toxic effects of exposure rate. d) Narcosis of sufficient magnitude to increase susceptibility to accidents. e) The reduction of ability to get to safety by their own means.</b> 90 mg/m<sup>3</sup> 20 ppm</p> <p><b>ACGIH TLV (1996-05-18)</b> Time Weighted Average (TWA) 45 mg/m<sup>3</sup> 10 ppm <b>Short Term Exposure Limit (STEL)</b> 90 mg/m<sup>3</sup> 20 ppm</p>
Phenol	<p><b>ACGIH TLV (1996-05-18)</b> Time Weighted Average (TWA) 19 mg/m<sup>3</sup> 5 ppm <b>OSHA PEL (1993-06-30)</b> Time Weighted Average (TWA) 19 mg/m<sup>3</sup> 5 ppm <b>NIOSH REL (1994-06-01)</b> Time Weighted Average (TWA) 19 mg/m<sup>3</sup> 5 ppm <b>Ceiling</b> 60 mg/m<sup>3</sup> 15.6 ppm</p>

Sodium Hydroxide	<p><b>ACGIH TLV (1994-09-01)</b> Ceiling 2 mg/m<sup>3</sup></p> <p><b>NIOSH REL (1994-06-01)</b> Ceiling 2 mg/m<sup>3</sup></p> <p><b>OSHA PEL (1993-06-30)</b> Time Weighted Average (TWA) 2 mg/m<sup>3</sup></p>
Ethanol	<p><b>ACGIH TLV (2008-01-01)</b> Pollutant concentration that should not be exceeded during working hours and which workers are believed to be exposed during a period of 15 minutes maximum, without experiencing: a) irritation. b) chronic or irreversible tissue damage. c) dependent toxic effects of exposure rate. d) Narcosis of sufficient magnitude to increase susceptibility to accidents. e) The reduction of ability to get to safety by their own means. 1,880 mg/m<sup>3</sup> 1,000 ppm</p> <p><b>OSHA PEL (1993-06-30)</b> Time Weighted Average (TWA) 1,900 mg/m<sup>3</sup> 1,000 ppm</p> <p><b>NIOSH REL (1994-06-01)</b> Time Weighted Average (TWA) 1,900 mg/m<sup>3</sup> 1,000 ppm</p>
Methanol	<p><b>ACGIH TLV (1994-09-01)</b> Time Weighted Average (TWA) 262 mg/m<sup>3</sup> 200 ppm</p> <p><b>Short Term Exposure Limit (STEL) 328 mg/m<sup>3</sup> 250 ppm</b></p> <p><b>OSHA PEL (1993-06-30)</b> Time Weighted Average (TWA) 260 mg/m<sup>3</sup> 200 ppm</p> <p><b>NIOSH REL (1994-06-01)</b> Time Weighted Average (TWA) 260 mg/m<sup>3</sup> 200 ppm</p> <p><b>Pollutant concentration that should not be exceeded during working hours and which workers are believed to be exposed during a period of 15 minutes maximum, without experiencing: a) irritation. b) chronic or irreversible tissue damage. c) dependent toxic effects of exposure rate. d) Narcosis of sufficient magnitude to increase susceptibility to accidents. e) The reduction of ability to get to safety by their own means. 325 mg/m<sup>3</sup> 250 ppm</b></p>

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**Individual protection measures**



- |                                   |   |  |
|-----------------------------------|---|--|
| <b>Hygiene measures</b>           | : | Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.   |
| <b>Eye/face protection</b>        | : | Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.   |
| <br><b><u>Skin protection</u></b> |   |  |
| <b>Hand protection</b>            | : | Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
| <b>Body protection</b>            | : | Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.  |
| <b>Other skin protection</b>      | : | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.  |
| <b>Respiratory protection</b>     | : | Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  |

## Section 9. Physical and chemical properties

### Appearance

- |                                      |   |  |
|--------------------------------------|---|--|
| <b>Physical state</b>                | : | Liquid   |
| <b>Color</b>                         | : | Clear, reddish-brown                                     |
| <b>Odor</b>                          | : | Slight alcoholic   |
| <b>Odor threshold</b>                | : | Not available  |
| <b>pH</b>                            | : | 9.8 - 10.2   |
| <b>Melting point/ Freezing point</b> | : | 0 °C (32.00 °F)  |
| <b>Boiling point</b>                 | : | 102 °C (215.60 °F)                                       |
| <b>Flash point</b>                   | : | Pensky-Martens Closed Cup: 65 °C (149.00 °F) (ASTM D 93) |



<b>Burning time</b>	:	Not available
<b>Burning rate</b>	:	Not available
<b>Evaporation rate</b>	:	0.6 ((n-Butyl acetate=1))
<b>Flammability (solid, gas)</b>	:	Not available
<b>Lower and upper explosive (flammable) limits</b>	:	<b>Lower:</b> Not available <b>Upper:</b> Not available
<b>Vapor pressure</b>	:	55 mm Hg @ 25 °C (77.00 °F)
<b>Vapor density</b>	:	Not available
<b>Relative density</b>	:	1.1751
<b>Solubility</b>	:	Not available
<b>Solubility in water</b>	:	Slightly
<b>Partition coefficient: n-octanol/water</b>	:	Not available
<b>Auto-ignition temperature</b>	:	Not available
<b>Decomposition temperature</b>	:	Not available
<b>SADT</b>	:	Not available
<b>Viscosity</b>	:	<b>Dynamic:</b> 1,450 - 1,650 cPs
		<b>Kinematic:</b> Not available

#### Other information

*The SDS is not to be used as a specification sheet. For Specific technical information on the product listed above, a sales specification sheet should be obtained from your Hexion representative.*

## Section 10. Stability and reactivity

<b>Reactivity</b>	:	Normally stable, but will polymerize at high temperatures with some evolution of heat.
<b>Chemical stability</b>	:	The product is stable.
<b>Possibility of hazardous reactions</b>	:	Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid</b>	:	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
<b>Incompatible materials</b>	:	Reactive or incompatible with the following materials: oxidizing materials acids
<b>Hazardous decomposition products</b>	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Resorcinol				
	LD50 Oral	Rat	301 mg/kg	-
	LD50 Oral	Rat	202 mg/kg	-
	LD50 Dermal	Rabbit	3,360 mg/kg	-
Phenol				
	LD50 Oral	Rat	317 mg/kg	-
	LC50 Inhalation	Rat	0.316 mg/l	-
	LD50 Dermal	Rabbit	630 mg/kg	-
Ethanol				
	LD50 Oral	Rat	7,000 mg/kg	-
	LC50 Inhalation	Rat	125 mg/l	4 h
Methanol				
	LD50 Oral	Rat	5,628 mg/kg	-
Cascophen(TM) LT-5210Q				
	LD50 Oral	Rat	> 2,001 mg/kg	-
	LC50 Inhalation	Rat	> 21 mg/l	4 h
	LC50 Inhalation	Rat	> 21 mg/l	1 h
	LD50 Dermal	Rabbit	> 2,001 mg/kg	-

**Conclusion/Summary** : Not available

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Resorcinol	Skin - Moderate irritant	Rabbit		24 hrs	-
	Skin - Severe irritant	Rabbit			-
	eyes - Severe irritant	Rabbit			-
Phenol	Skin - -	Rat	> 4		-
	eyes - Cornea opacity	Rabbit	> 3		-
Ethanol	Skin - Mild irritant	Rabbit			-
	Skin - Moderate irritant	Rabbit		24 hrs	-
	eyes - Severe irritant	Rabbit			-
	eyes - Mild irritant	Rabbit		24 hrs	-

	eyes - Moderate irritant	Rabbit		0.001 hrs	-
--	--------------------------------	--------	--	-----------	---

**Conclusion/Summary**

**Skin** : 16 CFR Part 1500.41 Rabbit Slight Skin Irritant  
**eyes** : 16 CFR Part 1500.42 Rabbit Severe Eye Irritant  
**Respiratory** : Not available

**Sensitization**

**Conclusion/Summary**

**Skin** : Not available  
**Respiratory** : Not available

**Mutagenicity**

**Conclusion/Summary** : Not available

**Carcinogenicity**

**Conclusion/Summary** : Not available

**Reproductive toxicity**

**Conclusion/Summary** : Not available

**Teratogenicity**

**Conclusion/Summary** : Not available

**Specific target organ toxicity (single exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
Resorcinol	Category 3 Category 1		Respiratory tract irritation central nervous system (CNS) blood system
Phenol	Category 1		eyes
Sodium Hydroxide	Category 1		respiratory tract
Ethanol	Category 3 Category 1		Respiratory tract irritation Narcotic effects central nervous system (CNS)
Methanol	Category 3 Category 1 Category 2		Respiratory tract irritation central nervous system (CNS) optic nerve

**Specific target organ toxicity (repeated exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
Resorcinol	Category 2		cardiovascular system

	Category 1 Category 2		thyroid Spleen liver kidneys
Phenol	Category 2		gastrointestinal tract kidneys eyes heart lungs liver skin
Ethanol	Category 1		liver
Methanol	Category 2		kidneys liver gastrointestinal tract skin respiratory tract

**Aspiration hazard**

Not available

**Information on the likely routes of exposure** : Not available

**Potential acute health effects**

**Eye contact** : Causes serious eye irritation.  
**Inhalation** : Harmful if inhaled. May cause respiratory irritation.  
**Skin contact** : May cause an allergic skin reaction.  
**Ingestion** : Irritating to mouth, throat and stomach.

**Symptoms related to the physical, chemical and toxicological characteristics**

**Eye contact** : Adverse symptoms may include the following:  
 pain or irritation  
 watering  
 redness  
**Inhalation** : Adverse symptoms may include the following:  
 respiratory tract irritation  
 coughing  
 reduced fetal weight  
 increase in fetal deaths  
 skeletal malformations  
**Skin contact** : Adverse symptoms may include the following:  
 irritation  
 redness  
 reduced fetal weight  
 increase in fetal deaths  
 skeletal malformations  
**Ingestion** : Adverse symptoms may include the following:  
 reduced fetal weight  
 increase in fetal deaths

skeletal malformations

**Delayed and immediate effects and also chronic effects from short and long term exposure**

**Short term exposure**

Potential immediate effects : Not available  
 Potential delayed effects : Not available

**Long term exposure**

Potential immediate effects : Not available  
 Potential delayed effects : Not available

**Potential chronic health effects**

Conclusion/Summary : Not available

General : Causes damage to organs through prolonged or repeated exposure:  
 Once sensitized, a severe allergic reaction may occur when  
 subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : Suspected of causing genetic defects.

Teratogenicity : May damage the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : May damage fertility.

**Numerical measures of toxicity**

**Acute toxicity estimates**

Not available

**Section 12. Ecological information**

**Toxicity**

Product/ingredient name	Result	Species	Exposure
resorcinol			
	Acute LC50 > 100 mg/l Fresh water	Fish - Rainbow trout,donaldson trout	96 h
	Acute LC50 40,000 µg/l Fresh water	Fish - Fathead minnow	96 h
	Acute LC50 100,000 µg/l Fresh water	Aquatic invertebrates. Water flea	48 h
Phenol			
	Acute LC50 8.9 mg/l Fresh water	Fish - Rainbow trout,donaldson trout	96 h
	Acute NOEC 0.077 mg/l Fresh water	Fish - Carp	60 d
	Acute EC50 3.1 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute NOEC 0.16 mg/l Fresh water	Aquatic invertebrates. Water flea	16 d
	Acute EC50 61.1 mg/l Fresh water	Aquatic plants - Microalgae	96 h

	Acute EC50 21 mg/l Fresh water	Micro-organism - Soil organisms	24 h
	Chronic NOEC 2.2 mg/l Fresh water	Aquatic invertebrates. Water flea	2 d
ethanol			
	Acute LC50 42,000 µg/l Fresh water	Fish - Rainbow trout,donaldson trout	96 h
	Acute LC50 100 mg/l Fresh water	Fish - Fathead minnow	96 h
	Acute EC50 2,000 µg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute EC50 100 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute EC50 20,000 mg/l Fresh water	Aquatic plants - Green Flagellate	96 h
	Acute EC50 10,000 mg/l Fresh water	Aquatic plants - Algae	96 h
	Acute EC50 10,000 mg/l Fresh water	Aquatic plants - Diatom	96 h
	Chronic NOEC 0.375 mg/l Fresh water	Fish - Eastern mosquitofish	84 d
	Chronic No observable effect concentration < 6,300 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
methanol			
	Acute EC50 13,000 mg/l Fresh water	Fish - Rainbow trout,donaldson trout	4 d

**Conclusion/Summary** : Not available

**Persistence/degradability**

**Conclusion/Summary** : Not available

**Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Resorcinol	0.8	-	low
Phenol	1.5	17.5	low
Ethanol	-0.35	-	low
Methanol	-0.77	-	low

**Mobility in soil**

**Soil/water partition coefficient (KOC)** : Not available

**Other adverse effects** : No known significant effects or critical hazards.

**Section 13. Disposal considerations**

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be

disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

### International transport regulations

Regulatory information	UN/NA number	Proper shipping name	Classes/*PG	Reportable Quantity (RQ)
CFR	1993	COMBUSTIBLE LIQUID, N.O.S. (Ethanol, Phenol)	Class CBL III	Phenol, Sodium Hydroxide
TDG		Non-regulated		
IMO/IMDG		Non-regulated		
IATA (Cargo)		Non-regulated		

\*PG : Packing group

**Special precautions for user** : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## Section 15. Regulatory information

### United States

**U.S. Federal regulations** : **United States - TSCA 12(b) - Chemical export notification:** None required.  
**United States - TSCA 5(a)2 - Final significant new use rules:** Not listed  
**United States - TSCA 5(a)2 - Proposed significant new use rules:** Listed  
 3(2H)-Isothiazolone, 5-chloro-2-methyl- 3(2H)-Isothiazolone, 2-methyl-  
**United States - TSCA 5(e) - Substances consent order:** Not listed

### SARA 313



		Product name	CAS number
Form R - Reporting requirements	:	Phenol	108-95-2
Supplier notification	:	Phenol	108-95-2

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

**California Prop. 65:** : WARNING: This product contains less than 0.1% of a chemical known to the State of California to cause cancer., WARNING: This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Methanol	No.	Yes.	No.	No.
2-Pentanone, 4-methyl-	Yes.	No.	No.	No.

**United States inventory (TSCA 8b)** : All components are listed or exempted.

#### Canada

**WHMIS (Canada)** : Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).  
Class D-1A: Material causing immediate and serious toxic effects (Very toxic).  
Class D-2A: Material causing other toxic effects (Very toxic).  
Class D-2B: Material causing other toxic effects (Toxic).

#### Canadian lists

**Canadian NPRI** : The following components are listed: Phenol Ethanol

**CEPA Toxic substances** : None required.

#### International regulations

**International lists** : **Australia inventory (AICS):** Not determined.  
**Canada inventory:** All components are listed or exempted.  
**Japan inventory:** Not determined.  
**China inventory (IECSC):** Not determined.  
**Korea inventory:** Not determined.  
**New Zealand Inventory (NZIoC):** Not determined.  
**Philippines inventory (PICCS):** Not determined.  
**United States inventory (TSCA 8b):** All components are listed or exempted.  
**Taiwan inventory (CSNN):** Not determined.

## Section 16. Other information

**Hazardous Material Information System III (U.S.A.) :**

Health	*	3
--------	---	---

<b>Flammability</b>	2
<b>Physical hazards</b>	0

**Caution:** HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868. The customer is responsible for determining the PPE code for this material.

**Full text of abbreviated H statements** : Not applicable.

### History

**Date of printing** : 09/09/2015  
**Date of issue/Date of revision** : 04/09/2015  
**Date of previous issue** : 12/28/2011  
**Version** : 10.0  
**Prepared by** : Product Safety Stewardship  
**Key to abbreviations** : ATE = Acute Toxicity Estimate  
 BCF = Bioconcentration Factor  
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
 IATA = International Air Transport Association  
 IBC = Intermediate Bulk Container  
 IMDG = International Maritime Dangerous Goods  
 LogPow = logarithm of the octanol/water partition coefficient  
 MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
 UN = United Nations  
**References** : Not available

### Notice to reader

The information provided herein was believed by Hexion Inc. ("Hexion") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Hexion are subject to Hexion's terms and conditions of sale. HEXION MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY HEXION, except that the product shall conform to Hexion's specifications. Nothing contained herein constitutes an offer for the sale of any product.

® and (TM) Licensed trademarks of Hexion Inc.