

SAFETY DATA SHEET

FOR INDUSTRIAL USE ONLY

Wonderbond® Hrdnr M-200L

Wonderbond® Hrdnr M-200L

Section 1. Product and company identification

GHS product identifier

MSDS Number Product type

Product type : Catalyst

Material uses : Wonderbond Hardener

Manufacturer/Supplier/Impor

ter

Hexion Inc.

180 East Broad Street Columbus, Ohio

000000103892

43215 USA

Contact person : 4information@hexion.com

Telephone : For additional health and safety or regulatory information, call

1 888 443 9466.

Emergency telephone number : For Emergency Medical Assistance

Call Health & Safety Information Services

1-866-303-6949

For Emergency Transportation Information CHEMTREC US Domestic (800) 424-9300 CHEMTREC International (703) 527-3887 CANUTEC CA Domestic (613) 996-6666

Section 2. Hazards identification

Classification of the substance or

mixture

SKIN CORROSION/IRRITATION - Category 1

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

CARCINOGENICITY - Category 1B

GHS label elements

Hazard pictograms :

Signal word : Dange

Hazard statements: H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H350 May cause cancer.

Precautionary statements

Wonderbond® Hrdnr M-200L Page:2/13

General : Not applicable.

Prevention : Obtain special instructions before use.

Do not handle until all safety precautions have been read and

understood.

Use personal protective equipment as required.

Wear protective gloves. Wear eye or face protection. Wear protective clothing.

Wash hands thoroughly after handling.

Response : IF exposed or concerned:

Get medical attention.

IF INHALED:

Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Immediately call a POISON CENTER or physician.

IF SWALLOWED:

Immediately call a POISON CENTER or physician.

Rinse mouth.

Do NOT induce vomiting. **IF ON SKIN (or hair):**

Take off immediately all contaminated clothing.

Rinse skin with water or shower.

Wash contaminated clothing before reuse.

Immediately call a POISON CENTER or physician.

IF IN EYES:

Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or physician.

Storage : Store locked up.

Disposal: Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Other hazards which do not result

in classification

None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% by weight	CAS
		number
Aluminum Nitrate Nonahydrate	50 - 70	7784-27-2
Phosphoric Acid	5 - 7	7664-38-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Wonderbond® Hrdnr M-200L Page:3/13

Section 4. First aid measures

Description of necessary first aid measures

Skin contact

Ingestion

Eye contact : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the

upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be

treated promptly by a physician.

Inhalation : Get medical attention immediately. Call a poison center or physician.

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery

position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

: Get medical attention immediately. Call a poison center or physician. Wash contaminated skin with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10

minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give

material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and

get medical attention immediately. Maintain an open airway. Loosen

tight clothing such as a collar, tie, belt or waistband.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give

mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

No action shall be taken involving any personal risk or without

See toxicological information (Section 11)

Protection of first aid personnel

Section 5. Fire-fighting measures

Wonderbond® Hrdnr M-200L Page:4/13

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.

None known.

Specific hazards arising from the chemical

Hazardous thermal decomposition products

In a fire or if heated, a pressure increase will occur and the container may burst.

 Decomposition products may include the following materials: phosphorus oxides

Special protective actions for firefighters

Special protective equipment for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

: Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13 of SDS). The spilled material may be neutralized with sodium carbonate, sodium bicarbonate or sodium hydroxide. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

Wonderbond® Hrdnr M-200L Page:5/13

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see section 8 of SDS). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from alkalis. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Estore in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Store locked up. Separate from alkalis. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Aluminum Nitrate Nonahydrate	ACGIH TLV () Calculated as Al Time Weighted Average (TWA) 2 mg/m3 Form: Soluble salt
Phosphoric Acid	ACGIH TLV (1994-09-01) Time Weighted Average (TWA) 1 mg/m3 Short Term Exposure Limit (STEL) 3 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 1 mg/m3 Pollutant concentration that should not be exceeded during working hours and which workers are believed to be exposed during a period of 15 minutes maximum, without experiencing: a) irritation. b) chronic or irreversible tissue damage. c) dependent toxic effects of exposure rate. d) Narcosis of sufficient magnitude to increase susceptibility to accidents. e) The reduction of ability to get to safety by their own means. 3 mg/m3 OSHA PEL (1993-06-30) Time Weighted Average (TWA) 1 mg/m3

Wonderbond® Hrdnr M-200L Page:6/13

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the

Wonderbond® Hrdnr M-200L Page:7/13

selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid

Color : Clear, colorless/colourless

Odor : Not available
Odor threshold : Not available

pH : 0.9 - 1.5 @ 25 °C (77.00 °F)

Melting point/ Freezing point : $0 \, ^{\circ}\text{C} \, (32.00 \, ^{\circ}\text{F})$

Boiling point : $100 \,^{\circ}\text{C} \, (212.00 \,^{\circ}\text{F})$

Flash point : Not determined

Burning time : Not available **Burning rate** : Not available

Evaporation rate : 0.62

Flammability (solid, gas) : Not available

Lower and upper explosive : Lower: Not applicable. (flammable) limits : Upper: Not applicable.

Vapor pressure : 17.5 mm Hg @ 21 °C (69.80 °F)

Vapor density : 1 [Air = 1]

Relative density : 1.29

Solubility : Not available Solubility in water : Dispersible

Partition coefficient: n- : Not applicable.

octanol/water

Auto-ignition temperature : Not applicable.

Decomposition temperature : Not available **SADT** : Not available

Viscosity : Dynamic: Not available

Kinematic: Not available

Other information

The SDS is not to be used as a specification sheet. For Specific technical information on the product listed above, a sales specification sheet should be obtained from your Hexion representative.

Section 10. Stability and reactivity

Wonderbond® Hrdnr M-200L Page:8/13

Reactivity : Stable under normal conditions.

Chemical stability : The product is stable.

Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid : No specific data.

Incompatible materials : Attacks many metals producing extremely flammable hydrogen gas

which can form explosive mixtures with air.

Reactive or incompatible with the following materials:

alkalis,

Hazardous decomposition products: Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Aluminum Nitrate Nonahydrate				
	LD50 Oral	Rat	3,671 mg/kg	-
Phosphoric Acid				
	LD50 Oral	Rat	1,250 mg/kg	-
	LC50 Inhalation	Rat	> 0.85 mg/l	1 h
	LD50 Dermal	Rat	1,260 mg/kg	-

Conclusion/Summary : Not available

Irritation/Corrosion

Conclusion/Summary

Skin:Not availableeyes:Not availableRespiratory:Not available

Sensitization

Conclusion/Summary

Skin : Not available
Respiratory : Not available

Mutagenicity

Conclusion/Summary : Not available

Carcinogenicity

Conclusion/Summary : Not available

Wonderbond® Hrdnr M-200L Page:9/13

Reproductive toxicity

Conclusion/Summary : Not available

Teratogenicity

Conclusion/Summary : Not available

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Phosphoric Acid	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available

Aspiration hazard

Not available

Information on the likely routes of

exposure

Not available

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : May give off gas, vapor or dust that is very irritating or corrosive to

the respiratory system.

Skin contact : Causes severe burns.

Ingestion : May cause burns to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion: Adverse symptoms may include the following:

stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available
Potential delayed effects : Not available

Long term exposure

Potential immediate effects : Not available **Potential delayed effects** : Not available

Wonderbond® Hrdnr M-200L Page: 10/13

Potential chronic health effects

Conclusion/Summary Not available

General No known significant effects or critical hazards.

May cause cancer. Risk of cancer depends on duration and level of Carcinogenicity

exposure.

Mutagenicity No known significant effects or critical hazards. **Teratogenicity** No known significant effects or critical hazards. No known significant effects or critical hazards. **Developmental effects Fertility effects** No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available

Section 12. Ecological information

Toxicity

Conclusion/Summary Not available

Persistence/degradability

Conclusion/Summary Not available

Mobility in soil

Soil/water partition coefficient

Other adverse effects No known significant effects or critical hazards.

Not available

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains

3.0 03/19/2015 11/20/2010 Version: Date of issue/Date of revision: Date of previous issue:

Wonderbond® Hrdnr M-200L Page:11/13

and sewers.

Section 14. Transport information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

International transport regulations

Regulatory information	UN/NA number	Proper shipping name	Classes/*PG	Reportable Quantity (RQ)
CFR	3098	OXIDIZING LIQUID, CORROSIVE, N.O.S. (Aluminum Nitrate, Phosphoric Acid)	Class 5.1 (8) II	
TDG	3098	OXIDIZING LIQUID, CORROSIVE, N.O.S. (Aluminum Nitrate, Phosphoric Acid)	Class 5.1 (8) II	
IMO/IMDG	3098	OXIDIZING LIQUID, CORROSIVE, N.O.S. (Aluminum Nitrate, Phosphoric Acid)	Class 5.1 (8) II	

*PG: Packing group

Special precautions for user

: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.'

Section 15. Regulatory information

United States

HCS Classification : Highly toxic material

Corrosive material

Carcinogen

Target organ effects

U.S. Federal regulations : United States - TSCA 12(b) - Chemical export notification: None

required.

United States - TSCA 5(a)2 - Final significant new use rules: Not listed United States - TSCA 5(a)2 - Proposed significant new use rules: Not

listed

United States - TSCA 5(e) - Substances consent order: Not listed

SARA 313

Wonderbond® Hrdnr M-200L Page: 12/13

		Product name	CAS number
Form R - Reporting	:	Nitric acid, aluminum salt	7784-27-2
requirements		(3:1)	
Supplier notification	:	Nitric acid, aluminum salt	7784-27-2
		(3:1)	

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

<u>California Prop. 65:</u> : None required.

United States inventory (TSCA:

8b)

All components are listed or exempted.

Canada

WHMIS (Canada) : Class D-1B: Material causing immediate and serious toxic effects (Toxic).

Class D-2B: Material causing other toxic effects (Toxic).

Class E: Corrosive material

Canadian lists

Canadian NPRI: The following components are listed: Nitric acid, aluminum salt (3:1)

Phosphoric acid

CEPA Toxic substances : None required.

International regulations

International lists : Australia inventory (AICS): All components are listed or exempted.

Canada inventory: All components are listed or exempted. **Japan inventory:** All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

Korea inventory: All components are listed or exempted.

New Zealand Inventory (NZIoC): All components are listed or exempted. Philippines inventory (PICCS): All components are listed or exempted. United States inventory (TSCA 8b): All components are listed or exempted.

Taiwan inventory (CSNN): All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System III (U.S.A.):

Health	*	3
Flammability		1
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Wonderbond® Hrdnr M-200L Page: 13/13

Full text of abbreviated H : Not applicable.

statements

History

Date of printing: 01/17/2017Date of issue/Date of revision: 03/19/2015Date of previous issue: 11/20/2010

Version : 3.0

Prepared by

Key to abbreviations

: Product Safety Stewardship

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods by

Rail

UN = United Nations

References : Not available

Notice to reader

The information provided herein was believed by Hexion Inc. ("Hexion") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Hexion are subject to Hexion's terms and conditions of sale. HEXION MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY HEXION, except that the product shall conform to Hexion's specifications. Nothing contained herein constitutes an offer for the sale of any product.

® and (TM) Licensed trademarks of Hexion Inc.