

MOLYKOTE® Hydraulic Oils

Features

- Lower overall maintenance costs
- Wider temperature range
- Longer oil-drain intervals
- Reduced lubricant consumption
- Extended equipment lifetime
- Reduced energy consumption
- Long life reduces lubricant usage, maintenance costs

Composition

- Hydrocracked mineral oil (MO) and polyalphaolefin/mineral oil (PAO/MO) based lubricants

Description

MOLYKOTE® Hydraulic Oils minimize formation of emulsions in contact with water due to the purity of the base fluid. They will generally perform successfully in hydraulic systems far longer than conventional hydraulic oils. Plants can gain significant savings from reduced oil consumption, reduced disposal cost, labor savings and fewer interruptions to production. These nontoxic oils are derived from hydrocracked or synthetic base stocks and can be used in systems designed for low-pour-point or high-flash-point mineral oils.

Typical properties

Specification writers: These values are not intended for use in preparing specifications. Please contact your local MOLYKOTE® sales representative prior to writing specifications on this product.

MOLYKOTE® brand Product	NSF ⁽¹⁾	ISO Grade	Viscosity @ 40°C, cSt	Viscosity @ 100°C, cSt	Viscosity @ 100°F, cSt	Viscosity @ 210°F, cSt	Viscosity Index	Flash Point, °F	Fire Point, °F	Pour Point, °C	Density @ 20°C, g/mL	Density @ 20°C, lb/gal	Base Oil	Additive Package
Hydraulic Oils														
L-0322 Hydraulic Oil	-	22	21.5	4.2	-	4.4	100	365	385	-21	0.852	-	MO	R&O/AW
L-0532FG Multi Purpose Light Oil	H-1	32	31.2	5.3	34.3	5.4	103	420	445	-18	0.857	7.13	MO	R&O/AW
L-0346 Hydraulic Oil	H-2	46	45	6.6	49.9	6.8	105	430	445	-21	0.864	7.19	MO	R&O/AW
L-0346FG Hydraulic Oil	H-1	46	44.5	6.6	49	6.7	100	425	440	-21	0.86	7.16	MO	R&O/AW
L-1346FG Synthetic Blend Hydraulic Oil	H-1	46	44.7	7.4	49.2	7.6	131	460	545	-42	0.832	7.11	PAO/MO	R&O/AW
L-1368FG Synthetic Blend Hydraulic Oil	H-1	68	68.2	10.3	75.6	10.5	138	470	565	-42	0.838		PAO/MO	R&O/AW
L-0368FG Hydraulic Oil	H-1	68	66	8.3	73.9	8.6	100	460	485	-15	0.867	7.22	MO	R&O/AW
L-0568 Multi Purpose Oil	H-2	68	68.5	9.2	76.3	9.4	110	450	480	-15	0.868	7.22	MO	R&O/AW
L-0510 Multi Purpose Oil	H-2	100	103	11.8	104	12.1	95	470	495	-15	0.876	7.29	MO	R&O/AW
L-0510FG Multi Purpose Oil	H-1	100	105.1	12	118.2	12.3	103	495	540	-15	0.866	7.21	MO	R&O/AW
L-1332FG Synthetic Hydraulic & Gear Oil	H-1	32	31.7	5.8	-	-	127	440	485	-42	0.834	-	PAO/MO	R&O/AW

⁽¹⁾The H-1 designation indicates the lubricated part can have incidental food contact not to exceed 10 ppm. The H-2 designation indicates the lubricated part cannot have contact with food.

How to use

Follow equipment manufacturer's recommendations for maintenance procedures and oil specifications.

To ensure the longest possible life for lubricating fluids, sample analysis is recommended. When utilized on a regular basis, sample analysis can track normal aging and depletion of additives in lubricating fluids. Sample analysis can identify abnormal contamination that may be limiting lubricant life. Contact MOLYKOTE® customer service for additional information.

Listing and specifications

MOLYKOTE® Hydraulic Oils are kosher approved and conform to USDA listing requirements under H-1 or H-2 designations (see Typical Properties table). An H-1 designation indicates the lubricated part can have incidental food contact not to exceed 10 ppm. An H-2 designation indicates the lubricated part cannot have contact with food.

Handling precautions

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION.

Usable life and storage

MOLYKOTE® Hydraulic Oils have a shelf life of 60 months from date of manufacture. Refer to product packaging for use-by date.

Packaging

MOLYKOTE® Hydraulic Oils are available in 18.9 and 208.2 L (5 and 55 gal) containers.

*DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted.
© 2003-2019 DuPont.*

The information set forth herein is furnished free of charge and is based on technical data that DuPont believes to be reliable and falls within the normal range of properties. It is intended for use by persons having technical skill, at their own discretion and risk. This data should not be used to establish specification limits nor used alone as the basis of design. Handling precaution information is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use and disposal are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. As with any product, evaluation under end use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate or a recommendation to infringe on patents.