

# SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY

Product name: POLYOX™ WSR N12K

Issue Date: 05/04/2015 Print Date: 05/27/2015

THE DOW CHEMICAL COMPANY encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

# **1. IDENTIFICATION**

Product name: POLYOX™ WSR N12K

# Recommended use of the chemical and restrictions on use

**Identified uses:** Thickener. Binder. Lubricant. Processing aid. We recommend that you use this product in a manner consistent with the listed use. If your intended use is not consistent with the stated use, please contact your sales or technical service representative.

# **COMPANY IDENTIFICATION**

THE DOW CHEMICAL COMPANY 2030 WILLARD H DOW CENTER MIDLAND MI 48674-0000 UNITED STATES

**Customer Information Number:** 

800-258-2436 SDSQuestion@dow.com

# EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 800-424-9300 Local Emergency Contact: 800-424-9300

# 2. HAZARDS IDENTIFICATION

# Hazard classification

This material is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200. Combustible dust

# Label elements

Signal word: WARNING!

#### Hazards May form combustible dust concentrations in air

# **Precautionary statements**

# Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Take precautionary measures against static discharge.

# Other hazards

May form explosive dust-air mixture. Slipping hazard.

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

This product is a mixture.

| Component              | CASRN         | Concentration |  |
|------------------------|---------------|---------------|--|
|                        |               |               |  |
| Poly(ethylene oxide)   | 25322-68-3    | >= 95.0 %     |  |
| Fumed silica (generic) | 112945-52-5   | <= 3.0 %      |  |
| Calcium as mixed salts | Not available | < 1.0 %       |  |
|                        |               |               |  |

# 4. FIRST AID MEASURES

# Description of first aid measures

**General advice:** If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: No emergency medical treatment necessary.

Skin contact: Wash off with plenty of water.

**Eye contact:** Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

**Ingestion:** If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

**Most important symptoms and effects, both acute and delayed:** Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

# Indication of any immediate medical attention and special treatment needed

**Notes to physician:** No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

# 5. FIREFIGHTING MEASURES

**Suitable extinguishing media:** Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Unsuitable extinguishing media: no data available

# Special hazards arising from the substance or mixture

**Hazardous combustion products:** During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide.

**Unusual Fire and Explosion Hazards:** Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Do not permit dust to accumulate. When suspended in air dust can pose an explosion hazard. Minimize ignition sources. If dust layers are exposed to elevated temperatures, spontaneous combustion may occur. Pneumatic conveying and other mechanical handling operations can generate combustible dust. To reduce the potential for dust explosions, electrically bond and ground equipment and do not permit dust to accumulate. Dust can be ignited by static discharge.

# Advice for firefighters

**Fire Fighting Procedures:** Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire. Hand held dry chemical or carbon dioxide extinguishers may be used for small fires. Dust explosion hazard may result from forceful application of fire extinguishing agents. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage.

**Special protective equipment for firefighters:** Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

# 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures:** Isolate area. Keep unnecessary and unprotected personnel from entering the area. Spilled material may cause a slipping hazard. Material becomes slippery when wet. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection. Refer to section 7, Handling, for additional precautionary measures.

**Environmental precautions:** Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

**Methods and materials for containment and cleaning up:** Contain spilled material if possible. Collect with vacuum equipment. Collect in suitable and properly labeled containers. Attempt to neutralize by adding materials such as Soda ash. See Section 13, Disposal Considerations, for additional information.

# 7. HANDLING AND STORAGE

**Precautions for safe handling:** Avoid contact with eyes. Wash thoroughly after handling. No smoking, open flames or sources of ignition in handling and storage area. Good housekeeping and controlling of dusts are necessary for safe handling of product. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Keep away from heat, sparks and flame. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

**Conditions for safe storage:** Store in accordance with good manufacturing practices. See Section 10 for more specific information.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# **Control parameters**

Exposure limits are listed below, if they exist.

| Component              | Regulation | Type of listing | Value/Notation                      |
|------------------------|------------|-----------------|-------------------------------------|
| Poly(ethylene oxide)   | US WEEL    | TWA aerosol     | 10 mg/m3                            |
| Fumed silica (generic) | OSHA Z-3   | TWA             | 20 million particles per cubic foot |
|                        | OSHA Z-3   | TWA             |                                     |

# Exposure controls

**Engineering controls:** Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations.

# Individual protection measures

Eye/face protection: Use safety glasses (with side shields).

# Skin protection

**Hand protection:** Chemical protective gloves should not be needed when handling this material. Consistent with general hygienic practice for any material, skin contact should be minimized.

**Other protection:** No precautions other than clean body-covering clothing should be needed.

**Respiratory protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator. The following should be effective types of air-purifying respirators: Particulate filter.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# Appearance

Physical state Color

Powder White to off-white

| Odor                                 | Ammoniacal                                      |
|--------------------------------------|---|
| Odor Threshold                       | No test data available                          |
| рН                                   | Not applicable                                  |
| Melting point/range                  | No test data available                          |
| Freezing point                       | Not applicable                                  |
| Boiling point (760 mmHg)             | Not applicable                                  |
| Flash point                          | closed cup No test data available               |
| Evaporation Rate (Butyl Acetate = 1) | Not applicable                                  |
| Flammability (solid, gas)            | May form combustible dust concentrations in air |
| Lower explosion limit                | No test data available                          |
| Upper explosion limit                | No test data available                          |
| Vapor Pressure                       | No test data available                          |
| Relative Vapor Density (air = 1)     | No test data available                          |
| Relative Density (water = 1)         | No test data available                          |
| Water solubility                     | Infinite  |
| Partition coefficient: n-            | no data available                               |
| octanol/water                        |   |
| Auto-ignition temperature            | No test data available                          |
| Decomposition temperature            | No test data available                          |
| Kinematic Viscosity                  | No test data available                          |
| Explosive properties                 | no data available                               |
| Oxidizing properties                 | no data available                               |
| Molecular weight                     | No test data available                          |

NOTE: The physical data presented above are typical values and should not be construed as a specification.

# **10. STABILITY AND REACTIVITY**

Reactivity: no data available

Chemical stability: Thermally stable at typical use temperatures.

Possibility of hazardous reactions: Polymerization will not occur.

**Conditions to avoid:** Product can oxidize at elevated temperatures. Generation of gas during decomposition can cause pressure in closed systems. Avoid static discharge. Avoid moisture. Avoid direct sunlight or ultraviolet sources.

Incompatible materials: Avoid contact with: Strong acids. Strong bases. Strong oxidizers.

**Hazardous decomposition products:** Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Carbon dioxide. Alcohols. Ethers. Hydrocarbons. Ketones. Polymer fragments.

# 11. TOXICOLOGICAL INFORMATION

Toxicological information on this product or its components appear in this section when such data is available.

### Acute toxicity

#### Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.

Typical for this family of materials. LD50, Rat, > 4,000 mg/kg Estimated. No deaths occurred at this concentration.

# Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

Typical for this family of materials. LD50, Rabbit, > 5,000 mg/kg Estimated.

#### Acute inhalation toxicity

No adverse effects are anticipated from inhalation. For respiratory irritation and narcotic effects: No specific, relevant data available for assessment.

The LC50 has not been determined.,

# Skin corrosion/irritation

Essentially nonirritating to skin.

# Serious eye damage/eye irritation

May cause slight eye irritation. Corneal injury is unlikely.

#### Sensitization

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization: No relevant data found.

# Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

# Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

# Carcinogenicity

Did not cause cancer in laboratory animals.

#### Teratogenicity

For the major component(s): Did not cause birth defects or any other fetal effects in laboratory animals.

# **Reproductive toxicity**

In animal studies, did not interfere with reproduction.

### **Mutagenicity**

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

# Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

# 12. ECOLOGICAL INFORMATION

Ecotoxicological information on this product or its components appear in this section when such data is available.

#### Toxicity

# Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

LC50, Pimephales promelas (fathead minnow), static test, 96 Hour, > 1,000 mg/l, OECD Test Guideline 203 or Equivalent

#### Acute toxicity to aquatic invertebrates

LC50, Daphnia magna (Water flea), static test, 48 Hour, > 100 mg/l, OECD Test Guideline 202 or Equivalent

Toxicity to bacteria IC50, Bacteria, 16 Hour, > 5,000 mg/l

# Persistence and degradability

Biodegradability: Biodegradation under aerobic static laboratory conditions is low (BOD20 or BOD28/ThOD between 2.5 and 10%). Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.
10-day Window: Fail
Biodegradation: 4.1 - 19.9 %
Exposure time: 28 d
Method: OECD Test Guideline 301B or Equivalent

Theoretical Oxygen Demand: 2.54 mg/mg

Chemical Oxygen Demand: 1.83 mg/mg

# **Biological oxygen demand (BOD)**

| v | ological oxygen demand (DOD) |         |  |
|---|------------------------------|---------|--|
|   | Incubation                   | BOD     |  |
|   | Time                         |         |  |
|   | 5 d                          | 0 - 3 % |  |
|   | 10 d                         | 0 - 3 % |  |
|   | 20 d                         | 5 - 6 % |  |

# Bioaccumulative potential

**Bioaccumulation:** For this family of materials: No bioconcentration is expected because of the relatively high molecular weight (MW greater than 1000).

# Mobility in soil

No relevant data found.

# 13. DISPOSAL CONSIDERATIONS

**Disposal methods:** DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Landfill.

# **14. TRANSPORT INFORMATION**

DOT

Not regulated for transport

# Classification for SEA transport (IMO-IMDG):

Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code Not regulated for transport Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

# **15. REGULATORY INFORMATION**

# **OSHA Hazard Communication Standard**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

This product is not a hazardous chemical under 29CFR 1910.1200, and therefore is not covered by Title III of SARA.

# Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

# Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

Calculated RQ exceeds reasonably attainable upper limit.RQComponentsCASRNRQEthylene oxide75-21-810 lbs RQ

# California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

WARNING: This product contains a chemical(s) known to the State of California to cause cancer.
Components
Ethylene oxide
75-21-8

# Pennsylvania Worker and Community Right-To-Know Act:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

ComponentsCASRNFumed silica (generic)112945-52-5

# **United States TSCA Inventory (TSCA)**

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

# 16. OTHER INFORMATION

# Revision

Identification Number: 101197122 / A001 / Issue Date: 05/04/2015 / Version: 3.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

# Legend

| OSHA Z-3 | USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts |
|----------|--|
| TWA      | 8-hour time weighted average                                       |
| US WEEL  | USA. Workplace Environmental Exposure Levels (WEEL)                |

# Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.