Safety Data Sheet



Revision Number: 003.1

1. PRODUCT AND COMPANY IDENTIFICATION

IDH number:

Product name:

Product type: Lubric Restriction of Use: None i Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

BONDERITE L-FG 69 FORGING LUBRICANT ACHESON known as DELTAGLAZE69 Lubricant coating None identified

Region:United StatesContact information:Telephone: +1 (860) 571-5100MEDICAL EMERGENCY Phone: Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone: CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet: www.henkelna.com

1224791

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW			
DANGER:	CAUSES SKIN IRRITATION.		
	MAY CAUSE AN ALLERGIC SKIN REACTION.		
	CAUSES SERIOUS EYE IRRITATION.		
	MAY CAUSE CANCER.		
	SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.		
	CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED		
	EXPOSURE.		
	SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD. CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED		

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
CARCINOGENICITY	1A
REPRODUCTIVE TOXICITY	2
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	1

PICTOGRAM(S)

Precautionary Statements

Prevention:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection.
Response:	F ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.
Storage:	Store locked up.
4004704	

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Boric acid	10043-35-3	10 - 20	
Quartz (SiO2)	14808-60-7	1 - 5	
C.I. Pigment Green 17	1308-38-9	1 - 5	
Aluminum sodium oxide	11138-49-1	1 - 5	

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES				
Inhalation:	If mist or vapor of this product is inhaled, remove person immediately to fresh air. Seek medical attention if symptoms develop or persist.			
Skin contact:	For skin contact flush with large amounts of water. Obtain medical attention if irritation persists.			
Eye contact:	Immediately flush eyes with water for at least 15 minutes, while holding eyelids open. Seek medical attention at once.			
Ingestion:	Get immediate medical attention. Do not induce vomiting.			
Symptoms:	See Section 11.			
Notes to physician:	Treat symptomatically and supportively.			
5. FIR	RE FIGHTING MEASURES			
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.			
Special firefighting procedures:	Wear full protective clothing. Wear self-contained breathing apparatus.			
Unusual fire or explosion hazards:	May liberate large quantities of dense, foul-smelling smoke which may contain unidentified toxic gasses.			
Hazardous combustion products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.			

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Do not allow product to enter sewer or waterways.
Clean-up methods:	Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations.

IDH number: 1224791

7. HANDLING AND STORAGE

Handling:

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Avoid breathing vapors or mists of this product. Use only with adequate ventilation. Do not take internally. For industrial use only.

Storage:

For safe storage, store between 0 °C (32°F) and 49 °C (120.2 °F) Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Mix gently and throughly before using. Keep from freezing.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Boric acid	6 mg/m3 STEL Inhalable fraction. 2 mg/m3 TWA Inhalable fraction.	None	None	None
Quartz (SiO2)	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust.	None	None
C.I. Pigment Green 17	0.003 mg/m3 TWA (as Cr(III)) Inhalable fraction.	1 mg/m3 PEL (as Cr) 0.5 mg/m3 PEL (as Cr)	None	None
Aluminum sodium oxide	1 mg/m3 TWA Respirable fraction.	None	None	None

Engineering controls:Provide local and general exhaust ventilation to effectively remove and
prevent buildup of any vapors or mists generated from the handling of this
product.Respiratory protection:If ventilation is not sufficient to effectively prevent buildup of
vapor/mist/fume/dust, appropriate NIOSH/MSHA respiratory protection must
be provided.Eye/face protection:Wear safety glasses; chemical goggles (if splashing is possible).Skin protection:Wear impervious gloves for prolonged contact. Gloves should be tested to
determine suitability for prolonged contact. Use of impervious apron and boots
are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Liquid Blue to blue-green Mild Not available. 6 17 mm hg <= 100 °C (<= 212°F)

Product name: BONDERITE L-FG 69 FORGING LUBRICANT ACHESON known as DELTAGLAZE69 Page 3 of 6

Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Flammability: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): VOC content: Viscosity:
Decomposition temperature.

>= 0 °C (>= 32°F) 1.29 Not determined Not applicable Not available. Not available. Not determined Not determined Disperses in water as a suspension Not determined 13 g/l 2,000 - 4,000 cp Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.
Incompatible materials:	This product may react with strong acids or oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Avoid excessive heat and ignition sources.
A	

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation:	Inhalation of vapors or mists of the product may be irritating to the respiratory system.	
Skin contact:	This product may cause irritation to the skin. Prolonged contact with this product may cause	
	allergic skin sensitization reactions.	
Eye contact:	This product is irritating to the eyes.	
Ingestion:	Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.	

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Boric acid	Oral LD50 (Mouse) = 3,450 mg/kg Oral LD50 (Rat) = 2,660 mg/kg Dermal LD50 (Rabbit) = > 2,000 mg/kg	Behavioral, Central nervous system, Developmental, Gastrointestinal, Irritant, Kidney, Liver, Reproductive, Skin, Less weight gain and food intake.
Quartz (SiO2)	None	Immune system, Lung, Some evidence of carcinogenicity
C.I. Pigment Green 17	None	No Data
Aluminum sodium oxide	None	Allergen, Central nervous system, Developmental, Irritant, Lung, Mutagen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Boric acid	No	No	No
Quartz (SiO2)	Known To Be Human Carcinogen.	Group 1	Yes
C.I. Pigment Green 17	No	No	No
Aluminum sodium oxide	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:

Do not empty into drains / surface water / ground water.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number:

Material, if discarded, is not expected to be a characteristic hazardous waste under RCRA. Wastes must be tested using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Immediate Health, Delayed Health This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). C.I. Pigment Green 17 (CAS# 1308-38-9).
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status:

Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Regulatory Affairs

Issue date: 09/06/2018

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.